Location of Construction: 2063 Congress St	Owner:		Phone:	Permit No. 7 1 0 9 2
Owner Address:	Lessee/Buyer's Name:	Phone: BusinessName:		DEDMIT ICCLIED
Contractor Name:	Address: Address: 443 Cumberland	Phone:	101 761-2467	Permit Issued: 1330ED
Past Use:	Proposed Use:	COST OF WORK:		OCT   0 1997
Office	Same	FIRE DEPT. Ap		
Proposed Project Description:		Signature.		Zoning Approval:
Make Interior Renovatio First Floor	Action: Ap Ap De	Special Zone or Reviews:  Shoreland Wetland Flood Zone Subdivision		
Permit Taken By: Mary-Greatk	Date Applied For:	September 1997	Date:	□ Site Plan maj □minor □mm [
3. Building permits are void if work is not startion may invalidate a building permit and			MH REQUIREMENT	☐ Interpretation ☐ Approved ☐ Denied  Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review
				Action:
I hereby certify that I am the owner of record of authorized by the owner to make this application	on as his authorized agent and I agree to co	vork is authorized by the conform to all applicable la	owner of record and that I have of this jurisdiction. In shall have the authority to	addition, □ Approved with Conditions □ Denied
if a permit for work described in the application areas covered by such permit at any reasonable				Date:
if a permit for work described in the application areas covered by such permit at any reasonable	hour to enforce the provisions of the cod	e(s) applicable to such pe 30 September 199		Date:CEO DISTRICT

## · COMMENTS

		<u> </u>				
10.15.97	HWY					
12:17:97	Interior	partituon	Umored	- Minor	elocation of stains also.	
Alumbi	us All	one mila.	Tomat	to use use	stains also	The American State of the Control of
Bl/h	Menon	1 /2000 .	(Brew)	re in ap	EUROS RESE	
- UE 10	oungry					
						P. Waller & P. Marier Report No.
	1					
			( <i>(</i>		Inspection Record	
				Type	mspection Record	Date
				Foundation:		
				Framing:		
				Plumbing:		
				Other:		

## **BUILDING PERMIT REPORT**

DATE:	: 10/7/97 . ADDRESS: 2063 (ingress /7
REAS	ON FOR PERMIT: Tanguation
BUILD	DING OWNER: Alià Cook
CONT	RACTOR: Major Rental + Property Management
	IT APPLICANT: William Shufter APPROVAL: 4, VIII \$20 26 29 DENIED
	de la de la comitación de
USE G	BOCA 1996 CONSTRUCTION TYPE 36
	CONDITION(S) OF APPROVAL
1. 2. 3. 4. 5. 6. 7.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)  Precaution must be taken to protect concrete from freezing.  It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.  Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)  All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.  Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.  Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material suc that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder eff
9. 10.	Headroom in habitable space is a minimum of 7'6".  Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group
11. 12. ·	minimum 11" tread. 7" maximum rise.  The minimum headroom in all parts of a stairway shall not be less than 80 inches.  Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension
13. 14.	shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.  Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.  All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
15.	The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
16.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

In the immediate vicinity of bedrooms

In each story within a dwelling unit, including basements

In all bedrooms

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-2 I-I shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an 17. approved type. 18. The Fire Alarm System shall be maintained to NFPA #72 Standard. The Sprinkler System shall maintained to NFPA #13 Standard. 19, All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections ر.20 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996) 21. No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work Stop Order shall be issued if this requirement is not met. 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 23. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. 24. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code. 25. £26. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade. 27. All requirements must be met before a final Certificate of Occupancy is issued, All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA 28. National Building Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National X29. Mechanical Code/1993).

This permit is being issued with the understanding that The wells

To be removed are Non-bearing wall- TF this is not the case

The walls must remain until you employ a situatural engineering

32.

33.

**levil** "Minimum height all Use Greage 42" , except Use Group R which is 36". In odd I 162 M and R and public parages and open parking attentions, open guards shall have that employe while a displicated of 4" casand pass through may opening. "Duants abolt not

Bud a control for the Core 2-1 & 2-4 is a minimum of 10° treat and

Death Late To refer to the manufactor and a secretary and a secretary of the Death and the Color of the Death and the Death and

Bullion Oil ment and on four heats operated a la strength of the mornibust manufacture of t

insidial becausely or expects tools. When wheleve are presided to previde discuss of recessor between

Campion (all and the light of the contract of

ies mod tien 14 inches († 1 länem) above the Sport A.L egeme et egeme kendere Jean slotsing modus skall bark a Indukeen int dans opendas beight diamainen of 14 lauken (6 länem). The miniscent has place opening width diamonina

The manuscript deal base across to two (I) squarate, terroic and approved arease of egress. A simple cell is acceptable when it calls directly from the approximant to the healthing energies with ne communications to other approximate units. If

hersingsising by enclosing with VI) hour sire-rated construction (subsiding fire docer and college, or by

Transport in historial cases in a minimum of 7%

P. Samuel Hoffses, Code Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

UMM9-

