City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Phone:

**1711 Congress Street 041	02 **Livada Securities		774-6145	Permit No:
Owner Address: 1711 Congress Street 04102	Lessee/Buyer's Name:	Phone:	BusinessName: Livada Securities	991102UED
Contractor Name: John Cyr Construction Inc.	Address: 834 Lawrence Rd. Pownal		88-4155	Permit Issued: 0CT _ 5 999
Past Use: Office	Proposed Use:	FIRE DEPT. De	\$ 42.00 pproved INSPECTION:	CITY OF PORTLAND
Proposed Project Description: Interior removations to include deswalls and one door way. Add two sid	elight windows.	PEDESTRIAN AC Action: A	pproved with Conditions:	Zoning Approval: Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision
Permit Taken By:	Date Applied For:	10-4-99		☐ Site Plan maj ☐minor ☐mm Zoning Appeal
 This permit application does not preclude the . Building permits do not include plumbing, se Building permits are void if work is not started tion may invalidate a building permit and sto 	eptic or electrical work. d within six (6) months of the date of iss p all work		rities	□ Variance □ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied
		1711 Congres Portaland, Mi		Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	n, Denied			
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

PHONE:

CEO DISTRICT

3

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Addressof Construction (include Portion of Building):	(on	Army St	Postland	04102	
Total Square Footage of Proposed Structure 300 ±		Jare Footage of Lot			
Tax Assessor's Chart, Block & Lot Number Chart# 2 1 9 Block# A Lot# 6 03	Owner:X LIVADA	Securitie	5	Telephone#: 774-61	45
Owner's Address: 1711 CONGRESS ST 04102	Lessee/Buyar's Name			Cost Of Work: 5,000,00	Fee \$ 42
	and One	gove n	r		
Contractor's Name, Address & Telephone	834 Lav	ureng RE	Polipal M	688-415	Rec'd By 4/5
Current Use: Office Space	Pro	oposed Use: 0	Pice up	are	
2) A Copy of	tioning) installation our Deed or Purc your Construction 3) A Plot Plan/S	on must comply hase and Sale A on Contract, if a ite Plan	with the 1993 greement Sovailable	BOCA Mechai	nical Code.
Minor or Major site plan review will be required for checklist outlines the minimum standards for a site plan.		l projects. The at	tached		DING INSPECTION
Unless exempted by State Law, construc	4) Building I		hy a ragistare	DEPT. OF BUIL	ORTLAND, ME
A complete set of construction drawings showing all					- A 1999
Cross Sections w/Framing details (including)	ig porches, decks v	v/ railings, and ac	cessory structu	res OCT	- 4 1990
Floor Plans & Elevations Nindow and door askedules				1131	2 20 12
 Window and door schedules Foundation plans with required drainage at 	nd dampproofing			IIII B B	EINBI
 Electrical and plumbing layout. Mechanica 		specialized equir	oment such as f	urnaces, chimney	s, gas
equipment, HVAC equipment (air handlin					
	Certificat	ion			
I hereby certify that I am the Owner of record of the named proper owner to make this application as his/her authorized agent. I agree application is issued, I certify that the Code Official's authorized reinforce the provisions of the codes applicable to this permit.	to conform to all appli	cable laws of this juri	sdiction In addition	n, if a permit for work	described in this

Building Permit Fee: \$30.00 for the 1st \$1000.cost plus \$6.00 per \$1,000.00 construction cost thereafter.

Additional Site review and related fees are attached on a separate addendum

Date:

Signature of applicant:

BUILDING PERMIT REPORT

		50CT-99 ADDRESS: 171/ Congress ST. CBL: 219-A-003
		NFOR PERMIT: 10 MAKE INTERIOR REDOVATIONS
	BUILD	ing owner: <u>Liva da SecuriTies</u>
	PERMI	TAPPLICANT: 1Contractor John Cyr Const, Inc.
	USE GF	ROUP CONSTRUCTION TYPE
		y's Adopted Bnilding Code (The BOCA National Building Code/1996 with City Amendments) y's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
		CONDITION(S) OF APPROVAL
	This per	rmit is being issued with the understanding that the following conditions are met: *1, *27*33 *35 +36
	Approve	ed with the following conditions:
V	<i>,</i> .	
X		This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained.
	2.	THE OF THE PART OF
		(A 24 hour notice is required prior to inspection)" ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."
	3.	Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than
		10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the
		footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the
		top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter
		membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor
		elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be
,		placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
	4.	Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17)
	5.	Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
	6.	Precaution must be taken to protect concrete from freezing. Section 1908.0
	7.	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify
		that the proper setbacks are maintained.
	8.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent
		interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private
		garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area
		by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the
	9.	garage side. (Chapter 4, Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National
	<i>)</i> .	Mechanical Code/1993). Chapter 12 & NFPA 211
	10.	Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building
		Code.
	11.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces
		for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use
		Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open
		parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but
		not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section
		with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of
		stairway. (Section 1014.7)
	12.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
	13.	Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11"
		tread 7" maximum rise (Section 1014.0)

approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1016.4)

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door

The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

14. 15.

- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
- 24. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min.72 hours notice) and plumbing inspections have been done.
 - 28. All requirements must be met before a final Certificate of Occupancy is issued.
 - 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).
 - 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993). (Chapter M-16)
 - 31. Please read and implement the attached Land Use Zoning report requirements.
 - 32. Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
 - ∆33. Glass and glazing shall meet the requirements of Chapter 24 of the building code.
 - 34. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code

	19961-,
£35.	This permit does not authorize The renoval of any
^	hearing, walls-
¥ 36.	Safely Elazing Shall be done in accordance with section 2405.
4	of The building Code
37.	

Samyer Hollsco, Quilding Inspector

Lt. MgDougatl, PFD Marge Schmuckal, Zoning Administrator

PSH 7/24/99 The &

38.

**On the basis of plans submitted and conditions placed on these plans and deviations shall require a separate approval.

ELECTRICAL PERMITCity of Portland, Me.

To the Chief Electrical Inspector, Portland Maine:

The undersigned hereby applies for a permit to make electrical installations in accordance with the laws of Maine, the City of Portland Electrical Ordinance,

National Electrical Code and the following specifications:

SITE LOCATION: 1711 CONGRESS ST

SURGAM CHANGE CH

Date 8-11-99
Permit # 219 - A - 003
CBL# 045104

OWNER TOTAL EACH FEE **OUTLETS** Smoke Detectors Receptacles Switches .20 **FIXTURES** .20 incandescent fluorescent Strips SERVICES TTL AMPS Overhead Underground <800 15.00 Overhead Underground >800 25.00 Temporary Service Overhead Underground TTL AMPS 25.00 25.00 METERS (number of) 1.00 MOTORS (number of) 2.00 RESID/COM Electric units 1.00 HEATING oil/gas units Interior Exterior 5.00 **APPLIANCES** Ranges Wall Ovens 2.00 Cook Tops Insta-Hot Water heaters Fans 2.00 2.00 Dryers Disposals Dishwasher Washing Machine 2.00 Compactors Spa Others (denote) 2.00 3.00 MISC. (number of) Air Cond/win 10.00 Air Cond/cent Pools **EMS** Thermostat 5.00 HVAC 10.00 Signs 5.00 Alarms/res 15.00 Alarms/com Heavy Duty(CRKT) 2.00 Circus/Carny 25.00 Alterations 5.00 15.00 Fire Repairs 1.00 E Lights E Generators 20.00 PANELS Service DISC Remote Main 4.00 5.00 TRANSFORMER 0-25 Kva 8.00 25-200 Kva Over 200 Kva 10.00

INSPECTION:

TELEPHONE

Will be ready _____

MINIMUM FEE/COMMERCIAL 35.00

or will call

ADDRESS _____

ley Mu 04411

ASTER LIC. # ______ 04564

25.00

35.00

LIMITED LIC. # ___

MINIMUM FEE

TOTAL AMOUNT DUE

SIGNATURE OF CONTRACTOR

Buan Wiley