Location of Construction:	Owner:	,	Phone:		Permit	Permit No:		
1717 Congress Street Owner Address:	Stroudwater Relig   Lessee/Buyer's Name:   Microcomplete Cleaning S	Phone:	Busines	sName:	_			
Contractor Name:	Address:		Phone:		Permi	l Issued:		
Burr Signs	10 Buttonwood, S.P. 04	106	799-118	3				
Past Use:	Proposed Use:	COST OF V	WORK:	PERMIT FEE:				
		\$	\$ 27,40					
		FIRE DEPT	[. □ Approved	INSPECTION:				
Office	Same w/signage		☐ Denied	Use Group: Type:				
					Zone:		ı	
and the second s		Signature:		Signature:	Zanina	219-A-4 Approval:	4	
Proposed Project Description:	ed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (PA		ES DISTRICT (P.A.D.)	2.011110	Approvat.			
		Action: Approved		ſ	Special Zone or Reviews			
Erect 12 sq. ft projecting sign		1	Approved with Conditions:			oreland		
		1	Donlad	[	1	etland		
						od Zone		
		Signature:		Date:		bdivision	m · . m .	
Permit Taken By:	Date Applied For.	/ /15/05			1 211	e Plan maj l	Uminor Umn	
Vicki Dover		4/15/97				Zoning A	ppeal	
1. This permit application does not preclude	e the Applicant(s) from meeting applicabl	e State and Federal	rules.		□Va	riance	1.1.	
					☐ Mis	☐ Miscellaneous		
2. Building permits do not include plumbing, septic or electrical work.						☐ Conditional Use		
3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-						☐ Interpretation		
tion may invalidate a building permit ar	nd stop all work				□De	proved nied		
						Historic Pres		
						☐ Not in District or Landmark ☐ Does Not Require Review		
Mail to Burr Signs						es not Requ quires Revie		
					Action	ı:		
	CERTIFICATION				ПА	poved		
I hereby certify that I am the owner of record		ed work is authorized	d by the owner of	record and that I have bee	,	proved with	Conditions	
authorized by the owner to make this applica					1			
if a permit for work described in the applicat					н (			
areas covered by such permit at any reasona					Date:			
	1	· / 11	1		Ì			
1100 11/1.	,	4/1	.5/97					
SIGNATURE OF A DRIVE ANT	ADDRESS:	DATE:	~	PHONE:	_			
SIGNATURE OF APPLICANT Craig Curr	rier	DAIE.		THORE.	ļ —			
					ł			
Burr Signs	<b>;</b>				<b>,</b>		1 1	
Burr Signs RESPONSIBLE PERSON IN CHARGE OF				PHONE:	CEO	DISTRICT		

### **BUILDING PERMIT REPORT**

DATE: 16 MAy 97 ADDRESS: 1717 Congress SX	
REASON FOR PERMIT: To Crect 1250 FT, Sign -	
BUILDING OWNER: BTroudwater Religious & Society	
CONTRACTOR: Bury Sign.	
PERMIT APPLICANT:APPROVAL: */	<del>DENIS</del> D

## **CONDITION(S) OF APPROVAL**

- 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
- 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
- 3. Precaution must be taken to protect concrete from freezing.
- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
- 7. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 8. Headroom in habitable space is a minimum of 7'6".
- 9. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread, 7" maximum rise.
- 10. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- Every sleeping room below the fourth story in buildings of use Groups R and 1-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
- 12. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 13. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 14. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- 15. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

### BIGNAGE

# PLEASE ANSWER ALL QUESTIONS

ADDRESS: 1717 Congress St. BONE:
OWNER: Microcomplete Chaning Senie Inc.
APPLICANT: BUN Signs
ASSESSOR NO.:
SINGLE TENANT LOT? YES NO
MULTI TENANT LOT? YES NO NO
FREESTANDING SIGN? YES NO DIMENSIONS (ex. pole sign)
MORE THAN ONE SIGN? YES NO DIMENSIONS
BLDG. WALL SIGN? YES NO DIMENSIONS 3'X4' (attached to bldg)
MORE THAN ONE SIGN? YES NO DIMENSIONS
(1) Sign for Missens Beleng
LOT FRONTAGE (FEET)
bldg frontage (feet) 38'-8"
AWNING YES NO IS AWNING BACKLIT? YES NO
HEIGHT OF AWNING:
IS THERE ANY COMMUNICATION, MESSAGE, TRADEMARK OR SYMBOL ON IT?
A SITE SKETCH AND BUILDING SKETCH SHOWING EXACTLY WHERE EXISTING AND NEW
SIGNAGE IS LOCATED MUST BE PROVIDED. SKETCHES AND/OR PICTURES OF THE
PROPOSED SIGNS ARE ALSO REQUIRED.

HYS'

REDECTIVE

ELECTRIC

MISS AN'S

OHERY EXISTING 38'-8"

Craig STeal

FINAL DRAFT

Sign Elevation- 3'x4' DIF MDO Projecting On Scroll Bracket

Scale- 1"=10"

BLACKET