Location of Construction: 54 Penrith Rd	Owner: John Ville		Phone:		Permit No: 960211
Owner Address:	Leasee/Buyer's Name:	Phone:	Busines	ssName:	PERMIT ISSUED
Contractor Name:	Address: 302 Brook St Westbr				Pe mit Issued: MAR 2 9 1996
Past Use:	Proposed Use:	COST OF WOR		PERMIT FEE: \$ 100.00	
l-fam	Same w/addition	FIRE DEPT. Signature:	Approved Denied	INSPECTION: Use Group of 3Type 30CA 43 Signature:	Zone: CBL: 219-A-029
Proposed Project Description:			ACTIVITII	ES DISTRICT (F).D	
Construct Addition (10 x 14)		Action: Signature:	Action: Approved E Approved with Conditions: E Denied E		Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision
Permit Taken By: Mary Gresik	Date Applied For:	26 March 1996			☐ Site Plan maj ☐ minor ☐ mm ☐
 Building permits do not include plumbin Building permits are void if work is not stion may invalidate a building permit an 	☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied				
		THERMIT ISSUED	YNNY RE	MIT ISSUED QUIREMENTS	Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action:
	CEDTIFICATION	SAG.		*70	☐ Appoved
I hereby certify that I am the owner of record authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonal	of the named property, or that the propose tion as his authorized agent and I agree to cion issued, I certify that the code official ble hour to enforce the provisions of the company to	d work is authorized by to conform to all applicabers authorized representate code(s) applicable to such	he owner of le laws of th ive shall ha n permit	record and that I have his jurisdiction. In addive the authority to ente	been
SIGNATURE OF APPLICANT Richard	Ledue ADDRESS:	DATE:		PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:				CEO DISTRICT 4	
Whit	e-Permit Desk Green-Assessor's C	Canary–D.P.W. Pink–Pi	ublic File	Ivory Card-Inspector	

4/12/96 Fordeth Sup - P	comments in Selbock of Reduces & Depth of
on & bappiel 10	
10-17-90 filed W/out fr	nal inspection.
	Inspection Record
	Type Date
	Foundation:
	Plumbing:Final:
	Other:

BUILDING PERMIT REPORT

	ss: 54 PonriTh Rd.
REASON FOR PERMIT: To Construct	a 10×14 sdd. Tion
BUILDING OWNER: John Willey	
CONTRACTOR: Richard Ledue	APPROVED: */ */ */ 4
PERMIT APPLICANT:	Discretio:

CONDITION OF APPROVAL OR DESPIAL

1. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

& 2. Precaution must be taken to protect concrete from freezing.

3. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

4. All vertical openings shall be enclosed with construction having a fire rating of at least one(1) hour, including fire doors with selfclosers.

5. Each apartment shall have access to two(2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.

6. The boiler shall be protected by enclosing with one(1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessible location between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 sq. feet per sprinkler.

7. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue, they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sq. feet.

8. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.

9. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, section 19, 919.3.2(BOCA National Building Code/1993), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- In the immediate vicinity of bedrooms
- 2. In all bedrooms

3. In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted.

10. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage

(Chapter 4 section 407.0 of the BOCA/1993)

Guardrail & Handrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open quards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.

All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023. & 1024. of the

City's building code. (The BOCA National Building Code/1993)

Stair construction in Use Group R-3 & R-4 is a minimum of 9" tread and 8-1/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum

Headroom in habitable space is a minimum of 7'6". **V** 14.

The minimum headroom in all parts of a stairway shall not be less than 80 inches.

All construction and demolition debris must be disposed at the City's 16. authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.

Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April

15 of the following year".

The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

This permit does not excuse the applicant from obtaining any license

which may be needed from the City Clerk's Office.

Hoffses, Chief of Inspection Services

Applicant: Richard ledue

Address: 54 Penr Th Rd.

Assessors No.: 219-A-29

Date: 3/2496

CHECK-LIST AGAINST ZONTNG ORDTNANCE

Date -

Zone Location - R-

Interior or corner lot -

Use - 10 X 1A

Sewage Disposal - Coty

Rear Yards - 25 rey - N

Side Yards - 12'reg - 206'shown Front Yards - 25'reg - 50'+ shown

Projections -

Height - | Story

Lot Area -

Building Area -

Area per Family -

Width of Lot -

Lot Frontage -

Off-street Parking -

Loading Bays -

Site Plan -

Shoreland Zoning/

Flood Plains -