Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 05/17/16

INVE

SolarEdge Single Phase Inverters

For North America

SE3000A-US / SE3800A-US / SE5000A-US / SE6000A-US / SE7600A-US / SE10000A-US / SE11400A-US

The best choice for SolarEdge enabled systems

- Integrated arc fault protection (Type 1) for NEC 2011 690.11 compliance
- Superior efficiency (98%)
- Small, lightweight and easy to install on provided bracket
- Built-in module-level monitoring
- Internet connection through Ethernet or Wireless
- Outdoor and indoor installation
- Fixed voltage inverter, DC/AC conversion only
- Pre-assembled Safety Switch for faster installation
- Optional – revenue grade data, ANSI C12.1

Single Phase Inverters for North A

SE3000A-US / SE3800A-US / SE5000A-US / SE6000A-US / SE7600A-US / SE10000A-US / SE11400A-US

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 05/17/16

	SE3000A-US	SE3800A-US	SE5000A-US	SE6000A-US	SE7600A-US	SE10000A-		
OUTPUT								
Nominal AC Power Output	3000	3800	5000	6000	7600	9980 @ 20 10000 @24		
Max. AC Power Output	3300	4150	5400 @ 208V 5450 @240V	6000	8350	10800 @ 208V 10950 @240V	12000	VA
AC Output Voltage Min.-Nom.-Max.[1] 183 - 208 - 229 Vac	-	-	✓	-	-	✓	-	
AC Output Voltage Min.-Nom.-Max.[1] 211 - 240 - 264 Vac	✓	✓	✓	✓	✓	✓	✓	
AC Frequency Min.-Nom.-Max.[1]	59.3 - 60 - 60.5 (with HI country setting 57 - 60 - 60.5)							Hz
Max. Continuous Output Current	12.5	16	24 @ 208V 21 @ 240V	25	32	48 @ 208V 42 @ 240V	47.5	A
GFDI	1							A
Utility Monitoring, Islanding Protection, Country Configurable Thresholds	Yes							Yes
INPUT								
Recommended Max. DC Power[2] (STC)	3750	4750	6250	7500	9500	12400	14250	W
Transformer-less, Ungrounded	Yes							
Max. Input Voltage	500							Vdc
Nom. DC Input Voltage	325 @ 208V / 350 @ 240V							Vdc
Max. Input Current[3]	9.5	13	16.5 @ 208V 15.5 @ 240V	18	23	33 @ 208V 30.5 @ 240V	34.5	Adc
Max. Input Short Circuit Current	45							Adc
Reverse-Polarity Protection	Yes							
Ground-Fault Isolation Detection	600kΩ Sensitivity							
Maximum Inverter Efficiency	97.7	98.2	98.3	98.3	98	98	98	%
CEC Weighted Efficiency	97.5	98	97.5 @ 208V 98 @ 240V	97.5	97.5	97 @ 208V 97.5 @ 240V	97.5	%
Nighttime Power Consumption	< 2.5				< 4			W
ADDITIONAL FEATURES								
Supported Communication Interfaces	RS485, RS232, Ethernet, ZigBee (optional)							
Revenue Grade Data, ANSI C12.1	Optional[4]							
Rapid Shutdown – NEC 2014 690.12	Functionality enabled when SolarEdge rapid shutdown kit is installed[5]							
STANDARD COMPLIANCE								
Safety	UL1741, UL1699B, UL1998 , CSA 22.2							
Grid Connection Standards	IEEE1547							
Emissions	FCC part15 class B							
INSTALLATION SPECIFICATIONS								
AC output conduit size / AWG range	3/4" minimum / 16-6 AWG				3/4" minimum / 8-3 AWG			
DC input conduit size / # of strings / AWG range	3/4" minimum / 1-2 strings / 16-6 AWG				3/4" minimum / 1-2 strings / 14-6 AWG			
Dimensions with Safety Switch (HxWxD)	30.5 x 12.5 x 7 / 775 x 315 x 172		30.5 x 12.5 x 7.5 / 775 x 315 x 191		30.5 x 12.5 x 10.5 / 775 x 315 x 260			in / mm
Weight with Safety Switch	51.2 / 23.2		54.7 / 24.7		88 .4 / 40.1			lb / kg
Cooling	Natural Convection				Fans (user replaceable)			
Noise	< 25				< 50			dBA
Min.-Max. Operating Temperature Range	-13 to +140 / -25 to +60 (-40 to +60 version available[6])							˚F / ˚C
Protection Rating	NEMA 3R							

(1) For other regional settings please contact SolarEdge support.
(2) Limited to 125% for locations where the yearly average high temperature is above 77˚F/25˚C and to 135% for locations where it is below 77˚F/25˚C. For detailed information, refer to http://www.solaredge.us/files/pdfs/inverter_dc_oversizing_guide.pdf
(3) A higher current source may be used; the inverter will limit its input current to the values stated.
(4) Revenue grade inverter P/N: SExxxxA-US000NNR2
(5) Rapid shutdown kit P/N: SE1000-RSD-S1
(6) -40 version P/N: SExxxxA-US000NNU4

RoHS

© SolarEdge Technologies, Inc. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: 07/2014. V.01. Subject to change without notice.