Location of Construction: 28 Sandy Terrace	Owner: Calazzo, Mu	irk 6 Kelli	Phone:		Permit No. 70598
Owner Address: SAA Prid, MS 04102	Lessee/Buyer's Name:	Phone:	Busines	ssName:	PERMIT ISSUED
Contractor Name:	Address:	Phoi	ne:		Permit Issued:
Past Use:	Proposed Use:	COST OF WOL		PERMIT FEE: \$ 35.00 INSPECTION:	GITY OF PORTLAND
	w/deck		Denied Denied	Use Group 3 Type: 5  BOC 996  Signature: Holla	Zone: CBL: 224-A-A-025
Proposed Project Description:			ACTIVITII	ES DISTRICT (PAD.)	Zoning Approval:
Construct Deck (16 x 20		Action:	Approved Approved Denied	with Conditions: [	Special Zone or Reviews:  Shoreland Wetland Flood Zone Subdivision
Permit Taken By:  Mary Gresik	Date Applied For:	Signature:		Date:	☐ Site Plan maj ☐minor ☐mm [
<ol> <li>Building permits do not include plumbing</li> <li>Building permits are void if work is not station may invalidate a building permit and</li> </ol>	arted within six (6) months of the date	of issuance. False informa			☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
			um.	PERMIT ISSUED H REQUIREMENTS	Historic Preservation  ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review  Action:
	CERTIFICATION			.,0,	□Appoved
I hereby certify that I am the owner of record of authorized by the owner to make this application	f the named property, or that the proposion as his authorized agent and I agree on is issued, I certify that the code office	sed work is authorized by to conform to all applicabial's authorized representations.	ole laws of thative shall ha	nis jurisdiction. In additio	<sub>n,</sub>   □Denied
if a permit for work described in the application areas covered by such permit at any reasonable	e hour to enforce the provisions of the	code(s) applicable to suc			
	e hour to enforce the provisions of the		607		
	e hour to enforce the provisions of the  ADDRESS:	10 June 1 DATE:	997	PHONE:	

~~	TO 0	700	 	
CO	h (% /ii	10/	Pal .	
8 . 8 .	7 I V I	II V	134	

	- A		Port State	t.		
7-15-9-1	HUUL	Unstructed	wort	notification	of inspection	
						Promotion of the second
A Commission of the Commission						
						The second secon
			τ			
				Т	Inspection Record	
			The second	Type Foundation:		Date
			7			
			,			
				Other:		
		and the control of the state of the control of the state				

Location of Construction:  28 Sandy Terrace  Owner:  Caiazzo, Ma		rk & Kelli			Permit No:9 7 0 5 9 8	
Owner Address: SAA Ptld, ME 04102	Lessee/Buyer's Name:	Phone:	Busines	sName:	PERMIT ISSUED	
Contractor Name:	Address:	Phon			Permit Issued:	
Past Use:	Proposed Use:	COST OF WOR \$ 3,350.00		<b>PERMIT FEE:</b> \$ 35.00		
1-fam	Same w/deck	FIRE DEPT.		Use Group & 3Type: 573	Zone: CBL: 224-A-A-025	
Proposed Project Description:  Construct Deck (16 x 20)		PEDESTRIAN A Action:	Approved	Signature: Afair S DISTRICT (P.A.D.) with Conditions:	Zoning Approval:  Special Zone or Reviews.  Shoreland Wetland Flood Zone Subdivision	
Permit Taken By: Mary Gresik	Date Applied For:	10 June 1997			☐ Site Plan maj ☐minor ☐mm ☐	
<ol> <li>Building permits do not include plumbing.</li> <li>Building permits are void if work is not station may invalidate a building permit and</li> </ol>	ted within six (6) months of the date of	f issuance. False informa-		PERMIT IESUSO REQUERRASO RESUS	☐ Miscellaneous ☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied  Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review  Action:	
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	n as his authorized agent and I agree to is issued, I certify that the code official	o conform to all applicable al's authorized representations.	he owner of le laws of th tive shall ha	record and that I have been is jurisdiction. In addition,	□ Approved □ Approved with Conditions □ Denied  Date:	
SIGNATURE OF APPLICANT Mark Carlaz	zo ADDRESS:	10 June 19 DATE:	997	PHONE:		
RESPONSIBLE PERSON IN CHARGE OF WO	ORK, TITLE			PHONE:	CEO DISTRICT	
White-	Permit Desk Green–Assessor's (	Canary–D.P.W. Pink–Pเ	ublic File	lvory Card-Inspector	A. Powers	

Applicant: Mank (>12720	Date: 6/4/4/
Address: 28 SAndy Ten ACE	CBL: 22AA - A-025
CHECK-LIST AGAINST ZONI	NG ORDINANCE
Date - 6418 1 1955	
Zone Location - R-3	
(Interior or corner lot -	
Proposed Use/Work - 16 x 20 Dexl	pers.
Sewage Disposal -	
Lot Street Frontage -	
Front Yard - NA	
Rear Yard - 25 ( reg - 100+ Show	
Rear Yard - 25' reg - 100 t show Side Yard - 9' reg - 9' + Show	
Projections -	
Width of Lot -	
Height -	
Lot Area - 16,864#	615541
Lot Coverage/Impervious Surface - 25 (	R430 My
Area per Family -	
Off-street Parking -	
Loading Bays -	26×34 884
Site Plan -	26×34 884 8×27 176
Shoreland Zoning/Stream Protection -	20 X 22 4 40
Flood Plains -	8 X 1 1 136
16	×20 (356)
	457

## **BUILDING PERMIT REPORT**

DATE: 12 June 9	ADDRESS: 28 Sandy Terrace
REASON FOR PERMIT: 7	o Construct a 16'x20' deck
BUILDING OWNER:	1 d220 man and the same of the
CONTRACTOR:	The first term of a property of the second section of the second section of the second section of the second section is a second section of the second section of the second section is a second section of the second section of the second section is a second section of the second section
PERMIT APPLICANT:	APPROVAL: X/X2, 48 × 10 ×27 DENIED

## **CONDITION(S) OF APPROVAL**

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

- 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
  - 3. Precaution must be taken to protect concrete from freezing.
- 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
- 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
- 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- 9. Headroom in habitable space is a minimum of 7'6".
- 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
  - 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
  - 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
  - 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
  - 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
  - 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
  - All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
    - In the immediate vicinity of bedrooms
    - In all bedrooms
    - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

17.	A portable fire	e extinguisher s	hall be locate	ed as per NFP	A #10. The	y shall bear	the label of	an approved	agency and	be of an
	approved type			-						

18. The Fire Alarm System shall be maintained to NFPA #72 Standard.

19. The Sprinkler System shall maintained to NFPA #13 Standard.

- 20. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.

22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.

25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.

dgind ilis e aved liede ynth <u>pasest an entre la entre</u>n as bestrong sos eveltaire stadie allement properties de An entre d'un est males (II) lâmes paset des lleur. All egrens et séaux from thomples yours l'aut descent au c entriques met glans execute het de cessage of le notate (Cléman). The appointuit entrélair opening width dimension

26. All electrical and plumbing permits must be obtained by a Master Licensed holders of their trade.

227. Oll Sono Tubes Shall rest on Footings with anchor between -

P Sample! Hoffses, Chief of Code Enforcement

cc: Lt. McDougall PFI

29.

## BASIC GUIDELINES FOR DECK PERMITS

Materials needed to apply for permit:

- 1) Plot Plan A Bird's eye view of your property showing where all your buildings are located in relationship to the lot lines and each other. You need to show those distances (the front, rear and sides) in feet.
- 2) <u>Construction Plan</u> Cross Section. What dimensional lumber/materials are being used and what is their make-up?
- 3) <u>Fee</u> Based on cost of work labor/materials. 25.00 1st 1,000 worth of work, 5.00 each additional 1,000.

The following check-off sheet can be used in most circumstances: Frost wall, min 4' below grade Foundation Sone tubes, min 4' below grade, 6" min on footing, hard pan or bedrock Sinch Whes Other Distance between foundation supports sill Joist Size Joist Span √ 16"oc 24"oc <u>Distance Between Joists</u> 5/4 other/explain Decking 10" min tread 7 3/4" max riser Stair Construction 36" Guard Height 42" Guards shall be located along open-sided walking surfaces located 15 1/2" above the floor or below grade. Single family - min 36", all others 42", measured vertically above the leading edge of the tread or adjacent walking . surface. BOCA 1005.5/1021.2 Balusters

Open guards shall have balusters or be of a solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall

not have an ornamental pattern that would provide a ladder effect.

osenst pluts 85

