## City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: Portland, ME 04102 28 Winding Way Woodfords Family Services 878-9663 Lessee/Buver's Name: Owner Address: Phone: BusinessName: 1037 Forest Ave. Portland. ME Hermit Issued: Contractor Name: Address: Phone: N/A COST OF WORK: Proposed Use: PERMIT FEE: Past Use: \$ 25.00 1-Pamily Handicapped FIRE DEPT. Approved INSPECTION: Residential ☐ Denied Use Group: Type: Zone: Signature: Signature: Zoning Approval Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved Change of Use from Residential to Handicapped Residential Special Zone or Reviews Approved with Conditions: ☐ Shoreland Denied □Wetland ☐ Flood Zone Date: ☐ Subdivision Signature: ☐ Site Plan maj ☐minor ☐mm ☐ Permit Taken By: Date Applied For: UB 6-29-99 Zoning Appeal □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous Building permits do not include plumbing, septic or electrical work. □ Conditional Use ☐ Interpretation Building permits are void if work is not started within six (6) months of the date of issuance. False informa-□ Approved tion may invalidate a building permit and stop all work... sassa Mail to: □ Denied Family Services Richard Farnsworth Historic Preservation P.O. Box 1768 □ Not in District or Landmark Portland, ME 04104-1768 □ Does Not Require Review PERMIT ISSUED WITH REQUIREMENTS ☐ Requires Review Action: CERTIFICATION □ Appoved I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been ☐ Approved with Conditions □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit June 29, 1999 SIGNATURE OF APPLICANT ADDRESS: DATE: PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

CEO DISTRICT

PHONE:



Type  Foundation: Framing: Plumbing: Final: Other:		COMMENTS
Date		

BUILDING PERMIT REPORT DATE: 30 June 97 ADDRESS: 28 Winder caused Resol BUILDING OWNER: PERMIT APPLICANT: **BOCA 1996** CONSTRUCTION TYPE USE GROUP CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 3. percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2 Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from comers of foundation and a 4. maximum 6' o.c. between bolts. (Section 2305.17) Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code. 5. Precaution must be taken to protect concrete from freezing. Section 1908.0 6 It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the 7. proper setbacks are maintained. 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached - side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4,

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical

Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an omamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1

Stair construction in Use Group R-3 & R-4is a minimum of 10" tread and 7 "maximum rise. All other Use Group minimum 11" tread,

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door

All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's.

The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic

All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's

Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be

approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of excess or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6) Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly

11.4.7) 44" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stainway. (Section 1014.7)

from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

The minimum headroom in all parts of a stainvay shall not be less than 80 inches. (6'8") 1014.4

(Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)

Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the

Section 407.0 of the BOCA/1996)

Code/1993). Chapter 12 & NFPA 211

7" maximum rise. (Section 1014.0)

extinguishment. (Table 302.1.1)

Headroom in habitable space is a minimum of 7'6". (Section 1204.0)

9.

10.

11.

12.

13.

14.

15.

16.

17.

13.

19.

	installed and maintained at the following locations):				
	<ul> <li>In the immediate vicinity of bedrooms</li> </ul>				
	In all bedrooms				
	• . In each story within a dwelling unit, including basements				
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive				
	power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.				
	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.				
	(Section 921.0)				
	The Fire Alarm System shall maintained to NFPA #72 Standard.				
	The Sprinkler System shall maintained to NFPA #13 Standard.				
	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the				
	City's Building Code. (The BOCA National Building Code/1996)				
	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any				
	street or sidewalk from the time of November 15 of each year to April 15 of the following year".				
	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from				
	design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspectio				
	Services.				
	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).				
	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all				
	electrical (min. 72 hours notice) and plumbing inspections have been done.				
•	All requirements must be met before a final Certificate of Occupancy is issued.				
	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building Code/1996).				
	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical				
	- 1 (1 to 1				
	Please read and implement the attached Land Use Zoning report requirements.				
	Boing, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.				
	Glass and glazing shall meet the requirements of Chapter 24 of the building code.				
_					
)	1				
Ι,					
177	el Horses, Building Inspector				
7	McDougall, PFD				
	Marge Schmuckal, Zoning Administrator				

\*\*On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

## THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

## **Building or Use Permit Pre-Application** Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the information below for a Building or

NOTE\*\*If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted. NDING WAY Location/Address of Construction: Tax Assessor's Chart, Block & Lot Number Telephone Charte 225 LOW COL DOODFORDS FAMILY SERVICES Owner's Address Cost Of Work: Lessee Buyer's Name (If Applicable) \$ 25.00 HANDICAPPED RESIDENTIAL BESIDENTIAL TO Rac'd By: 113 Contractor's Name, Address & Telephone Separate permits are required for Internal & External Plumbing, HVAC and Electrical installation. All construction must be conducted in compliance with the 1996 B.O.C.A. Building Code as amended by Section 6-Art II. All plumbing must be conducted in compliance with the State of Maine Plumbing Code. •All Electrical Installation must comply with the 1996 National Electrical Code as amended by Section 6-Art III. HVAC(Heating, Ventilation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. You must Include the following with you application: \* SEND TO: Woodfords family Services 1) A Copy of Your Deed or Purchase and Sale Agreement Richard Farnsworth P.D. BOX 1768 2) A Copy of your Construction Contract, if available 3) A Plot Plan (Sample Attached) Portland Me 64104-1768 If there is expansion to the structure, a complete plot plan (Site Plan) must include: The shape and dimension of the lot, all existing buildings (if any), the proposed structure and the distance from the actual property lines. Structures include decks perches, a bow windows cantilever sections and roof overhangs, as well as shed suspection CITY OF PORTLAND, ME pools, garages and any other accessory structures Scale and required zoning district setbacks JUN 2 9 1999 4) Building Plans (Sample Attached) A complete set of construction drawings showing all of the following elements of construction: Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures) Floor Plans & Elevations Window and door schedules Foundation plans with required drainage and dampproofing Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included. Certification I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record

laws of this jurisdiction. In addition, if a permit for work described in this application is issued. I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit Signature of applicant:

and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable

Building Permit Fie: \$25.00 for the 1st \$1,000 cost plus \$5.00 per \$1.000.00 construction post thereafter. O:INSPICORRESPININGENT: APADSFOLX PD