CITY OF PORTLAND, MAINE DEVELOPMENT REVIEW APPLICATION PLANNING DEPARTMENT PROCESSING FORM

2009-0039

	Pla	anning Copy	A	oplication I. D. Number
Davidson district and the second			4/	21/2009
Portland International Jetport Applicant			A	oplication Date
			Δ.	mandmant to Dlan Jatuart Darking La
1001 Westbrook Street, Portland, ME 04102 Applicant's Mailing Address				mendment to Plan-Jetport Parking Lo roject Name/Description
Applicants Maining Address		2378 - 2378	Congress St, Portlai	
Consultant/Agent		Address of P		ia, marro
	ax: (207) 774-7740	233 A00200		
Applicant or Agent Daytime Telephone, Fax		Assessor's R	Reference: Chart-Block	r-Lot
Proposed Development (check all that apply):	New Building Buil	ding Addition	Change Of Use	Residential Office Retail
Manufacturing Warehouse/Distribution		pt 0 □ Condo		
Walland daring Valendaso Bishibation	Y ranking Lot		Culci (ope	
Proposed Building square Feet or # of Units A	Acreage of Site Pr	0	rbed Area of the Site	Airport Business Zoning
	To reage of Site Pi	oposed Total Distu	Thed Area of the Site	Zoning
Check Review Required:				Design Review
Site Plan (major/minor)	ing Conditional - PB	Subdivision # of	lots	☐ DEP Local Certification
		Shoreland	☐ Historic Preserva	tion
	ing Conditional - ZBA			Site Location
Amendment to Plan - Staff Review		Zoning Variance	Flood Hazard	Housing Replacement
After the Fact - Major		Stormwater	Traffic Movemen	t Other
After the Fact - Minor		PAD Review	14-403 Streets R	eview
Fees Paid: Site Plan Sub	division	Engineer Revie	ew	Date
Planning Approval Status:		Reviewer		
	1 10 111	The state of the s		
	roved w/Conditions Attached		Denied	
See	Attached			
Approval Date Approv	val Expiration	Extension	ı to	Additional Sheets Attached
OK to Issue Building Permit				Attacrica
	signature	date		
Performance Guarantee Reg	uired*	☐ Not Requ	uired	
* No building permit may be issued until a perforr	nance guarantee has beel	n submitted as indic	cated below	
Performance Guarantee Accepted				
	date		amount	expiration date
Inspection Fee Paid				
	date	-	amount	_
☐ Building Permit Issue				
	date			
Performance Guarantee Reduced				
T chomanoe durantee reduced	date	rem:	aining balance	signature
Tamparan Cartificate of Occupancy	3.3.13			5.3
Temporary Certificate of Occupancy	date	Condition	ns (See Attached)	expiration date
· · · · · · · · · · · · · · · ·	date			expiration date
Final Inspection	1.1.		-toto	_
	date		signature	
Certificate Of Occupancy				
	date			
Performance Guarantee Released				_
	date		signature	
Defect Guarantee Submitted				
	submitted date	-	amount	expiration date
Defect Guarantee Released				

date

signature



Stantec Consulting Services Inc. 22 Free Street Suite 205

Portland ME 04101-3900 Tel: (207) 775-3211 Fax: (207) 775-6434

April 17, 2009 File: 195210313

Ms. Barbara Barhydt
Development Review Services Manager
Planning Division
389 Congress Street 4th Floor
Portland, Maine 04101

Dear Ms. Barhydt:

Reference:

Site Plan Amendment Application

Portland International Jetport - Remote Parking Lot

Portland, Maine

Please find enclosed seven (7) copies of the application for a Site Plan Amendment for construction of drainage improvements at the Portland International Jetport's remote parking lot on outer Congress Street. The scope of work of the drainage improvements includes:

- demolition of existing stormwater quality unit and stormdrain system;
- construction of a dry-detention basin;
- construction of eleven (11) engineered stormwater bio-filter chambers (StormTreat Systems);
- minor site landscaping and vegetation restoration;

The improvements are required in order to bring the facility into compliance with current Maine Department of Environmental Protection's Stormwater Management standards. No expansion or reconstruction of the existing paved parking lot is proposed, and no impacts to existing protected resources are anticipated.

Please feel free to contact us during your review with any questions or if you need additional information. We look forward to receiving your comments.

Sincerely,

STANTEC CONSULTING SERVICES INC.

David P. Nadeau, P.E. Transportation Engineer

Tel: (207) 775-3211 Fax: (207) 775-6434 dave.nadeau@stantec.com

Attachment:

as stated

c. Cuyler Feagles - PWM



PORTLAND INTERNATIONAL JETPORT (PWM) – PORTLAND, MAINE

SITE LOCATION OF DEVELOPMENT - MINOR AMENDMENT APPLICATION

SITE LOCATION OF DEVELOPMENT LAW 38 M.R.S.A. §481-490

MINOR AMENDMENT PERMIT APPLICATION

for

PWM REMOTE PARKING LOT ON OUTER CONGRESS STREET

Prepared for:
City of Portland
Department of Waterfront and Transportation
Portland International Jetport
1001 Westbrook Street
Portland, Maine 04102

Prepared by:
Stantec Consulting Services Inc.
22 Free Street
Portland, Maine 04101

March 2009

TAT TA , U これのこ AMME

Vendor Number: 26514

Check Date: 2009-03-09

Check Number: 190847

1,000.00 1,000.00 Amount Paid Discount Taken 0.00 Invoice Amount 1,000.00 Invoice Date 05-MAR-09 Invoice Number MANCK.MAR09

Net Check Amount: (US Dollars)

Stantec Consulting Inc.

Bank Of America Delkalb County Atlanta, GA 061112788-

611 GA

64-1278

190847

DATE

******** And 00 Cents And 50 Cents

PAY

TO THE ORDER OF

Treasurer, State of Maine 16 state House Station Agusta, ME 04333

US Funds

\$*****1,000.00

THIS DOCUMENT CONTAINS A GRADIENT COLOUR BACKGROUND . INVISIBLE FLUORESCENT PATTERN UNDER CONVENIENCE FIELD XXX . SECURITY MICHOPRINTING . TRUE WATERMARK

74921 405 "0190847" "061112788"

PORTLAND INTERNATIONAL JETPORT (PWM)

Application for Minor Amendment to the Site Location of Development Permit for

Proposed Improvements at Remote Parking Lot

Table of Contents

SUI	RMIT APPLICATION & PRE-APPLICATION MEETING SUMMARY BMISSIONS CHECKLIST ISTING MDEP PERMIT	SECTION B
	STING WIDER FERWIT	
	DEVELOPMENT DESCRIPTION (SITE LOCATION SECTION 1)	
	PROJECT LOCATION	
	PROJECT DESCRIPTION	
1.3	PROJECT SCHEDULE / CONSTRUCTION PLANS	1.1
2.0	TITLE, RIGHT OR INTEREST (SITE LOCATION SECTION 2)	2.1
3.0	FINANCIAL CAPACITY (SITE LOCATION SECTION 3)	3.1
3.1	PROJECT FUNDING	3.1
3.2	ESTIMATED PROJECT COSTS	
4.0	TECHNICAL ABILITY (SITE LOCATION SECTION 4)	4.1
5.0	VISUAL QUALITY AND SCENIC CHARACTER (SITE LOCATION SECT	TION 6)5.1
6.0	WILDLIFE AND FISHERIES (SITE LOCATION SECTION 7)	6.1
7.0	HISTORIC SITES (SITE LOCATION SECTION 8)	7.1
8.0	UNUSUAL NATURAL AREAS (SITE LOCATION SECTION 9)	8.1
9.0	SOILS (SITE LOCATION SECTION 11)	9.1
10.	0STORMWATER MANAGEMENT (SITE LOCATION SECTION 12)	10.1
10.	1INTRODUCTION	10.1
	2ORIGINAL TEMPORARY PARKING LOT	
	3PERMANENT PARKING LOT	
	4EXISTING PAVED DRIVE	
	5METHODOLOGY	
10	6PRECIPITATION	10.1

Stantec

PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT

	ontents TIONSRY	
11.0URBAN	MPAIRED STREAM SUBMISSIONS (SITE LOCATION SECTION 13	3)11.1
12.0BASIC S	TANDARDS (SITE LOCATION SECTION 14)	12.1
	JCTION	
12.2SCHEDU	LE	12.1
12.3GENERA	L CONSTRUCTION DETAILS	12.1
	Seeding and Revegetation Plan	
	Fall/Winter Seeding and Stabilization	
	Monitoring Details	
12.4INSPECT	TON AND MAINTENANCE	12.1
12.4.1	Inspection Schedule during Construction	12.1
	Inspection Procedures during Construction	
	Maintenance Procedures during Construction	
	Inspection Procedures and Maintenance after Construction	
	EEPING	
	Housekeeping during Construction	
	Spill Prevention and Response Procedures	
	Potential Spill Area Identification	
	Spill Prevention Procedures	
	Groundwater Protection	
	Fugitive Sediment and Dust	
	De-watering	
	Non-stormwater Discharges	
	Housekeeping after Construction	
	NS	
	KEEPING	
	TFICATION	
12.0KE-CEK	IFICATION	12.1
13.0SOLID W	ASTE (SITE LOCATION SECTION 18)	13.1
14.0NOTICES	S (SITE LOCATION SECTION 25)	14.1
APPENDICES		
DRAWING SE	ET	APPENDIX 1

Department of Environmental Protection Bureau of Land & Water Quality 17 State House Station Augusta, Maine 04333

Telephone: 207-287-3901

FOR DEP USE	FORM A PAGE 1
ATS#	
Гotal Fees:	
Date: Received	

04/08

SITE LOCATIO	N OF DE	VELOP	MENT PERM	II API	PLICATIO	UN 30		A. 98401-470
PLEASE TYPE OR PRINT I This application is for:	N INK ON	20	acre development		rine Oil Tei	rminal		or Amendment or Amendment
CHECK THE ONE THAT	APPLIES)		nning Permit		ucture		NIIII	Of Amenument
CHECK THE ONE THAT I			tallic Mining		odivision	- In	<u>I</u> David Nac	dean
I. Name of Applicant:	City of P	ortland	• . I T-4 a -4)	The state of the s	e of Agent: plicable)			onsulting Services Inc.
			ional Jetport)		t's Mailing			treet, Suite 205
2. Applicant's	389 Con	gress Stre	et	Addr				Maine 04101-3900
Mailing Address:		, Maine 0		200000000000000000000000000000000000000		and the second second second second	207-775-3	
3. Applicant's		eagles, (P	WM)	8. Agent's Daytime 207-775-3211 Phone #:				
Daytime Phone #:	207-756-			9. Agent's Fax #: 207-775-6434				
4. Applicant's Fax #:	207-774-	7740						
5. Applicant's <i>e-mail address</i> (license will be sent via e-mail)					ent's <i>e-mail (</i> will be sent		dave.nade	eau@stantec.com
			PROJECT INFO	RMAT	ION	n disper		
11. Name of Development:	Portland I	nternatio	nal Jetport – Rem					
12. Map and Lot #'s:	Map #: 233	Lot #: 3	3. Deed Reference	e#*s:		Book #:		Page #: 262
14. Location of Project City/Town:	Portland		15. County: Cumb		16. UTM Northing		858149.3 1 E	Lasting
18. Brief Description of Project including total parcel size:	Chapter 50	0 Stormwa	nts at the Jetport On ater Standards. Applevelopment of Exi	proximat	e Area of Pro	oposed L	Congress Disturbanc	Street to Address Current e: 0.6 acres;
19. Type of Direct Watershe (Check all that apply)	d:	te not mos te most at :	t at risk		River, stream Urban impa	m or bro ired stre		Coastal wetland Wellhead or public water
19. Name of Waterbody Pro			Long C	reek				
21. Amount of Developed A	rea: Total	acres:	Existing Deve					ed area: 0.21 acres
22. Amount of Impervious	Area: Total	acres:	Existing Imper	vious are	eas: 3.45 acre	es New	v Impervio	ous area: 0.0 acres
23. Development started pr			W	Yes No				
24. Development or any polaction?	rtion of the	site subje	ect to enforcement	1	⊠ No		ne of enfor	rcement staff involved?
25. Common scheme of dev	elopment?	∏ Yes ⊠ No	26. Title, Right	or Inter		ease		purchase option written agreement
27. Natural Resources Prot	ection Act		quired?:	☐ Yes ⊠ No	1 "	□ P:	BR 🗌	Tier 1 Full Permit Tier 2
28. Existing DEP Permit nu				-W-M				
29. Names of DEP staff per at the pre-application meet	rson(s) pres	ent Bill B	ullard; Ben Viola	. —				
30. Does agent have an in	terest in		Yes No					
project? If yes, what is			ING AND SIGNAT	CHIPES 1	LOCATED	ON PAC	GE 2	

IMPORTANT: IF THE SIGNATURE BELOW IS NOT THE APPLICANT'S SIGNATURE, ATTACH LETTER OF AGENT AUTHORIZATION SIGNED BY THE APPLICANT.

CERTIFICATIONS / SIGNATURES

"I certify under penalty of law that I have personally examined the information submitted in this document and all

By signing below the applicant (or authorized agent), certifies that he or she has read and understood the following:

ased on my inquiry of those individuals immediately responsible for obtaining the ation is true, accurate, and complete. I am aware there are significant penalties for uding the possibility of fine and imprisonment. I authorize the Department to enter the application, at reasonable hours, including buildings, structures or conveyances on the
cy of any information provided herein.
ASSISTANT FACILITIES
Title MANAGER Date: 3/18/09
this Site Law application form and my signature, I am filing notice of my intent to carry ork which meets the requirements of the Maine Construction General Permit (MCGP). I read and will comply with all of the MCGP standards.
s form is not being signed by the landowner or lessee of the property, attach mentation showing authorization to sign.
ed C. te 101 Date: 3/18/89
CERTIFICATION aring this application and/or attaching pertinent site and design information hereto, by application for development approval is complete and accurate to the best of his/her
Re/Cert/Lic No.:
Engineer 10683
P.E. Geologist Soil Scientist
3011 3Cleriust
Land Surveyor
Soil Scientist Land Surveyor Site Evaluator
Active Member of the Maine Bar
Site Evaluator

SITE PRE-APPLICATION MEETING SUMMARY

	DATE: 2-11-09
I	PROJECT NAME: Portland Jetport - REMOTE PARKING 10+ OF R+ 22
	PROJECT LOCATION:
	APPLICANT: CITY OF PORTLAND
ı	CONSULTANT/FIRM: Stanfec - DAJE NADEAU D. HOFFWAR DWGlet Androse
	DEP PROJECT MANAGER: DWV V V V V V V V V V V V V V V V V V V
	OTHER PARTICIPANTS: Artie Sewall - PHD Jeffort
	Jan Viols
	Check any sections discussed in detail at the pre-application meeting and describe any relevant issues or requirements conveyed to the applicant. All information requested in the
	application should be submitted <u>unless otherwise noted below:</u>
	La CO IS THE MAN ISSUED FOR
	□ Section 1. Project Description
	TEMPORARY USE OF PARKING LOT IN 2001. 3.5 WELL
	Section 1. Project Description #_ 13760-18-W-M 1550ED FOR TEMPORARY USE OF PARKING LOT IN 2001. 3.5-acm. LOT Applicant proposes to make permanent use of Lot -
	Section 2. Title, right, of interest
	(Deed) Property is ownED By City Page: 2607
	□ Section 3. Financial Capacity Constr ESTUMATE N \$230,600
-0	3
provide	FUNDING DETAILS THRUS CITY
	□ Section 4. Technical Ability / Resource in farmation
	2 Codion in technical state of the state of
	Section 5. Noise (require submission only if applicable)
	☐ Section 6. Visual Quality & Scenic Character / - WARRATIVE

	Section 7. Wildlife & Fisheries - Letter (from fite?)
3 9	Section 8. Historic Sites - letter (from files?)
	Section 9. Unusual Natural Areas - See Move
	tion 10. Buffers – NA
	Section 11. Soils - / TEST PIT IN PORCH AREA + STORM TREAS FILE MATERIAL ON SITE areas FILE MATERIAL OF pand / STORMFORT
	Section 12. Stormwater management
	Basic standards:
	General standards: V 7 Stolen The Ab UNITS
	Flooding standard: 1 yes 2-10-25 42 Pre & Post Dear
	Urban Impaired Stream standard: V Long Creek (18 18514 18 1665)
	Other standards, if applicable 10 kg
☐ apj	Section 13. Maintenance of common facilities or property (require submission if policable) yes - maintenance plan by Jetport STAFF
	Section 14: Erosion & sedimentation control - 45

	Section 15: Groundwa	ater NA
	Section 16: Water sup	pply NA
	Section 17: Wastewat	ter disposal NA
	Section 18: Solid Was	ste - SMALL AMT OF WOOD WASTE -OLD SW DEVICES
	Section 19: Flooding	- 168 IN FLOOD ZONE
	Section 20: Blasting(require submission only if applicable)
	Section 21: Air emiss	sions(require submission only if applicable) NA
	Sections 22, 23, and 2	24: Odors, water vapor, and sunlight (require submission if
sı	Section 25: Notices (ubmission)	(required to be published within 30 days prior to application yes - ABUTTERS, PUBLIC POTICE IN PARE
Α	dditional Notes:	

Preapplication Meeting Notes Site Location of Development Last Revised: March 1, 2006

ADDITIONAL INFORMATION:
Will an NRPA permit be required for the proposed development? YesNo
Was the applicant/agent informed of the current application fee?Yes No
Was the applicant/agent informed of the maximum and probable processing time?
Was the applicant/agent supplied with the current MCGP standard booklet? ルチ Yes No

TO THE APPLICANT:

PLEASE INSURE THAT ALL PLANS AND REPORTS ARE STAMPED AND SIGNED BY THE APPROPRIATE PROFESSIONAL.

PLEASE ENSURE THAT, WITHIN THIRTY DAYS PRIOR TO FILING, A NOTICE OF INTENT TO FILE IS MAILED BY CERTIFIED MAIL TO ABUTTERS AND THE MUNICIPAL OFFICE, AND PUBLISHED ONCE IN A LOCAL NEWSPAPER.

A PUBLIC INFORMATION MEETING, HELD BY THE APPLICANT, IS REQUIRED BEFORE THE SUBMISSION OF ALL NEW SITE LOCATION APPLICATIONS EXCEPT FOR RESIDENTIAL SUBDIVISIONS WITH 20 OR FEWER DEVELOPABLE LOTS.

THIS SUMMARY IS BASED ON THE INFORMATION PRESENTED TO THE DEPARTMENT IN THE MEETING. NEW OR ADDITIONAL INFORMATION MIGHT REQUIRE THE COMMENTS TO BE CHANGED OR SUPPLEMENTED.

WHEN THE APPLICATION IS READY FOR SUBMISSION, PLEASE CONTACT THE PROJECT MANAGER TO ARRANGE FOR A PRE-SUBMISSION MEETING. PRE-SUBMISSION MEETINGS ARE MANDATORY FOR ALL APPLICATIONS FOR WHICH A PRE-APPLICATION MEETING HAS BEEN HELD, UNLESS WAIVED IN WRITING BY THE DEPARTMENT AND AS AGREED TO BY THE APPLICANT.

SUBMISSIONS CHECKLIST

If a provision is not applicable, put "NA"

	Section 1. Development description
	A. Narrative
\frac{1}{\sqrt{1}}	Objectives and details
	Existing facilities (with dates of construction)
-	B. Topographic map
	 Location of development boundaries
	2. Quadrangle name
	C. Construction plan
	Outline of construction sequence (major aspects)
	2. Dates
	D. Drawings
	Development facilities
	a. Location, function and ground area
NA	b. Length/cross-sections for roads
	2. Site work (nature and extent)
	3. Existing facilities (location, function ground area and floor area)
	4. Tonography
VA VA V	 Topography a. Pre- and post-development (contours 2 ft or less)
	a. Pre- and post-development (contours 2 it of less)
	 b. Previous construction, facilities and lot lines
\int	Section 2. Title, right or interest (copy of document)
	obotion at this, right of interest (copy of accumum,
	Section 3. Financial capacity
1	A. Estimated costs
	B. Financing
\int	Letter of commitment to fund
<u></u>	2. Self-financing
NA	a. Annual report
NA NA	b. Bank statement
	3. Other
NA	a. Cash equity commitment
NO	b. Financial plan
NIA	c. Letter
20 20 20 20 20 20 20 20 20 20 20 20 20 2	4. Affordable housing information
1017	4. Allordable flousing information
	Section 4. Technical ability (description)
J.	A. Prior experience (statement)
	B. Personnel (documents)
	b. Tersonner (documents)
	Section 5. Noise
NA	A. Developments producing a minor noise impact (statement)
	Residential developments
	Certain non-residential subdivisions
	Schools and hospitals
+	Other developments
+	a. Type, source and location of noise
+	• •
-	b. Uses, zoning and plans c. Protected locations
<u>¥</u> _	d. Minor nature of impact

NA	e. Demonstration
	B. Developments producing a major noise impact (full noise study)
	1. Baseline
	a. Uses, zoning and plans
	b. Protected locations
	c. Quiet area
	2. Noise generated by the development
	a. Type, source and location of noise
	b. Sound levels
	c. Control measures
+	d. Comparison with regulatory limits
4	e. Comparison with local limits
	Section 6. Visual quality and scenic character(narrative, description, visual impact analysis)
	Section 7. Wildlife and fisheries (narrative)
$\sqrt{}$	Section 8. Historic sites (narrative)
	Section 9. Unusual natural areas (narrative)
	Section 10. Buffers
NA	A. Site plan and narrative
+	
	Section 11. Soils
	A. Soil survey map and report
NA	Soil investigation narrative
	2. Soil survey map
	B. Soil survey intensity level by development type
	1. Class A (High Intensity) Soil Survey
	 Class B (High Intensity) Soil Survey Class C (Medium High-Intensity) Soil Survey
	4. Class D (Medium Intensity) Soil Survey
	C. Geotechnical Investigation
NA	D. Hydric soils mapping
	Si vijano sene mapping
_	Section 12. Stormwater management
$\sqrt{}$	A. Narrative
<u> </u>	Development location
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Surface water on or abutting the site Description pends and lakes.
	 Downstream ponds and lakes General topography
- /	5. Flooding
Ť	6. Alterations to natural drainage ways
1	7. Alterations to land cover
	8. Modeling assumptions
	9. Basic standard
<u> </u>	10. Flooding standard
-\	11. General standard
	12. Parcel size 13. Developed area
	14. Disturbed area
_	15. Impervious area
	B. Maps
$\sqrt{}$	1. U.S.G.S. map with site boundaries
1	2. S.C.S. soils map with site boundaries
	C. Drainage Plans (a pre-development plan and a post-development plan)

- 1. Contours
- 2. Plan elements
- 3. Land cover types and boundaries
- 4. Soil group boundaries
- 5. Stormwater quantity subwatershed boundaries
- 6. Stormwater quality subwatershed boundaries
- 7. Watershed analysis points
- 8. Hydrologic flow lines (w/flow types and flow lengths labeled)
- 9. Runoff storage areas
- 10. Roads and drives
- 11. Buildings, parking lots, and other facilities
- 12. Drainage system layout for storm drains, catch basins, and culverts
- 13. Natural and man-made open drainage channels
- 14. Wetlands
- 15. Flooded areas
- 16. Benchmark
- 17. Stormwater detention, retention, and infiltration facilities
- 18. Stormwater treatment facilities
- 19. Drainage easements
- 20. Identify reaches, ponds, and subwatersheds matching stormwater model
- 21. Buffers
- D. Runoff analysis (pre-development and post development)
 - 1. Curve number computations
 - 2. Time of concentration calculations
 - 3. Travel time calculations
 - 4. Peak discharge calculations
 - 5. Reservoir routing calculations
- E. Flooding Standard
 - 1. Variance submissions (if applicable)
 - a. Submissions for discharge to the ocean, great pond, or major river
 - i. Map
 - ii. Drainage plan
 - iii. Drainage system design
 - iv. Outfall design
 - v. Easements
 - b. Insignificant increase
 - i. Downstream impacts
 - c. Submissions for discharge to a public stormwater system
 - i. Letter of permission
 - ii. Proof of capacity
 - ii. Outfall analysis and design (pictures)
 - 2. Sizing of storm drains and culverts
 - 3. Stormwater ponds and basins
 - a. Impoundment sizing calculations
 - b. Inlet calculations
 - c. Outlet calculations
 - d. Emergency spillway calculations
 - e. Subsurface investigation report
 - f. Embankment specifications
 - g. Embankment seepage controls
 - h. Outlet seepage controls
 - i. Detail sheet
 - i. Basin cross sections
 - k. Basin plan sheet
 - 4. Infiltration systems
 - a. Well locations map
 - b. Sand and gravel aquifer map

- c. Subsurface investigation report with test pit or boring logs
- d. Permeability analysis
- e. Infiltration structure design
- f. Pollutant generation and transport analysis
- g. Monitoring and operations plan
 - Locations of storage points of potential contaminants
 - ii. Locations of observation wells and infiltration monitoring plan
 - iii. Groundwater quality monitoring plan
- Drainage easement declarations.
- F. Stormwater quality treatment plan peak discharge calculations
 - 1. Basic stabilization plan
 - a. Ditches, swales, and other open channel stabilization
 - b. Culvert and storm-drain outfall stabilization
 - c. Earthen slope and embankment stabilization
 - d. Disturbed area stabilization
 - e. Gravel roads and drives stabilization
 - 2. General Standard
 - a. Calculations for sizing BMP
 - b. Impervious area calculation
 - c. Developed area calculation
 - d. Summary spreadsheet of calculations
 - 3. Phosphorus control plan
 - a. Calculations for the site's allowable phosphorus export
 - b. Calculations for determining the developed site's phosphorus export
 - c. Calculations for determining any phosphorus compensation fees
 - 4. Offset Credits
 - a. Urban impaired stream
 Offset credit calculation
 - b. Phosphorus credit determination
 - i. Location map
 - ii. Scaled plan
 - iii. Title and right
 - iv. Demolition plan
 - v. Vegetation plan
 - vi. Offset credit calculation
 - vii. Calculation for the new allowable export
 - 5. Runoff treatment measures
 - a. structural measures
 - i. Design drawings and specifications
 - ii. Design calculations
 - iii. Maintenance plan
 - iv. TSS removal or phosphorus treatment factor determinations
 - v. Stabilization plan
 - b. Vegetated buffers
 - i. Soil survey
 - ii. Buffer plan
 - iii. Turnout and level spreader designs
 - iv. Deed restrictions
 - 6. Control plan for thermal impacts to coldwater fisheries
 - 7. Control plan for other pollutants
 - 8. Engineering inspection of stormwater management facilities
- G. Maintenance of common facilities or property
 - 1. Components of the maintenance plan
 - A. Maintenance of facilities by owner or operator
 - 1. Site owner or operator (name legally responsible party)

ty estrictions k er estrictions ility ict
estrictions k er estrictions ility cict
estrictions k er estrictions ility cict
estrictions k er estrictions ility cict
k estrictions ility : ict
estrictions ility cict
estrictions ility : ict
estrictions ility : ict
ility : ict lity
ility : ict lity
ility : ict lity
: ict lity
: ict lity
lity
lity
lity
lity
lity estrictions
lity estrictions
lity estrictions
lity estrictions
estrictions

	Protected natural resources
-	
	6. Site stabilization
<u></u>	B. Implementation schedule
J	C. Erosion and sediment control plan
_	Pre-development and post-development contours
	2. Plan scale and elements
<u>~</u>	3. Land cover types and boundaries
	4. Existing erosion problems5. Critical areas
<u> </u>	6. Protected natural resources
	7. Locations (general)
	8. Locations of controls
	9. Disturbed areas
	10. Stabilized construction entrance
<u> </u>	D. Details and specifications (for both temporary and permanent measures)
<u> </u>	E. Design calculations
	F. Stabilization plan 1. Temporary seeding
	Permanent seeding
~	3. Sodding
-	4. Temporary mulching
	5. Permanent mulching
	G. Winter construction plan
	Dormant seeding Winter and bling
	Winter mulching H. Third-party inspections
	Inspector's name, address, and telephone number
	2. Inspector's qualifications
J	3. Inspection schedule
	4. Contractor contact
	5. Reporting protocol
	Section 15. Groundwater
10	A. Narrative
NA	Location and maps
	2. Quantity
_	3. Sources
	4. Measures to prevent degradation
	B. Groundwater protection plan
	C. Monitoring plan
	Monitoring points
	Monitoring frequency
	Background conditions
	4. Monitoring parameters
	5. Personnel qualifications
-	6. Proof of training7. Equipment and methods
+	Requipment and methods Requipment and methods Requipment and methods Requipment and methods Requipment and methods
	9. Reporting requirements 9. Reporting requirements
+	10. Remedial action plan
+	D. Monitoring well installation report
1	Well location map
+	2. Elevation data
	3. Well installation data
	4. Well construction details
V	5. Borehole logs

NA H	 6. Summary of depth measurements 7. Characteristics of subsurface strata 8. Well installation contract 9. Schematic cross-sections 10. Monitoring point summary table 11. Protective casing 12. On-site well identification
NA H	Section 16. Water supply A. Water supply method 1. Individual wells (evidence of sufficient/healthful supply) a. Support of findings by well drillers b. Support of findings by geologist 2. Common well(s) (reports) a. Hydrogeology report b. Engineering report c. Well installation report d. Long-term safe yield and zone of influence determination e. Public water supply i. Proposed well or wells ii. Existing well or wells iii. Water quality analysis 3. Well construction in shallow-to-bedrock areas 4. Additional information 5. Off-site utility company or public agency 6. Other sources B. Subsurface wastewater disposal systems (locations of systems and wells) C. Total usage (statement re: total anticipated water usage)
NA H	Section 17. Wastewater disposal A. On-site subsurface wastewater disposal systems (investigation results) 1. Site plan 2. Soil conditions summary table 3. Logs of subsurface explorations 4. Additional test pits, borings or probes a. Soil conditions A b. Soils with Profiles 8 and 9 parent material c. Soil conditions D d. Disposal field length 60 feet or greater 5. 3-bedroom design 6. Larger disposal systems a. System design details b. Plan view c. Cross sections
	d. Test pit data e. Mounding analysis B. Nitrate-nitrogen impact assessment 1. When required a. Exempted i. Conventional systems meeting certain setbacks ii. Denitrification systems b. Special conditions and other exemptions 2. Assumptions a. Initial concentration b. Background concentration c. Contribution from development

NA H	d. Mixing and dilution e. Severe-drought scenario f. Wastewater flow to subsurface wastewater disposal fields 3. Assessment report minimum requirements a. Narrative and calculations b. Site plan i. Well locations ii. 10 mg/l and 8 mg/l isocons iii. Groundwater contours and groundwater flow divides c. References 4. Denitrification systems a. Design plans and specifications b. Installation information c. Monitoring plan d. Maintentance e. Backup system D. Municipal facility or utility company letter E. Storage or treatment lagoons
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	Section 18. Solid waste (list: type, quantity, method of collection and location) A. Commercial solid waste facility (final disposal location) B. Off-site disposal of construction/demolition debris (final disposal location) C. On-site disposal of woodwaste/land clearing debris 1. Applicability of rules (evidence re: applicability of rules) 2. Burning of wood wastes a. Delineation on site plan b. Plans for handling unburned woodwaste and woodash c. Evidence of capacity to accept waste (approved facility) d. Usage of materials e. Data on mixing ratios and application rates D. Special or Hazardous Waste
NA T	Section 19. Flooding A. Explanation of flooding impact B. Site plan showing 100-year flood elevation C. Hydrology analysis D. FEMA flood zone map with site boundaries
NA NA	Section 20. Blasting A. Site Plan or map B. Report 1. Assessment 2. Blasting plan
<u>NA</u> NB	Section 21. Air emissions (narrative and summary) A. Point and non-point sources identified B. Emission components (point sources)
NA NA NA	Section 22. Odors A. Identification of nature/source B. Estimate of areas affected C. Methods of control)
NA	Section 23. Water vapor (narrative)
NA	Section 24. Sunlight (statement and drawing, if required)

Section 25. Notices A. Evidence that notice sent B. List of abutters for purposes of notice

Supplimental requirements for Wind Energy Developments only:

Section 26. Shadow flicker

A. A copy of the Windpro Anaylsis and associated narrative

Section 27. Public Safety

A. Design safety certifications or other documents attesting to the safety of the wind turbine equipment.

B. Evidence pertaining to overspeed controls

C. Site plan documenting safety setbacks zones for each wind turbine

B. Other documents as necessary to demonstrate safety considerations

Section 28. Tangible Benefits

NA Narrative demonstration of tangible benefits

Section 29. Decommissioning

A. Description of implementation trigger for decommissioning

B. Description of extent of decommissioning

NAC. Itemization of total cost to complete decommissioningD. Demonstration of financial assurance for completeness of decommissioning plan

Section 30. Generating Facility-visual Quality and Scenic Character

NA (narrative, description, visual impact analysis)



STATE OF MAINE DEPARTMENT OF ENVIRONMENTAL PROTECTION 17 STATE HOUSE STATION AUGUSTA, MAINE 04333

ANGUS S. KING, JR.

DEPARTMENT ORDER

IN THE MATTER OF

CITY OF PORTLAND)	SITE LOCA	ATIC	ON OF		
DEVELOPMENT						
Portland, Cumberland County)					
JETPORT TEMPORARY PARKING LOT)	MODIFICAT	COL	I		
L-13760-18-W-M (approval))	FINDINGS	OF	FACT	AND	ORDER

Pursuant to the provisions of 38 M.R.S.A. Sections 481 $\underline{\text{et}}$ $\underline{\text{seq.}}$, the Department of Environmental Protection has considered the application of the CITY OF PORTLAND with the supportive data, agency review comments, and other related materials on file and FINDS THE FOLLOWING FACTS:

- 1. In Department Order #L-13760-18-A-N, dated October 9, 1987, the Department approved existing post-1970 improvements at the Portland International Jetport as described in Finding 1 of that Order, and a 29 lot commercial subdivision on a 763 acre parcel of land between Congress Street and Johnson Road in the City of Portland. The Department has approved a number of expansions and modifications to the Jetport in subsequent Orders. Department Order #L-13760-18/31-J-A, dated November 26, 1996, approved the relocation of the existing access road from Johnson Road and the construction of a new access road from Congress Street to the existing Jetport loop road. In Department Order #L-13760-18-R-A, dated February 16, 2001, the Department approved a five year improvement program at the jetport with a planning permit.
- The applicant proposes to construct a temporary parking lot to be used during construction of the parking garage and other airport improvements. The parking lot will have approximately 3% acres of impervious area and it is located on outer Congress Street adjacent to the Portland snow dump. There are numerous wetlands on the project site but they will not be impacted by the parking lot.
- 3. The applicant submitted a stormwater management plan and a erosion and sedimentation control plan for the proposed project which were reviewed by the Division of Watershed Management of the Bureau of Land and Water Quality (DWM). Stormwater quantity will increase off the project site, but the increase will be on to other land owned by the applicant, prior to the stormwater's discharge into Long Creek. The applicant will meet stormwater quality standards by utilizing a Vortech System, Model 16000. DWM has stated that the stormwater management plan and the erosion and sedimentation control plan submitted by the applicant meet Department standards.
- 4. No other issues have been identified.



2 of 3

5. Based on its review of the application, the Department finds the requested modification to be in accordance with all relevant Departmental standards. All other findings of fact, conclusions and conditions remain as approved in Department Order #L-13760-28-A-N, and subsequent orders.

BASED on the above findings of fact, and subject to the conditions listed below, the Department makes the following conclusions pursuant to 38 M.R.S.A. Sections $481 \ \underline{\text{et}} \ \underline{\text{seq.}}$:

- A. The applicant has provided adequate evidence of financial capacity and technical ability to develop the project in a manner consistent with state environmental standards.
- B. The applicant has made adequate provision for fitting the development harmoniously into the existing natural environment and the development will not adversely affect existing uses, scenic character, air quality, water quality or other natural resources in the municipality or in neighboring municipalities.
- C. The proposed development will be built on soil types which are suitable to the nature of the undertaking and will not cause unreasonable erosion of soil or sediment nor inhibit the natural transfer of soil.
- D. The proposed development meets the standards for storm water management in Section 420-D and the standard for erosion and sedimentation control in Section 420-C.
- E. The proposed development will not pose an unreasonable risk that a discharge to a significant groundwater aquifer will occur.
- F. The applicant has made adequate provision of utilities, including water supplies, sewerage facilities, solid waste disposal and roadways required for the development and the development will not have an unreasonable adverse effect on the existing or proposed utilities and roadways in the municipality or area served by those services.
- G. The activity will not unreasonably cause or increase the flooding of the alteration area or adjacent properties nor create an unreasonable flood hazard to any structure.

THEREFORE, the Department APPROVES the application of the CITY OF PORTLAND to construct a temporary parking lot, SUBJECT TO THE FOLLOWING CONDITIONS a

- 1. The Standard Conditions of Approval, a copy attached.
- 2. In addition to any specific erosion control measures described in this or previous orders, the applicant shall take all necessary actions to ensure that its activities or those of its agents do not result in noticeable erosion of soils or fugitive dust

emissions on the site during the construction and operation of the project covered by this approval.

3. All other Findings of Fact, Conclusions and Conditions remain as approved in Department Order #L-13760-18-A-N, and subsequent orders, and are incorporated herein.

DONE AND DATED AT AUGUSTA, MAINE, THIS 26 DAY OF June, 2001.

DEPARTMENT OF ENVIRONMENTAL PROTECTION


By:

MARTHA G. KIRKPATRICK, COMMISSIONER

PLEASE NOTE THE ATTACHED SHEET FOR GUIDANCE ON APPEAL PROCEDURES...

Date of initial receipt of application 5-7-01 Date of application acceptance 5-16-01

Date filed with Board of Environmental Protection LK/L13760WM



STANDARD CONDITIONS

STRICT CONFORMANCE WITH THE STANDARD AND SPECIAL CONDITIONS OF THIS APPROVAL IS NECESSARY FOR THE PROJECT TO MEET THE STATUTORY CRITERIA FOR APPROVAL.

- 1. This approval is dependent upon and limited to the proposals and plans contained in the application and supporting documents submitted and affirmed to by the applicant. Any variation from the plans, proposals and supporting documents is subject to the review and approval of the Board prior to implementation. Further subdivision of proposed lots by the applicant or future owners is specifically prohibited, without prior approval by the Board of Environmental Protection, and the applicant shall include deed restrictions to this effect.
- 2. The applicant shall secure and comply with all applicable Federal, State and local licenses, permits, authorizations, conditions, agreements, and orders, prior to or during construction and operation as appropriate.
- 3. The applicant shall submit all reports and information requested by the Board or Department demonstrating that the applicant has complied or will comply with all conditions of this approval. All preconstruction terms and conditions must be met before construction begins.
- 4. Advertising relating to matters included in this application shall refer to this approval only if it notes that the approval has been granted WITH CONDITIONS, and indicates where copies of those conditions may be obtained.
- 5. Unless otherwise provided in this approval, the applicant shall not sell, lease, assign or otherwise transfer the development or any portion thereof without prior written approval of the Board where the purpose or consequence of the transfer is to transfer any of the obligations of the developer as incorporated in this approval. Such approval shall be granted only if the applicant or transferee demonstrates to the Board that the transferee has the technical capacity and financial ability to comply with conditions of this approval and the proposals and plans contained in the application and supporting documents submitted by the applicant.
- 6. If the construction or operation of the activity is not begun within two years, this approval shall lapse and the applicant shall reapply to the Board for a new approval. The applicant may not begin construction or operation of the development until a new approval is granted. Reapplications for approval shall state the reasons why the development was not begun within two years from the granting of the initial approval and the reasons why the applicant will be able to begin the activity within two years from the granting of a new approval, if granted. Reapplications for approval may include information submitted in the initial application by reference.
- 7. If the approved development is not completed within five years from the date of the granting of approval, the Board may reexamine its approval and impose additional terms or conditions or prescribe other necessary corrective action to respond to significant changes in circumstances which may have occurred during the five-year period.
- 8. A copy of this approval must be included in or attached to all contract bid specifications for the development.
- 9. Work done by a contractor pursuant to this approval shall not begin before the contractor has been shown by the developer a copy of this approval.

(2/81)/Revised November 1, 1979

1.0 DEVELOPMENT DESCRIPTION (Site Location Section 1)

The city of Portland, Maine (the applicant) is filing a Minor Amendment application pursuant to the Site Location of Development Act, Title 38, M.R.S.A. Section 481-490 for proposed improvements at the Portland International Jetport.

1.1 PROJECT LOCATION

The project site is located at the Portland International Jetport's remote parking lot on outer Congress Street, in the city of Portland, Cumberland County. The site is approximately 1,600 feet west of Interstate 95, 300 feet north of the South Portland city line, and 2,000 feet east of the Westbrook city line. The site is entered by the access road for the city of Portland's snow dump facility. Refer to Figure 1.1 included in this section for the project location identified on the USGS quadrangle map for Portland - West, Maine.

The area of proposed disturbance at the site is adjacent to the southern edge of the existing parking lot in an area that is currently covered by grass. An existing stormdrain system and Vortech water quality unit are currently located in the area. It is bounded to the east and southeast by a large freshwater wetland system that drains to Long Creek, and to the west and southwest by the existing access road. Refer to Figure 1.2 included in this section for the project location identified on an aerial photograph.

1.2 PROJECT DESCRIPTION

The existing facility consists of a paved automobile parking lot approximately 3.5 acres in size. The development was permitted and constructed in 2001 under permit no. L-13760-18-W-M as a temporary parking facility for use during construction of a parking garage and associated improvements at the Portland International Jetport. It was originally intended that the parking lot would be used to offset the temporary loss in parking capacity during construction of the garage improvements, and then be removed at the completion of the garage project. The site was anticipated to be returned to a natural vegetated condition.

In the ensuing period, there has been additional growth at the Jetport which has required the continued use of the parking lot during peak parking demand periods. The applicant is therefore now proposing to change the status of the lot from temporary to permanent status for continued use as overflow parking. The original development design and permitting completed in 2001 addressed the Site Law standards in effect at the time. Discussions with MDEP staff have indicated that due to the proposed change in status of the facility, the current standards for Site Law, specifically the changes to Chapter 500 Stormwater Management must now be addressed.

In order to meet the current stormwater standards, the existing stormwater management system will be upgraded. The existing system consists of a series of catch basins and stormdrains that


Stantec PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT

DEVELOPMENT DESCRIPTION (Site Location Section 1)
March 13, 2009

collect runoff and discharge it through a Vortech water quality unit. Since Vortech units no longer meet MDEP's requirements for water quality (other than for pre-treatment), upgrade to meet current standards will consist of removal of the existing Vortech water quality device, and installation of 11 StormTreat bio-filter chambers. To ensure that peak rates of runoff for the post development condition do not exceed the pre development rates (prior to 2001), a dry detention basin will be constructed. Other than these drainage improvements, no expansions or redevelopment of the parking facility are proposed. No impacts to wetlands or other protected resources are proposed.

1.3 PROJECT SCHEDULE / CONSTRUCTION PLANS

Preliminary construction plans indicating the proposed improvements are included in the appendix at the back of this application. Construction and final stabilization of the proposed improvements are currently proposed for the summer / fall of 2009.





Stantec Consulting Services Inc.

22 Free Street, Suite 205 Portland ME U.S.A. 04101-3900

Tel. 207.775.3211 Fax. 207.775.6434

www.stantec.com

PORTLAND INT. JETPORT IMPROVEMENTS TO REMOTE LOT

Figure No.

Title

LOCATION MAP







remote lot loc File: photo.dwg January 2009 195210313



Stantec

Stantec Consulting Services Inc.

22 Free Street, Suite 205 Portland ME U.S.A. 04101-3900

Tel. 207.775.3211 Fax. 207.775.6434

www.stantec.com

Client/Project

PORTLAND INT. JETPORT IMPROVEMENTS TO REMOTE LOT

Figure No.

1.2

Title

LOCATION PHOTO

2.0 TITLE, RIGHT OR INTEREST (Site Location Section 2)

The applicant possesses all title, right and interest in the project property. A copy of the deed for the property parcel, reference Book 2457, Page 262 is included in this section.

MAP KEY No.26

PARCELS DATA SHEET

GRANTOR: Edward S. Finks et. als. TO GRANTEE: City of Portland

TYPE OF INSTRUMENT:

Warranty Deed

DEED REFERENCE:

Book 2457 Page 262 DATE:

02/13/59 Instrument 02/13/59 Acknowledged


02/13/59 Recorded

AREA:

Acres + or -

Except deed to Portland Water District, B.2383, P.121.

REMARKS:



Know all Men by these Presents. That

We, Edward S. Finks and Dowthy L. Finks, of Portland, in the County of Cumberland and State of Maine in consideration of one dollar and other valuable consideration paid by the City of Portland, a body politic and corporate, located in said County and State.

the receipt whereof we do hereby acknowledge, do hereby give, grant, burgain, sell and convey unto the said City of Portland, its successors and assigns, the following described parcel of land with the buildings thereon located on the southeasterly side of Congress Street, formerly known as the County Road, leading to Suxton, and the morthwesterly side of the Payne Road, being partly in said Portland and parcly in South Portland, and bounded and described as follows: the southerly side of Congress Street, formerly County Road, leading from Corham to Portland, at the northeasterly corner of lead formerly belonging to one Bailey, later of McInnes; thence running southwest by said Bailey land seventeen hundred sixty (1760) feet to a stake and corner Serioning on seventy (1270) feet to a stake and corner at land formerly of W. F. Dresser, now of the Crosby heirs; thence northeast by said Dresser land ten bundred thirty-three (1033) feet to a stake and corner; thence southeast by said Dresser land twenty-one hundred thirty-five (2135) feet, more or less, to land of Maine Turnpike Authority; thence mortherly by a curving line by said Maine Turnpike less, to land of Maine Turnpike Authority; thence northerly by a curving line by said Maine Turnpike Authority land twelve hundred forty-four and seventy-four bundredths (1244.74) feet to land of Frank P. Cummings' heirs; thence northwesterly by said Frank P. Cummings' heirs land twenty-one hundred niaety-six (2196) feet, more or less, to said Congress Street; thence westerly by said Congress Street eleven hundred twenty (1120) feet, more or less, to the point of beginning, excepting therefrom the following described parcel of land conveyed by the Grantors to the Portland Water District by warranty deed, dated November 17, 1957, and recorded in Cumberland County Registry of Deeds in Book 2383, Page 121: Beginning at a point on the dividing line between land of the Grantors and land of Maine Turnpike Authority, said point being two hundred eighty-three and three tenths (283.3) feet southwesterly along said dividing line from the intersection of said and three tenths (283.3) feet southwesterly along said dividing line from the intersection of said dividing line and land now or formerly of Frank P. Commings, (1) Thence North 56°18' West one hundred twenty-four and seventeen hundredths (124.17) feet to a point; (2) thence North 19 535' West cleven hundred eighty-three and fifty-nine hundredths (1183.59) feet to said Cummings land; West eleven hundred eighty-three and fifty-nine hundredths (1183.59) feet to said Cummings land;

(3) thence northwesterly by said Cummings land three hundred fourteen and five hundredths (314.05) feet to a point; (4) thence South 120514 East on a line parallel with and seventy-five (75) feet distant from the second course above mentioned, a distance of sixteen hundred twenty-nine and vith and one hundred and fifty (150) feet to a point; (5) thence South 56018 East on a line parallel Maine Turnpike Authority land; (6) thence mortheasterly by said Maine Turnpike Authority land; (6) thence mortheasterly by said Maine Turnpike Authority land one hundred and fifty (150) feet, more or less, to the point of beginning.

The land of the said the said frame to the Grantore all rights; wasements; and privileges reserved to the Grantore Being the same premises conveyed to during the Main of the said frame the said fram

Being the same premises conveyed to drantors herein by Valter g. Korzeniewski et al dated June 26, 1951, recorded in Comberland County Registry of Peeds in Book 2051, Page 147 except as otherwise herein excepted.

To Have and to Hold the aloregranted and bargained premises, with all the privileges and appurenances thereof, to the said City of Purtland, its successors

steems and assigns, to its and their use and behoof forever. And we do its successors covenant with the said Grantee hatom and assigns, that we are at we are lawfully seried in fee of the premises; that they are tree of all incumbrances good right to sell and convey the same to the said Granies to hold as aloresaid; and that we and our same to the said Grantee . Its successors where and assigns forever, squimt the lawful claims and demands of all persons. helps and sasigns shall and will warrant and defend the In Witness Whereof. We. Edward S. Finks and Dorothy L. Finks , husband and wife

joining in this deed as Grantors and relinquishing and conveying all rights by descent and all other manney health and the description of the latter of the in the year of our Lord one thousand nine hundred and fifty-nine.

State of Maine. County of Cumberland Personally appeared the above named Eduard S. Finks and Dorothy L. Finks February 13. 19 59 .

and acknowledged the largoing in ed w ha their two act and doed.

..... Justice of the Peace.

STATE OF MAINE CUMBERLAND COUNTY, SS.

REJISTRY OF DUEDS Received FEB 1 3 1959 al 3 o'clock 55 mm 11 BOOK 145-7 PAGE 162

Min and recorded





3.0 FINANCIAL CAPACITY (Site Location Section 3)

3.1 PROJECT FUNDING

The City of Portland will be funding the proposed drainage improvement project under the existing Portland City Council approval for the Phase II Parking Garage project that is currently being constructed. The City Council appropriated funds for the project on June 18, 2007 under Order 263-06/07.

3.2 ESTIMATED PROJECT COSTS

The estimated project cost for the remote lot drainage improvements is approximately \$300,000, including permitting, design, and construction costs. Refer to attached *Engineer's Preliminary Opinion of Probable Construction Costs* for a breakdown of the major construction work items. It should be noted that the numbers on the *Engineer's Preliminary Opinion of Probable Construction Costs* form are based on the engineer's estimate of the project cost, and that the actual project cost will be based on the result of a competitive bid process for construction. Should the bid results require a significant change in the proposed project, a revised project description (Section 1) will be forwarded to the MDEP and, if required, an application for a project modification will be filed.

Preliminary Opinion of Probable Construction Costs

Portland International Jetport - Remote Lot Drainage Improvements As of 3/20/09

StormTreat Filter Chambers w/ Detention Pond

Item	Quantity	Unit	Unit Price	Amount
StormTreat Chamber	11	EA	15000	165000
6" HDPE Distribution Line	100	브	30	3000
4" / 2" HDPE Stormdrain	160	占	25	4000
18" HDPE Stormdrain	30	느	50	1500
LL Spreaders	2	EA	1500	3000
DMH / Outlet Riser	-	EA	2000	2000
Erosion Control	_	S	10000	10000
Earthwork	2500	ζ	15	37500
Topsoil, Seed & Mulch	22	MSF	175	3850
Demolition	_	rs	2000	2000
SUBTOTAL				\$237,850
Contingency (15%)				\$35,677.50
TOTAL ALTERNATIVE 2				\$273,527.50

4.0 TECHNICAL ABILITY (Site Location Section 4)

The Portland International Jetport and the remote parking lot are owned and operated by the city of Portland and its agents. The Jetport employs a parking management company (Standard Parking) to run day-to day operations at the remote lot.

The Portland International Jetport has contracted with Stantec Consulting Services Inc. to provide technical expertise for the design, permitting and construction administration of the proposed improvements at the remote parking lot that are detailed within this application. Resumes of key Stantec personnel involved with the project have been included to demonstrate experience and expertise with completing similar projects.

David P. Nadeau PE

Project Manager



Mr. Nadeau's responsibilities include project management and design services on a variety of airport and transportation infrastructure improvement projects. His experience includes civil and airport engineering design; stormwater analyses and drainage system design; environmental and local permitting services; construction administration and inspection services; and topographic and airport obstruction surveys. He also has experience with federal and state grant procedures on a variety of projects.

EDUCATION

Bachelor of Science, Civil Engineering, University of Maine, Orono, Maine, 1999

REGISTRATIONS

Professional Engineer #10683, State of Maine

PROJECT EXPERIENCE

Airports & Aviation

Aircraft Apron Expansion & Alterations to Mitigation Sites, Knox County Regional Airport, Owls Head, Maine

Project engineer responsible for the design of the ± 7.7-acre apron expansion; preparation of pavement design report; amendments to MDEP Site Location Permit and local permits; and design of stormwater management plan. The project also included regrading of wetland mitigation sites to alleviate safety hazards. Responsibilities included CAD drafting, preparation of final plans, and details for all work.

Construction of Aircraft Parking Apron and Reconstruction of Taxiway D, Robert LaFleur Airport, Waterville, Maine

Project engineer responsible for the design for the construction of $a\pm 3.2$ -acre aircraft parking apron expansion. The project also included reconstruction of 1,750 feet of taxiway, design of an automobile parking area, extension of utility service to future hangar facilities, and grading and drainage design for four eight-unit T-hangar facilities adjacent to Taxiway D. Additional responsibilities included preparation of the state environmental permit that included drainage analyses and design of stormwater quality treatment swales.

Construction of Aircraft Rinse Facility, Brunswick Naval Air Station, Brunswick, Maine

Project engineer responsible for the drainage design of de-icing facility consisting of trench drain system with simultaneous storm drain trunk line.

Construction of T-hangars, Lawrence Municipal Airport, North Andover, Massachusetts

Project engineer responsible for the present and future development drainage analyses for the construction of T-hangars.

Drainage Repairs, Claremont Municipal Airport, Claremont, New Hampshire

Project engineer responsible for the drainage analysis, which determined the cause of significant erosion on airport site.

Responsibilities included design of the new storm drain system.

Expansion of Aircraft Parking Apron, Bethel Regional Airport, Bethel, Maine

Project engineer/manager responsible for the design for the 13,200-square yard aircraft parking apron expansion. The project included use of reworked on-site soils as subbase material to reduce project construction costs, a new gravel automobile parking area and access road, relocation of the airport fuel facility, extension of utility services to a new terminal area, and site lighting for the aircraft and automobile parking areas. Additional responsibilities included preparation of the state environmental permit; on-site resident inspection during reconstruction; and coordination with local, state, and federal agencies throughout the life of the project.

David P. Nadeau PE

Project Manager

Expansion of Parking Apron and Reconstruction of Taxiway, Central Maine Regional Airport, Norridgewock, Maine

Project engineer responsible for the preparation of state environmental permit application for the expansion of the aircraft parking apron and reconstruction of the taxiway.

Expansion of Passenger Baggage Claim, Portland International Jetport, Portland, Maine

Project engineer responsible for the site work design and associated planning department permitting for the baggage claim facility expansion project. Design work included relocation and upgrade of existing utility and storm drain systems in highly congested area, as well as security fence and gate relocation along ATC restricted zone.

Obstruction Removal, Grubbing and Grading, Biddeford Municipal Airport, Biddeford, Maine

Project designer for a ± 7-acre vegetation removal project. The project included clearing tree and brush obstructions from FAR Part 77 surfaces and grubbing, grading, and seeding the disturbed areas. Additional duties included preparing the environmental permit applications for the project.

Overlay South A and K Taxiways, Logan International Airport, East Boston, Massachusetts

Resident Inspector for the structural overlay of the south A and K taxiways located in the south terminal area of the airport. Work included the construction of Stub Taxiway K-3 and the installation of associated taxiway guidance signs. Adjacent turf islands were graded and sodded to enhance drainage. In addition, the project adjusted in-pavement taxiway lights, as well as drainage and utility structures. The project was phased to minimize impacts on operations by performing most construction activities during off-peak hours (nights and weekends).

Partial FAR Part 77 Phase 3 Obstruction Removal and Lighting, Dillant-Hopkins Airport, Keene, New Hampshire

Project engineer responsible for the present and future development drainage analyses and assisted in preparation of environmental permits for the obstruction removal project to eliminate penetrations to the FAR Part 77 airspace within the precision instrument approach to Runway 2. The project also included the installation of 5,000 linear feet of chain-link security fence and gates.

Partial Reconstruction and Extension of Runway 14-32, Rangeley Municipal Airport, Rangeley, Maine

Project engineer responsible for the drainage analysis, design of taxiway lighting system, and preparation of project specifications.

Phase I-Parking Garage, Portland International Jetport, Portland, Maine

Project engineer responsible for the grading and drainage design for the new six-story parking garage, access loop road and parking area improvements. The design included a deep gravity storm drain system with stormwater quality unit.

Responsibilities included the preparation of local and environmental permit applications as well as the stormwater discharge permit.

Reconstruction and Expansion of General Aviation Apron, Belfast Municipal Airport, Belfast, Maine

Project designer for the reconstruction of the existing 1.6-acre apron and 2.5-acre apron expansion to accommodate a future development consisting of 29 hangars. The project also included upgrades to the drainage system and preparation of state environmental permits.

Project Manager

Reconstruction and Extension of Runway 14-32, Bethel Regional Airport, Bethel, Maine

Project engineer responsible for the full-depth reconstruction and 900-foot extension of Runway 14-32. Project included clearing of runway approaches, including wetlands, installation of full perimeter security fence, design of subsurface wastewater treatment facility, and replacement of windsock and segmented circle. Also assisted in the preparation of the Site Location Permit amendment application, which included stormwater analysis as well as an erosion and sedimentation control plan. Additional work included full-time inspecting during construction, and surveying approaches to verify removal of all penetrations. Responsibilities included CAD drafting, preparation of final plans, and details for all work.

Reconstruction of Runway 3-21, Knox County Regional Airport, Owls Head, Maine

Project engineer responsible for the design of the partial-depth reconstruction of Runway 3-21, which is a 4,000-foot B-II runway. Project duties included topographic survey of site, conceptual and final design, preparation of Pavement Design Report, and various administrative tasks.

Reconstruction of Taxiway D, Lawrence Municipal Airport, North Andover, Massachusetts

Project engineer responsible for the present and future development drainage analyses for the reconstruction of Taxiway D.

Reconstruction of Taxiway F, Worcester Regional Airport, Worcester, Massachusetts

Project engineer responsible for the present and future development drainage analyses for the reconstruction of Taxiway F.

Reconstruction of Terminal Apron, L.G. Hanscom Field, Bedford, Massachusetts

Project engineer responsible for the grading design for the reconstruction of the terminal apron and associated CAD drafting work.

Replace Medical Facility, Pease Air National Guard Base, Newington, New Hampshire

Project engineer responsible for the grading and storm drain design for the new medical facility site. Also completed and filed the Site Specific Application.

Runway 14-32 Repair, Greenville Municipal Airport, Greenville, Maine

Project engineer responsible for preparation of the contracts, bidding, and grant paperwork. The project involved minor repairs to runway.

T-hangar Development, Bethel Regional Airport, Bethel, Maine

Project and resident engineer responsible for the site grading and drainage design for two four-unit T-hangar facilities adjacent to the aircraft parking apron and construction inspection services.

Upgrade Aircraft Parking Apron, Pease Air National Guard Base, Newington, New Hampshire

Project engineer responsible for the design of the storm drain system, which included use of trench-drains and oil-water separators.

Wetland Mitigation Site A, Knox County Regional Airport

Project engineer responsible for development of the plans and specifications for the mitigation measures to wetland mitigation site.

Mixed-Use

Limerick Business Park, Limerick, Maine

Project manager/designer for a 1,500 foot access road serving 11 business park lots. Work included conceptual design and environmental permitting for the 11 individual lots. Prepared bid documents in compliance with Community Development Block Grant funding of project.

Oxford Hills Business Park Development, Oxford, Maine

Project engineer responsible for the topographic survey for the preliminary design of a future commercial business park.

David P. Nadeau PE

Project Manager

Sports, Recreation & Leisure

Trail and Base Lodge Area Improvements, Big Rock Ski Area, Mars Hill, Maine

Project engineer responsible for the preparation of state environmental permit application for the trail and base lodge improvements.

Urban Land

Waterville Business Park Subdivision Plan Review, Waterville, Maine

Project engineer responsible for the drainage analysis and stormwater management plan of the Waterville Airport Business Park Subdivision.

Also prepared drainage plans and performed associated CAD drafting.

Gregg A. Cohen

Senior Environmental Analyst



Mr. Cohen has experience with environmental regulations and permitting, as well as conducting field assessments and evaluating natural resources. He acts as a coordinator with various environmental agencies to identify issues of concern and other relevant factors as they relate to Environmental Assessments, Airport Master Plan Updates, and the project planning process.

EDUCATION

M.S., Resource Management and Administration, Antioch New England Graduate School, Keene, New Hampshire, 2000

B.A., English, University of Alaska, Anchorage, Alaska, 1994

Certification of US Army Corps of Engineers Wetland Delineation Methodology, University of New Hampshire, Durham, New Hampshire, 2005

ACC/ACI - NA/FAA Airport NEPA Training Course, FAA's New Order 5050.4B for Airport Actions, Alexandria, Virginia, 2006

PROJECT EXPERIENCE

Airports & Aviation

Airport Master Plan Update, Wiscasset Municipal Airport, Wiscasset, Maine

Environmental Analyst responsible for preparing environmental review of impacts associated with short-term planning projects for inclusion in the Airport Master Plan Update. Prepared VMP for vegetative obstruction removal project and subsequent vegetation management program implemented by the airport.

Augusta State Airport, Augusta, Maine

Environmental Analyst responsible for preparing VMP to address vegetative obstructions to protected airspace at the airport. VMP included identification of required easements to remove obstructions located off airport property. VMP also included maintenance strategies intended to prevent vegetation at airport from becoming penetrations at some time in the future. Currently preparing Facility SWPPP in accordance with MPDES permitting requirements.

Biddeford Municipal Airport, Biddeford, Maine

Senior Environmental Analyst responsible for preparation of a series of environmental review and compliance documents to assist with the management of environmental issues at the airport. These documents included an Environmental Assessment for runway safety area upgrades, Vegetation Management Plan for a proposed vegetative obstruction removal project and the subsequent vegetation management program to be implemented by the airport, and compilation of a SWPPP in accordance with the Maine Pollutant Discharge Elimination System. Also prepared environmental review of impacts associated with short-term planning projects for inclusion in the Airport Master Plan Update.

Central Maine Regional Airport, Norridgewock, Maine

Prepared an Environmental Assessment for proposed runway safety area improvements, an environmental review of impacts associated with short-term planning projects for inclusion in the Airport Master Plan Update. a Site Location of Development Permit application in accordance with Maine Department of Environmental Protection regulations for upgrades to aircraft apron and taxiway, and Spill Prevention Control and Countermeasure and Stormwater Pollution Prevention plans for the airport.

Dillant-Hopkins Airport

Environmental Analyst responsible for preparation of a Site Specific Permit application for proposed apron expansion. Prepared Site Specific Permit application and Construction SWPPP for vegetation obstruction removal project. Assisted with the completion of Airport Master Plan Update.

Environmental Assessments for Newport and Block Island Airports, Rhode Island

Environmental Analyst responsible for assisting in the preparation of the Environmental Assessments for the two airports. Conducted field work involving wetland delineation and Global Positioning System (GPS) wetland mapping.

Gregg A. Cohen Senior Environmental Analyst

Environmental Permitting and Vegetation Management Plan, L.G. Hanscom Field, Bedford, Massachusetts

Environmental Analyst responsible for assisting in the preparation of environmental permits and VMP associated with obstruction removal project. Conducted field work involving GPS wetland mapping and vegetative sample plotting.

Houlton International Airport

Environmental Analyst responsible for preparing VMP for a proposed vegetative obstruction removal project and the subsequent vegetation management program to be implemented by the airport. Assisted with the preparation of Facility SWPPP for the airport.

Integrated Contingency Plan, New Hampshire Army National Guard (Environmental Analyst)

Prepared ICPs for five New Hampshire Army National Guard installations. ICPs provide each installation with an emergency spill and contingency response plan intended to reduce the potential of a hazardous material spill and establish appropriate response measures in the event of a release of hazardous materials. The ICP conforms to both New Hampshire State and Federal contingency planning requirements.

Knox County Regional Airport Environmental Assessment, Owls Head, Maine

Senior Environmental Analyst responsible for preparing an Environmental Assessment for proposed taxiway construction and runway safety area (RSA) improvements. Prepared NRPA and ACOE wetlands permit applications for impacts associated with taxiway consideration and RSA improvements. Prepared Stormwater Pollution Prevention Plan (SWPPP) for the airport in accordance with National Pollutant Discharge Elimination System requirements. The SWPPP presents pollution prevention techniques and best management practices intended to prevent or reduce the discharge of pollutants in stormwater runoff from the facility.

Prepared Spill Prevention Control and Countermeasure (SPCC) plan for the airport in accordance with Title 40, Code of Federal Regulations, Part 112. The SPCC was prepared in order to prevent any discharge of oil into or upon navigable waters of the United States or adjoining shorelines.

Mt. Washington Regional Airport, Whitefield, New Hampshire

Environmental Analyst responsible for preparing Site Specific Permit application in accordance with New Hampshire Department of Environmental Services regulations for proposed runway extension project. Prepared Facility SWPPP for the airport and assisted with the completion of Airport Master Plan Update.

Northern Aroostook Regional Airport, Frenchville, Maine (Environmental Analyst)

Prepared Facility SWPPP in accordance with MPDES permitting requirements. Prepared SPCC plan for the airport in accordance with Title 40, Code of Federal Regulations, Part 112. The SPCC was prepared in order to prevent any discharge of oil from the facility. Currently assisting with the preparation of a VMP intended to mitigate vegetative obstructions located on and off airport property.

Off-Airport Vegetative Obstruction Removal Design, North Central Airport, Smithfield, Rhode Island

Senior Environmental Analyst responsible for survey within four parcels off airport property to determine tree top elevations. Evaluated data to determine extent of vegetative obstructions to protected airspace and designed tree clearing project proposing six acres of upland and three acres of wetland vegetation to be removed from the four avigation easement areas. Prepared design plans and construction specifications and submitted to FAA for review and approval.

Pease Air National Guard Base, Newington, New Hampshire (Environmental Analyst)

Prepared Stormwater Pollution Prevention Plans for Construction Activities in accordance with NPDES permitting requirements for Phases 1 and 2 of a three-phase apron expansion project.

Gregg A. Cohen Senior Environmental Analyst

Runway Extension and Reconstruction, Bethel Regional Airport, Bethel, Maine

Environmental Analyst responsible for assisting in preparation of an Environmental Assessment for runway extension and reconstruction project. Prepared Site Location of Development Permit application for runway reconstruction and extension. Prepared Storm Water Pollution Prevention Plan for Construction Activities prior to construction of the project. Prepared Spill Prevention Control and Countermeasures Plan for the airport.

Runway Safety Area Upgrade, Auburn-Lewiston Municipal Airport, Auburn, Maine

Environmental Analyst responsible for assisting with the preparation of an Environmental Assessment for runway safety area upgrades. Prepared VMP for vegetative obstruction removal project and subsequent vegetation management program implemented by the airport. Assembled Natural Resources Protection Act (NRPA) Permit application and SWPPP for Construction Activities for RSA upgrade and obstruction removal projects.

Runway Safety Area Upgrade, Belfast Municipal Airport, Belfast, Maine

Environmental Analyst responsible for preparing Environmental Assessment for runway safety area upgrades and proposed vegetative obstruction removal project. Assembled NRPA Permit application for wetland impacts associated with RSA upgrade and obstruction removal projects and prepared SWPPP for Construction Activities for RSA upgrade and obstruction removal projects. Currently preparing VMP and SWPPP for the airport.

Vegetation Management Plan/Herbicide Treatment, Lawrence Municipal Airport, North Andover, Massachusetts

Senior Environmental Analyst responsible for overseeing selective herbicide treatment of approximately 65 acres of vegetation on airport property. Directed herbicide application crew daily with regard to specific application methodologies within designated vegetation management areas (VMAs) as specified in the airport's VMP prepared by Stantec. Project was completed in a three week period and was the initial treatment in the airport's herbicide management program. Success of eradicating target species will be evaluated in early fall 2008. Results of evaluation will be used to assist with the preparation of the next phase of herbicide management.

Wetland Delineations, US Army Corps of Engineers

Environmental Analyst responsible for wetland field delineations conducted in Rhode Island, New Hampshire and Maine. Delineations involved field verification of wetland boundaries, preparing wetland function and value assessments, processing appropriate U.S. Army Corps of Engineers data records and performing GPS mapping of wetland flags.

Andrea Tavares

Project Civil Engineer



A certified Engineer-In-Training, Ms. Tavares has five years experience and is responsible for the coordination and technical support of site engineering projects from initial project formulation through completion of construction. Ms. Tavares has a wide range of project experience but focuses mainly on institutional, commercial, and residential developments.

Ms. Tavares' diverse background in civil engineering includes site engineering, drainage design, hydrology and hydraulics, water resources, sanitary sewer design, and construction phase services. She has been directly involved in bringing projects through local and state permitting agencies, including the Site Plan Approval process with the Boston Water and Sewer Commission.. Ms. Tavares provides her project team with a valuable asset, contributing a full range of civil engineering skills and expertise as well as excellent technological skills. She is proficient in AutoCad 2008, LDD, and HydroCad (stormwater modeling software).

EDUCATION

BS, Civil Engineering, State University of New York, Buffalo, New York, 2003

PROFESSIONAL ASSOCIATIONS

Member, Boston Society of Civil Engineers Section

PROJECT EXPERIENCE

Healthcare

The Mallory Building Renovation, Boston, Massachusetts (Project Civil Engineer)

Civil engineering services for a building which will be renovated into Healthcare for the Homeless. Services include all new utility services for drainage, sewer, gas and electric. Site plan approval was obtained from Boston Water and Sewer Commission.

Multi-Unit / Family Residential

Newbridge on the Charles, Dedham, Massachusetts (Project Civil Engineer)

Project includes approximately 165-acres of development. Involved from the early stages of permitting at a local and state level through engineering design and now construction. Currently responsible for the construction administration of site utilities. Responsible for all stormwater calculations, engineering drawings and details, and continued coordination with project team, contractor and municipal parties.

Sports, Recreation & Leisure

Cronin Memorial Skating Rink, Revere, Massachusetts (Project Civil Engineer)

Project civil engineer responsible for stormwater management and site utilities design for this full service skating rink overseen by the Department of Conservation and Recreation. Low impact stormwater design included: vegetated water quality swale and sediment forebay, and a limited number of drainage structures.

Harvard University Stadium, Boston, Massachusetts (Project Civil Engineer)

Project civil engineer responsible for the design of the stormwater management system for the addition of an artificial turf field and seasonal sport bubble. The stormwater management system included the use of subsurface chambers for the storage of runoff.

Westwood High School Turf Renovation, Westwood, Massachusetts (Project Civil Engineer)

Project civil engineer responsible for field layout, stormwater management design and specifications for the renovation of an artificial turf field with lighting.

5.0 VISUAL QUALITY AND SCENIC CHARACTER (Site Location Section 6)

The proposed improvements will be located adjacent to the existing edge of pavement in a grassed area that slopes down from the parking lot to a brush covered wetland area. The change in elevation is approximately 15 feet. The proposed improvements will require some regrading of the existing slope to construct the dry detention basin. The dry detention basin embankment side slopes will be vegetated in the same manner that exists today. The proposed improvements will not significantly impact the view from off-site properties to the south and east as only the embankment will remain visable. The improvements will only be visable from the north side by users of the parking lot facility when they are adjacent to the detention basin. Therefore, no significant changes to the visual quality or scenic character, as seen from off-site abutting properties are anticipated.

6.0 WILDLIFE AND FISHERIES (Site Location Section 7)

The proposed drainage improvements are located in an area that was previously disturbed during the original construction of the parking lot in 2001. As such, impacts to protected resources are not anticipated as a result of the current project. The Maine Department of Inland Fisheries and Wildlife (IF&W) was contacted to determine the presence of threatened or endangered species and rare or essential habitat on or within the vicinity of the proposed project location. A copy of the correspondence from Stantec Consulting Services Inc. is included within this section. A copy of the response from IF&W will be forwarded to the Department upon receipt.



Stantec Consulting Services Inc. 22 Free Street Suite 205 Portland ME 04101-3900 Tel: (207) 775-3211

Fax: (207) 775-6434

February 25, 2009

Ms. Judy Walker, Assistant Regional Wildlife Biologist Maine Department of Inland Fisheries and Wildlife Wildlife Division, Region A 358 Shaker Road Grey, Maine 04039

Dear Ms. Walker:

Reference:

Site Location of Development Permit Application Remote Parking Lot - Portland International Jetport

Portland, Maine

The Portland International Jetport is in the process of preparing a Site Location of Development permit application for grading and drainage improvements for their remote parking facility located on outer Congress Street (Route 22) in Portland, Maine. The scope of the proposed project includes constructing a stormwater detention pond and water quality units adjacent to the existing edge of pavement at the project site. The area of proposed disturbance was previously filled and graded during the initial construction of the parking lot in 2001. In order to complete the permitting process, we are interested in obtaining information regarding any rare, threatened or endangered species, or exemplary natural communities located on or within the vicinity of this project.

A location map and aerial photo of the site and surrounding area, along with a preliminary site plan of the proposed improvements has been included to assist you in your determination. If you have any questions or require further information, please do not hesitate to contact me. Your time and effort in this matter are greatly appreciated.

Sincerely,

STANTEC CONSULTING SERVICES INC.

David P. Nadeau, P.E.

Project Manager Tel: (207) 775-3211 Fax: (207) 775-6434

dave.nadeau@stantec.com

Attachment:

as stated

c. Mr. Cuyler Feagles - PWM Mr. Dwight Anderson - DH

7.0 HISTORIC SITES (Site Location Section 8)

The proposed drainage improvements are located in an area that was previously disturbed during the original construction of the parking lot in 2001. As such, impacts to protected resources are not anticipated as a result of the current project. The Maine Historic Preservation Commission (MHPC) was contacted to determine the presence of any locations of historical, cultural, or archaeological significance within the vicinity of the proposed project. A copy of the response correspondence from MHPC indicating that "there will be no historic properties affected by the proposed undertaking" is included within this section.



Stantec Consulting Services Inc. 22 Free Street Suite 205 Portland ME 04101-3900

Tel: (207) 775-3211 Fax: (207) 775-6434

February 25, 2009

Mr. Earle G. Shettleworth, Jr., State Historic Preservation Officer Maine Historic Preservation Commission 55 Capitol Street 65 State house Station Augusta, Maine 04333-0065


Dear Mr. Shettleworth:

Reference:

Site Location of Development Permit Application

Remote Parking Lot - Portland International Jetport

Portland, Maine



A location map and aerial photo of the site and surrounding area, along with a preliminary site plan of the proposed improvements has been included to assist you in your determination. If you have any questions or require further information, please do not hesitate to contact me. Your time and effort in this matter are greatly appreciated.

Sincerely,

STANTEC CONSULTING SERVICES INC.

David P. Nadeau, P.E. Project Manager

Tel: (207) 775-3211 Fax: (207) 775-6434 dave.nadeau@stantec.com

Attachment:

as stated

c. Mr. Cuyler Feagles - PWM Mr. Dwight Anderson - DH Based on the information submitted, I have concluded that there will be no historic properties affected by the proposed undertaking, as defined by Section 106 of the National Historic Preservation Act.

STANTEC CONSULTING SERVICES INC.

Consequently, pursuant to 36 CFR 800.4(d)(1), no further Section 106 consultation is required unless additional resources are discovered during project implementation pursuant to 36 CFR 800.13.

11/09

Kirk F. Mohney,

Deputy State Historic Preservation Officer

Maine Historic Preservation Commission

Waine Historie i reservation Commission

8.0 UNUSUAL NATURAL AREAS (Site Location Section 9)

The proposed drainage improvements are located in an area that was previously disturbed during the original construction of the parking lot in 2001. As such, impacts to protected resources are not anticipated as a result of the current project. The Maine Department of Conservation (DoC) was contacted to determine the presence of rare or unique botanical features on or within the vicinity of the proposed project location. A copy of the response correspondence from DoC indicating that according to their information, "there are no rare botanical features documented specifically within the project area" is included within this section.



STATE OF MAINE DEPARTMENT OF CONSERVATION 93 STATE HOUSE STATION AUGUSTA, MAINE

() 4 3 3 3 - () () 9,3



March 3, 2009

David Nadeau Stantec Consulting Services, Inc 22 Free Street Suite 205 Portland, ME 04101-3900

Re: Rare and exemplary botanical features, Portland Jetport remote parking lot improvement, Portland, Maine.

Dear Mr. Nadeau:

I have searched the Natural Areas Program's Biological and Conservation Data System files in response to your request of February 25, 2009 for information on the presence of rare or unique botanical features documented from the vicinity of the project site in the City of Portland, Maine. Rare and unique botanical features include the habitat of rare, threatened, or endangered plant species and unique or exemplary natural communities. Our review involves examining maps, manual and computerized records, other sources of information such as scientific articles or published references, and the personal knowledge of staff or cooperating experts.

Our official response covers only botanical features. For authoritative information and official response for zoological features you must make a similar request to the Maine Department of Inland Fisheries and Wildlife, 284 State Street, Augusta, Maine 04333.

According to the information currently in our Biological and Conservation Data System files, there are no rare botanical features documented specifically within the project area. This lack of data may indicate minimal survey efforts rather than confirm the absence of rare botanical features. You may want to have the site inventoried by a qualified field biologist to ensure that no undocumented rare features are inadvertently harmed.

If a field survey of the project area is conducted, please refer to the enclosed supplemental information regarding rare and exemplary botanical features documented to occur in the vicinity of the project site. The list may include information on features that have been known to occur historically in the area as well as recently field-verified information. While historic records have not been documented in several years, they may persist in the area if suitable habitat exists. The enclosed list identifies features with potential to occur in the area, and it should be considered if you choose to conduct field surveys.

PHONE: (207) 287-8044 FAX: (207) 287-8040 TIY: (207) 287-2213

Rare and Exemplary Botanical Features in the Project Vicinity

Documented within a Four-Mile Radius of the Proposed Improvements at Portland Jetport Remote Parking, Portland, Maine.

Habitat Description	Rich hardwood forests, usually alluvial.	In Maine, habitat is between downslope seeps (with horsetails and wetland sedges) and upslope mixed oak/huckleberry forest. Preferred soil type is Deerfield Loamy Sand.	In Maine, habitat is between downslope seeps (with horsetails and wetland sedges) and upslope mixed oak/huckleberry forest. Preferred soil type is Deerfield Loamy Sand.	Meadows, lawns, and streambanks.	Meadows, lawns, and streambanks.	Fresh, brackish or alkaline waters, and stream edges.	Rich, often rocky, hardwood forests.
State Protection Status	S	ш	ш	ш	ш	OS	SC
State Rarity Rank	S3		S	S2	S5	S5	S2
Global Rarity Rank	G5	93	G 3	G5	G5	G	G5
<u>Last Seen</u>	2006-05-10	1911	1911-06-29	1924-08-20	1924-08-21	1972-06-13	1872-08
Scientific Name Common Name	Allium tricoccum Wild Leek	Carex polymorpha Variable Sedge	Carex polymorpha Variable Sedge	Selaginella apoda Creeping Spike-moss	Selaginella apoda Creeping Spike-moss	Zannichellia palustris Horned Pondweed	Phegopteris hexagonoptera Broad Beech Fern

Rare and Exemplary Botanical Features in the Project Vicinity

Documented within a Four-Mile Radius of the Proposed Improvements at Portland Jetport Remote Parking, Portland, Maine.

Scientific Name Common Name Suaeda calceoliformis American Sea-blite Ranunculus ambigens	<u>Last Seen</u> 1932-09-12	Global Rarity Rank G5	State Rarity S2 S1	State Protection Status T	Habitat Description Rocky or gravelly saltmarshes and sea-strands. Sloughs, ditches, and muddy swamps.
Water-plantain Spearwort					

Page3

STATE RARITY RANKS

- Critically imperiled in Maine because of extreme rarity (five or fewer occurrences or very few remaining individuals or acres) or because some aspect of its biology makes it especially vulnerable to extirpation from the State of Maine.
- S2 Imperiled in Maine because of rarity (6-20 occurrences or few remaining individuals or acres) or because of other factors making it vulnerable to further decline.
- Rare in Maine (20-100 occurrences).
- S4 Apparently secure in Maine.
- S5 Demonstrably secure in Maine.
- SH Known historically from the state, not verified in the past 20 years.
- Apparently extirpated from the state, loss of last known occurrence has been documented.
- SU Under consideration for assigning rarity status; more information needed on threats or distribution.
- S#? Current occurrence data suggests assigned rank, but lack of survey effort along with amount of potential habitat create uncertainty (e.g. S3?).
- Note: State Rarity Ranks are determined by the Maine Natural Areas Program.

GLOBAL RARITY RANKS

- G1 Critically imperiled globally because of extreme rarity (five or fewer occurrences or very few remaining individuals or acres) or because some aspect of its biology makes it especially vulnerable to extinction.
- G2 Globally imperiled because of rarity (6-20 occurrences or few remaining individuals or acres) or because of other factors making it vulnerable to further decline.
- G3 Globally rare (20-100 occurrences).
- G4 Apparently secure globally.
- G5 Demonstrably secure globally.
- GNR Not yet ranked.
- Note: Global Ranks are determined by NatureServe.

STATE LEGAL STATUS

- Note: State legal status is according to 5 M.R.S.A. § 13076-13079, which mandates the Department of Conservation to produce and biennially update the official list of Maine's Endangered and Threatened plants. The list is derived by a technical advisory committee of botanists who use data in the Natural Areas Program's database to recommend status changes to the Department of Conservation.
- E ENDANGERED; Rare and in danger of being lost from the state in the foreseeable future; or federally listed as Endangered.
- T THREATENED; Rare and, with further decline, could become endangered; or federally listed as Threatened.

NON-LEGAL STATUS

- SC SPECIAL CONCERN; Rare in Maine, based on available information, but not sufficiently rare to be considered Threatened or Endangered.
- PE Potentially Extirpated; Species has not been documented in Maine in past 20 years or loss of last known occurrence has been documented.

9.0 SOILS (Site Location Section 11)

According to the USDA Natural Resources Conservation Service (NRCS) web soil survey for Cumberland County, Maine, the proposed area of disturbance is located on the approximate border between two soil types, classified as Hollis fine sandy loam and Scantic silt loam. Refer to the attached Soil Survey for Cumberland County, Maine.

Hollis soils generally consist of shallow, somewhat excessively drained, moderately coarse textured soils. The soils formed in glacial till and are typically found on uplands in the northern and central parts of the county, and in coastal areas. Depth to bedrock typically ranges from 12 to 18 inches. Permeability is moderately rapid, and available water capacity is low.

Scantic soils consist of deep, nearly level, poorly drained, medium-textured soils that are underlain by fine-textured material. Scantic soils formed in marine and lacustrine sediment. A water table is typically at a depth of one foot for most of the year, and depth to bedrock is five feet or more.

A test pit (TP-1) was conducted in the area of the proposed detention basin to verify the geotechnical conditions at the site (Test Pit Log included in this section). The test pit showed a layer of fill approximately 37 inches in depth over native material. This fill was placed during the original construction of the parking lot in 2001 to provide the required grades. The soils beneath the layer of fill are identified as a silty clay / clay material down to the bottom of the exploration which is in-line with what is typically seen in the lower subsoil and the substratum for Scantic soils.

Mottling was encountered at a depth of approximately 27 inches, which is approximately 2 feet above the bottom of the proposed detention pond. Construction of the detention pond in this area however is not anticipated to have a significant impact on groundwater characteristics. The proposed detention pond will consist of excavating a portion of the existing 3:1 fill slope on the north side, and constructing an embankment on the south side. The bottom of pond will be sloped to drain to the detention pond outlet at a minimum grade of 1.5%. Any groundwater that would potentially seep from the north side slope into the detention pond will be returned to the downstream wetland system at the outlet of the proposed pond.

Spoil Area Stony Spot

111

MAP LEGEND

Area of	Area of Interest (AOI)	8	Very Stony Spot
	Area of Interest (AOI)	≯ •	Wet Spot
Soils		4	Offier
	Soil Map Units	1 000	
Speci	Special Point Features	Special	Special Line Features
3	Blowout	J	Guily
) [3 3 3	Short Steep Slope
X		ζ	Other
*	Clay Spot	Political Features	atures
*	Closed Depression	٥	Cities
×	Gravel Pit	Water Features	ures
•:	Gravelly Spot		Oceans
9	Landfill	}	Streams and Canals
4	Lava Flow	Transportation	tion
ᆌ	Marsh or swamp	‡	Rails
×	Mine or Quarry	}	Interstate Highways
0	Miscellaneous Water	>	US Routes
⊚	Perennial Water		Major Roads
>	Rock Outcrop	}	Local Roads
+	Saline Spot		
<i>::</i> :	Sandy Spot		
	Severely Eroded Spot		
\(\)	Sinkhole		
A	Slide or Slip		
ø	Sodic Spot		

MAP INFORMATION

Map Scale: 1:2,410 if printed on B size (11" × 17") sheet.

The soil surveys that comprise your AOI were mapped at 1:24,000.

Please rely on the bar scale on each map sheet for accurate map measurements.

Source of Map: Natural Resources Conservation Service Web Soil Survey URL: http://websoilsurvey.nrcs.usda.gov Coordinate System: UTM Zone 19N NAD83

This product is generated from the USDA-NRCS certified data as of the version date(s) listed below.

Soil Survey Area: Cumberland County and Part of Oxford County,

Survey Area Data: Version 7, Jan 8, 2009

Date(s) aerial images were photographed: 6/7/1997

The orthophoto or other base map on which the soil lines were compiled and digitized probably differs from the background imagery displayed on these maps. As a result, some minor shifting of map unit boundaries may be evident.

Map Unit Legend

	Cumberland County and Part of Oxford	County, Maine (ME005)	
Map Unit Symbol	Map Unit Name	Acres in AOI	Percent of AOI
Во	Biddeford silt loam	5.0	7.3%
BuB	Buxton silt loam, 3 to 8 percent slopes	1.8	2.7%
BuC2	Buxton silt loam, 8 to 15 percent slopes, eroded	3.4	5.0%
EmB	Elmwood fine sandy loam, 0 to 8 percent slopes	2.2	3.3%
HrB	Hollis fine sandy loam, 3 to 8 percent slopes	4.4	6.5%
HrC	Hollis fine sandy loam, 8 to 15 percent slopes	12.6	18.8%
PbC	Paxton fine sandy loam, 8 to 15 percent slopes	2.1	3.2%
Sn	Scantic silt loam	35.9	53.3%
Totals for Area of Interes	st	67.4	100.0%

SUBSURFACE WASTEWATER DISPOSAL SYSTEM 17:1 @ PROPOSED STORM, BASIN RETPO		Maine Dept.Health & Human Services Division of Environmental Health (207) 287-5672 Fax: (207) 287-3165
Town, City, Plantation Street, Ros	ad, Subdivision	Owner's Name
SOUTH PORTURALD. ME POUTE 22 PORTLAND. INT. JETPORT - OFFEITE PA	RK. LOT	P.W.M.
SOIL DESCRIPTION AND CLASSIFICATION		tion Holes Shown Above)
Observation Hole TP-1 ☐ Test Pit ☐ Boring	Observation Hole	☐ Test Pit ☐ Boring
6"-1/- " Depth of Organic Horizon Above Mineral Soil	" Depth of (Organic Horizon Above Mineral Soil
Texture Consistency Color Mottling	Texture Co	onsistency Color Mottling
Esta Fri. + OL +		+ + + +
(\$10 (Stoney) + + 1/0 = 5	sello — — —	+ +
S Coarse - light	ce (ii)	王 王 ヨ
Fan med + ol. +	Surface (inches)	
S S S S S S S S S S S S S S S S S S S	Soil E	王 王 ∃
30	Depth Below Mineral Soil	
33 + + + +		\pm \pm \pm
SILTY FIRM DKOL 37	3elov	
# 40 Clay TO DROLL BR Clay - V. FIRM - BR	Tube	+ + +
\$50 BOE TOG NO REPUSAL	A = = = = = = = = = = = = = = = = = =	<u></u>
Soil Classification Slope Limiting Ground Water	Soil Classification Sla	ope Limiting [] Ground Water Factor [] Restrictive Layer [] Bedrock" [] Pit Depth
SOIL DESCRIPTION AND CLASSIFICATION	N (Location of Observa	tion Holes Shown Above)
SOIL DESCRIPTION AND CLASSIFICATION Observation Hole	T	
SOIL DESCRIPTION AND CLASSIFICATION Observation Hole Test Pit Boring "Depth of Organic Horizon Above Mineral Soil	Observation Hole	tion Holes Shown Above) Test Pit Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling	Observation Hole " Depth of C	
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of C Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of C Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of C Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of C Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of O Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of O Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of O Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of O Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring " Depth of Organic Horizon Above Mineral Soil Texture Consistency Color Mottling O	Observation Hole " Depth of O Texture C	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring "Depth of Organic Horizon Above Mineral Soil Texture	Observation Hole " Depth of O Texture C O	☐ Test Pit ☐ Boring Organic Horizon Above Mineral Soil
Observation Hole Test Pit Boring	Observation Hole " Depth of O Texture C O	Test Pit Boring Drganic Horizon Above Mineral Soil onsistency Color Mottling
Observation Hole	Observation Hole " Depth of O Texture C O	Test Pit Boring Drganic Horizon Above Mineral Soil onsistency Color Mottling
Observation Hole Test Pit Boring	Observation Hole —— "Depth of O Texture C O Soil Classification SI	Test Pit Boring Drganic Horizon Above Mineral Soil onsistency Color Mottling

FORM E 2/02

SOIL CONDITIONS SUMMARY TABLE

SUMMARY LOG OF SUBSURFACE EXPLORATIONS AT PROJECT SITES

Project Name: Arundel Seasonal Cottage Resort Applicant Name: REM Development, LLC

Project Location (municipality): Route 1, Arundel, Maine

	Exploration	√ or X	Description of subsurface materials	Denths t	o (check one)	: 🗵 inche	s 🗆 cm	Ground
	Symbol (TP 1, B 2, etc.)	if at SSWD Field	by: Soil profile/condition (if by S.E.), Soil series name (if by C.S.S.), or by	Mottling (seasonal watertable)	Bedrock	Firm or Restrictive Layer	Limit of Exploration	Surface Slope (%)
	TP-I	N/A	Geologic unit (if by C.G.) MOILPPOFITE/CONDITION(SE)	21"	N/A	33-37"	96"	33%
	11 (NIA	70104 401106/00100/1010/1010/1010	<i>D</i> .	14/18	21	132	John Ja
-						,		
		-						
-								
-	· ·							
-								

Name Printed/typed/ Fee 25 and / 15 / Cert/Lic/Reg. # 55	
Name Printed/typed/ // / Cert/lic/Reg. # [9
Name Finded typed FREDERIC LICHT CEIVLICIRES. # 55	340
Title: ☐ Licensed Site Evaluator ☐ Certified Soil Scientist☐ Certified Geologist ☐ Other: P.F. # 706.9	•

affix professional seal

10.0 STORMWATER MANAGEMENT (Site Location Section 12)

10.1 INTRODUCTION

The project site is located at the Portland International Jetport's remote parking lot on outer Congress Street, in the city of Portland, Cumberland County. The site is approximately 1,600 feet west of Interstate 95, 300 feet north of the South Portland city line, and 2,000 feet east of the Westbrook city line. The site is entered by the access road for the city of Portland's snow dump facility. Refer to Figure 1.1 included in Section 1 of this application for the project location identified on the USGS quadrangle map for Portland - West, Maine.


The existing facility consists of a paved automobile parking lot approximately 3.5 acres in size. The development was permitted and constructed in 2001 under permit no. L-13760-18-W-M as a temporary parking facility for use during construction of a parking garage and associated improvements at the Portland International Jetport. It was originally intended that the parking lot would be used to offset the temporary loss in parking capacity during construction of the garage improvements, and then be removed at the completion of the garage project. The site was anticipated to be returned to a natural vegetated condition.

In the ensuing period, there has been additional growth at the Jetport which has required the continued use of the parking lot during peak parking demand periods. The applicant is therefore now proposing to change the status of the lot from temporary to permanent status for continued use as overflow parking. The original development design and permitting completed in 2001 addressed the Site Law standards in effect at the time. Discussions with MDEP staff have indicated that due to the proposed change in status of the facility, the current standards for Site Law, specifically the changes to Chapter 500 Stormwater Management must now be addressed.

10.2 ORIGINAL TEMPORARY PARKING LOT

According to MDEP's stormwater standards in effect during the original permitting of the facility, stormwater quality standards were required to be met if a project included 20,000 square feet or more of impervious area or 5 acres or more of disturbed area in the direct watershed of a waterbody most at risk from new development. The parking lot included approximately 3.5 acres of impervious area and was therefore required to meet the sliding scale total suspended solids (TSS) standard.

To achieve the TSS removal, a vegetated swale and stromwater quality treatment unit was installed. Currently, stormwater from the temporary lot sheet flows across the parking lot to the swale along the east and south sides of the lot. The swale conveys the stormwater to a series of catch basins located along the swale flow path. The catch basins are connected with an 18" diameter drainage pipe which conveys runoff into a stormwater quality treatment unit. The unit installed was manufactured by Vortechs, model 16000. Stormwater is discharged from the Vortechs unit to a stone apron and sheet flows across approximately 50 feet of vegetated terrain



Existing Wetland Culvert









Page 2

Summary for Subcatchment EX-1:

Runoff


12.50 cfs @ 12.30 hrs, Volume=

1.375 af, Depth> 1.19"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	Αı	rea (sf)	CN D	escription		
*		4,921	98 Ir	npervious	(existing ro	ad), HSG D
*		5,801			s (existing)	
	3	57,905		rush, Fair,		
*	2	34,603	77 V	Vetlands w	<u>ith brush c</u>	over, Fair, HSG D
1000	6	03,230	77 V	Veighted A	verage	
	5	98,309	F	ervious Ar	ea	
		4,921	Impervious Area			
						B 1.0
	Tc	Length	Slope	Velocity	Capacity	Description
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
	10.7	150	0.0365	0.23		Sheet Flow, A-B
						Grass: Short n= 0.150 P2= 3.18"
	10.0	754	0.0325	1.26		Shallow Concentrated Flow, B-C
						Short Grass Pasture Kv= 7.0 fps
	20.7	904	Total			

Subcatchment EX-1:



Page 3

Summary for Reach DP-1: Existing Wetland Culvert

Inflow Area =

13.848 ac, 0.82% Impervious, Inflow Depth > 1.19" for 2 Year event

Inflow

12.50 cfs @ 12.30 hrs, Volume=

1.375 af


Outflow

12.50 cfs @ 12.30 hrs, Volume=

1.375 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



Page 4

Summary for Subcatchment EX-1:

Runoff


22.58 cfs @ 12.30 hrs, Volume=

2.419 af, Depth> 2.10"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	Α	rea (sf)	CN D	Description		
*	acouttings on annihilation Males	4,921	98 lı	npervious	(existing ro	ad), HSG D
*		5,801			s (existing)	
	3	57,905		Brush, Fair,		
*	2	34,603	77 V	Vetlands w	<u>rith brush c</u>	over, Fair, HSG D
parallel	6	03,230	77 V	Veighted A	verage	
	5	98,309	Pervious Area			
		4,921	Impervious Area			
	~.	l avandla	Clana	Volonity	Capacity	Description
	Tc	Length	Slope	Velocity (ft/sec)	(cfs)	Description
-	(min)	(feet)	(ft/ft)		(013)	
	10.7	150	0.0365	0.23		Sheet Flow, A-B
						Grass: Short n= 0.150 P2= 3.18"
	10.0	754	0.0325	1.26		Shallow Concentrated Flow, B-C
						Short Grass Pasture Kv= 7.0 fps
-	20.7	904	Total			

Subcatchment EX-1:



Page 5

Summary for Reach DP-1: Existing Wetland Culvert


Inflow Area = 13.848 ac, 0.82% Impervious, Inflow Depth > 2.10" for 10 Year event

Inflow = 22.58 cfs @ 12.30 hrs, Volume= 2.419 af

Outflow = 22.58 cfs @ 12.30 hrs, Volume= 2.419 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



Page 6

Summary for Subcatchment EX-1:

Runoff


28.97 cfs @ 12.29 hrs, Volume=

3.091 af, Depth> 2.68"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Ar	ea (sf)	CN D	escription		
×		4,921	98 Ir	npervious	(existing ro	ad), HSG D
*		5,801	91 G	ravel road	s (existing)	, HSG D
	3	57,905		rush, Fair,		
*	2	34,603	77 V	<u>Vetlands w</u>	<u>rith brush co</u>	over, Fair, HSG D
	6	03,230	77 V	Veighted A	verage	
	5	98,309	P	ervious Ar	ea	
		4,921	Ir	mpervious	Area	
	Tc	Length	Slope	Velocity	Capacity	Description
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
-	(min) 10.7	(feet) 150	(ft/ft) 0.0365	(ft/sec) 0.23	(cfs)	Sheet Flow, A-B
e*************************************	(min) 10.7 10.0				(cfs)	Sheet Flow, A-B Grass: Short n= 0.150 P2= 3.18" Shallow Concentrated Flow, B-C Short Grass Pasture Kv= 7.0 fps

Subcatchment EX-1:



Page 7

Summary for Reach DP-1: Existing Wetland Culvert

Inflow Area =

13.848 ac, 0.82% Impervious, Inflow Depth > 2.68" for 25 Year event

28.97 cfs @ 12.29 hrs, Volume=

3.091 af


Inflow Outflow

28.97 cfs @ 12.29 hrs, Volume=


3.091 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



POST-DEVELOPMENT CONDITIONS STORMWATER CALCULATIONS



Storm Treat Systems Existing Wetland Culvert









Prepared by Stantec Consulting Services Inc., Printed 3/25/2009 HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 2

Summary for Subcatchment PR-1A:

Runoff :


3.69 cfs @ 12.07 hrs, Volume=

0.272 af, Depth> 2.73"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	Area (sf)	CN	Description		
*	47,718	98	Impervious	Parking Lo	t, HSG D
	4,404	80	>75% Gras	s cover, Go	ood, HSG D
- Armondo	52,122	96	Weighted A	verage	
	4,404		Pervious Ar	ea	
	47,718		Impervious	Area	
	Tc Length (min) (feet)	Slop (ft/	•	Capacity (cfs)	Description
1000	5.0				Direct Entry, Min. Value

Subcatchment PR-1A:



Page 3

Summary for Subcatchment PR-1B:

Runoff

= 7.83 cfs @ 12.09 hrs, Volume=


0.604 af, Depth> 2.62"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	A	rea (sf)	CN D	escription		
*	1	02,680	98 Ir	npervious	Parking Lo	t, HSG D
*		13,217	78 V	egetated S	Swale, HSG	D
		4,492	80 >	75% Gras	s cover, Go	ood, HSG D
Constitution	1	20,389	95 V	Veighted A	verage	
		17,709		ervious Ar		
		02,680		npervious		
	·	,				
	Тс	Length	Slope	Velocity	Capacity	Description
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	•
-	2.2	150	0.0100	1.13		Sheet Flow, A-B
						Smooth surfaces n= 0.011 P2= 3.18"
	1.7	337	0.0250	3.21		Shallow Concentrated Flow, B-C
						Paved Kv= 20.3 fps
	0.1	18	0.3000	3.83		Shallow Concentrated Flow, C-D
						Short Grass Pasture Kv= 7.0 fps
	1.6	143	0.0100	1.50		Shallow Concentrated Flow, D-E
						Grassed Waterway Kv= 15.0 fps
	1.2	325	0.0040	4.44	7.85	
						Diam= 18.0" Area= 1.8 sf Perim= 4.7' r= 0.38'
						n= 0.011 PVC, smooth interior
	6.8	973	Total			

Page 4

Subcatchment PR-1B:



Page 5

Summary for Subcatchment PR-1C:

Runoff


0.47 cfs @ 12.08 hrs, Volume=

0.033 af, Depth> 1.26"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	Α	rea (sf)	CN D	Description			
*		13,663	,663 78 Detention Basin, HSG D				
Colon	13,663		Pervious Area				
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description	
*****	5.0					Direct Entry,	

Subcatchment PR-1C:



Summary for Subcatchment PR-1D:

Runoff


0.46 cfs @ 12.21 hrs, Volume=

0.044 af, Depth> 1.66"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	Α	rea (sf)	CN	Description					
*		4,921	98	mpervious (existing access road)					
*		8,871	77	Brush, Fair, HSG D					
		13,792 8,871 4,921		Weighted A Pervious Ai Impervious	ea -				
	Tc (min)	Length (feet)	Slope (ft/ft)		Capacity (cfs)	Description			
6,000	13.6	150	0.0200	0.18		Sheet Flow, A-B Grass: Short n= 0.150 P2= 3.18"			
	1.7	321	0.0450	3.18		Shallow Concentrated Flow, B-C Grassed Waterway Kv= 15.0 fps			
	15.3	471	Total						

Subcatchment PR-1D:



Page 7

Summary for Subcatchment PR-1E:


7.14 cfs @ 12.44 hrs, Volume= Runoff

0.917 af, Depth> 1.19"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 2 Year Rainfall=3.18"

	Aı	ea (sf)	CN D	escription			.pmpromov400			
*		5,801								
	1	62,865		rush, Fair,						
*	2	34,603	77_V	<u>Vetlands w</u>	ith brush co	over, Fair, HSG D				
	4	03,269	77 V	Veighted A	verage					
	4	03,269	P	ervious Ar	ea					
						B				
	Тс	Length	Slope	Velocity	Capacity	Description				
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)					
	13.9	150	0.0190	0.18		Sheet Flow, A-B				
						Grass: Short n= 0.150 P2= 3.18"				
	5.5	293	0.0160	0.89		Shallow Concentrated Flow, B-C				
						Short Grass Pasture Kv= 7.0 fps				
	10.4	674	0.0240	1.08		Shallow Concentrated Flow, C-D				
						Short Grass Pasture Kv= 7.0 fps				
COMM	29.8	1,117	Total							

Subcatchment PR-1E:



Page 8

Summary for Reach 5R: Storm Treat Systems


Inflow Area = 4.591 ac, 77.67% Impervious, Inflow Depth > 0.21" for 2 Year event

Inflow = 0.05 cfs @ 5.20 hrs, Volume= 0.082 af

Outflow = 0.05 cfs @ 5.20 hrs, Volume= 0.082 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach 5R: Storm Treat Systems



Page 9

Summary for Reach DP-1: Existing Wetland Culvert

Inflow Area =

13.848 ac, 25.75% Impervious, Inflow Depth > 1.38" for 2 Year event

Inflow =

10.29 cfs @ 12.45 hrs, Volume=

1.594 af


Outflow =

10.29 cfs @ 12.45 hrs, Volume=

1.594 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



#2

Primary

HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 10

Summary for Pond 1P: Detention Pond

4.591 ac, 77.67% Impervious, Inflow Depth > 2.49" for 2 Year event Inflow Area = 0.953 af Inflow 12.18 cfs @ 12.09 hrs, Volume= 3.16 cfs @ 12.47 hrs, Volume= 0.677 af, Atten= 74%, Lag= 23.3 min Outflow 0.05 cfs @ 5.20 hrs, Volume= Primary -0.082 af 3.11 cfs @ 12.47 hrs, Volume= 0.595 af Secondary =

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Peak Elev= 89.39' @ 12.47 hrs Surf.Area= 7,962 sf Storage= 19,993 cf

Plug-Flow detention time= 175.8 min calculated for 0.677 af (71% of inflow) Center-of-Mass det. time= 85.0 min (868.7 - 783.7)

Volume	Invert	Avail.Stor	rage Stora	ge Description	
#1	85.40'	40,41	5 cf Cust	om Stage Data (Pr	rismatic) Listed below (Recalc)
E14:	0	ω¢ Λ	les Ciare	Cum Store	
Elevatio		rf.Area	Inc.Store		
(feet	t)	(sq-ft)	(cubic-feet)	(cubic-feet)	
85.4	0	125	0	0	
86.0	0	1,683	542	542	
87.0	0	5,253	3,468	4,010	
88.0	0	6,565	5,909	9,919	
88.2	0	6,773	1,334	11,253	
89.0	0	7,567	5,736	16,989	
90.0	0	8,589	8,078	25,067	
91.0	0	9,787	9,188	34,255	
91.6	1	10,408	6,159	40,415	
Device	Routing	Invert	Outlet Dev	rices	
#1	Secondary	90.00'	5.0' long	x 8.0' breadth Broa	ad-Crested Rectangular Weir
	•		Head (feet	0.20 0.40 0.60	0.80 1.00 1.20 1.40 1.60 1.80 2.00
				3.50 4.00 4.50 5	
					.70 2.69 2.68 2.68 2.66 2.64 2.64
			2.64 2.65	2.65 2.66 2.66 2	2.08 2.70 2.74

18.0" x 29.0' long Culvert CPP, square edge headwall, Ke= 0.500 #3 Secondary 85.00' Outlet Invert= 83.90' S= 0.0379 '/' Cc= 0.900 n= 0.013 Corrugated PE, smooth interior 8.0" Vert. Orifice/Grate X 2.00 C= 0.600 #4 Device 3 88.20'

0.05 cfs To StormTreat Systems at all elevations

Primary OutFlow Max=0.05 cfs @ 5.20 hrs HW=85.46' (Free Discharge) 2=To StormTreat Systems (Exfiltration Controls 0.05 cfs)


Secondary OutFlow Max=3.11 cfs @ 12.47 hrs HW=89.39' (Free Discharge)

-1=Broad-Crested Rectangular Weir (Controls 0.00 cfs) **3=Culvert** (Passes 3.11 cfs of 16.23 cfs potential flow)

85.40'

4=Orifice/Grate (Orifice Controls 3.11 cfs @ 4.45 fps)

Pond 1P: Detention Pond



Summary for Subcatchment PR-1A:


Runoff = 5.18 cfs @ 12.07 hrs, Volume=

0.389 af, Depth> 3.90"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	A	rea (sf)	CN	Description					
4	·	47,718	98	Impervious Parking Lot, HSG D					
		4,404	80	>75% Grass cover, Good, HSG D					
		52,122		Weighted A					
	4,404 Pervious Area 47,718 Impervious Area								
	Tc (min)	Length (feet)	Slope (ft/ft)	,	Capacity (cfs)	Description			
	5.0	111000000000000000000000000000000000000				Direct Entry, Min. Value			

Subcatchment PR-1A:



Summary for Subcatchment PR-1B:


11.08 cfs @ 12.09 hrs, Volume= Runoff

0.873 af, Depth> 3.79"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	Aı	rea (sf)	CN D	escription		
*		02,680			Parking Lo	
		13,217 4,492			Swale, HSG s cover, Go	ood, HSG D
200000	120,389 95 Weighted Average 17.709 Pervious Area					
	17,709 102,680			npervious A		
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description
	2.2	150	0.0100	1.13		Sheet Flow, A-B
	1.7	337	0.0250	3.21		Smooth surfaces n= 0.011 P2= 3.18" Shallow Concentrated Flow, B-C Paved Kv= 20.3 fps
	0.1	18	0.3000	3.83		Shallow Concentrated Flow, C-D
	1.6	143	0.0100	1.50		Short Grass Pasture Kv= 7.0 fps Shallow Concentrated Flow, D-E Grassed Waterway Kv= 15.0 fps
	1.2	325	0.0040	4.44	7.85	
						n= 0.011 PVC, smooth interior
Comm	6.8	973	Total			

Subcatchment PR-1B:



Page 15

Summary for Subcatchment PR-1C:

Runoff


0.83 cfs @ 12.08 hrs, Volume=

0.057 af, Depth> 2.18"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	Area (sf) CN Description						
*		13,663 78 Detention Basin, HSG D					
besse		13,663	F	ervious Ar	ea		
		Length				Description	
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)		
kooso	5.0					Direct Entry,	

Subcatchment PR-1C:



Page 16

Summary for Subcatchment PR-1D:

Runoff =


0.75 cfs @ 12.21 hrs, Volume=

0.071 af, Depth> 2.69"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	Α	rea (sf)	CN I	Description						
*		4,921	98 I	mpervious (existing access road)						
*		8,871	77	Brush, Fair, HSG D						
	13,792 84 Weighted Average 8,871 Pervious Area 4,921 Impervious Area				ea					
	Tc (min)	Length (feet)	Slope (ft/ft)	-	Capacity (cfs)	Description				
-	13.6	150	0.0200	0.18		Sheet Flow, A-B				
	1.7	321	0.0450	3.18		Grass: Short n= 0.150 P2= 3.18" Shallow Concentrated Flow, B-C Grassed Waterway Kv= 15.0 fps				
-	15.3	471	Total							

Subcatchment PR-1D:




Summary for Subcatchment PR-1E:

Runoff = 12.91 cfs @ 12.42 hrs, Volume= 1.613 af, Depth> 2.09"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 10 Year Rainfall=4.37"

	Αı	ea (sf)	CN D	escription						
*		5,801	91 0	Gravel roads (existing), HSG D						
	1	62,865		Brush, Fair,						
*	2	34,603	77 V	<u>Vetlands w</u>	ith brush c	over, Fair, HSG D				
	4	03,269	77 V	Veighted A	verage					
	4	03,269	F	ervious Ar	ea					
	Tc	Length	Slope	Velocity	Capacity	Description				
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)					
	13.9	150	0.0190	0.18		Sheet Flow, A-B				
						Grass: Short n= 0.150 P2= 3.18"				
	5.5	293	0.0160	0.89		Shallow Concentrated Flow, B-C				
						Short Grass Pasture Kv= 7.0 fps				
	10.4	674	0.0240	1.08		Shallow Concentrated Flow, C-D				
						Short Grass Pasture Kv= 7.0 fps				
Berend	29.8	1,117	Total							

Subcatchment PR-1E:



Summary for Reach 5R: Storm Treat Systems


4.591 ac, 77.67% Impervious, Inflow Depth > 0.23" for 10 Year event Inflow Area =

0.086 af 3.79 hrs, Volume= Inflow 0.05 cfs @

3.79 hrs, Volume= 0.086 af, Atten= 0%, Lag= 0.0 min Outflow 0.05 cfs @

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach 5R: Storm Treat Systems



Prepared by Stantec Consulting Services Inc.

HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 19

Summary for Reach DP-1: Existing Wetland Culvert


Inflow Area = 13.848 ac, 25.75% Impervious, Inflow Depth > 2.36" for 10 Year event

Inflow = 18.85 cfs @ 12.42 hrs, Volume= 2.724 af

Outflow = 18.85 cfs @ 12.42 hrs, Volume= 2.724 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



Prepared by Stantec Consulting Services Inc.

HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 20

Summary for Pond 1P: Detention Pond

4.591 ac, 77.67% Impervious, Inflow Depth > 3.64" for 10 Year event Inflow Area = 1.391 af 17.44 cfs @ 12.09 hrs, Volume= Inflow 1.111 af, Atten= 66%, Lag= 18.1 min 5.98 cfs @ 12.39 hrs, Volume= Outflow 3.79 hrs, Volume= 0.086 af 0.05 cfs @ Primary 5.93 cfs @ 12.39 hrs, Volume= 1.024 af Secondary =

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Peak Elev= 90.25' @ 12.39 hrs Surf.Area= 8,887 sf Storage= 27,238 cf

Plug-Flow detention time= 155.8 min calculated for 1.110 af (80% of inflow) Center-of-Mass det. time= 80.1 min (855.0 - 774.9)

Volume	Invert	Avail.Storage	e Storage [Description	
#1	85.40'	40,415 c	f Custom	Stage Data (Pris	matic) Listed below (Recalc)
Elevation (feet)	Surf.A (se		nc.Store bic-feet)	Cum.Store (cubic-feet)	
85.40		125	0	0	
86.00	1,	683	542	542	
87.00	5,	253	3,468	4,010	
88.00	6,	565	5,909	9,919	
88.20	6,	773	1,334	11,253	
89.00	7,	567	5,736	16,989	
90.00	8,	589	8,078	25,067	
91.00	9,	787	9,188	34,255	
91.61	10,	,408	6,159	40,415	

Device	Routing	Invert	Outlet Devices
#1	Secondary	90.00'	5.0' long x 8.0' breadth Broad-Crested Rectangular Weir Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00 2.50 3.00 3.50 4.00 4.50 5.00 5.50
			Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64 2.65 2.65 2.66 2.68 2.70 2.74
#2	Primary	85.40'	0.05 cfs To StormTreat Systems at all elevations
#3	Secondary	85.00'	18.0" x 29.0' long Culvert CPP, square edge headwall, Ke= 0.500
•	,		Outlet Invert= 83.90' S= 0.0379 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior
#4	Device 3	88.20'	8.0" Vert. Orifice/Grate X 2.00 C= 0.600

Primary OutFlow Max=0.05 cfs @ 3.79 hrs HW=85.46' (Free Discharge) 2=To StormTreat Systems (Exfiltration Controls 0.05 cfs)

Secondary OutFlow Max=5.92 cfs @ 12.39 hrs HW=90.25' (Free Discharge) -1=Broad-Crested Rectangular Weir (Weir Controls 1.52 cfs @ 1.22 fps)

-3=Culvert (Passes 4.40 cfs of 18.05 cfs potential flow)


4-Orifice/Grate (Orifice Controls 4.40 cfs @ 6.31 fps)

Prepared by Stantec Consulting Services Inc.

HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 21

Pond 1P: Detention Pond



Summary for Subcatchment PR-1A:


Runoff = 6.06 cfs @ 12.07 hrs, Volume=

0.460 af, Depth> 4.61"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Α	rea (sf)	CN I	Description				
*		47,718	98	Impervious Parking Lot, HSG D				
		4,404	80 :	>75% Grass cover, Good, HSG D				
pane.		52,122	96	Neighted A	verage			
	4,404 Pervious Area							
		47,718]	mpervious	Area			
	-,-		01	\	0	Description		
	Tc	Length	Slope		Capacity	Description		
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)			
	5.0					Direct Entry, Min. Value		

Subcatchment PR-1A:



Page 23

Summary for Subcatchment PR-1B:


13.01 cfs @ 12.09 hrs, Volume= Runoff

1.035 af, Depth> 4.49"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Aı	rea (sf)	CN D	escription		
*		02,680			Parking Lo	
*		13,217 4,492			Swale, HS0	ood, HSG D
outstands	1	20,389				JOC, 1100 D
	120,389 95 Weighted Average 17,709 Pervious Area					
	1	02,680	lr	mpervious	Area	
	Тс	Length	Slope	Velocity	Capacity	Description
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	,
	2.2	150	0.0100	1.13		Sheet Flow, A-B
	4 ***		0.0050	0.04		Smooth surfaces n= 0.011 P2= 3.18"
	1.7	337	0.0250	3.21		Shallow Concentrated Flow, B-C Paved Kv= 20.3 fps
	0.1	18	0.3000	3.83		Shallow Concentrated Flow, C-D
	•					Short Grass Pasture Kv= 7.0 fps
	1.6	143	0.0100	1.50		Shallow Concentrated Flow, D-E
	4.0	205	0.0040	4 4 4	7 05	Grassed Waterway Kv= 15.0 fps Circular Channel (pipe), E-F
	1.2	325	0.0040	4.44	7.85	Diam= 18.0" Area= 1.8 sf Perim= 4.7' r= 0.38'
						n= 0.011 PVC, smooth interior
Environes	6.8	973	Total			

Subcatchment PR-1B:



Printed 3/23/2009

Page 25

Summary for Subcatchment PR-1C:

Runoff

-


1.06 cfs @ 12.08 hrs, Volume=

0.073 af, Depth> 2.78"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Α	rea (sf)	CN D			
*		13,663	78 D	etention B	asin, HSG	D
Elizabeth		13,663	P	ervious Ar	ea	
	Тс	Length	•			Description
	(min)	(feet)	(ft/ft)	(ft/sec)	(cfs)	
towe	5.0					Direct Entry,

Subcatchment PR-1C:



Summary for Subcatchment PR-1D:

Runoff


= 0.93 cfs @ 12.21 hrs, Volume=

0.088 af, Depth> 3.33"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Α	rea (sf)	CN [Description						
*		4,921	98 I	mpervious	npervious (existing access road)					
*		8,871	77 E	Brush, Fair,	HSG D					
-		13,792	84 \	Neighted A	verage					
		8,871	F	Pervious Ar	ea					
		4,921	case part of the case of the c	mpervious	Area					
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description				
acus	13.6	150	0.0200	0.18		Sheet Flow, A-B				
	1.7	321	0.0450	3.18		Grass: Short n= 0.150 P2= 3.18" Shallow Concentrated Flow, B-C Grassed Waterway Kv= 15.0 fps	3-A			
energy (15.3	471	Total							

Subcatchment PR-1D:



Summary for Subcatchment PR-1E:


16.57 cfs @ 12.42 hrs, Volume= Runoff

2.062 af, Depth> 2.67"

Runoff by SCS TR-20 method, UH=SCS, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Type III 24-hr 25 Year Rainfall=5.08"

	Aı	rea (sf)	CN D	escription					
*	ant a summer and demonstrated in the State of the State o	5,801	91 Gravel roads (existing), HSG D						
	1	62,865							
* 234,603 77 Wetlands with brush cover, Fair, HSG D									
	403,269 77 Weighted Average								
	4	03,269	Р	ervious Ar	ea				
	Tc (min)	Length (feet)	Slope (ft/ft)	Velocity (ft/sec)	Capacity (cfs)	Description			
-	13.9	150	0.0190	0.18		Sheet Flow, A-B			
	E	202	0.0160	0.89		Grass: Short n= 0.150 P2= 3.18" Shallow Concentrated Flow, B-C			
	5.5				Short Grass Pasture Kv= 7.0 fps				
	10.4 674 0.0240 1.08			Shallow Concentrated Flow, C-D					
						Short Grass Pasture Kv= 7.0 fps			
	29.8	1 117	Total						

Subcatchment PR-1E:



Page 28

Summary for Reach 5R: Storm Treat Systems


4.591 ac, 77.67% Impervious, Inflow Depth > 0.23" for 25 Year event Inflow Area =

Inflow 0.05 cfs @ 3.24 hrs, Volume= 0.088 af

0.088 af, Atten= 0%, Lag= 0.0 min 3.24 hrs, Volume= Outflow 0.05 cfs @

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach 5R: Storm Treat Systems



Summary for Reach DP-1: Existing Wetland Culvert

Inflow Area =

13.848 ac, 25.75% Impervious, Inflow Depth > 2.98" for 25 Year event

Inflow =

25.12 cfs @ 12.38 hrs, Volume=


3.435 af

Outflow = 25.12 cfs @ 12.38 hrs, Volume=

3.435 af, Atten= 0%, Lag= 0.0 min

Routing by Stor-Ind+Trans method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs

Reach DP-1: Existing Wetland Culvert



Page 30

Summary for Pond 1P: Detention Pond

Inflow Area = 4.591 ac, 77.67% Impervious, Inflow Depth > 4.33" for 25 Year event

Inflow = 20.57 cfs @ 12.09 hrs, Volume= 1.655 af

Outflow = 9.28 cfs @ 12.29 hrs, Volume= 1.372 af, Atten= 55%, Lag= 12.1 min

Primary = 0.05 cfs @ 3.24 hrs, Volume= 0.088 af Secondary = 9.23 cfs @ 12.29 hrs, Volume= 1.284 af

Routing by Stor-Ind method, Time Span= 0.00-24.00 hrs, dt= 0.01 hrs Peak Elev= 90.49' @ 12.29 hrs Surf.Area= 9,180 sf Storage= 29,448 cf

Plug-Flow detention time= 144.6 min calculated for 1.372 af (83% of inflow)

Center-of-Mass det. time= 75.6 min (846.6 - 771.0)

Volume	Invert Ava	ail.Storage	Storage	e Description	
#1	85.40'	40,415 cf	Custon	n Stage Data (Pri	smatic) Listed below (Recalc)
Elevation (feet)	Surf.Area (sq-ft)		.Store c-feet)	Cum.Store (cubic-feet)	
85.40	125		0	0	
86.00	1,683	ı	542	542	
87.00	5,253	ı	3,468	4,010	
88.00	6,565		5,909	9,919	
88.20	6,773		1,334	11,253	
89.00	7,567	•	5,736	16,989	
90.00	8,589	•	8,078	25,067	
91.00	9,787	•	9,188	34,255	
91.61	10,408	;	6,159	40,415	

Device	Routing	Invert	Outlet Devices
#1	Secondary	90.00'	
			Head (feet) 0.20 0.40 0.60 0.80 1.00 1.20 1.40 1.60 1.80 2.00
			2.50 3.00 3.50 4.00 4.50 5.00 5.50
			Coef. (English) 2.43 2.54 2.70 2.69 2.68 2.68 2.66 2.64 2.64
			2.64 2.65 2.65 2.66 2.68 2.70 2.74
#2	Primary	85.40'	0.05 cfs To StormTreat Systems at all elevations
#3	Secondary	85.00'	18.0" x 29.0' long Culvert CPP, square edge headwall, Ke= 0.500
	•		Outlet Invert= 83.90' S= 0.0379 '/' Cc= 0.900
			n= 0.013 Corrugated PE, smooth interior
#4	Device 3	88.20'	8.0" Vert. Orifice/Grate X 2.00 C= 0.600

Primary OutFlow Max=0.05 cfs @ 3.24 hrs HW=85.46' (Free Discharge) 2=To StormTreat Systems (Exfiltration Controls 0.05 cfs)

Secondary OutFlow Max=9.23 cfs @ 12.29 hrs HW=90.49' (Free Discharge)

1=Broad-Crested Rectangular Weir (Weir Controls 4.52 cfs @ 1.84 fps)


—3=Culvert (Passes 4.71 cfs of 18.53 cfs potential flow) —4=Orifice/Grate (Orifice Controls 4.71 cfs @ 6.74 fps) Prepared by Stantec Consulting Services Inc.

Printed 3/25/2009

HydroCAD® 8.50 s/n 001619 © 2007 HydroCAD Software Solutions LLC

Page 31

Pond 1P: Detention Pond



11.0 URBAN IMPAIRED STREAM SUBMISSIONS (Site Location Section 13)

The Urban Impaired Stream standard must be met when a project located within the direct watershed of an urban impaired stream or stream segment listed in Chapter 502 results in three acres or more of impervious area or 20 acres or more of developed area. The remote parking lot consists of approximately 3.45 acres of impervious surface in the watershed of Long Creek, a waterbody identified as an urban impaired stream. Therefore, the Urban Impaired Stream standard must be met for this project.

To meet the standard, a combination of mitigation credits and payment of a compensation fee is proposed. The mitigation credits will be obtained from on-site treatment of impervious and landscaped areas in excess of that required to meet the General Standards (95% for impervious / 80% for developed). Additionally, a portion of the existing access road will also receive treatment by the proposed water quality Best Management Practices (BMPs). As shown in the attached Figure 11.1, approximately 10,657 SF of non-roof impervious, and 1,779 SF of landscaped lawn area will be treated by the proposed BMPs to earn mitigation credits.

A compensation fee will be required to be paid to make up the difference between the earned credits and required credits. The City of South Portland has developed a Compensation Fee Utilization Plan for projects within the Long Creek watershed. The applicant proposes to provide a compensation fee into this plan in the amount of \$14,700.00 Below is a summary of the required and earned mitigation credits proposed for this project.

Required Credits:

Non-Roof Impervious=1.73 Credits Landscaped=0.02 Credits

Earned Mitigation Credits:

Non-Roof Impervious=0.27 Credits Landscaped=0.01 Credits

Compensation Fee Required:

Non-Roof Impervious=\$14,600.00 Landscaped=\$100.00

Total=\$14,700.00

Portland International Jetport -Remote Parking Lot Site Location of Development Permit - Minor Amendment Application

FIGURE 11.1

URBAN IMPAIRED STREAM STANDARD
Required Compensation Calculations

Non-Roof Impervious Area			Landscaped Area		
Total Project Area	H	150,735 SF	Total Project Area	11	8,896 SF
95% Requiring BMP Treatment	11	143,198 SF	80% Requiring BMP Treatment	H	7,117 SF
Receiving BMP Treatment*	11	153,855 SF	Receiving BMP Treatment	ARABAN KARAMENTAN KARAMENT	8,896 SF
Excess to be used as mitigation credit	11	10,657 SF	Excess to be used as mitigation credit	11	1,779 SF
*Note: Includes 3,120 SF (260'x12') of existing access road.	sting acces	ss road.			

Total Credit Earned	0.11 0.27 Impervious Credits	0.16	0.01	Total Required Credit	1.73	0.02
Earned Credit	1.5 per acre =	0.9 per acre =	0.3 per acre =	Rea. Credit	0.5 per acre	0.1 per acre
	equired Sizing 3,120 SF	7,537 SF	1,779 SF		150,735 SF	8,896 SF
Mitigation Credits Earned	Retrofit with General Standards at Required Sizing -Road	-Low Use Parking Lot	-Lawn	Required Mitigation Credits	Total Non-Roof Impervious Area	Total Landscaped Area

Remaining Credits Needed

(Earned - Required Credits)
1.73 credits - 0.27 credits = 1.46 credits
0.02 credits - 0.01 credits = 0.01 credits 11 11

Impervious Credits Landscape Credits

Compensation Fee Required

	Compensation Fee	\$14,600	\$100
		II	II
	Conversion Factor	0.5 Credit = \$5,000	0.1 Credit = \$1,000
on Fee	Credits	1.46	0.01
Convert Credits to Compensation Fee		Non-Roof Impervious Area	Landscaped Area

TOTAL COMPENSATION FEE REQUIRED \$14,700

12.0 BASIC STANDARDS (Site Location Section 14)

12.1 INTRODUCTION

This plan for Erosion and Sedimentation Control (ESC) has been developed to provide a strategy for controlling soil erosion and sedimentation during and after construction of the proposed development. This plan is based on Standards and Specifications for Erosion Prevention in Developing Areas as contained in the 2005 online version of the *Maine Erosion and Sediment Control BMP Manual* for the Maine Department of Environmental Protection and on Appendix A, *Erosion and Sedimentation Control*, of the Maine Department of Environmental Protection Rules, 06-96, Chapter 500 Stormwater Management, effective November 16, 2005. The narrative contained in this section is combined with the Plan Sheets and the Erosion Control Details found in the back of this application to create an overall erosion control plan, which addresses the stabilization of the site and the protections of off-site water resources.

12.2 SCHEDULE

This project is anticipated to take place during the 2009 construction season, from approximately August 1, 2009 through September 1, 2009.

12.3 GENERAL CONSTRUCTION DETAILS

The equipment anticipated to be used for construction may include the following: excavator, backhoe, bulldozer, loader, trucks, compactor, and grader. Intensive on-site erosion control methods will be utilized. The following methods will be undertaken to provide maximum protection to the soil, water, and abutting lands:

- 1. Permanent soil erosion control measures for all slopes, channels, ditches, or any disturbed land areas will be completed within seven (7) calendar days after final grading has been completed. When it is not possible or practical to permanently stabilize disturbed land, temporary erosion control measures will be implemented within seven (7) calendar days of exposure of soil. Temporary erosion control measures shall include at a minimum the application of wood fiber mulch at a rate of 75-90 lbs per 1000 SF by the wet application method as outlined in Item T-901 of the contract specifications. Within 75 feet of a wetland area (including lakes and streams), mulch will be applied within 48 hours, or prior to any storm event, whichever is first.
- 2. Prior to grubbing or any earthmoving operation, siltation fence will be installed across the slope on the contour at the downhill limit of the work as protection against construction related erosion. Siltation fence shall also be installed at the downhill limit of the base of soil stockpiles.
- 3. Temporary siltation control risers will be installed at all existing culvert/ storm drain inlet locations in accordance with Maine Erosion and Sedimentation Control BMP B-3.

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

- 4. All siltation fence will be inspected by the contractor on a weekly basis, following any significant rainfall (1/2 inch or more) or snowmelt, or daily during prolonged rainfall. All damaged siltation fence will be repaired and/or replaced immediately. Trapped sediment will be removed before it has accumulated to one half of the installed siltation fence height. Siltation fence no longer serviceable due to sediment accumulation will also be repaired and/or replaced as necessary. Any sediment deposits remaining in place after the siltation fence or filter barrier is no longer required will be incorporated into the existing grade, seeded, and mulched.
- 5. Removal of temporary sediment control measures shall occur within thirty (30) days of permanent stabilization.
- 6. To provide permanent protection against erosion, riprap will be placed at all storm drain inlets and outlets as shown on the contract drawings in accordance with Maine Erosion and Sedimentation Control BMP E-2 and E-3.
- 7. All ditch bases to be seeded will also be lined with erosion control mesh to stabilize the ditch channels until vegetation is established. Stone check dams and temporary mulching will be used to stabilize any section of rough graded ditch that will not be final graded and permanently stabilized within seven (7) days of initial disturbance.
- 8. Native topsoil shall be saved, stockpiled, mulched, and reused as much as possible on the site. Stockpiles will be stabilized by seeding and mulching within seven (7) days of the formation of the stockpile. Near wetland areas (including lakes and streams), seeding and mulching shall completed within 24 hours of the formation of the stockpile. Uphill of stockpiles, stabilized ditches and/or berms will be constructed to divert stormwater runoff away from the piles. Side slopes of topsoil stockpiles will not exceed 2:1.

12.3.1 Seeding and Revegetation Plan

Upon completion of site construction, all areas previously disturbed will be treated as stated below. These areas will be closely monitored by the contractor until such time as a satisfactory growth of vegetation is established.

- 1. Loam will be spread over all disturbed areas and graded to a uniform depth of 4 inches.
- 2. All exposed surfaces not to be final graded for thirty (30) days or more will be seeded with winter rye, oats, annual ryegrass, or sudangrass perennial, depending on the time of year in accordance with Maine Erosion and Sedimentation Control BMP A-2 for details and specifications.
- 3. Agricultural limestone and fertilizer will be incorporated into the soil prior to seeding at the rate of 1-2 tons per acre and 15 lbs per 1,000 SF, respectively, per Item T-901 in the contract specifications.

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

- 4. Disturbed areas will be seeded at the rate of 1 lb. per 1000 SF. The seed mix will be specified in Item T-901 of the contract specifications.
- 5. Seeding will be completed between the dates of May 1 and September 15. Irrigation will be completed during the period of June 1 to August 15, as necessary.
- 6. Areas which have been temporarily or permanently seeded shall be mulched immediately following seeding.
- 7. In accordance with Maine Erosion and Sedimentation Control BMPs A-1 and C-4, and Item T-908 in the contract specifications, hay mulch will be applied at the rate of 75-90 lbs. per 1000 SF. Mulch shall be anchored with biodegradable netting on steep slopes (7:1 or greater) and on areas within 100 feet of lakes, streams, and wetlands. Erosion control mix can be used on slopes between 3:1 and 2:1.
- 8. All mulches will be inspected periodically, particularly after rainfall. If less than 90% of the disturbed area is covered, additional mulch will be spread.
- 9. All sediment control structures will remain in place until vegetation is established. Established means a minimum of 85% of the area is vegetated with vigorous growth.

12.3.2 Fall/Winter Seeding and Stabilization

In accordance with the Maine Erosion and Sedimentation Control BMP A-3, please note the following:

By September 1-

All grass-lined ditches and channels will be constructed and stabilized. All slopes greater than 7:1 to be vegetated will be seeded and mulched (past September 15, mulch anchoring should be used on slopes greater than 20:1, and heavy grade mats and biodegradable netting should be used in conjunction on slopes greater than 12:1 and on side slopes of ditches). If this is not completed then:

By October 1-

Sod will be placed in all ditch channels where vegetation has not been established. Sod will extend to a height of one foot above ditch channel bottom. All slopes greater than 7:1 will be seeded to a winter cover crop of rye at a rate of 3 lbs per 1000 SF. If the rye fails to grow at least three inches or fails to cover at least 75% of the slope by November 1, or if sod is not placed in the appropriate ditch channels, then:

By November 1-

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

The ditch will be lined with stone riprap. The slope will be covered with erosion control mix or stone riprap, or alternatively:

By November 15-

The disturbed soil will be mulched at the winter rate and anchored properly. No construction is anticipated to take place after November 15.

The winter construction period is from November 1 to April 15.

- 1. Winter excavation and earthwork shall be completed such that no more than 1 acre of the site is without stabilization at any one time. The exposed area will be limited to that in which work is to occur during the following 15 days and those areas that can be mulched in one day prior to any snow event.
- 2. Hay mulch will be applied to a depth of 4 inches (150 lbs. per 1000 SF).
- 3. After each day of final grading, any disturbed area will be stabilized with anchored mulch or erosion control mesh. No ground surface should be visible through the mulch.
- 4. Soil stockpiles will be mulched at winter rates within 24 hours of stocking and reestablished prior to rain or snowfall. No stockpiles will be place within 100 feet of lakes, streams, wetlands, or other natural resources.

12.3.3 Monitoring Details

Sedimentation and erosion control structures will be inspected weekly by the contractor, and all structures damaged by construction equipment, vandals, or the elements will be repaired immediately. Following rainstorms and during runoff events, the site and all structures will be repaired and/or additional erosion control structures will be installed prior to continuing the construction.

Following the final seeding, the site will be inspected to ensure that the vegetation has been established. Reseeding will be carried out, with follow-up inspections, in the event of any unsatisfactory growth.

After the project area has stabilized, the contractor will remove all siltation fence and any other temporary erosion control measures.

Implementation and monitoring of erosion control measures will be the responsibility of the contractor under the supervision of the project engineer and the resident project representative for Stantec Consulting Services Inc.

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

12.4 INSPECTION AND MAINTENANCE

The Engineer will have a resident project representative (RPR) at the site during the construction project. The RPR will conduct routine inspections of all erosion and sedimentation controls. The RPR will also be responsible for ensuring that maintenance of erosion and sedimentation structures, when required, is performed in a timely and effective manner. After construction, airport maintenance personnel will also conduct inspections and perform routine maintenance. See *Inspection and Maintenance Plan- Responsible Parties* form included in the back of this Section for a list of the appropriate persons designated to perform these duties at the airport.

12.4.1 Inspection Schedule during Construction

All areas disturbed by construction that have not been permanently stabilized will be inspected at least once every seven (7) calendar days. These areas will also be inspected (within 24 hours) following any storm event in which 0.5 inches or more of rain occurs in a 24-hour period. The RPR will inspect the erosion and sedimentation controls in accordance with the schedule indicated above and note any required corrections in the Daily Inspection Report. Inspection forms and certification forms for erosion control are located in the back of this section.

Inspections will include all areas of the site disturbed by construction activity and areas used for storage of materials exposed to precipitation. Inspectors must look for evidence of, or the potential for, pollutants entering the stormwater conveyance system or an infiltration area. Sedimentation and erosion control measures identified in this ESC plan will be inspected to ensure proper operation. Discharge locations, where accessible, shall be inspected to ascertain the effectiveness of erosion control measures in preventing significant impacts to waters of the United States (including wetlands). Locations where vehicles enter or exit the site will be inspected for evidence of off-site sediment tracking (see Section 12.5.4, *Fugitive Sediment and Dust*).

Upon completion of construction activities, all areas that have been temporarily or permanently stabilized will be inspected by the Engineer/ RPR to ensure that final stabilization has been successful.

12.4.1.1 Inspection Procedures during Construction

Inspections shall be conducted by the on-site engineer/RPR. The following items shall be inspected as described below:

Hay bales: Hay bale lines will be inspected to insure that bales are intact and remain snugly butted to each other and firmly embedded in the ground. Depth of sediment behind the bales will be noted and removed if sediment exceeds one-half the height of the bale.

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

Silt Fence: Silt fence will be inspected to insure that the fence line is intact with no breaks or tears, and that the bottom of the fabric is securely buried in the ground. Areas where the fence is excessively sagging or where support posts are broken or uprooted will be noted and repaired. Depth of sediment behind the fence will be noted and removed when sediment exceeds one-third the height of the fence.

Discharge Points: All discharge points will be inspected, where practicable, to monitor the effectiveness of erosion control measures in preventing impacts to receiving waters and wetlands. If impacts to surface waters or wetlands are observed, the source of such impacts will be located immediately and improvements made to erosion and sedimentation controls in order to prevent the reoccurrence of impacts to surface waters. Any impacts observed and corrective measures taken will be noted in the inspection log and recorded in this ESC Plan.

Vehicle Access Points: Locations where vehicles enter and exit the site will be inspected for evidence of off-site sedimentation tracking. Any incidences of sedimentation tracking in these areas will be corrected immediately and noted in the inspection log. Corrective measures taken to prevent future occurrences of off-site sediment tracking will also be recorded in the inspection log and ESC Plan.

12.4.1.2 Maintenance Procedures during Construction

Maintenance procedures will be implemented as soon as possible after the need for maintenance is recognized. Contractors will utilize Good Housekeeping practices to minimize the possibility of erosion and sedimentation and spills and leaks of potential pollutants. Hazardous materials will be handled with the utmost care in accordance with state and federal regulations and the recommendations of the Manufacturer. Erosion controls will be maintained as noted below.

Hay bales: Any broken, excessively tilted or undermined hay bales will be promptly replaced or re-installed. When sediment builds up behind bales to one-half the height of the bale, the sediment will be removed or a second row of bales added. Washouts at the ends of the hay bales will be repaired and additional bales added.

Silt Fence: Sediment will be removed when it reaches one-third the height of the silt fence. Care will be taken to avoid damaging the fence during clean-out. Any areas of damaged or torn fabric, broken posts or undermined fence will be repaired immediately.

Discharge Points: Any sediment or debris accumulated at the discharge points will be removed and disposed of appropriately. As stated above, if impacts to surface waters or wetlands are observed, the source of such impact will be located immediately and improvements made to erosion and sedimentation controls in order to prevent the reoccurrence of impacts to surface waters.

PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14) March 13, 2009

General: Any debris blowing or flowing off the site will be immediately collected. Any unsafe storage practices noted in the inspection will be immediately remedied. Temporary and permanent seeding and/or planting will be inspected for bare spots, washouts, and healthy growth.

12.4.2 Inspection Procedures and Maintenance after Construction

Refer to the attached Stormwater System Inspection & Maintenance Plan included at the end of this section.

12.5 HOUSEKEEPING

12.5.1 Housekeeping during Construction

Potential pollution sources that may reasonably be expected to affect the quality of stormwater at the construction site include construction debris, soil stockpiles, and fluids associated with construction equipment (fuel and oils).

Precautions will be implemented which minimize the risk of potential pollutants impacting stormwater. All construction debris and soil stockpiles will be stabilized and placed away from surface water resources and catch basins. No stockpiled material will remain on site after the completion of the project. Construction debris will be removed from the site and disposed of properly.

If necessary, staging and storage areas will be established prior to construction. Staging areas will be located in upland areas removed from stormwater conveyance channels, catch basins and surface waters including wetlands. If necessary, contractor supplies and equipment will also be kept in this designated area. It is intended that all machinery and equipment be fueled and maintained at the designated staging area. However, heavy machinery and equipment will be fueled and maintained on site when necessary. Fuel and oils will not be stored in the project area.

12.5.2 Spill Prevention and Response Procedures

The following measures and strategies are intended to provide an overview of proper spill prevention and response procedures at the facility during construction activities in order to minimize the risk of accidental spills/releases to the greatest extent possible.

12.5.2.1 Potential Spill Area Identification

The activities and areas where spills are likely to occur are fueling and oiling areas (i.e. staging areas and construction areas).

12.5.2.2 Spill Prevention Procedures

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

To reduce spill potential, it is recommended that caution be used when filling vehicles and equipment with fuel in order to prevent overflows, that the topping off of fuel tanks be avoided, and that material transfer procedures which reduce the chance of spills be implemented.

The spill response plan (i.e., clean up) for this construction site will be as follows:

- The OWNER and CONTRACTOR will be responsible for implementing the spill response plan during construction.
- Spill response equipment will be stored in the staging area. The spill response equipment will include at a minimum:

<u>Safety equipment</u>: eye guards, protective clothing, fire extinguisher, and rubber gloves.

In the event of a spill or release:

- 1. Notify the City of Portland Fire Department of any emergency spill or leak. The phone number for emergency response is 911.
- 2. Notify appropriate State agencies:

Oil Spills must be reported to the MDEP at 1-800-482-0777. The MDEP may be reached at this number 24 hours/day.

Hazardous Materials Spills must be reported to the Department of Public Safety at 1-800-452-4664. The Department of Public Safety may be reached at this number 24 hours/day.

The following procedures will be followed by all personnel in the event of a reportable quantity spill or leak. A reportable quantity release occurs when a quantity of hazardous material is spilled or released within one 24-hour period of time and exceeds the reportable quantity level assigned to that substance.

- The facility is required to immediately notify the National Response Center at 1-800-424-8802 for chemical or oil spills that impact surface waters (including wetlands) or compromise water quality standards.
- The Facility Stormwater Pollution Prevention Plan (SWPPP) will be updated within 14 calendar days of a spill or leak of reportable quantity. The update will include a description of the release, an account of the circumstances leading to the release, and the date of the release. In addition, the SWPPP will be reviewed to identify measures to prevent the recurrence of such releases, and it will be modified where appropriate.

Stantec

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

- The Spill Prevention, Control and Countermeasures Plan (SPCC) will be updated within 14 calendar days of a spill or leak of reportable quantity. The update will include a description of the release, an account of the circumstances leading to the release, and the date of the release. In addition, the SPCC will be reviewed to identify measures to prevent the recurrence of such releases, and it will be modified where appropriate.
- In the event of a reportable quantity discharge, the facility will also submit to the EPA within 14 calendar days of knowledge of the release, a written description of the release (including the type and estimate of the amount of material released), the date that such release occurred, the circumstances leading to the release, and steps to be taken to modify the pollution prevention plan at the airport.

All appropriate personnel will receive instruction pertaining to proper spill response and notification procedures.

12.5.3 Groundwater Protection

Liquid petroleum products and other materials with the potential to contaminate groundwater will not be stored or handled in areas of the site draining to an infiltration area. An "infiltration area" is any area of the site that accumulates runoff that infiltrates into the soil. Dikes, berms, sumps, and other forms of secondary containment that prevent discharge to groundwater may be used to isolate portions of the site for the purposes of storage and handling of these materials. The appropriate pollutant removal Best Management Practices (BMPs) will be consulted prior to onsite storage of these materials in order to prevent impacts to groundwater quality.

12.5.4 Fugitive Sediment and Dust

Locations where vehicles enter or exit the site will be inspected weekly for evidence of off-site sediment tracking. If off-site sediment tracking is observed, the sediment will be removed and measures taken to prevent future occurrences of off-site sediment tracking. A temporary stabilized construction entrance will be used by construction equipment to minimize sediment tracking. Oil will not be used for dust control; water will not be drawn from a stream without first obtaining a permit.

12.5.5 Debris and Other Materials

Any debris blowing or flowing off the site will be immediately collected. Any unsafe storage practices noted during inspection will be immediately remedied. Contractors will utilize Good Housekeeping practices to minimize the possibility of erosion and sedimentation and spills and leaks of potential pollutants. Hazardous materials will be handled with the utmost care in accordance with state and federal regulations and the recommendations of the manufacturer.

Stantec

PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

12.5.6 De-watering

In the event that dewatering and / or predrainage is necessary for construction of the proposed improvements, adequate filter BMP's shall be provided to ensure that runoff leaving the site shall be relatively free of sediment. This may include installation of a pumped discharge sediment control device such as Dirtbag supplied by ACF Environmental, Wilmington, MA (978-657-0711), a riprap lined settling basin, or approved equivalent. The collected water will not flow over disturbed areas.

12.5.7 Non-stormwater Discharges

The following non-stormwater discharges may occur on the site during the construction period:

- Discharges from fire fighting activities
- Waters (without soap) used to wash vehicles or control dust in accordance with efforts to minimize off-site sediment tracking

All allowed non-stormwater discharges will be directed to a storm drainage system or a natural conveyance channel without impacting disturbed areas. Any illicit connections to the stormwater drainage system will be eliminated and any associated non-stormwater discharges will be reported in order to achieve compliance with all current federal, state and local requirements.

12.5.8 Housekeeping after Construction

WASTE MATERIALS: Any waste materials will be collected and stored in a manner that will prevent materials from entering drainage systems including storm drain pipes, natural conveyance channels, wetlands or other off-site areas. Material will be regularly collected and disposed of off-site in a manner consistent with federal, state and local regulations.

HAZARDOUS WASTE: Any and all hazardous materials will be used and/or disposed of in accordance with the manufacturer's recommendations and in a manner that is consistent with state and federal regulations.

Good Housekeeping practices will also include the maintenance of clean surfaces by pavement sweeping, using brooms and/or shovels, picking up garbage and waste material regularly, checking maintenance equipment for proper operation, conducting routine inspections to check for leaks and conditions that could lead to discharge of chemicals or contact with stormwater by waste materials, ensuring spill clean-up procedures are understood and implemented by employees, and maintaining appropriate material storage and inventory practices. The stormwater drainage system will be inspected as required to ensure proper operation. The Stormwater Pollution Prevention Plan (SWPPP) and Spill Prevention Control and

Stantec

PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

Countermeasure Plan (SPCC) developed for this airport contains a more detailed plan which addresses Good Housekeeping strategies after construction is complete.

12.6 REVISIONS

The Erosion and Sedimentation Control Plan, Inspection and Maintenance Plan, and Good Housekeeping Plan will be amended whenever there is a change in design, construction, operation, or maintenance at the construction site that has or could have a significant effect on the discharge of pollutants to the waters of the United States not previously addressed in this plan.

These Plans will also be amended if during inspections or investigations by the RPR, regulating officials, or designated facility inspector, it is determined that the plans are ineffective in eliminating or significantly minimizing pollutants in stormwater discharges from the facility site. The plan will be modified as necessary to include additional BMPs designed to correct identified problems. Revisions to these Plans will be completed within seven (7) calendar days following the inspection.

If existing BMPs require modification or if additional BMPs are necessary for any reason, implementation will be completed within seven (7) calendar days of inspection and prior to the next storm event. If implementation before the next storm event is impracticable, the situation will be documented in the Plans and alternative BMPs will be implemented as soon as possible.

12.7 RECORD KEEPING

Within 24 hours of inspections, both during and after construction, a report (log) will be prepared summarizing the scope of the inspection and any corrective actions taken, the names and qualifications of the person(s) making the inspections, and the date(s) and time of inspection. Additional information listed in the following two paragraphs will also be included:

If the inspection occurs during construction, the report will include a description of major observations about the operation and maintenance of erosion and sedimentation controls, materials storage areas if exposed to precipitation, and vehicular access points to the parcel. Major observations will include, if necessary, BMPs that need maintenance, BMPs that are not performing as intended or are inadequate for a particular location, and location(s) where additional BMPs are needed.

If the inspection occurs after the construction is complete, the report will include a description of the inspection finding or maintenance task that was performed. In addition, if a clean-out of any sediments or debris was required, the location of disposal after removal will be noted.

The inspection reports will be signed by the responsible person designated by the registrant. These reports will be filed with the plan and kept on-site for a minimum of three years after the date of the Notice of Termination (NOT). The permittee will submit a NOT to the Maine

Stantec PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT BASIC STANDARDS (Site Location Section 14)

BASIC STANDARDS (Site Location Section 14)
March 13, 2009

Department of Environmental Protection within 20 days of achieving permanent stabilization at the site **or** after coverage under an alternative permit has been obtained.

12.8 RE-CERTIFICATION

The airport will submit a certification of the following to the Department within three months of the expiration of each five-year interval from the date of issuance of the permit: identification and repair of erosion problems; inspection and repair of the stormwater control system; and maintenance of the erosion and stormwater control system(s), including the maintenance of post-construction inspection/log reports (refer to documents in the back of this section).

INSPECTION AND MAINTENANCE DURING CONSTRUCTION

	INSPECTIO	N REPORT FORM	s FOR EROSION	CONTROLS	
			DATE:		
			OF LAST RAIN F		
AREA STABILIZATION	DATE LAST DISTURBED	DATE OF NEXT DISTURB.	STABILIZED2	STABILIZED WITH/BY	
TO BE PERFOR	MED BY:		ON C	R	

BEFORE:

INSPECTION REPORT FORMS FOR STABILIZATION PRACTICES INSPECTOR:_____ DATE:____ DAYS SINCE LAST RAINFALL: ____AMOUNT OF LAST RAIN FALL ___INCHES IN PLACE? CONDITION SEDIMENT WASHED ACTION LOCATION OUTOR DEPTH OF OVERTOPPE CONTROL D STABILIZATION REQUIRED: TO BE PERFORMED BY:______BEFORE:____ ON OR

INSPECTION AND MAINTENANCE AFTER CONSTRUCTION

STORMWATER SYSTEM INSPECTION & MAINTENANCE PLAN Remote Parking Lot – Drainage Improvements Portland International Jetport Portland, Maine

1. Maintenance Responsibility:

It shall be the responsibility of the **Portland International Jetport** to implement the Stormwater Maintenance Plan in accordance with the provisions set forth herein:

Owner: Portland International Jetport 1001 Westbrook Street

Portland, Maine 04102

B. Telephone:

(207) 874-8877

Fax:

(207) 774-7740

C. Contact Person: Artie Sewall, Operations Manager

2. Inspection of Drainage Structures:

- A. Inspect all catch basins, drain manholes, culverts, ponds, soil filters and outlet structures once each month inclusive from March through November. Owner may designate a responsible party to perform monthly inspections. Inspection shall include as a minimum:
 - 1) Visual inspection of grates and covers. Report any defective or damaged frames and covers and repair or replace such defects prior to the next month's inspection.
 - Visual inspection of catch basins and drain manholes. Report any loose, broken or defective bricks or risers. Report any cracked or leaking structures including top section, barrel sections, bottom section, and seals. Repair or waterproof defects as needed to restore integrity of structure prior to next inspection.
 - 3) Visual inspection of catch basin sumps. Remove sediment from each basin as required when sediment level reaches a level of six inches below outlet pipe. Sediment shall be removed and disposed of off-site to an acceptable location in such a manner so as not to be washed into stormwater flowpaths or other drainage structures.
 - 4) Visual inspection of pipe inlets and outlets. Remove accumulated debris or sediment from pipe inverts to prevent obstruction of flow.
 - 5) Visual inspection of detention pond including sideslopes, embankments, vegetated areas, riprap spillways, aprons and outlets. Remove accumulated debris or sediment from detention pond bottom. Mow, trim, cut, reseed, repair or replant vegetated areas. Mowing should be performed on a limited basis, no more than twice per year in order to maintain grass length less than 12 inches in height.

6) Upon completion of final monthly inspection each November report all outstanding defects, damage or maintenance deficiencies to Owner in writing identifying each location, defect or deficiency and take corrective action to restore all components of the stormwater management system immediately prior to significant snow and icing conditions.

3. Emergency Measures:

Owner or designated responsible party shall report any problems in performance, damage or other defects, which may significantly reduce the efficiency, or performance of the system. Such problems shall be reported immediately to Owner without waiting until next scheduled maintenance inspection. Owner shall authorize responsible party, where applicable, to perform emergency repairs as required insuring proper operation of system.

4. Annual Maintenance:

- A. Prior to, or at the time of, the initial monthly inspection in March of each year the Owner or his designated party shall perform, or engage a contractor to perform, maintenance to remove accumulated winter sand and debris from all pavement areas, to prevent washing of sediment into structures and underground storage pipes. The following measures may be used:
 - 1) Mechanical sweepers
 - 2) Vacuum sweepers
 - 3) Pavement flushing may be used only if followed by sump cleaning of all structures.
- B. Following pavement cleaning, a visual inspection shall be made of all catch basin sumps. Sediment and debris shall be removed if sediment has reached a depth of at least six inches in any basin sump.

5. General Maintenance:

General maintenance shall include preventive measures related to the site, which may help preserve and maintain the stormwater management system. Such measure should include, but not be limited to:

- A. Removal of trash, debris, leaves, broken or fallen twigs and branches, etc. from the site, especially in areas where such objects may be washed into the stormwater management system.
- B. Removal of spills, broken glass, etc. which may have the potential to enter the stormwater management system.
- C. Repairs to culverts, rip-rap, ditches, eroded areas, landscaping, lawns, etc. of the site to reduce the potential for sedimentation and to improve the efficiency of the stormwater management system.

STORMTREAT Operation & Maintenance

Operation and maintenance of the StormTreat System is limited to annual inspections and solids removal on an asneeded basis. Annual inspections should include the following steps:

- 1. Check the discharge flow rate. The lower outlet is designed to discharge at a rate of 2 gallons/minute. This provides for a retention time of approximately 10.7 hours for the full tank to empty following a storm event. The discharge rate should be checked by directly measuring a timed-discharge volume if the outlet is "daylighted" or through "falling-level" measurements inside the central sedimentation chambers. The total static volume of the tank is 1280 gallons and the height of the tank is 4 feet, therefore a 2 gallon/minute discharge rate can be observed as the water level in the tank falling at a rate of 4.5 inches/hour.
- 2. Measure sediment depth inside the sedimentation chamber and schedule a pump-out if depth reaches 5 inches. A future pump-out date can be estimated by projecting based upon sediment accumulation rates since the last measurement or since original installation. On average, StormTreat Systems need to have sediment removed once every three years. This can be done using a standard septic system pump truck.
- 3. Observe wetland plant conditions and height during growing season. Wetland plants may need to be supplemented during the first three growing seasons depending upon local site conditions. Established plants should be trimmed back in order to maintain access to tank lids and debris should be cleaned from wetland chamber surface.

between storms

Detention Basin Operation, Maintenance, Management and Inspection Checklist

Project: Portland International Jetport -	- Remote Parking Lo	<u>t</u>
Location: Portland, Maine		
Site Status:		
Date:		
Time:		
Inspector:		
MAINTENANCE ITEM	SATISFACTORY / UNSATISFACTORY	COMMENTS (see last page if more space is needed)
1. Debris Cleanout (Monthly)		
Basin Bottom/ Trench Surface Clear of Debris		
Inlet/ Inflow Pipes Clear of Debris		
Outlet Clear of Debris		
Emergency Spillway Clear of Debris		
2. Sediment Traps or Forebays (Ann	ual)	
Obviously trapping sediment		
Greater than 50% of storage volume remaining		
3. Vegetation (monthly)		
Mowing done no more than 2X/YR (kept less than 12 inches high)		
No evidence of erosion		
Fertilized (avoid if poss.), harvested, pruned, or weeded as needed		
4. Dewatering (Bi-annually; After Ma	ijor Storms)	
Basin dewaters within 24 hours		

MAINTENANCE ITEM	SATISFACTORY / UNSATISFACTORY	COMMENTS	
5. Sediment Cleanout of Basin (Annual)			
No evidence of sedimentation			
Sediment accumulation does not yet require cleanout (no noticeable loss of detention volume capacity)			
6. Inlets (Annual)			
Good condition			
No evidence of erosion			
7. Outlet/Overflow Spillway (Annual,	After Major Storms		
Good condition, no need for repair			
No evidence of erosion			
8. Aggregate Repairs (Annual)			
Surface of aggregate clean			
Top layer of stone does not need replacement			
Trench does not need rehabilitation		·	
9. Structural Repairs (Annual, After N	lajor Storms)		
Embankment in good repair			
Side slopes are stable			
No evidence of erosion			
10. Fences/Access Repairs (Annual)			
Fences in good condition			
No damage which would allow undesirable entry			
Lock and gate function adequate			
Access point in good condition			

If clean-out of any sediments or debris is required, indicate where the sediment and debris was disposed after removal.

Comments:

Actions to be Taken:

IMPORTANT

INSPECTION CERTIFICATION FORM

CERTIFICATION:

I CERTIFY UNDER PENALTY OF LAW THAT THIS DOCUMENT AND ALL ATTACHMENTS WERE PREPARED UNDER MY DIRECTION IN ACCORDANCE WITH A SYSTEM DESIGNED TO ASSURE THAT QUALIFIED PERSONNEL PROPERLY GATHERED AND EVALUATED THE INFORMATION SUBMITTED. BASED ON MY INQUIRY OF THE PERSON OR PERSONS WHO MANAGE THE SYSTEM, OR THOSE PERSONS DIRECTLY RESPONSIBLE FOR GATHERING INFORMATION, THE INFORMATION SUBMITTED IS, TO THE BEST OF MY KNOWLEDGE AND BELIEF, TRUE, ACCURATE AND COMPLETE. I AM AWARE THAT THERE ARE SIGNIFICANT PENALTIES FOR SUBMITTING FALSE INFORMATION, INCLUDING THE POSSIBILITY OF FINE AND IMPRISONMENT FOR KNOWING VIOLATIONS.

Note: The Site Location of Development permit application is included after the title page of the document prepared for this project.

PROJECT COVERED BY THIS PERMIT:

PROJECT DESCRIPTION:

Remote Parking Lot – Drainage Improvements

Outer Congress Street

ADDRESS/LOCATION: Portland International Jetport

1001 Westbrook Street Portland, Maine 04102

REQUIRED SIGNATURES:

Note: This certification must be completed after each inspection to signify that the inspection has been properly completed and the site has been found to be in compliance with Maine Site Location of Development regulations.

SIGNED:	-
TITLE:	<u></u>
COMPANY:	
ADDRESS:	-
TELEPHONE:	
DATE:	-

13.0 SOLID WASTE (Site Location Section 18)

A small amount of construction debris will be produced during construction of the proposed improvements. It is anticipated that all excavated materials will be re-used for construction of embankments or re-used as topsoil. The existing Vortech water quality unit and several catch basin structures are proposed to be demolished. The frames and covers will be salvaged for re-use, but the concrete and stormdrain piping will be removed from the site and disposed of at an appropriate licensed facility in accordance with all applicable local, state and federal requirements. The estimated amount of demolition material is approximately 25-30 cubic yards. The contractor that is awarded the construction work will be required to submit a disposal plan identifying the ultimate site of disposal to the applicant for review and approval prior to commencing work.

Stantec PORTLAND INTERNATIONAL JETPORT REMOTE PARKING LOT

14.0 NOTICES (Site Location Section 25)

Notice of Intent to File was sent by certified mail to all property abutters and was published in the Portland Press Herald. Included in this section are the following items:

- 1. Copy of Notice of Intent to File (Form B)
- 2. Public Notice Filing and Certification (Form C)
- 3. List of Abutting Property Owners

PUBLIC NOTICE: NOTICE OF INTENT TO FILE

Please take notice that

Portland International Jetport, 1001 Westbrook Street, Portland, Maine 04101, 207-756-8313 (Name, Address and Phone # of Applicant)

is intending to file a Site Location of Development Act permit application with the Maine Department of Environmental Protection pursuant to the provisions of 38 M.R.S.A. §§ 481 thru 490 on or about

March 16, 2009 (anticipated filing date)

The application is for

Construction of Drainage Improvements

(description of the project)

at the following location:

Portland International Jetport Remote Parking Lot adjacent to City Snow Dump, 2378 Congress Street, Portland, Maine (project location)

A request for a public hearing or a request that the Board of Environmental Protection assume jurisdiction over this application must be received by the Department in writing, no later than 20 days after the application is found by the Department to be complete and is accepted for processing. A public hearing may or may not be held at the discretion of the Commissioner or Board of Environmental Protection. Public comment on the application will be accepted throughout the processing of the application.

For Federally licensed, permitted, or funded activities in the Coastal Zone, review of this application shall also constitute the State's consistency review in accordance with the Maine Coastal Program pursuant to Section 307 of the federal Coastal Zone Management Act, 16 U.S.C. § 1456. (Delete if not applicable.)

The application will be filed for public inspection at the Department of Environmental Protection's office in Portland during normal working hours. A copy of the application may also be seen at the municipal offices in Portland, Maine. (town)

Written public comments may be sent to the regional office in Portland, Augusta, or Bangor where the application is filed for public inspection:

MDEP, Southern Maine Regional Office, 312 Canco Road, Portland, Maine 04103

PUBLIC NOTICE FILING AND CERTIFICATION

The DEP Rules, Chapter 2, require an applicant to provide public notice for all Site Location projects with the exception of minor revisions and condition compliance applications. In the notice, the applicant must describe the proposed activity and where it is located. "Abutter" for the purposes of the notice provision means any person who owns property that is BOTH (1) adjoining and (2) within one mile of the delineated project boundary, including owners of property directly across a public or private right of way.

- 1. **Newspaper:** You must publish the Notice of Intent to File in a newspaper circulated in the area where the activity is located. The notice must appear in the newspaper within 30 days prior to the filing of the application with the Department. You may use the attached Notice of Intent to File form, or one containing identical information, for newspaper publication and certified mailing.
- 2. **Abutting Property Owners:** You must send a copy of the Notice of Intent to File by certified mail to the owners of the property abutting the activity. Their names and addresses can be obtained from the town tax maps or local officials. They must receive notice within 30 days prior to the filing of the application with the Department.
- 3. **Municipal Office:** You must send a copy of the Notice of Intent to File <u>and</u> a **duplicate of the entire application** to the Municipal Office.

ATTACH a list of the names and addresses of the owners of abutting property.

CERTIFICATION

By signing below, the applicant or authorized agent certifies that:

- 1. A Notice of Intent to File was published in a newspaper circulated in the area where the project site is located within 30 days prior to filing the application;
- 2. A certified mailing of the Notice of Intent to File was sent to all abutters within 30 days of the filing of the application;
- 3. A certified mailing of the Notice of Intent to File, and a duplicate copy of the application was sent to the town office of the municipality in which the project is located; and
- 4. Provided notice of, if required, and held a public informational meeting in accordance with Chapter 2, Rules Concerning the Processing of Applications, Section 14, prior to filing the application. Notice of the meeting was sent by certified mail to abutters and to the town office of the municipality in which the project is located at least ten days prior to the meeting. Notice of the meeting was also published once in a newspaper circulated in the area where the project site is located at least seven days prior to the meeting.

The Public Informational Meeting was held on _	N/A · · · · · · · · · · · · · · · · · · ·
	Date
Approximately <u>N/A</u> members of the p	public attended the Public Informational Meeting.
Signature of Applicant or authorized agent	

SYSCO Food SVCS of Northern

Tew England Inc.

Thomas Drive

Westbrook, ME 04092

203*000*114* /003*000*115

Sablegolf, LLC 1000 Market Street ortsmouth, NH 03801 003*000*006/ 069//003/A


ity of Portland 389 Congress Street Portland, ME 04101 33 A002001/A006001 u47//005// Royal Four LLC. C/O Richard Atkinson 47 Thomas Drive Westbrook, ME 04092 003-000-117


Parker - Hannifin Corp 6035 Parkland Blvd. Cleveland, OH 44124 234 A002001

Portland Water District 225 Douglass Street Portland, ME 04102 A233 A005001 Silvex Inc. 45 Thomas Drive Westbrook, ME 04092 003*000*118

072//018//

Maine Turnpike Authority
430 Riverside St.
Portland, ME 04103
233 A001001/A008001/069//002/A
047//004//
1515 Sable LLC
1515 Sable Oaks Drive
South Portland, ME 04102








To Control of the Con	CienVProject	PORTLAND INTERNATIONAL JETPORT	REMOTE PARKING LOT DRAINAGE IMPROVEMENTS	Daylond Molno
Antine C.	Cfentif	2 4	至五	å

JEIPORI	REMOTE PARKING LOT DRAINAGE IMPROVEMENTS	Portland, Maine	GRADING AND DRAINAGE PLAN	
닉	분동	Por	1913	

	Revision	0
Scala 1"=20"	Sheet	1 of 5
Project No. 195210313	Drawing No.	5






Py Appl. 17184.00

Den. Chid, Degn. WAMSO Re Name Std. 7_deloft.deg


REMOTE PARKING LOT DRAINAGE IMPROVEMENTS Pouland, Maina Clen/Project PORTLAND INTERNATIONAL JETPORT

Tue DETAILS


AS NOTED Project No. 195210313 $^{\circ}$




SPECIFIC APPLICATION THEN WHERE THE INLET DRAINS A RELATIVELY YEAT AREA (SLOPES NO GREATRE THAN SX) WHERE SHEET OR OVERLAND FLOMS (NOT EXCEEDING 0.5 cfs) ARE TYPICAL. HAY BALE DROP INLET SEDIMENT FILTER SCALE, N.T.S.




HAY BALE SILTATION FENCE SCALE, N.T.S. REMOVE SILT PERIODICALLY AS NECESSARY. REMOVE SILT AND HAY BALES WHEN CONSTRUCTION HAS BEEN COMPLETED.




RIP RAP QUTFALL DETAIL SCALE: N.T.S.



RIP RAP INLET DETAIL SCALE: N.T.S.



- The remote management according to the property of the propert
 - HILDS EQU. CONDITIONS, THE USE OF STAFLE OR STAFL EDWING GRENEY THAN 4" MAY BE RECESSIFY TO PROPERLY SCUIET HE BLANKETS.



- NOT CHIEF BANGET IN DESCRIPT OF BANGET HER SECONDAL PROPERTY FOR STREET, BY PANCE IN THE PROPERTY SEC ALMERT RESERVED, ALL BANGET WITE SECONDAL PROPERTY FOR SECONDAL PROPERTY OF PANCES IN THE SECONDAL PROPERTY OF THE SECONDAL CONTINUES AS SHOWN IN THE SECONDAL PROPERTY OF SECONDAL
 - DIO CYCR DIO (SWINZ STAZ) WIN 4.4-6" OYCRAP. UIT A DOUBLE FOR OF NO 4" ON CROSS DOUS SUICE ELANCETE. TO 0" OT SOC SLOSS UNSTIE AMORED WIN A NOW OF STAMLES/FIRMES APPROXIMA
- AND THE STATE OF T

NOTE.

** NESTRANT D. ALLM. STOCKE, TO STOCKE THE STOCK

EROSION CONTROL MESH CHANNEL INSTALLATION DETAIL SCARE N.T.S.

INSTAM NOS BEDI ENGLEROS, DE PROMOZ A STRATOR FOR CONTRILLARO SOL, DOCOM, AND SEDIMENTION OURING AND ATTEL CONSTINCTION TO THE TOTAL DIMENSION OF THE SECOND OF THE CONTRILLOR OF THE TREATED STATE SECOND OF THE TREATED STATE SECOND OF THE TREATED SECOND OF THE TREA

HE EQUIPMENT ANTICATED TO BE USED FOR CONSTRUCTION MAY NACLUE THE FOLLOWIG, EACHWIGH, BALLDOZER, LOUCER, TRUCKS, LOUCOMPACHE, ANTICASE, ON THE TRUCKS ALCOMES, ALCHOUSE WE IS UTILIZED. THE FOLLOWING ULTHOOS WILL BE UNDERTHER IN PRODUCE ALCOMES, THE SCALE WHITH, AND ABITING LOUCE.

. PROB TO CRUBBING OR ANT COTHADONG DETANDIN, STATION FONCE WILL BE INSTILLED ACROSS THE SLOPE ON THE CONTIGUIAT THE TOWN AS PROTECTIVE ANASIST CONSTRUCTION RELATED ENSING. SLATION TEXICE SMILL ALSO BE NETALLED AT THE CONTINUE OF THE BEGG OF SOIL SCHOOLES. TIJPOONT STANON CONTRO, NGENS SAAL BE NSTALED AT AL EXSTING CURGAT/ STONOMAN NACT LOCATIONS. SEE ALME ENOSION SEDISTRANDI CONTROL BYP D-3.

A LA SEADH FREQ. (THE WHINE STORTED AGENCE AGENCES THE REPORTED FOR CONDICION OF ACCESS WAS AGENCED. A CALL OF A SEADH FREQUENCY AND A CALL OF A C I, REJOUL OF SULMON FENCE / ITLA-DAMP SEDUENT CONTROL MÉJSURES SHALL OCCUR WITHIN THAITY (30) DAYS OF PERUMENT STABLIZATION.

AL DICH BASE TO BE SEEDD SWIL ALD BE LVED WIN DROOM COMPO. MESH TO SHAUJE THE DICH CHANNES UNT. MEDIATON IS SHOW CONSIDES, SHOW CONCER, WAS AND THAN-OWN MACHONG WIFE ISSUED ON SHAULT ANY SECTION OF NOOM COADD DICH THAT NOT THAL DADGE AND FEMARICAL SHAULED WHICH THE VIEW (7) DAYS. . TO PROMOT PROTECTION AGNOST REGISCON, PIPRAP WILL BE PLACTD AT ALL STONIOWIN WILTS AND QUILLTS AS SHOWN ON THE CONTRACT STRANGS, SEE ALSO WANE EROSSON AND SEDWENTATION CONTROL, BUY E-2 AND E-3.

). THE EPOSED MEA SHOULD BE LUNTED TO THAT IN INFICH WORK IS TO OCCUR DURNO THE FOLLOWING 13 DAYS. SEEDING, AND, REVEEKTABUR PLAN.

WORDENDY OF STE CONSTRUCTION, ALL MEAS PREMAUSTY DISTURIED MILL BE TREATED AS STATED BELOIK. THESE MEAS WILL BE CLOSEN MUNICATED OF THE CONTINUED WITH, SUCH THE AS A SAISTACTORY GROWIN OF VECTANON IS ESTABLISHED. LOAM WILL BE SPREAD OVER ALL DISTURBED AREAS AND GRADED TO A UNIFORM DEPTH OF 4 WCHES. Notes

DISTURBED ANDAS WAL BE SEEDED AT THE RATE OF 1 LB PER 1000 SF. SEE ITEM 7-801-2.1 IN THE CONTRACT SPECIFICATIONS FOR SEED A AGRICACIURA, LUGGICINE AND FERFLEZCH WILL BE INCORPOINTED INTO THE SOL PROR TO SEEDING. SEE ITEM T-901-22 AND 2.3 IN THE CONTRACT SPECIFICATIONS FOR DETAILS. 2. AL DROGED SUFFICE NOT TO BE THAL BUILD FOR THE THE OF THAT AND STORMER THE DATE, ANNUAL THROUGH ON THE STEED WITH WHITE RIFE, DATE, ANNUAL STEED WAS STEED S. SEEDIG MIL DE COUPLETED BETWEEN THE DATES OF JAXY 1 AND SEPTEMBER 15. WINDATION JAXY DE RECUMED DURING THE PERIOD OF TIME 1 TO AUGUST 15. areas which have been teuporariy or peddjanty seeded saull be aulched invedately follomag seedhio

. HAY BUICH WEL BE APPLIED AT THE BATE OF 73—80 LEB FOR 1000 ST. MUCH SMALL BE MICHORED WITH BOOKENDARE METHON ON DEPENDENCE SIGNAL OF MICHORED WAS ANNEXED THE FOR YOUR SETTING THE SETTING TO SET OF THE OFFICE OFFICE AND THE CHARGE WAS THE USE OFFICE OFFICE OFFICE OFFICE OFFICE AND THE CHARGE STATE AT SA WE HEN THE

D. ALL SCONENT CONTROL STRUCTURES YALL RELIAN IN PLACE UNTIL VECETATION IS ESTABLISHED. ESTABLISHED WEAKS A WANDING OF BSSL OF THE AREA S VECETATION WITH VECTABLISH SHOWING. а. АД МІОНІЗ SWAL ВЕ NSPECTED РЕВОФСАЦУ, РАМСШАЛІУ АТЕЛ ПАНТАL. Г. LESS THAN 80% OF THE DISTURBED AREA IS CONFRED, МОБЛОМ, МАСОН RILL BE SPRED.

SEE HANK EROSION AND SEDIMENTATION CONTROL BUP A-3 FOR DETAILS ON THE FOLLOWING

AL (1805-160) House and downed hell of construction for staded to a serve delate han in its received well of AL (1805-160) delate serve delate in construction of serve the serve han is a first of the serve construction of the serve is the serve that in construction of serve serve of serves of serves of serves of the serve in the serve is the serve in the serve is the serve in the serve is the serve of serves of serves of serves of the serve in the serve is the serve i

CODRIL IN TACIO N AL DIGH DAWRIGS BRIGG WEITHINS HAS HEN FETRAERINGS 500 WELF DERDO TO A HEIDER OF OR FOOT TO WEITHE THE WEITH STREET WEITHINGS TO WEITHINGS TO A WEITHINGS TO A WEITHING THE WEITHING THE WEITHINGS TO WEITHINGS TO WEITHINGS TO WEITHINGS TO WEITHINGS TO WEITHINGS TO WE WEITHINGS TO WEITHIN

NORWBER 1-THE DITCH WILL BE UNED WITH STONE RIPRAP. THE SLOPE WILL BE CONCRED WITH ERGSION CONTROL MIX OR STONE RIPRAP, OR, TERMINELY:

Norwert 10— The ostumbed son, wal be aucojed at the mater ince and amonored properly. E water construction persod is from norgaber 1 to april 16,

WHITE ECONNION AND CORTHMONN SHALL BE COUNTIND SUCH THAT NO MORE THAN 1 ACRE OF THE SITE OF WINDOW SYNGLIZHION AT ANY INEL. THE LIMITED THAN IN HIGH WENCH IS TO OCCUR DARWE THE FOLLOWING IS DAYS AND THOSE AND SHALL BE LUCKED IN ONE LAY PROVINCED THAN SON EVENT.

SOL STOCKHES WIL BE MILOJED AT WATER ARTHY 24 HOURS OF STOCKHO AND RESTIVALISHED PRICH TO RAIN OR SYMPFALL. NO STOCKHES MIL BE PLACED WITHIN 100 FEET OF LACES, STREAMS, NETLANDS, OR OTHER NATURAL RESOURCES. HAY NUICH WILL BE APPLED TO A DESTIN OF 4 INCHES (180 LES PER 1000 ST). ANTER ELE DEN OF THA, ERAUAN ANT PERTURBED MATE, NILL BE STABLIZED WITH ARCHITED MALCH OR ERGEON CONTING, MESH, NO SERVICES SHOULD BY WEST, PROMOBIN THE MALCH.

PROTOCOLOGY OF THE CHARGES AND THE THROUGH THE THROUGH THE CHARGES AND THROUGH THE THROUGH THE THROUGH THE THROUGH THE THROUGH THE THROUGH THE THROUGH THROUGH THE THROUGH THR лидения од притират на становите постои на становите постои становите на harlinda and acatoring of erioda compigurata will be the responsblit of the contractor under the superason of The project engineer and the inspector for stance consultang seraces, Mic.



INSTALL EROSION CONTROL MESH TO A HEIGHT OF 4" ABOVE DITCH CENTERLINE GRADE. (SEE DETAL THIS SHEET)

TYPICAL DITCH SECTION SCALE: N.T.S.



Stantec

Opposition Reserved

Deposition of the supposition of the supposition

9) rept. YTALIO


Re Hors: SALL ern_colitifier Grv. Chd. Digt. WAMAN


PORTLAND INTERNATIONAL JETPORT

REMOTE PARKING LOT DRAINAGE IMPROVEMENTS Portland, Malne

EROSION CONTROL NOTES AND DETAILS

	Revision	0
Scale AS NOTED	Sheet	3 at 5
 Project No. 195210313	Drawing No.	ຮ







Strengthening a Remarkable City. Building a Community for Life

www.partlandmaine.goi

Planning & Urban Development Department Penny St. Louis Littell, Director

Planning Division
Alexander Jaegerman, Director

May 8, 2009

Cuyler Feagles
Portland International Jetport
1001 Westbrook St.
Portland, ME 04102

RE: 2378 Congress St. CBL: 233-A002

Application ID: 2009-0039

Dear Mr. Feagles:

On May 8, 2009, the Portland Planning Authority approved an amendment to a site plan for drainage improvements on the remote parking lot of the Portland International Jetport.

The approval is based on the submitted site plan 5/8/09. If you need to make any modifications to the approved site plan, you must submit a revised site plan for staff review and approval.

Please note the following provisions and requirements for all site plan approvals:

- 1. The site shall be developed and maintained as depicted in the site plan and the written submission of the applicant. Modification of any approved site plan or alteration of a parcel which was the subject of site plan approval after May 20, 1974, shall require the prior approval of a revised site plan by the Planning Board or the planning authority pursuant to the terms of this article. Any such parcel lawfully altered prior to the enactment date of these revisions shall not be further altered without approval as provided herein. Modification or alteration shall mean and include any deviations from the approved site plan including, but not limited to, topography, vegetation and impervious surfaces shown on the site plan. No action, other than an amendment approved by the planning authority or Planning Board, and field changes approved by the Public Services authority as provided herein, by any authority or department shall authorize any such modification or alteration.
- 2. Final sets of plans shall be submitted digitally to the Planning Division, on a CD or DVD, in AutoCAD format (*,dwg), release AutoCAD 2005 or greater.
- 3. A performance guarantee covering the site improvements as well as an inspection fee payment of 2.0% of the guarantee amount and seven (7) final sets of plans must be submitted to and approved by the Planning Division and Public Works prior to the release of the subdivision plat for recording at the Registry of Deeds or prior to the release of a building permit, street opening permit or certificate of occupancy for site plans. If you need to make any modifications to the

approved plans, you must submit a revised subdivision or site plan application for staff review and approval.

- 4. The site plan approval will be deemed to have expired unless work in the development has commenced within one (1) year of the approval or within a time period agreed upon in writing by the City and the applicant. Requests to extend approvals must be received before the expiration date.
- 5. A defect guarantee, consisting of 10% of the performance guarantee, must be posted before the performance guarantee will be released.
- 6. Prior to construction, a pre-construction meeting shall be held at the project site with the contractor, development review coordinator, Public Work's representative and owner to review the construction schedule and critical aspects of the site work. At that time, the site/building contractor shall provide three (3) copies of a detailed construction schedule to the attending City representatives. It shall be the contractor's responsibility to arrange a mutually agreeable time for the pre-construction meeting.
- 7. If work will occur within the public right-of-way such as utilities, curb, sidewalk and driveway construction, a street opening permit(s) is required for your site. Please contact Carol Merritt at 874-8300, ext. 8828. (Only excavators licensed by the City of Portland are eligible.)

The Development Review Coordinator must be notified five (5) working days prior to date required for final site inspection. The Development Review Coordinator can be reached at the Planning Division at 874-8632. Please make allowances for completion of site plan requirements determined to be incomplete or defective during the inspection. This is essential as all site plan requirements must be completed and approved by the Development Review Coordinator prior to issuance of a Certificate of Occupancy. Please schedule any property closing with these requirements in mind.

If there are any questions, please contact Eric Giles at 874-8723.

Sincerely,

Alexander Jaegerman Planning Division Director

Electronic Distribution:

Penny Littell, Planning & Development Dept. Director Alexander Jaegerman, Planning Division Director Barbara Barhydt, Development Review Services Manager Philip DiPierro, Development Review Coordinator Marge Schmuckal, Zoning Administrator Tammy Munson, Inspections Division Lisa Danforth, Administrative Assistant Michael Bobinsky, Public Works Director Kathi Earley, Public Works Bill Clark, Public works Jim Carmody, City Transportation Engineer Keith Gautreau, Fire Prevention Jeff Tarling, City Arborist Assessor's Office Approval Letter File Hard Copy: Project File



Stantec Consulting Services Inc. 22 Free Street Suite 205 Portland ME 04101-3900 Tel: (207) 775-3211

Tel: (207) 775-3211 Fax: (207) 775-6434

May 8, 2009 File: 195210313

Mr. Eric Giles
Planning Division
389 Congress Street 4th Floor
Portland, Maine 04101

Dear Mr. Giles:

Reference:

Site Plan Amendment Application

Portland International Jetport - Remote Parking Lot

Portland, Maine

Please find enclosed seven (7) copies of the final stamped Site Plan drawings with revisions based on review comments received from Mr. Dan Goyette of Woodard & Curran (review comment letter attached). A reduced set of drawings (11"x17") is also enclosed, along with a CD containing the electronic copies of the drawings, in both PDF and AutoCAD format.

Please feel free to contact us if any additional information is required.

Sincerely,

STANTEC CONSULTING SERVICES INC.

David P. Nadeau, P.E. Transportation Engineer Tel: (207) 775-3211

Fax: (207) 775-6434 dave.nadeau@stantec.com

Attachment: as stated

c. Cuyler Feagles - PWM

dpn u:\195210313 (wan)\aviation\planning\portland planning\review comment cover letter.doc

41 Hutchins Drive Portland, Maine 04102 www.woodardcurran.com

T 800.426.4262 T 207.774.2112 F 207.774.6635

MEMORANDUM



TO: Eric Giles

FROM: Dan Goyette, PE

DATE: April 30, 2009

RE: Jetport Satellite Parking Lot

Woodard & Curran has reviewed the Site Plan Application for the construction of drainage improvements at the Portland International Jetport's remote parking lot on outer Congress Street. The Applicant proposes to construct a dry detention basin with eleven engineered stormwater bio-filter chambers.

Documents Reviewed

• Site Plan Amendment Application and Attachments dated April 17, 2009 prepared by Stantec.

Comments

The outlet control structure should have a three foot sump depth.

We have no additional comments at this time. Please contact our office if you have any questions.

DRG 203939.56









