



Luminaire Schedule											
Symbol	Label	Quantity	Manufacturer	Catalog Number	Description	Lamp	Number Lamps	Filename	Lumens Per Lamp	Light Loss Factor	Wattage
	S	10	LIGHTING SCIENCE GROUP	LSR4 150W NW R4 M 16 2B XXX HS GR	Prolific Under CLEAR PLASTIC LENS Roadway Optics House Side Shield; mounted at 22ft	WHITE LEDS	1	lsr4_150w_n w_r4_mvolt_2b_xxx_hs_g.r3d	10450.68	0.9	150
	C-OFF	24	Lithonia Lighting	DSXSC LED 30C 700 40K TSM MVOLT	DSX SURFACE CANOPY FIXTURE WITH 3 LIGHT ENGINES, 700mA DRIVER, 4000K LEDs, TSM OPTIC; mounted at 9.5ft	LED	1	DSXSC_LED_30C_700_40K_TSM_MVOLT.ies	6858.34	0.9	67
	WP	6	INDUSTRIAL LIGHTING	WPCM-60WLED-UNIV	LED WALL MOUNTED AREA LUMINAIRE; mounted at 10ft	LED	1	WPCM-60WLED-UNIV.ies	5068.758	0.9	66.4

Statistics							
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min	Avg/Max
Calc Zone #1		3.5 fc	16.5 fc	0.0 fc	N/A	N/A	0.2:1
Outside of Parking Lot		0.1 fc	3.1 fc	0.0 fc	N/A	N/A	0.0:1
Under Canopy		20 fc	27 fc	14 fc	1.9:1	1.4:1	0.7:1

Designer
Heidi G. Connors
Visible Light, Inc.
24 Stickney Terrace
Suite 100
Hampton, NH 03842
Date
7/25/2014
Scale
Not to Scale
Drawing No.
Summary