



NOTE:

- 1) SEE A40.1 FOR PARTITION TYPES
- 2) SEE A60.1 FOR DOOR / FRAME TYPES
- 3) INTERIOR DIMENSIONS SHOWN ARE TO FINISHED WALL SURFACE
- 4) ALL FURNITURE TO BE SUPPLIED AND INSTALLED BY OWNER
- 5) PROVIDE CONTROL JOINTS IN GPDW PARTITIONS AT A MAXIMUM SPACING OF 30'-0". LOCATE AT EDGE OF DOOR OPENING UP TO CEILING WHERE POSSIBLE. REVIEW WITH ARCHITECT.
- 6) SEE D4/A82.1 FOR TYPICAL DOOR FRAME LOCATIONS WITHIN GPDW PARTITION.
- 7) EXTERIOR DIMENSIONS SHOWN ARE TO FACE OF BRICK (AS INDICATED) OR FACE OF STUD.
- 8) SEE E4/A81.1 FOR FIRE EXTINGUISHER MOUNTING HEIGHTS

SYMBOLS LEGEND:

==== DENOTES STEEL BRACE FRAME

* DENOTES TO SHIM OUT STEEL STUDS TO CLEAR STEEL BRACE FRAME WITH 7/8" METAL HAT CHANNELS AT 24" OC HORIZ

DENOTES DOOR NUMBER SEE A60.1 FOR INFO

DENOTES ROOM NAME AND NUMBER SEE A61.1 FOR INFO

Project Title
**WOODARD & CURRAN
OFFICE ADDITION**

PORTLAND, MAINE

HA Project No. **05178**

Key Plan

Mark	Date	Description

Drawing Status	

Drawing Title
THIRD FLOOR PLAN

PA / PE: **JMB** Drawn By: **MCM**

Drawing Number

A10.3

THIRD FLOOR PLAN
1/8" = 1'-0" 0 4' 8' 12' REF: NA **A1**