

- 7. Stair, elevator shaft vents, and other outdoor air intake and exhaust openings in the building envelope are equipped with motorized dampers.
- 8. Cargo doors and loading dock doors are weather sealed.
- 9. Recessed lighting fixtures installed in the building envelope are Type IC rated as meeting ASTM E283, are sealed with gasket or caulk.
- 10. Building entrance doors have a vestibule equipped with self-closing devices.
Exceptions:
 - Building entrances with revolving doors.
 - Doors not intended to be used as a building entrance.
 - Doors that open directly from a space less than 3000 sq. ft. in area.
 - Doors used primarily to facilitate vehicular movement or materials handling and adjacent personnel doors.
 - Doors opening directly from a sleeping/dwelling unit.

Section 3: Compliance Statement

Compliance Statement: The proposed envelope design represented in this document is consistent with the building plans, specifications and other calculations submitted with this permit application. The proposed envelope system has been designed to meet the 2009 IECC requirements in COMcheck-Web and to comply with the mandatory requirements in the Requirements Checklist.

<p style="text-align: center; color: red; font-weight: bold;">Ryan Kanteres- SSA</p> <hr style="border: 0; border-top: 1px solid black; margin-bottom: 5px;"/> <p>Name - Title Architect - Project Manager</p>	<p>Signature</p> <div style="text-align: center;">  </div>	<p style="color: red; font-weight: bold;">3/24/16</p> <hr style="border: 0; border-top: 1px solid black; margin-bottom: 5px;"/> <p>Date</p>
--	--	---