Owner Name: Heritage Realt Contractor Name Atlantic Comf Phone: n/a Proposed Use: Same: Instal H	y Limite :: ort Syste	ed Partnership	Owner Address: 535 Boylston St Contractor Address PO Box 665 Bid Permit Type:	<u>r 8 - 2 6 1</u>		Phone:	004001
Heritage Realt Contractor Name Atlantic Comf Phone: n/a Proposed Use:	: ort Syst	· · · · · · · · · · · · · · · · · · ·	535 Boylston St Contractor Address PO Box 665 Bid Permit Type:	<u>r 8 - 2 6 1</u>		17/p	
Contractor Name Atlantic Comf Phone: n/a Proposed Use:	: ort Syst	· · · · · · · · · · · · · · · · · · ·	Contractor Address PO Box 665 Bid Permit Type:	<u>r 8 - 2 6 1</u>			
Atlantic Comf Phone: n/a Proposed Use:	ort Syst	ems	PO Box 665 Bid Permit Type:			Phone	
Phone: n/a Proposed Use:		ems	Permit Type:	deford			
n/a Proposed Use:	<del></del>		1			20728463	360
Proposed Use:			T T T T A A		1		
I -			HVAC	HVAC			
Same: Instal H			Permit Fee:	Cost of Worl	st of Work: CEO District:		7
	leating System			- 1	00.00	3	
			FIRE DEPT:	Approved	INSPEC		
				Denied	Use Grou	ıp:	Type:
					<b> </b>	0/	0
			L JX	en (		LILL)	-
					Signature		<i>Y</i>
			PEDESTRIAN ACT	IVITIES DIST	RHCT (P	A.D.	(
			Action: Appro	ved App	roved w/C	conditions [	Denied
			Signature:		j	Date:	
Applied For:			Zoning	Annrova			
28/2001			2011116	Sippiora			
t preclude the	Special Zone or Reviews		ws Zon	ing Appeal		Historic Preservation	
<ol> <li>This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.</li> </ol>		☐ Shoreland		☐ Variance		☐ Not in District or Landman	
plumbing,	nbing, Wetland		Miscell	Miscellaneous		Does Not Require Review	
septic or electrical work.  3. Building permits are void if work is not started within six (6) months of the date of issuance.  False information may invalidate a building permit and stop all work		lood Zone Conditional Use			Requires Review		
		Subdivision		Interpretation		Approved	
	☐ Sit	e Plan	☐ Approv	ed		Approved w/	Conditions
	Мај [	Minor MM	☐ ☐ Denied			Denied	
	Date:		Date:		Dat	e:	
	plumbing, rk is not started e of issuance.	z8/2001  It preclude the icable State and She plumbing,  It is not started by the icable State and She icable She icable State and She icable She i	28/2001  It preclude the icable State and Shoreland  It plumbing, Wetland  It plumbing, Wetland  It plumbing, Shoreland  It plumbing, Shoreland	Signature:   PEDESTRIAN ACT	Signature:   PEDESTRIAN ACTIVITIES DIST	Signature:   Signature   Signature   Signature   Signature   PEDESTRIAN ACTIVITIES DISTRICT (PACTIVITIES DISTRICT) (PACTIVITIES DISTRIC	Signature:   Signature:   Signature:   PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.)     Action:   Approved   Approved w/Conditions   Date:     Applied For:   Zoning Approval


DATE

PHONE

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE



## APPLICATION FOR PERMIT HEATING OR POWER EQUIPMENT



01.1056

To the INSPECTOR	OF BUI	LDINGS.	PORTLAND.	ME.
------------------	--------	---------	-----------	-----

The undersigned hereby applies for a permit to install the following heating,	cooking or power equipment in
accordance with the Laws of Maine, the Building Code of the City of Portland, and t	he following specifications:

Location 1636 Brighton AVE, PINETAEE S.C. Use of Building Rotain Clothing Date 8-27-01				
Name and address of owner of appliance Heritage Proper				
535 BOYISTON ST., BOSTON	MA LUT			
Installer's name and address ATIANTIC COMEAT S				
PO. Box 665, 392 HIII ST. Biddeford	ME 04005 Telephone 307-284-6360			
Location of appliance:	Type of Chimney:			
☐ Basement ☐ Floor	☐ Masonry Lined			
☐ Attic ☐ Roof	Factory built			
Type of Fuel:	☐ Metal			
Gas Oil Solid	Factory Built U.L. Listing #			
NATURAL NO CT 2(0)	· · · · · · · · · · · · · · · · · · ·			
Appliance Name: WAK Roof TOP (8)	□ Direct Vent			
U.L. Approved Yes \( \text{No} \( \( \) \(	Type UL#			
Will appliance be installed in accordance with the manufacture's	Type of Fuel Tank			
installation instructions? Yes	Oil			
	Gas			
IF NO Explain:	- <b> </b>			
	Size of Tank			
The Type of License of Installer:	Number of Tanks			
Master Plumber #				
Solid Fuel #	Distance from Tank to Center of Flame feet.			
Gas # PNT 687				
Other				
J Ouici				
Approved	Approved with Conditions			
Fire:	☐ See attached letter or requirement			
Ele.:	A			

White - Inspection

Bldg.:

Signature of Installer

Yellow - File

Pink - Applicant's

Gold - Assessor's Copy

430, w

## BUILDING PERMIT REPORT

	DATE: 28 Aug. 200/ ADDRESS: 1030 Brigh Ton Ave. CBL: 363-44-994
	REASON FOR PERMIT: Heating System
	BUILDING OWNER: HeriTage Property Forest ment Trust  PERMIT APPLICANT: ICONTRACTOR HUBATIC CONSTORT Sys
	PERMIT APPLICANT: ICONTRACTOR HUan TIC Confort Sec
	USE GROUP: M CONSTRUCTION TYPE: 2C CONSTRUCTION COST: PERMIT FEES: 30.00
,	The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
	This permit is being issued with the understanding that the following conditions shall be note \$1.435

. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of 12" in diameter, 7' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17

5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H.-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) R-3 (ONE & TWO FAMILY DWELLINGS) GUARD HEIGHT IS 36" MINIMUM.
- 12. Headroom in habitable space is a minimum of 7'6'. (Section 1204.0)
- 13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 1/2" maximum rise. All other Use Group minimum 11" tread.
  7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria witter section 1011.3 but not less then 36.
- 16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 18. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 19. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

- 20. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms.

In each story within a dwelling unit, including basements

21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)

22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.

- 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.
- 24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)

25. Section 25 - 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

- 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection
- 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces &
- All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.

29. All requirements must be met before a final Certificate of Occupancy is issued.

- 30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
- 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)

32. Please read and implement the attached Land Use Zoning report requirements.

33. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.

34. Bridging shall comply with Section 2305.16.

35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)

36. All flashing shall comply with Section 1406.3.10.

J	And treatment are an area and a second area area.		
37	All signage shall be done in accordance with Section 3102.0 sign	is of the City's Building Code, (Th	ie BOCA National Building Code 1999).
V ==	The Table The	made a sthust	milanxlucie of The
X 38	Before phasing unit on The	100F a 3/14014	raj unulysis or
مس)	roof Shall be done to show The	existing roof	has BelCabacily
			. 7
	To hardle The New roof Load-		
_			

del Hotises Building Inspector

McDougall, PFD

Marge Schmuckal, Zoning Administrator
Michael Nugent Inspection Service Manager

PSH IO'L'OO

\*\*This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

\*\*\*\*ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

\*\*\*\*\*CERTIFICATE OF OCCUPANCY FEE \$50.00