



FRAMING PLAN SYMBOLS KEY

| | |
|---|--|
| □ | WOOD POST |
| ○ | STEEL COLUMN |
| ○ | NUMBER OF WOOD STUDS IN POST BELOW |
| A | COLUMNS ABOVE THIS LEVEL |
| C | COLUMNS CONTINUOUS THROUGH THIS LEVEL |
| — | JOIST BEARING |
| — | CONTINUOUS JOIST WITH INTERMEDIATE BEARING |
| — | FLUSH FRAMED JOIST BEARING WITH HANGER |
| — | WOOD STUD BEARING WALL BELOW |
| X | NUMBER OF TRIM STUDS UNDER HEADER |
| X | NUMBER OF KING STUDS ADJACENT TO HEADER |

- BOND OUT AT CMU OPENING - SEE GENERAL NOTES
- SOLID GROUT CMU AT STAIR CONNECTIONS - TYP.
- CMU STAIR SHAFT - SEE SECTION FOR DETAILS
- 3/4" FLOOR SHEATHING TO CONTINUE @ "BUMP OUT" - TYP.

SECOND FLOOR FRAMING PLAN 'C'

Scale: 1/4" = 1'-0"

Date: 02/09/2016

1 S1.2c

NOTES:

- SEE SHEET S1.0 FOR GENERAL STRUCTURAL NOTES
- ALL WOOD COLUMNS IN 2x6 WALLS SHALL BE (3) 2x6 AND IN 2x4 WALLS SHALL BE (3) 2x4 UNLESS NOTED OTHERWISE ON PLANS
- ALL BEAMS ARE FLUSH UNO
- ALL HEADERS IN 2x BEARING WALLS ARE (2) 9 1/4" LVL UNO
- ALL FLOOR JOIST TO BE 16" P.E. FLOOR TRUSSES @ 16" W/ LSL RIM - TYP UNO
- FLOOR SHEATHING TO BE 3/4" T+G, SEE GENERAL NOTES FOR ADDITIONAL INFORMATION - TYP
- ALL TRUSS TO TRUSS CONNECTIONS BY MANUFACTURER - TYP UNO
- TRUSS DESIGNER TO COORDINATE TRUSS LAYOUT WITH FLOOR OPENING, PLUMBING, AND UTILITY REQUIREMENTS - TYP

Professional Engineer Seal: 2/10/16

Prepared For: **PORTLAND HOTEL, INC**

Consultant: **ARCHETYPE architects**
48 Union Wharf Portland, Maine 04101
(207) 772-0022 ARCHETYPE@ARCHETYPEPA.COM

Architect: **ARCHETYPE architects**

Project: **HAMPTON INN**
Address: _____
City, State: _____

Revisions: **PERMIT SET**

Scale: 1/4" = 1'-0"

SECOND FLOOR FRAMING PLAN 'C'

S1.2c