



W  
N  
E  
S  
SECOND FLOOR PLAN  
SCALE: 1/8" = 1'-0"

| KEYED NOTES |   |
|-------------|---|
| ①           | 4'-0" x 8'-0" x 3/4" PLYWOOD FROM 6" AFF TO 3/4" AFF BY 6% FOR MOUNTING OF TELEPHONE EQUIPMENT. |

  

| GENERAL NOTES |   |
|---------------|---|
| 1.            | ALL PARTITIONS THAT HAVE NO PARTITION TYPE REFERRED ON FLOOR PLAN SHALL BE PARTITION TYPE [ ]   |
| 2.            | PROVIDE DOUBLE STUDS @ 16" O.C. AND 8/16 GA. STEEL SHEATHING GRAB BARS, COAT PANTS, TIE TO STEEL SUPPORTS, ETC., ARE SECURED TO WALL. |
| 3.            | RESISTANCE TO PENETRATION SHALL BE MAINTAINED THROUGHOUT THE ENTIRE PARTITION SYSTEM TO MAINTAIN THE FIRE RATING OF PARTITION.        |
| 4.            | ALL DOWNSPOTS (WHI BOSTS) SHALL BE CONNECTED TO STORM LINE DRAIN - REFER TO CIVIL DRAWINGS FOR BOOTS AND CONNECTIONS.                 |
| 5.            | CONCRETE SHALL BE FINISHED TO MATCH EXISTING DETAILS ON CONCRETE CURB.  |
| 6.            | EXISTING GATE SIZE & OPENING DIMENSIONS WHERE SAFE IS BUILT IN ARE TO BE VERIFIED WITH THE OWNER.                                     |

  

| PARTITION & DOOR SYMBOLS |   |
|--------------------------|---|
| [Symbol]                 | NEW PARTITION   |
| [Symbol]                 | INDICATES PARTITION FROM FLOOR TO CEILING ABOVE   |
| [Symbol]                 | INDICATES PARTITION FROM FLOOR TO CEILING WITH SOUND RESISTING INSULATION                       |
| [Symbol]                 | INDICATES 1/2" PRECAST SHAKE PARTITION FROM FLOOR TO DECK ABOVE                                 |
| [Symbol]                 | INDICATES 1/2" PRECAST SHAKE PARTITION FROM FLOOR TO DECK ABOVE                                 |
| [Symbol]                 | INDICATES 1/2" PRECAST SHAKE PARTITION FROM FLOOR TO DECK ABOVE WITH SOUND RESISTING INSULATION |
| [Symbol]                 | INDICATES CHASE PARTITION FROM FLOOR TO DECK ABOVE WITH SOUND RESISTING INSULATION              |