

PRIMARY AND ROOF BRACING PLAN

WALKER 5989 01.09.02

1 1'-0" Dimension Key

1. USE 1/2 DIA. A325 BOLTS FOR PURLIN TO FRAME, GIRT TO FRAME, AND GIRT TO CLIP CONNECTIONS UNLESS NOTED OTHERWISE. SEE JOB DETAILS FOR BOLT LENGTHS.

2. SLOT REINFORCEMENT PLATES NEED NOT BE LOCATED ON THE SAME SIDE OF THE WEB AS THE HILLSIDE WASHER.

OR COMPONENT FURNISHED BY VP EXCEPT TO ANY DESIGN OR PER-FORMANCE REQUIREMENTS SPECIFIED BY VP.

THE VP ENGINEER'S SEAL APPLIES
ONLY TO THE WORK PRODUCT OF
VP AND DESIGN AND PERFORMANCE
REQUIREMENTS SPECIFIED BY VP.
THE VP ENGINEER'S SEAL DOES
NOT APPLY TO THE PERFORMANCE
OR DESIGN OF ANY OTHER PRODUCT
OR COMPONENT FUNDICINE BY VP.

OR COMPONENT FUNDICINE BY VP. Coll. Load: Gravity 1.00, Uplift 0.00 psf

Snow Exposure Category: 3
Seismic Hazard / Use Group: Group 1
Building Use:Standard Occupancy Structures

THIS DRAWING, INCLUDINGTHE INFORMATIONHEREON, REMAINSTHE PROPERTY OF VP BUILDINGS. IT IS PROVIDED SOLELY FOR ERECTING THE BUILDING DESCRIBED IN THE APPLICABLE PURCHASE ORDER AND SHALL NOT BE MODIFIED, REPRODUCEDOR USED FOR ANY OTHER PURPOSE WITHOUT PRIOR WRITTEN APPROVAL OF VP BUILDINGS.

THE GENERAL CONTRACTOR AND/OR ERECTORIS SOLELY RESPONSIBLE FOR ACCURATE, GOOD QUALITY WORKMANSH IN ERECTINGTHIS BUILDING IN CONFORMANCE WITH THIS DRAWING, DETAILS REFERENCED IN THIS DRAWING, ALL APPLICABLE VP ERECTION GUIDES, AND INDUSTRY STANDARDS PERTAINING TO PROPER ERECTION, INCLUDING THE CORRECTUSE OF TEMPORARY BRACING.

DXC 1/2/02 VP Buildings, Inc. PRIMARY AND ROOF BRACING PLAN

3200 Players Club Circle Memphis TN 38125 BUILDER PATCO Construction Inc CUSTOMEP
BIG MOOSE HARLEY-DAVIDSON Portland, Maine Big Moose Harley-Davidson Bia Moose Harlev.vpc

VP BUILDINGS VARCO-PRUDEN

WI0115377-01 12/27/2001 DRAWN/CHECK AMZ KAF VPC VERSION: 3 PS-1 of