340439

273- F-006 Map#____Lo Zone BUILDING PERMIT APPLICATION Fee Please fill out any part which applies to job. Proper plans must accompany form. Permit #

Lot#

Approved with Conditions HISTORIC PRESERVATION Not in District nor Landmark Does not require review Subdivision Requires Review. Private Side Action: Approved. Public Yes Smoke Detector Required ž Square Footage Signature Side 3. Must conform to National Electrical Code and State Law. Size Site Plan Floodplain Yes_ Name Span Lot Size For Official Use Only Yes Number of Fire Places Subdivision: Ownership: Date: Chase Spacing Back Variance_ ŝ ģ CONTINUED TO REVERSE SIDE 1. Approval of soil test if required Planning Board Approval: Yes_ Zoning Board Approval: Yes_ Provided Setbacks: Front, 2. No. of Tubs or Showers Street Frontage Provided: 1. Ceiling Joists Size: 2. Ceiling Strapping Size. 5. No. of Other Fixtures Shoreland Zoning Yes. 1. Truss or Rafter Size_ 3. Roof Covering Type Service Entrance Size: (Explain) 4. No. of Lavatories 4. Insulation Type 2. Sheathing Type Conditional Use: 5. Ceiling Height: 3. No. of Flushes Special Exception 3. Type Ceilings: Heating: Type of Heat: 2. Pool Size: Permit Received By Signature Solution Signature Swimming Pools: Review Required: Inside Fire Limits. Type: Other_ Estimated Cost Type: Time Limit. Bldg Code. Chimneys: Plumbing: Electrical: Ceiling: Zoning: Roof: 0 [X 00 Sills must be anchored. Spacing 16" O.C. Weather Exposure Conversion Side(s) 50 C 864 Phone # Phone # Span(s) storage Size: Proposed Use:_ Size: Size: Lot Size: Total Sq. Ft. # of New Res. Units Past Use: Spacing. Spacing Span(s) 0 0 0 Sub.: Condominium Rear Size Size ż CONSTRUCT 0 # Bedrooms 3 LOCATION OF CONSTRUCTION \$1000 3. Lally Column Spacing: 5. Bridging Type:
6. Floor Sheathing Type:
7. Other Material: Yes 4. Fire Wall if required 3. Wall Covering Type. 6. Corner Posts Size 10. Masonry Materials 2. Set Backs - Front 5. Other Materials 4. Foundation Size: 1. Studding Size Seasonal 7. Insulation Type 8. Sheathing Type 11. Metal Materials 4. Header Sizes 3. Footings Size: 1. Studding Size 2. Header Sizes 2. No. windows Building Dimensions L 9. Siding Type Est. Construction Cost: 1. Type of Soil: # of Existing Res. Units. Girder Size: 4. Joists Size: 3. No. Doors 1. Sills Size: Bracing: Explain Conversion Is Proposed Use: 5. Other Exterior Walls: Interior Walls: Foundation: Contractor. # Stories: Address: Address: Owner: Floor:

White - Tax Assessor

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE	I hereby certify that I am the owner of record of the named property, or that the propowner to make this application as has authorized agent and I agree to conform to application is issued, I certify that the code official or the code official's authorized reasonable hour to enforce the provisions of the code(s) applicable to such permit. SIGNATURE OF APPLICANT ADDRESS			COMMENTS	Late Fee \$	1	Site Plan Review Fee \$	FEES (Breakdown From Front)					PLOT PLAN
	I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as has authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this reasonable hour to enforce the provisions of the code official's authorized representative shall have the authority to enter areas covered by such permit at any signature of applicant. ADDRESS ADDRESS PHONE NO.	CERTIFICATION						From Front)	1977年の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の日本の				
No.	ner of record and that I have been authorized by the on. In addition, if a permit for work described in this hority to enter areas covered by such permit at any 2077754470						/ Date	Inspection Record					

PHONE NO.

BUILDING PERMIT REPORT

Nilress 2 16.6 5,- Date 17/19/9
Reason for Permit Ta Construct a 16 x16 Shed
Bldg.Owner:
Contractor: Cunen
Permit Applicant:
Approval: X/X/6/

CONDITION OF APPROVAL:

- 1. Before concrete for foundation is placed, approvals from Public Works and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection).
 - 2. Precaution must be taken to protect concrete from freezing.
 - 3. It is strongly recommended that a register land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 4. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hr., including fire doors with selfclosers.
 - 5. Each apartment shall have access to (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 6. The boiler shall be protected by enclosing with one (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply system having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessible locations between the sprinkler and the connection to the domestic water supply. Minimum pipe size shall be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 square feet per sprinkler.
- 7. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside opening without the use of special knowledge or separate tools. Where windows are provided as a means of egress or rescue, they shall have a sill height not more than 44 inches (1118 mm) above the floor. All egress or rescue windows from sleeping room must have minimum net clear opening height dimension shall be 24 inches (610 mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sg.ft.
- 8. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the building code 919.3.2 (BOCA National Building Code 1993), and NFPA 101 Chapter 18 & 19.

- 9. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by Fire l'artitions and floor/ceiling assembly; lies which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1993).
- 10. Guz drails & Handrails A guardrai system is a system of building components located hear the oper sides of elevated wilking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Group 42", except Use Group R which is 36". In occupancies in Use Group A, B, EH-4, II, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 11. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023. 1024.0 of the City's building code (The POCA National Building Code/1993).
- 12. Stair construction in Use Group R-3, R-4 is a minimum of 9" tread and 8-1/4" maximum rise.
- 13. Headroom in habitable space is a minimum of 7'6".
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 15. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final certificate or occupancy is issued or demolition permit is granted.
- 16. Section 25-135 of the Municipal Code for the City of Portland states: "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 17. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

Sincerely,

P. Samuel Moffses Chief of Inspections

/dmm 01/14/94 (redo w/additions)

FAM OLAS 2 POE STREET FORTHAND ME 01415LL

(2) Approx & 1000.00 or (3) pron to complete by Aug/Sep 94 O Shed on coment blocks redicted. White D SMEd D ロ

(2)			Constr		bus a del
(3) (4)	FL00.	n 2 }	6 (a) 2×6	NStruci	70N
			D	11	owenk blocks
				1 10	2x6 pressure treated
			D		
			10	PAMI	- Durs
				207	775-1470