0.4	6D (L. 2.35.)	D 11.11 YY		Do	ermit No: Issue I		CBL:	
	y of Portland, Maine Congress Street, 04101	_	• •	711	01-0574 JUN -		278A E0	13001
Loca	tion of Construction:	Owner Name:		Owne	er Address:		Phone:	
208 Pinecrest Rd Li Da Teng & I			Lin Yee Ng Jts		Pinecrest Rd Portland	Me 04 I	207-879-9	0031
Busi	ness Name:	Contractor Name				UNILA	Phone	
n/a		M.J. Metcalf		134 Bonnybank Terrace So. Portland 2077992			d 20779924	15
Less	ec/Buyer's Name	Phone:		Permit Type:			Zene: 2	
n/a		n/a		Gar	Garages - Attached			K->
Past	Use:	Proposed Use:		Регп	Permit Fee: Cost of Work: CEO District:			
Sin	gle family	Same: Build 2	ame: Build 22' X 24' Attached		\$90.00 \$1	00.000,1	3	
	•	Garage. Call N	arage. Call M.J. Metcalf at 799-		E DEPT: Approve	INSPE	PECTION: U	
1		2415 when rea	dy.		_ Approved		se Group R.3 Type 53	
				Denied		• 1		
						801	03/108/19	995
Prop	osed Project Description:					WITH	+BEYS IN	111
Bui	ld 22' X 24' Attached Gara	ge.	,	Signa	ımıe.	Signa	1.1A	
		Called Tal	Ked To Gotal	PEDE	ESTRIAN ACTIVITIES I	ISTRICE	e.X.D.	1
		called Tal,	17	Actio	on Approved	Approved w	/Conditions	Denied
1		refors. 1	0			D		
				Signa	Signature.		Date:	
	oit Taken By:	Date Applied For:			Zoning Appro	oval		
cił	1	05/21/2001	Carriel 7 and the David		7		Wat for Day	
 This permit application does not preclude the 		Special Zone or Revi	1/1			Historic Preservation		
Applicant(s) from meeting applicable State and Federal Rules.		Shoreland N#		Variance		Not in District or Landmark		
2.	Building permits do not include plumbing, septic or electrical work.		Wetland		Miscellaneous		Docs Not Regime Review	
 Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work 			Flood Zone		Conditional Use		Requires Review	
					Interpretation		Approved	
			Site Plan		Approved		Approved w/	Conditions
			Maj Minor MM	M 🗌	Denied		Denied	2
			Date: Sh	6)	Date:	D	Date:	<i>)</i>
			1 / 1	1				
						-	DANE LOCKE	-D
							RMIT ISSUE	
						WITH	REQUIREM	FM12
			CERTIFICAT	ION				

PERMIT ISSUED

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provision of the code(s) applicable to such permit.

SIGNATURE OF APPLICANT	ADDRESS	DATE	PHONE
RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE		DATE	PHONE.

6-7-01 fre con on site w/Builderwent over all reg. * permit. TM.

1/3/01 Chedled Setteds
(1'on rem

10'10' on side

used plot plan

Marge rotes 10' 10'
pick sheet musing

OKE to pom_



CITY OF PORTLAND, MAINE

Department of Building Inspection

	5	5 21	20 01
Received from N	1 J. Mot	calf	a fee
of Ninety	dollars	/100 Dollars	\$ 90,00
install erect alter	22' × 24'	Attacher	
move demolish	h		
	Pinecrest k	Est. Cost \$	11,000,00
CBL# 27	8 A - 6 013		
CK 4 88	2		
		Inspector of buildi	ngs
		Per Ch	1

THIS IS NOT A PERMIT

No work is to be started until PERMIT CARD is actually posted upon the premises. Acceptance of fee is no guarantee that permit will be granted. PRESERVE THIS RECEIPT. In case permit cannot be granted the amount of the fee will be refunded upon return of the receipt less \$5.00 or 10% whichever is greater.

WHITE - Applicant's Copy YELLOW - Office Copy PINK - Auditors Copy

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Location/Address of Construction: 200	8 P;	necrest 1	PJ.		<u> </u>	
Total Square Footage of Proposed Structure	528	Square Footage of L	ot g	7470		
Tax Assessor's Chart, Block & Lot Number	Owner: Da	Teng Li	_	Telephone	#: 9031	
Chart# 278 Block# A- E Lot# 013				874-	9087	
Lessee/Buyer's Name (If Applicable) Owner's/Purchaser/Lessee Address: Cost Of Work: Fee: \$ 11,000. \$						
Current use: 5 F						
If the location is currently vacant, what was prior use: Approximately how long has it been vacant: Proposed use:						
Project description: 22x24' a	ttache	d garage				
Contractor's Name, Address & Telephone: M.J. Metalf, 134 B Applicants Name, Address & Telephone:	Ponnyba 99-2413	nt Terrace	, So. 7	Portlan	J ME.	
5ame						
Who should we contact when the permit is read Telephone: 799 - 2415	dy: <u>///.x</u>	T. Mettalf				
If you would like the permit mailed, what mail		hould we use:			clas	
134 Bonnybank Ter					2/2/	
So. Partland ME. C	11100			Re	c'd By: n	

BIIII DING PERMIT PEPORT

/	Billiont - Knjj - El O41
	REASON FOR PERMIT: To Construct 22'x 24 attached Private 99ruge
	REASON FOR PERMIT: To Construct 22 x 24 attached Private 99rage
	BUILDING OWNER: Li Da Teng & Lin Yee Ng
	PERMIT APPLICANT:
	USE GROUP: R-3 CONSTRUCTION TYPE: 53 CONSTRUCTION COST: 11,000.0 FERMIT FEES: 90,00
	The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
	This permit is being issued with the understanding that the following conditions shall be met: 4/42 44 6 8

This permit i	s being	issued w	ith the und	erstanding	that the following	owing condit	ions shall be m	et: ×1 ×2	44	16×8
		1		(7	77					

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 4. Foundations anchors shall be a minimum of ½" in diameter, 7' into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17

5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

 All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/1" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)

12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)

13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 ½" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

- 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria under section 1011.3 but not less then 36".
- 16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

18. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)

19. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic

Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

In the immediate vicinity of bedrooms

In all bedrooms

• In an bedrooms

In each story within a dwelling unit, including hasements

- 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard.

23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard.

24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)

25. Section 25 – 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

- 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics).
- 28. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.

29. All requirements must be met before a final Certificate of Occupancy is issued.

- 4X-30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996).
 - 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)

32. Please read and implement the attached Land Use Zoning report requirements.

★33. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.

34. Bridging shall comply with Section 2305.16.

*35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0)

36. All flashing shall comply with Section 1406.3.10.

37. All signag	shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).
X 38 Your	anulication Shows only a Concrete Stub For The Foundation.
200	HEARC A OF The 11 of A
3EC110	1 1816,4 OF 170 blac Cade requires a minimum of a 4' hos
wall,	ha design by a professional engineer. No work is To
be do	ne until either you sulmit new plans or design by enginer
Sybmit	ed and approved by This office
X39 VO	n elon shows ax 6" rafters at 16"05, MAX Span would be
10/8"	2x8/0 1600C msx 5pan 136"
240 17hg	proposed 6"X10" bean does not show any columns supports
A ALGESC	5ubmit 17/15 105 x
Sankel Hoff	es, Building Inspector Se e Wew Plaze
CO:XV LI. N	Dougall, PFD
	Schmuckal, Zoning Administrator
	Nugent Inspection Service Manager

PSH 10/1/00

**This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

****ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.

*****CERTIFICATE OF OCCUPANCY FEE \$50.00