# WATTS®

## WD Series

Tag: _____

## PDI Certified Grease Interceptor

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 08/30/16

**SPECIFICATION**: Watts Drainage WD Series PDI Certified recessed or floor mounted epoxy coated steel grease interceptor with gasketed epoxy coated steel skid-proof cover secured with hex head center bolt(s), removable baffle assembly, deep seal trap with cleanout, external cast iron flow control fitting, and no hub (standard) connections.

| Flow Rate (Select One) | | |
|---|---|---|
| Suffix | Description | |
| 4 | 4 GPM | ☐ |
| 7 | 7 GPM | ☐ 4 |
| 10 | 10 GPM | ☐ |
| 15 | 15 GPM | ☐ |
| 20 | 20 GPM | ☐ 4 |
| 25 | 25 GPM | ☐ |
| 35 | 35 GPM | ☐ 4 |
| 50 | 50 GPM | ☐ |

| Options (Select One or More) | | |
|---|---|---|
| Suffix | Description | |
| -B | Sediment Bucket | ☐ |
| -E | Extension | ☐ |
| -FC | Flange & Clamp Device | ☐ |
| -HD | Heavy Duty (10,000 lb.) Traffic Cover | ☐ |
| -O | Inlet & Outlet other than Standard Size | ☐ |
| -SS | Stainless Steel | ☐ |
| -THD | Threaded Connections | ☐ |
| -US | Buy American Compliant | ☐ |

| Interceptor Catalog Number | Flow Rate GPM | Grease Capacity Lbs | A Inlet & Outlet | B Base to Center | C Top to Center | D Length | E Width | F Height |
|---|---|---|---|---|---|---|---|---|
| WD-4 | 4 | 8 | 2"(51) | 7-3/4"(197) | 3-1/4"(83) | 16"(406) | 10"(254) | 11"(279) |
| WD-7 | 7 | 14 | 2"(51) | 8-1/2"(216) | 3-1/2"(89) | 18"(457) | 13"(330) | 12"(305) |
| WD-10 | 10 | 20 | 2"(51) | 8-1/2"(216) | 3-1/2"(89) | 21-3/4"(552) | 14"(356) | 12"(305) |
| WD-15 | 15 | 30 | 2"(51) | 10-1/2"(267) | 3-1/2"(89) | 22"(559) | 15"(381) | 14"(356) |
| WD-20 | 20 | 40 | 3"(76) | 11-1/2"(292) | 3-1/2"(89) | 24"(610) | 15-3/4"(400) | 15"(381) |
| WD-25 | 25 | 50 | 3"(76) | 12"(305) | 4-1/2"(114) | 26"(660) | 16-1/2"(419) | 16-1/2"(419) |
| WD-35 | 35 | 70 | 3"(76) | 14"(356) | 5"(127) | 30"(762) | 18"(457) | 19"(483) |
| WD-50 | 50 | 100 | 4"(102) | 16"(406) | 5-1/2"(140) | 32"(813) | 22"(559) | 21-1/2"(546) |

Job Name _____ Contractor _____

Job Location _____ Contractor's P.O. No. _____

Engineer _____ Representative _____

WATTS Drainage reserves the right to modify or change product design or construction without prior notice and without incurring any obligation to make similar changes and modifications to products previously or subsequently sold. See your WATTS Drainage representative for any clarification. Dimensions are subject to manufacturing tolerances.

WATTS®
**Specification Drainage Products**
**USA:** 100 Watts Road, Spindale, NC, 28160-2298; TEL: 828-288-2179 TOLL-FREE: 1-800-338-2581 www.watts.com