



FEATURES:

- TWO ACCESS DOORS FOR EASY ACCESS
- 18" WIDE INCLINED NON-OVERLOADING WHEELS
- ALUMINUM CASTING
- ANCA AIR & SOUND CERTIFIED
- VISIBILE PITCH MOTOR PALLETS
- THERMAL OVERLOAD PROTECTION SINGLE PHASE
- MOTOR COVER
- DISCONNECT SWITCH

OPTIONS:

- SIF11 - STRAIGHT DISCHARGE, SQUARE DUCT CONNECTION.
- SIF11 - INLET SQUARE DUCT CONNECTION
- SIF11 - OVERHEAD MOUNT - PRE-INSTALLED MOUNTS (1-365).
- 1-15-RDD DAMPER
- EXTRA SET OF BELTS
- HANGING SPRING VIBRATION ISOLATORS (SET OF 4), FOR INDOOR OR OUTDOOR USE WITH SQUARE INLINE FANS. (45A165)



UNIVERSAL MOUNTING BRACKET
 1/2" DIA. WRENCH ROD ONLY
 USED WITH CEILING VIBRATION ISOLATORS
 CAN BE REBORNED IN THE FIELD IF NEEDED

CUSTOMER APPROVAL TO MANUFACTURE:

Approved as Noted
 Approved with ND Exception Taken
 Revised and Resubmit

SIGNATURE _____ Date ____





CAPTIVEAIR

JOB Tinpan Bakery	
LOCATION Biddeford, ME,	JOB # 2745465
DATE 8/18/2016	DRAWN BY BFC-21
DWG # 3	REY.
SCALE 1/4" = 1'-0"	