City of Portland, Maine - Building	g or Us <mark>e Permit Appli</mark>	cation 389 Congres	s Street, 04101, Tel: (20	7) 874-8703, FAX: 874-8716
Location of Construction:	Owner:	,	Phone: (W)	Permit No: QQ Q 3 4
60 Essex St. Poreland, ME	Ron Kimball		761-7748 /776-852	2
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	PERMIT ISSUED
Contractor Name:	Address:	Pho	ne:	Permit Issued:
Haine-Wide Construction	P. O. Box 2106, Augu	sta, ME 04338 80	00 452 1040	APR 3 1998
Past Use:	Proposed Use:	COST OF WO		APR 1 5 1990
		\$ 14,689	\$ 98500	
1-FAB	I-FAM	FIRE DEPT.	Approved INSPECTION:	ICITY OF PORTLAND
			Denied Use Group 13 Typ	e: 5/2
	ż		BOCA 86_, 1	Zone: CBL: 284-F-001 5 Z
		Signature:	Signature:	Zoning Approval:
Proposed Project Description:			ACTIVITIES DISTRICT (P.A.)	D.) Zoning Approva.
		Action:	Approved	Special Zone or Reviews:
Build & erect 24x30 garage			Approved with Conditions:	□ □ Shoreland
attached with breezeway			Denied	□ □ Wetland
				☐ Flood Zone
D 1 T 1 D	15	Signature:	Date:	☐ Subdivision ☐ Site Plan maj ☐minor ☐mm □
Permit Taken By:	Date Applied For:	4/9/98		Zotte Flatt maj Zimilet Zimile
Mary				Zoning Appeal
 This permit application does not preclude the A 	□ Variance			
2. Building permits do not include plumbing, se	☐ Miscellaneous ☐ Conditional Use			
3. Building permits are void if work is not started		te of issuance False informa		□ Interpretation
tion may invalidate a building permit and sto		te of issuance. I alse informa		□Approved
tion may invalidate a building permit and stop	p all work		-1.1	□ Denied
		LIT	8/4/98	
Tom - F91 A Set back				Historic Preservation
1-10		lacae 15 th	Ser DACK	☐ Not in District or Landmark ☐ Does Not Require Review
APPEAL SUSTAINED 10/8/9	8	1000	3110	☐ Requires Review
		, 0	A = ED	
		2001/6	A LAC ENTE	Action:
		moran	politing	
	CERTIFIC	100	- 1 2	☐ Appoved
I hereby certify that I am the owner of record of the	7 7	1 1	nd that I have	
authorized by the owner to make this application a		1 hours	ction. In add	atton,
if a permit for work described in the application is areas covered by such permit at any reasonable ho		two lives	thority to en	Date:
areas covered by such permit at any reasonable no	di to emorce die provisions	(10, 01)	AcX	
		1 -12+	by Chil	
PRV L	1 20 34	17)	16	The state of the s
SIGNATURE OF APPLICANT Ron Kimball	ADDRESS:	1 1 1 8	75 10. has	
		LOROLD)	1 maye	
RESPONSIBLE PERSON IN CHARGE OF WORK	CTITLE	inster.	PHONE:	CEO DISTRICT
TEGO ONGIDES LENGON IN CHARGE OF WORL	.,		HOLL	CEO DISTRICT
White Do	mit Dock Groon Accessor's	Canany_D PW Pink_P	ublic File Ivory Card-Inspect	0.5

COMMENTS

4-14-98 Phone conversation w/ Mr. Kimball, has breczeway already existing. Will be pouring
Slap for garage soon. Will contact me when ready to pour
6-12-98 Had Footer in Place and weve Pouring wall when I arrived (13:40)
Set Backs appier to Beok, Pouring walls with a standard 2500 mix
with heavy water being mixed to make the wall Run all From the
Front their is no Pour Ranp, So the strong is Runing From the 12' to mark
on the Side walls all the way to the Rear T.ER.
6-17.98 Sam H + T. Reinsborougs meet with home owner, Blue Rock Rep., Mr Coriner
who owns the Foundation co. and Mainewide Rep. at 12 N., mo coriner said
he will till the voids in the wall with water Plug, and the Blue Rock Rep.
will be sending us a Letter on the Streamth of the wall and will stand
Behind the test., The Posting is Lifted and work may proceed.
Inspection Record Type
Type A / / Date

Type
Foundation: T-ER. Per. Hgrement with Sount, 6-17-98

Framing:
Plumbing:
Final:
Other:

BUILDING PERMIT REPORT

DAT	E. 13 APRIL 98 ADDRESS: 60 ESSCX ST. 284-F-901/902
REA	SON FOR PERMIT: To Congirual breezeway & garage
B บไโ	LDING OWNER: Ron Kimball
CON	TRACTOR: MAINE-Wide Const.
PER	MIT APPLICANT: ROA KIMBOLL
	GROUP BOCA 1996 CONSTRUCTION TYPE 58
	CONDITION(S) OF APPROVAL
This	Permit is being issued with the understanding that the following conditions are met:
Ann	roved with the following conditions: */*2*5, *24*26 *29
X ,1.	This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
£2.	Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be
3.	obtained. (A 24 hour notice is required prior to inspection) Precaution must be taken to protect concrete from freezing.
3. 4	It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to
	verify that the proper setbacks are maintained.
X 5.	Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from
, ,	adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire
	resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the
	interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch
6.	gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA
0.	National Mechanical Code/1993).
7	Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's
	building code.
8	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking
	surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level.
	Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M
	and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder
	effect (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more
	than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than
	2".
9.	Headroom in habitable space is a minimum of 7'6".
10.	Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum
	11" tread. 7" maximum rise
11.	The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
12.	Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special
	knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more
	than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear
	opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches
	(508nm), and a minimum net clear opening of 5.7 sq. ft.
13	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it
1.5	exits directly from the apartment to the building exterior with no communications to other apartment units.
14	All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.)
	closet 3. (Over 3 stories in neight reduterness to the facility is two (2) none.)

16. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the

15

automatic extinguishment.

The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing

provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101
Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
In the immediate vicinity of bedrooms
• In all bedrooms
In each story within a dwelling unit, including basements
In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
The Fire Alarm System shall be maintained to NFPA #72 Standard.
The Sprinkler System shall maintained to NFPA #13 Standard.
All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
Ventilation shall meet the requirements of Chapter 12 Sections 1210. Of the City's Building Code.
All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade.
All requirements must be met before a final Certificate of Occupancy is issued.
All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA National Building Code/1996).
Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical Code/1993).
Please read and implement the attached Land Use-Zonung report requirements.
2 AA

Marge Schmuckat

17.

18 19. 20.

21

22

27

28 **⊀**29

30.

31.

32.