

SECTION 096513 - RESILIENT BASE AND ACCESSORIES

PART 1 - GENERAL

1.1 SECTION REQUIREMENTS

- A. Submittals: Product Data and Samples.
- B. Extra Materials: Deliver to Owner at least 20 linear feet, of each type and color of resilient wall base installed.

PART 2 - PRODUCTS

2.1 WALL BASE VB-1

- A. Products:
 - 1. Johnsonite Traditional Wall Base
- B. Color and Pattern: As indicated on drawings.
- C. ASTM F 1861, Type TV (vinyl).
- D. Group (Manufacturing Method): I (solid).
- E. Style: Cove (with top-set toe).
- F. Minimum Thickness: 0.080 inch.
- G. Height: 4 inches.
- H. Lengths: Cut lengths 48 inches long or coils in manufacturer's standard lengths.
- I. Outside Corners: Job formed or premolded.
- J. Inside Corners: Job formed or premolded.

2.2 RESILIENT ACCESSORIES

- A. Products:
 - 1. Compatible products by Johnsonite.
- B. Color: As noted on Finish Schedule.
- C. Description:

1. Cap for cove resilient sheet floor covering.
2. Carpet edge for glue-down applications.
3. Reducer strip for resilient floor covering.
4. Joiner for tile and carpet.

D. Material: Rubber.

2.3 INSTALLATION ACCESSORIES

- A. Trowelable Leveling and Patching Compounds: Latex-modified, portland cement- or blended hydraulic cement-based formulation provided or approved by flooring manufacturer for applications indicated.
- B. Adhesives: Water-resistant type recommended by manufacturer to suit products and substrate conditions.

PART 3 - EXECUTION

3.1 INSTALLATION

- A. Prepare concrete substrates according to ASTM F 710. Verify that substrates are dry and free of curing compounds, sealers, and hardeners.
- B. Adhesively install resilient wall base and accessories.
- C. Install wall base in maximum lengths possible. Apply to walls, columns, pilasters, casework, and other permanent fixtures in rooms or areas where base is required.
- D. Install stair-tread-nose filler to nosing substrates that do not conform to tread contours.
- E. Install reducer strips at edges of floor coverings that would otherwise be exposed.

END OF SECTION 096513