City of Portland, Maine – Buildi				
Location of Construction: 68 Bishop Street 04103	Owner:	A .	Phone: 878-7890	Permit No:
Owner Address:	Lessee/Buyer's Name:	Phone:	BusinessName:	000034
Contractor Name:	Address:	Phone:		Permit Issued:
Past Use:	Proposed Use:	COST OF WORK \$50,000.00	PERMIT FEE: \$ 324.00	JAN 1 4 2000
Warehouse	Shows offer conta	FIRE DEPT. A		CITY OF PORTLAND
	Example made us	Signature:	BACAR.	Zone: CRI:
Proposed Project Description:	of	- Digitale.	TIVITIES DISTRICT (PA.D	2.) Zoning Approval:
Interior renoveaténs	Also must the parton based uses par	A A	pproved pproved with Conditions: enied	Special Zone or Reviews: Shoreland Wetland
	Submitted to m	Signature:	Date:	□ Flood Zone □ Subdivision
Permit Taken By:	Date Applied For:	n 3 2000 K		☐ Site Plan maj ☐minor ☐mm
 This permit application does not preclude the Building permits do not include plumbing, Building permits are void if work is not startion may invalidate a building permit and seconds. 	septic or electrical work. ted within six (6) months of the date of iss			Zoning Appeal Variance Miscellaneous Conditional Use Interpretation Approved Denied
EXPIRE	ED	Й	RERMITIESUED WITH REQUIREMENTS	Historic Preservation Not in District or Landmark Does Not Require Review Requires Review Action:
	CERTIFICATION			□Appoved
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	he named property, or that the proposed we n as his authorized agent and I agree to co is issued, I certify that the code official's	onform to all applicable l authorized representative	laws of this jurisdiction. In addice is a shall have the authority to ent	been Denied With Conditions
areas of such permit at any reasonable	Jan 3 20		Wi	PERM
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	H REQUIRE UED
RESPONSIBLE PERSON IN CHARGE OF WO	PK TITI E		PHONE:	CMENTS
	Permit Desk Green-Assessor's Can	nary-D.P.W. Pink-Publ		CEO DISTRICT

COMMENTS

			ter first Ingl. Jak	
Type Foundation: Framing: Plumbing: Final:				
Date				

BUILDING PERMIT REPORT
DATE: 3 Jan. 99 ADDRESS: 68 BIShop ST. CBL: 293-C-664
REASON FOR PERMIT: Interior henovations
BUILDING OWNER: William Boyle
PERMIT APPLICANT: /CONTRACTOR OWNER
USE GROUP 5-2 CONSTRUCTION TYPE: CONSTRUCTION COST: 59,060 PERMIT FEES 32469
The City's Adopted Building Code (The BOCA National Building code/1996 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
This permit is being issued with the understanding that the following conditions are met: *1 20 23 *27 × 30 *39
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A

24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING.

- Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6', of the same material. Section 1813.5.2
- Foundations anchors shall be a minimum of 12" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305,17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete from freezing. Section 1908.0

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the

proper setbacks are maintained.

- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-bv-side to rooms in the above occupancies shall be completely separated from the interior spaces and the artic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1.2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)
- All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

11. Guardrails & Handrails: A guardrail system is a system of building components located near the oOpen sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)

12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)

13. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)

16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)

18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

19.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's
	Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be
	installed and maintained at the following locations):
	 In the immediate vicinity of bedrooms In all bedrooms
	Section with the Associated Accessment to
	In each story within a dwelling unit, including basements
-2 0.	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
	(Section 921.0)
	The Fire Alarm System shall maintained to NFPA #72 Standard.
	The Sprinkler System shall maintained to NFPA #13 Standard.
23.	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the
	City's Building Code. (The BOCA National Building Code/1996)
24.	Section 25 - 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any
25	street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25.	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a
	design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection
26	Services.
	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & artics).
21.	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
28	All requirements must be met before a final Certificate of Occupancy is issued.
	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building
27.	Code/1996).
30.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BQCA National Mechanical
2	Code/1993). (Chapter M-16) Sepaste Dermits Are required to New Age
	Please read and implement the attached Land Use Zoning report requirements.
	Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
	Bridging shall comply with Section 2305.16.
	Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)
	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1996),
	A MINIMUM OF a one hour Fire severation shall be maintained but
m	een Tonant 5 Daces -
32.	Fine partition's shall be constructed as por section 711,0 (fire Po-litions
_ <	of The bldg. Cody.
_38	All peretrutions of Fire partitions shall comply with section 714,0 of
	124 blag. Codu.

toruel Horises, Building Inspector

McDougall, PFD
Mage Schmuckal, Zoning Administra

Marke Schmuckal, Zoning Administrator

PSH 11/25/99

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

****CERTIFICATE OF OCCUPANCY FEE \$50.00

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Attached Single Family Dwellings/Two-Family Dwelling Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

Total Square Footage of Proposed Structure	Square Footage of Lou	
Tax Assessor's Chart, Block & Lot Number Chart# 293 Block# Lot# 004	Boyle Buildings, Ir	Telephone#: 878.7890
Owner's Address: 70 Bishop St.	Lessee/Buyer's Name (If Applicable)	Cost Of Work: Fee \$ 334.
Proposed Project Description. (Please be as specific as possible) Interior of new bldg.		
Contractor's Name, Address & Telephone William	Boyle /Boyle Buildings	Inc. Rec'd By
Current Use: Ware nouse	Proposed Use: Selve	
•All construction must be conducted in complia •All plumbing must be conducted	for Internal & External Plumbing, HVAC and Electrica nace with the 1996 B.O.C.A. Building Co- ted in compliance with the State of Main ith the 1996 National Electrical Code as a	de as amended by Section 6-Art II. te Plumbing Code.

•HVAC(Heating, Ventililation and Air Conditioning) installation must comply with the 1993 BOCA Mechanical Code. DEPT. OF BUILDING INS

CITY OF PORTLAND, ME

2000

You must Include the following with you application:

1) ACopy of Your Deed or Purchase and Sale Agreement 2) A Copy of your Construction Contract, if available

3) A Plot Plan/Site Plan

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

4) Building Plans

Unless exempted by State Law, construction documents must be designed by a registered design professional.

A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures)
- Floor Plans & Elevations
- Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Certification

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to cuforce the provisions of the codes applicable to this permit.

Signature of applicant: Hanen	1 Lunuella	Date: 1/3/00
/ wan	7 nangella.	

Mone peoples AlliAure Else Where BANGOT Phanes only & No ME Contra Desfriss?

Veserching

Across The