G315 Series

| | | | The second second second second | <u> </u> | | | | |
|-------------------------------|----------|----------|----------------------------------|---------------------------------|----------------------------------|--|--|--|
| Model | G315/5 | G315/6 | G315/7 | G315/8 | G315/9 | | | |
| Performance Data | | | | | | | | |
| Gross Output (MBH) | 350 | 454 | 559 | 663 | 768 | | | |
| # of Sections | 5 | 6 | 7 | 8 | 9 | | | |
| Max. Input Gas (MBH) | 433 | 556 | 678 | 801 | 924 | | | |
| Max. Input Oil (GPH) | 3.0 | 3.85 | 4.7 | 5.6 | 6.4 | | | |
| Net IBR (MBH) | 304 | 395 | 486 | 577 | 668 | | | |
| Boiler HP | 10.4 | 13.6 | 16.6 | 19.8 | 22.9 | | | |
| Max. Operating Pressure (psi) | 87 | 87 | 87 | 87 | . 87 | | | |
| Combustion Efficiency Oil | 86.8% | 86.9% | 87% | 87.1% | 87.1% | | | |
| Combustion Efficiency Gas | 84.2% | 84.3% | 84.4% | 84.4% | 84.5% | | | |
| Thermal Efficiency Oil | 83.3% | 84.3% | 84.9% | 85.4% | 85.7% | | | |
| Thermal Efficiency Gas | 80.8% | 81.8% | 82.4% | 82.8% | 83.1% | | | |
| Number of Sections | 5 | 6 | 7 | 8 | 9 | | | |
| Piping Connections | | | | | | | | |
| Vent Connection Size, in | | | 7 | | | | | |
| Supply, in | 3 | | | | | | | |
| Return, in | 3 | | | | | | | |
| Physical Dimensions | | | | | | | | |
| Overall Boiler Length, in | 44 19/64 | 50 19/32 | 56 ⁵⁷ / ₆₄ | 63 ³ / ₁₆ | 69 31/64 | | | |
| Boiler Block Length, in (LK) | 38 3/16 | 44 31/64 | 50 ²⁵ / ₃₂ | 57 ³ / ₃₂ | 63 ²⁵ / ₆₄ | | | |
| Boiler Door Thickness, in | 5 | | | | | | | |
| Minimum Boiler Width, in | 28 | | | | | | | |
| Height, in | 40¾ | | | | | | | |
| Fire Box Depth, in | 31 | 371/2 | 43¾ | 50 | 561/4 | | | |
| Fire Box Diameter, in | 15¾ | | | | | | | |
| Fire Box Volume (cu. ft.) | 5.19 | 6.39 | 7.59 | 8.79 | 9.99 | | | |
| Dry Weight (lbs.) | 1,197 | 1,391 | 1,585 | 1,779 | 1,973 | | | |
| Water Content (gal.) | 37.8 | 45.2 | 52.6 | 60.0 | 67.4 | | | |
| Operating Weight (lbs.) | 1,512 | 1,768 | 2,024 | 2,280 | 2,545 | | | |

Operational Requirements of the G315

- The boiler must be placed on a smooth, level concrete base, 33½" wide.
- Cement in the base (or place on its top) either 4" x ¼" flat steel plates or 4" x 2" x ¼" angle irons for boiler support.
- Set boiler high limits above 122°F (149
 °F for modulating gas burner) for safe
 boiler operation.
- Low fire setting must be at least 60% of full fire for a LHL burner.
- Maintain minimum of 158°F in the boiler in case of ice water return temperatures.
- Buderus recommends the use of customized Beckett or Riello F series burners when firing the G315 with oil. (Available from Buderus.)
- Use Power Flame or Riello for gas firing. (Available from Buderus.)







MEA APPROVED CRN APPROVED

Approval numbers are subject to periodic changes and updates. Please visit www.buderus.us for the most up-to-date approval numbers.



