Inspections Division
Date: 04/03/14

SANYO North America Corporation

Wall Mounted Heat Pump

18KHS72

Overview | Specifications | Features | Resources | Dealer Images

Model No.	18KHS72
Unit Model No.	Indoor Unit: **KHS1872** Outdoor Unit: **CH1872**
Capacity (Btu/h)	Cooling: 17,500 (4,000~17,500) Heating: 20,400 (4,400~20,400)
Moisture Removal High (Pints/H)	4.89
Dry Air Flow - Hi / Med / Low (CFM)	417 / 479 / 524

Inspections Division
Date: 04/03/14

EER (Cooling)	20
ER (Cooling)	11.7
HSPF (Heating)	10.0
Power Supply - V, Phase (Hz)	230/208V, 1PH, 60Hz
Running Amps	Cooling: 7/7.7 (1.2~7.7) Heating: 7.4/8.1 (1.3~8.1)
Power Input (W)	Cooling: 1,500/1,500 (250~1,500) Heating: 1,575/1,575 (270~1,575)
Back-up Heater (kW)	---
Fuse or Circuit Breaker Capacity (A)	20
Controls	Microprocessor
Low Ambient Control	---
Wireless Remote Controller	Included
Fan Speeds	High / Med / Low & Auto
Timer	1hr OFF and 24-hr PROGRAM
Air Deflection	Horizontal: Manual Vertical: Automatic
Air Filter (dB-A)	Washable
Refrigerant (dB-A)	R-410A
Refrigerant Control	Electric Expansion Valve
Operation Sound (dB-A)	Indoor (Hi / Med / Low): 42 / 38 / 30 / 28 Outdoor (Hi): 51-52
Refrigerant Piping	Flare Type 1/4" Discharge 1/2" Suction
Refrigerant Pipe Length	Max. 98Ft.
Elevation	Outdoor Above: Max. 50Ft.

Inspections Division
Date: 04/03/14

Difference*	Outdoor Below: Max. 50Ft.
Height	Indoor Unit: 11-23/32" Outdoor Unit: 26-3/8"
Width	Indoor Unit: 41-15/16" Outdoor Unit: 34-21/32"
Depth	Indoor Unit: 8-19/32" Outdoor Unit: 11-7/32"
Net Weight	Indoor Unit: 26.5 lbs. Outdoor Unit: 97.0 lbs.

*This is maximum elevation difference when the indoor unit is located above the outdoor unit.

Copyright © 2014 Sanyo North America Corporation, All rights reserved.

Panasonic USA

- About Panasonic
- Career Opportunities
- Panasonic Eco Ideas
- Corporate Social Responsibility
- For Investors

Copyright © 2013 Panasonic Corporation of North America. All rights reserved. | Privacy Policy