Location of Construction: 10 Wilkie St.	Owner: *** David Ca	rdona	Phone:	797-6234	Permit No:
Dwner Address: *10 Wilkie St. Portland 04103	Lessee/Buyer's Name:	Phone:	Busines	sName:	001108
Contractor Name:	Address:	Pho	one:		Permit Issued: `
Past Use:	Proposed Use:	COST OF WC	RK:	PERMIT FEE: \$ 30.00	SEP 2 9 2000
Single Family	Single Family	FIRE DEPT. I	☐ Approved] Denied	INSPECTION: Use Group: 4 Type: BOCA92/11	Zone: CBL: 307-F-021
roposed Project Description:		Signature: PEDESTRIAN	ACTIVITI	Signature: S DISTRICT (VA.D.)	Zoning Approval
10 x 8 shed for storage		Action: Signature:	Approved	with Conditions: Date:	□ 5 Sides - Acas - 25 From Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone □ Subdivision
ermit Taken By: Gayle	Date Applied For:	September 28,	, 2000 GG		Site Plan maj Ominor Omm I
 This permit application does not preclude t Building permits do not include plumbing Building permits are void if work is not station may invalidate a building permit and 	, septic or electrical work. rted within six (6) months of the date of		ia-		 Miscellaneous Conditional Use Interpretation Approved Denied
				PERMITISSUED WITH REQUIREMENTS	Historic Preservation
				MIII.	Action:
I hereby certify that I am the owner of record of authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonable	on as his authorized agent and I agree to n is issued, I certify that the code officia	o conform to all application of a second conformation of the second configuration of t	y the owner of able laws of th tative shall ha	record and that I have b his jurisdiction. In additi	een Appoved Approved with Conditions ion, all Date:
		September 28, 1	2000		ED
IGNATURE OF APPLICANT	ADDRESS:	DATE:		PHONE:	PERMIT ISSUED PERMIT ISSUED INTH REQUIREMENTS

10/	10/00 Pre-am	WITS male	Shed does not meet	mon
lord it	equirements, G	n _		-
-				
			····	

		······································		

Inspection Record

Туре	Date
Foundation:	
Framing:	
Plumbing:	
Final:	
Other:	

. *

In the interest of processing	Buildir Addition To D	DNSTRUCTION CANN PERMIT IS ISSUED ag or Use Permit Pre-Ap s/Alterations/Accessory etached Single Family D e quickest possible manner, ple	plication Structures Owelling	
		Use Permit. l estate or personal property		
City, Location/Address of Construction		ets must be made before perm est Portluc	$\frac{1}{2} M \tau O 4$	
Tax Assessor's Chart, Block & L Chart# 307 Block#	F Lat 00	Daviel Ca	rdarig	Telephone#: 7976234
Owner's Address: 10 Wilkie S		Lessee/Buyer's Name (If Applicat	ole) C	ost Of Work: Fee
Proposed Project Description:(Pl	ease be as specific as possible	morer and	grill yard	
Contractor's Name, Address & To	elephone I (irdana	Rec'd By	100
•HVAC(Heating, Ven You must Include the f If there is expansion to • The shape and din property lines. Str pools, garages and	tilation and Air Cond following with you 1) A Copy of Yo 2) A Copy of y 3) A the structure, a co nension of the lot, all est	our Deed or Purchase an your Construction Cont Plot Plan (Sample Atta mplete plot plan (Site Pla sisting buildings (if any), the pr porches, a bow windows cantile ructures.	omply with the 1993 nd Sale Agreemen ract, if available ached) n) must include: roposed structure and A	BOCA Mechanical Code. [] t mdistance from the actual
A complete set of cons	truction drawings s	ilding Plans (Sample At howing all of the followin	ng elements of con	SEP 2 Section: 200
 Floor Plans & Ele Window and door Foundation plans Electrical and plun equipment, HVAC 	vations schedules with required drainage nbing layout. Mechanic Cequipment (air handlin	al drawings for any specialized ag) or other types of work that Certification	l equipment such as fu may require special re	maces, chimneys, gas view must be included.
I hereby certify that I am the	y the owner to make this on if a permit for work (named property, or that the pro- is application as his/her authori described in this application is as covered by this permit at an	ized agent. I agree to c issued, I certify that the	e Code Official's authorized
that I have been authorized b of this jurisdiction. In additio representative shall have the codes applicable to this perm	authority to enter all are uit.	-		

	DATE: 28 Sept. DK ADDRESS: 10 WILKIE ST. CBL: 307-F-
3	REASON FOR PERMIT: 8 × 10 She d
1	BUILDING OWNER: David Gardong -
Ŧ	PERMIT APPLIÇANT:/CONTRACTOR_OWNEL
τ	Use group: $\dot{\mathcal{U}}$ construction type: 5.3 construction cost: permit fees:
	'he City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) 'he City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
	CONDITION(S) OF APPROVAL
т -	This permit is being issued with the understanding that the following conditions Shall be met: $\frac{4}{42}$, $\frac{42}{36}$, $\frac{29}{4}$, $\frac{4}{36}$
	· 5-
1. 1. 2. 3.	This permit does not excuss the applicant from meeting applicable State and Federal rules and laws. Before concrete soft foundation is placed, approval g from the Development Beview Coordinator and Inspection Services must be obtained. 24 hour notice is required prior to inspection) " <u>ALL</u> LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING." Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing.
	thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforation shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone with the protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone
4.	shall be covered with not less than 6" of the same material. <u>Section 1813.5.2</u> Foundations anchors shall be a minimum of 1/2" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. <u>Section 2305.17</u>
. 5.	Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
6. 7.	Precaution must be taken to protect concrete from freezing. <u>Section 1908.0</u> It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that
8.	spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages atta side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch
9.	gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999) All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanic
10	Code/1993). Chapter 12 & NFPA 211 Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
11.	Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces fo purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42" In occupancies in Use Group A, B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters of of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern tha would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but i more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Section 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
12. 13.	Headroom in habitable space is a minimum of 7'6". (Section 1204.0) Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/" maximum rise</u> . All other Use Group minimum 11" trea
	7" maximum rise. (Section 1014.0) The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
15.	Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools Where windows are provided as <u>means of egress or rescue</u> they shall have a sill height not more than 44 inches (1118mm) above the floor. A egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minim net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
16.	Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
	All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
17.	

•

- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall installed and maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 24. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
- 28. All requirements must be met before a final Certificate of Occupancy is issued.
- 229. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1999).
- 30. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
- 31. Please read and implement the attached Land Use Zoning report requirements.
- 32. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code. 33. Bridging shall comply with Section 2305.16.
 - 34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)
 - 35. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).

, mini Real 11 MIN amin reme fises, Building Inspector Lt. McDougall, PFD Marge Schmuckal, Zoning Administrator PSH 11/25/99

**This Permit is herewith issued,on the basis of plans submitted and conditions placed the plans, any deviations shall require a separate approval.

••••THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

**** Certificate of Occupancy Fees: \$50.00 each

***** All PLANS THAT REQUIRE A PROFESSIONAL DESIGN'S SEAL,(AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000 OR REQUIVALENT.



