1 DOOR TYPES
1/4" = 1'-0"

FRAME TYPES:

GLAZING SCHEDULE

KEY	GLAZING TYPE
GL-1	INSULATED CLEAR TEMPERED GLAZING
GL-2	FIRE RATED INSULATED GLAZING
GL-3	CLEAR TEMPERED GLASS
GL-4	CLEAR INSULATED TEMPERED GLASS
GL-5	FIRE RATED GLAZING

DOOR SCHEDULE

DOOR								FRAME						GENERAL			
		SIZE									DETAILS						
DOOR NO.	TYPE	WIDTH	HEIGHT	THICKNESS	MATERIAL	FINISH	INSULATED	TYPE	MATERIAL	THRESHOLD	HEAD	JAMB	SILL	CLOSER	FIRE RATING (MINUTES)	F.O.B. ACCESS	REMARKS
100.1	C	3'-0"	7'-0"	1 3/4"	FG	PTD	Y	1	FG	AL	-	-	-	Y	-	-	ENTRY DOOR
100.2	A	3'-0"	7'-0"	1 3/4"	WD	PTD	Y	1	WD	-	-	-	-	Y	-	-	-
102.1	B	3'-0"	7'-0"	1-3/4"	WD	PTD	Y	1	WD	-	-	-	-	-	-	-	-
103.1	B	3'-0"	7'-0"	1-3/4"	WD	PTD	Y	1	WD	-	-	-	-	-	-	-	-
104.1	B	3'-0"	7'-0"	1-3/4"	WD	PTD	Y	1	WD	-	-	-	-	-	-	-	-
105.1	C	3'-0"	7'-0"	1 3/4"	FG	PTD	Y	1	FG	AL	-	-	-	Y	-	-	ENTRY DOOR

HARDWARE KEY
MLS - MORTISE LOCK SET
LS - LOCK SET
PR - PRIVACY SET
PS - PASSAGE SET
LP - LEVER PULL
PH - PEEPHOLE LENSE

MATERIALS: KEY
AL - ALUMINUM
STL - STEEL
MTL - METAL
WD - WOOD
FG - FIBERGLASS

FINISH KEY
PTD - PAINTED
ANO - ANODIZED ALUMINUM
STN - STAINED

DOOR NOTES:

1.) ALL EXTERIOR GLAZING TO BE LOW-E ARGON FILLED INSULATED GLAZING UNITS

2.) FRAME ALL OPENINGS WITH ELEVATIONS

3.) SEAL EXTERIOR DOORS TO ROUGH OPENING WITH LOW EXPANDING FOAM INSULATION - SEE DETAILS

4.) ALL DOOR HARDWARE TO BE 'LEVER' TYPE

5.) ALL EXTERIOR DOORS TO BE WEATHER-STRIPPED

6.) ALL DOORS TO BE SOLID CORE DOORS

WINDOW SCHEDULE LEGEND

T = TEMPERED GLASS
FG = FIBERGLASS
AL = ALUMINUM
DH = DOUBLE HUNG
AW = AWNING
LV = LOUVER
F = FIXED
GL = GLIDER

3 WINDOW TYPES
1/4" = 1'-0"

WINDOW SCHEDULE

KEY	ACTION	ROUGH * OPENING (WxH) VIF	TO LINTEL HEIGHT FROM SUB FLOOR	DETAILS HEAD	JAMB	SILL	MATERIAL	FINISH	FOR TEMPERED GLASS LOCATIONS SEE WINDOW ELEVATION TYPES FOR MASONRY OPENING DIMENSIONS COORDINATE COURSING WITH EXTERIOR ELEVATION SHEETS AND PLAN AND SECTION DETAIL SHEETS REMARKS
A	DH	3'-1" X 4'-6-1/2"	7'-0"	-	-	-	VL	-	NAILING FLANGE
B	AW	3'-1" X 3'-0-1/2"	7'-0"	-	-	-	VL	-	NAILING FLANGE
C	DH	6'-1" X 4'-6-1/2"	7'-0"	-	-	-	VL	-	NAILING FLANGE

4 TYPICAL WINDOW TRIM
NOT TO SCALE

WINDOW NOTES:

1.) COORDINATE AND ADJUST ROUGH OPENING DIMENSIONS TO ACCOMMODATE SILL PAN FLASHING SYSTEM

2.) FULL SCREENS ALL OPENINGS

3.) ALL GLAZING LOCATED WITHIN 18" OF FINISHED FLOOR TO BE TEMPERED GLASS

4.) ALL EXTERIOR GLAZING TO BE INSULATED

5.) FRAME ALL OPENINGS WITH ELEVATIONS

6.) SEAL WINDOW TO ROUGH OPENING WITH LOW EXPANDING FOAMINSULATION - SEE DETAILS

Notes:

1. For the most current details, installation video and product information, see our web site at www.graceconstruction.com
2. RIPCORD® (Split Release on Demand) can be removed from Grace Vycor® Plus for ease of installation
3. Install Grace Vycor Plus in order shown by numbers
4. If applicable, leave release paper on lower half of sill flashing until future tie-in
5. Install Grace Vycor Plus and weather-resistive barrier to form water-shedding laps
6. Detail also relevant for Grace Vycor V40

Reviewed for Code Compliance
Inspections Division
Portland, Maine
Date: 02/05/18

REGISTERED ARCHITECT
RYAN J. SENATORE
No. 3322
STATE OF MAINE

© 2017 RYAN SENATORE ARCHITECTURE

OFFICE BUILDING
547 RIVERSIDE STREET
PORTLAND, MAINE

RSA
RYAN SENATORE
ARCHITECTURE
565 CONGRESS STREET
PORTLAND, MAINE 04101
207-650-6414
senatorearchitecture.com

CONSULTANTS:

REVISIONS:

DATE:	DECEMBER 29, 2017
PROJECT No.	1788
DRAWN BY:	RJS, JPF
CHECKED BY:	RJS
SCALE:	AS NOTED

SHEET TITLE:
DOOR AND WINDOW SCHEDULE

A7-0