cation of Construction: Owner: Define:		Phone:	Permit No.9 7 0 0 3 2	
Owner Address:	Leasee/Buyer's Name:	Phone:	BusinessName:	PERMIT ISSUED
Contractor Name: Journ Construction	Address: 216 Bancro		04102 773-3934	Permit Issued: JAN 1 6 1997
Past Use:	Proposed Use:	COST OF WORK: \$ 15,000.00	PERMIT FEE: \$ 95.00	CITY OF PORTLAND
Auto Parts Sales/Service	Retail	FIRE DEPT. ☐ Ap ☐ De Signature:		Zone: CBL: 314-2-022
Proposed Project Description:			TIVITIES DISTRICT (P.U	
Change Use Make Int/Ext Renovacions		Ap	proved proved with Conditions: nied Date:	□ Special Zone or Reviews: □ Shoreland □ Wetland □ Flood Zone □ Subdivision
Permit Taken By:	Date Applied For:	Jasuary 1997		☐ Site Plan maj ☐ minor ☐ mm ☐
 Building permits do not include plumbing, se Building permits are void if work is not started tion may invalidate a building permit and stop 	l within six (6) months of the date of iss	uance. False informa-		☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
30-3529/15380		W	PERMIT ISSUED ITH REQUIREMENT	Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review
	CERTIFICATION			Action:
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	as his authorized agent and I agree to cossued, I certify that the code official's a	nform to all applicable la uthorized representative	lws of this jurisdiction. In ac shall have the authority to e	ddition, Denied
rampel forus		09 January		
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	

		Final: Other:		
		Plumbing:		
		Type Foundation:		Date
			Inspection Record	
6/19/98	Work Cylett	P		
4/24/98	· Work Citales	<u> </u>		
the don	1156 Cl . 20, C	COMMENTS		

BUILDING PERMIT REPORT

DATE	:	ADDRESS:_	517 Warran Huc
REAS	ON FOR PERMIT:	: Monofin	
BUIL	DING OWNER:	Edward Blyler	
CONT	TRACTOR:	Jone, Cut	
		Controll Jones	APPROVAL: * 3 * 13 * 15 * 18 DENIED: * 19 1
		CONDITION OF AI	PPROVAL OR-MENIAL
1. 2.	Before concrete for fou	xcuse the applicant from meeting indation is placed, approvals from ir notice is required prior to insp	g applicable State and Federal rules and laws. In the Development Review coordinator and Inspection Services must ection)
′3, ′4.	Precaution must be tak	en to protect concrete from freez	ing. yor check all foundation forms before concrete is placed. This is
7.	done to worlfy that the	proper cethacks are maintained	
5.	Private garages located adjacent interior space	I be neath habitable rooms in occurs by fire partitions and floor/ceiling arrange attached side-by-side to	upancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from ing assembly which are constructed with not less than 1-hour fire to rooms in the above occupancies shall be completely separated from
\$49.	the interior spaces and	the attic area by means of ½ inc	th gypsum board or the equivalent applied to the garage means of 72 age side. (Chapter 4 Section 407.0 of the BOCA/1996)
6.,	Guardrail & Wandraile	· A mardrail system is a system (of building components located near the open sides of elevated ssibility of an accidental fall from the walking surface to the lower

Headroom in habitable space is a minimum of 7'6". 7.

would provide a ladder effect.

Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group 8. minimum 11" tread, 7" maximum rise.

The minimum headroom in all parts of a stairway shall not be less than 80 inches. 9.

Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or 10. exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.

level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that

Each apartment shall have access to two (20 separate, remote and approved means of egress. A single exit is acceptable 11. when it exits directly from the apartment to the building exterior with no communications to other apartment units.

All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with 12. self closer's.

The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by 13. providing automatic extinguishment.

- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the 14. provisions of the City's building code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms

In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

15.	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an
\bigcirc	approved type.
16.	The Fire Alarm System shall be maintained to NFPA #72 Standard.
17.	The Sprinkler System shall maintained to NFPA #13 Standard.
(18.)	All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
(19)	All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached,
	Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
20.	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
21.	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
22.	This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
23.	Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code.
24.	
25,	
26,	
(%	2/2//
P. Sam	uel Hoffses CHef of Code Enforcement
	#####################################

cc: Lt. McDougall, PFD
Marge Schmuckal

