

**City of Portland, Maine – Building or Use Permit Application** 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 517 Warren Ave		Owner: Meiler, Ed		Phone:		Permit No: 970078	
Owner Address:		Leasee/Buyer's Name: Wholesale Cabinet Outlets		Phone:		Business Name:	
Contractor Name: Wholesale Cabinet Outlets		Address: 517 Warren Ave Portland, ME 04103		Phone: 797-8716		<div style="border: 2px solid black; padding: 5px; text-align: center;"> <b>PERMIT ISSUED</b>                  Permit Issued:  <b>JAN 31 1997</b>  <b>CITY OF PORTLAND</b> </div>	
Past Use: Service (engines)		Proposed Use: Retail		COST OF WORK: \$ 7,500.00 PERMIT FEE: \$ 65.00			
Proposed Project Description: Change Use Make Interior Renovations		FIRE DEPT. <input type="checkbox"/> Approved <input type="checkbox"/> Denied Signature: <i>[Signature]</i>		INSPECTION: Use Group: Type: Signature: <i>[Signature]</i>		Zone: CBL: 314-B-022 Zoning Approval: <i>[Signature]</i> <b>Special Zone or Reviews:</b> <input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <input type="checkbox"/> Flood Zone <input type="checkbox"/> Subdivision <input type="checkbox"/> Site Plan <input type="checkbox"/> major <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/>	
PEDESTRIAN ACTIVITIES DISTRICT (P.U.D.) Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied Signature: _____ Date: _____		Zoning Appeal <input type="checkbox"/> Variance <input type="checkbox"/> Miscellaneous <input type="checkbox"/> Conditional Use <input type="checkbox"/> Interpretation <input type="checkbox"/> Approved <input type="checkbox"/> Denied					
Permit Taken By: Mary Gresik		Date Applied For: 21 January 1997		Historic Preservation <input type="checkbox"/> Not in District or Landmark <input type="checkbox"/> Does Not Require Review <input type="checkbox"/> Requires Review		Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied Date: 1/28/97	

D.E. Kitchen Dist., Inc.  
398 Cedar Hill St  
Marlborough, MA 01752

**PERMIT ISSUED WITH REQUIREMENTS**

**CERTIFICATION**

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

*[Signature]* 21 January 1997

SIGNATURE OF APPLICANT: Paul Lombardi ADDRESS: DATE: PHONE:

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

CEO DISTRICT 7

COMMENTS

3/16/98 Phone to business disconnected.

4/24/98 Work completed - This tenant has since moved out (R)

Inspection Record

Type	Date
Foundation: _____	_____
Framing: _____	_____
Plumbing: _____	_____
Final: _____	_____
Other: _____	_____

## BUILDING PERMIT REPORT

DATE: 1/29/97 ADDRESS: 517 Warren Ave

REASON FOR PERMIT: Change of use

BUILDING OWNER: Rleiker

CONTRACTOR: Wholesale Cabinet

PERMIT APPLICANT: Paul Lombardi APPROVAL: \*14 \*16 \*19 \*20  
DENIED: \* \*25

### CONDITION OF APPROVAL ~~OR DENIAL~~

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.
2. Before concrete for foundation is placed, approvals from the Development Review coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
3. Precaution must be taken to protect concrete from freezing.
4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) UL 103.
7. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42" , except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
8. Headroom in habitable space is a minimum of 7'6".
9. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
10. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
11. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
12. Each apartment shall have access to two (20 separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
13. All vertical openings shall be enclosed with construction having a fire rating of at least one (1)hour, including fire doors with self closer's.
14. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. *and smoke protection.*
15. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms
  - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

16. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.

17. The Fire Alarm System shall be maintained to NFPA #72 Standard.

18. The Sprinkler System shall maintained to NFPA #13 Standard.

19. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)

20. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.

21. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".

22. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.

23. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.

24. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.


25. A one hour fire separation required between tenants

26.

27.

  
P. Samuel Hoffses, Chief of Code Enforcement

cc: Lt. McDougall, PFD  
Marge Schmuckal



71'0"

TO COMMON AREA  
BOILER + ELECTRICAL ROOM

3'0" SOLID WOOD DOOR  
EXISTING

WAREHOUSE STORAGE AREA  
FOR KITCHEN CABINET  
INVENTORY

36'3"

58'1"

3'0" SOLID WOOD DOOR TO WAREHOUSE

VANITY  
DISPLAY  
AREA

KITCHEN  
CABINET  
DISPLAY  
AREA

3'0" STEEL DOOR TO MAIN FINE  
EXISTING

SALES  
AREA

32'10"

\* WALLS SEPARATING SHOWROOM FROM WAREHOUSE  
CONSTRUCTED OF 3 1/2" METAL STUDS FROM FLOOR  
TO ROOF CLAD W/ 5/8" FIRE RATED SHEET ROCK ON  
BOTH SIDES AND INSULATED WITH 3 1/2" FIBERGLASS  
INSULATION.

\* INTERIOR SHOWROOM WALLS FOR CABINET  
DISPLAY INSTALLATION, CONSTRUCTED OF 3 1/2" WOOD  
STUDS 8' IN HEIGHT WITH 1/2" SHEET ROCK  
ON BOTH SIDES. SALES AREA WALLS ARE  
4 1/2" IN HEIGHT.

$7'1" \times 50' = 410\$$   
 ~~$36'5" \times 50' = 1825\$$~~

NO SITE PLAN  
REQ.

7'1"

3'0" STEEL DOOR  
EXISTING

BATHROOM

LAV TOILET

9'0"

ELECTRIC OVERHEAD  
GARAGE DOOR (EXISTING)

3'0" SOLID WOOD DOOR TO WAREHOUSE

3'0" STEEL GLASS DOOR  
W/ SIDE LIGHT  
OPENS OUT

13'1"

ENTRANCE

EXISTING

