City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716 Location of Construction: Owner: Phone: Permit No: 270 Riverside St Tidy Up Car Wash Lessee/Buyer's Name: Phone: BusinessName: Stop & Shoppe Food Mart 774-9095 Permit Issued: Contractor Name: Address: Phone: Sign Design COST OF WORK: Proposed Use: PERMIT FEE: Past Use: 44.20 Gas sta **FIRE DEPT.** □ Approved INSPECTION: Convenience STore Same ☐ Denied Use Group: Type: CBL:316-B-008 Zone: Signature: Signature: Zoning Approval: Proposed Project Description: PEDESTRIAN ACTIVITIES DISTRICT (P.A.D.) Action: Approved Special Zone or Reviews: Alter Signage - Enlargen Approved with Conditions: ☐ Shoreland Denied □ Wetland ☐ Flood Zone □ Subdivision Signature: Date: ☐ Site Plan maj ☐minor ☐mm ☐ Date Applied For: Permit Taken By: Mary Gresik 15 July 1997 **Zoning Appeal** □ Variance This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules. ☐ Miscellaneous 2. Building permits do not include plumbing, septic or electrical work. ☐ Conditional Use 3. Building permits are void if work is not started within six (6) months of the date of issuance. False informa-☐ Interpretation □ Approved tion may invalidate a building permit and stop all work... ☐ Denied Historic Preservation □ Not in District or Landmark ☐ Does Not Require Review ☐ Requires Review Action: CERTIFICATION ☐ Appoved ☐ Approved with Conditions I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been □ Denied authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued. I certify that the code official's authorized representative shall have the authority to enter all Date: areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit 15 July 1997 SIGNATURE OF APPLICANT Todd Flanery ADDRESS: DATE: PHONE: RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE: **CEO DISTRICT**

White-Permit Desk Green-Assessor's Canary-D.P.W. Pink-Public File Ivory Card-Inspector

BUILDING PERMIT REPORT

DATE: 23 July 97 ADDRESS: 270 Priverside ST
REASON FOR PERMIT: To Frect Signage
BUILDING OWNER: Tidy Up Car Wash
CONTRACTOR: Sign Design
PERMIT APPLICANT: Todd Flanery APPROVAL: *1 *2 *22 DENIED

CONDITION(S) OF APPROVAL

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

- Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 3. Precaution must be taken to protect concrete from freezing.
 - 4. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 5. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)
 - 6. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993) U.L. 103.
 - 7. Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
 - 8. Guardrail & Handrails A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - 9. Headroom in habitable space is a minimum of 7'6".
 - 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
 - 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
 - 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
 - 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
 - 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
 - All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and

I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)

- 17. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
- 18. The Fire Alarm System shall be maintained to NFPA #72 Standard.
- 19. The Sprinkler System shall maintained to NFPA #13 Standard.
- All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996)
- 21. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
- 22. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 23. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
- 24. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office.
- 25. Ventilation shall meet the requirements of Chapter 12 Sections 1210. of the City's Building Code.

26.	All electric						Licensed holde					0
27.	19ef	ore	any	Work	beg1	25	a SI	-4c	Tura	PLO	270	, (_
_	The	Propo	rsed	51917	must	Бe,	Submil	ted	and	dippr	o vea	

(Plan Showing Found pole and Sign design and Structure

Samuel Hoffses, Chief of Code Enforcement

cc: Lt. McDougall, PFD Marge Schmuckal

SIGNAGE

PLEASE ANSWER ALL QUESTIONS

	Address: 270 Rivus, Je St. Zone: B-4
	owner: Tidy UP Can aligh Assessors #:
	Applicant: Shouse
	pedulerny existry Election 351 to 25
	Single Tenant Lot?: Yes No No
	Multi Tenant Lot?: Yes No 60 #MTX >> Shorts
	Freestanding (Ext pole sign)? Yes Dimensions
	More than (1) one sign?: Yes No Dimensions
	Bldg Wall Sign (att to bldg)? Yes No Dimensions
1 a	List all existing signage and their dimensions:
CWF	8) 14x9 Pole Sign - Riverside St.
to,	4x9 /Pole sign - Warran Ave.
1×8	3 Centry signs @ 33" x 81" 2 Paskere Signs 3 xs
,	Lot Frontage(feet): Tenant Frontage(feet):
	AWNINGS
	Awning?: Yes No Is Awning Backlit?: Yes No
	Is there any comunication, message, trademark or symbol on awning?
	Height of Awning?:
	PLEASE NOTE: Approvals for signs on the Public Sidewalk and temporary signs come under different requirements and regulations.
	ALSO: See reverse side for additional information, requirements and

materials needed for signage application submittal.

STOP & SHOPPE

Fuel

Convenience

Change Jame
Existing 429 to

(hause
Elevation from 35'

to 25'

Fee 25.00 96.59 FFAT . 20 = 1920 10191 444.20

GAS PRICE SIGN

\footstark \chi_{\xi_X}

PROPERTY OF

Sign Design, Inc.

Customer:

Project:

Date:

Revised:

Approved: