

CHECK GRAPHIC SCALE BEFORE USING

C.C.R.D. BOOK 27825 PAGE 68

RIVERSIDE SUBDIVISION PLANNING BOARD CONDITIONS OF APPROVAL DATED SEPTEMBER 21, 2010

1. THE APPLICANT SHALL SUBMIT A LETTER FROM PORTLAND TRAILS CONFIRMING PERMISSION TO ESTABLISH DRAINAGE EASEMENT(S) WITHIN THE CONSERVATION EASEMENT OF LOT 4 FOR CORPORATION COUNSEL REVIEW AND APPROVAL.

2. THE APPLICANT SHALL SUBMIT FINAL AND EXECUTED COPIES OF VARIOUS PROPERTY AGREEMENTS AND EASEMENTS ASSOCIATED WITH THE SUBDIVISION FOR CORPORATION COUNSEL REVIEW AND APPROVAL PRIOR TO THE RELEASE OF THE SUBDIVISION PLAT.

3. THE SUBDIMSION RECORDING PLAT SHALL INCLUDE A NOTATION THAT A TRAFFIC MOVEMENT PERMIT WILL BE NECESSARY IF AND WHEN THE TRIP LEVELS FOR THE SUBDIVISION REACHES PERMIT

4. UNLESS OTHERWISE APPROVED BY THE PLANNING BOARD UNDER SITE PLAN REVIEW, UNDERGROUND UTILITIES SHALL BE REQUIRED.



ZONE IM DIMENSIONAL REQUIREMENTS

- 1. CORRECTIONAL PRERELEASE FACILITIES: TEN THOUSAND (10,000) SQUARE FEET
- B. MAXIMUM IMPERVIOUS SURFACE RATIO: I-M ZONE: SEVENTY-FIVE (75) PERCENT.
- C. MAXIMUM BUILDING HEIGHT: I-M ZONE: SEVENTY-FIVE (75) FEET.
- D. MINIMUM SIDE YARDS: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-M ZONE: EACH STRUCTURE SHALL BE SET BACK ONE (1) FOOT FROM EACH SIDE PROPERTY LINE FOR EACH ONE (1) FOOT OF BUILDING HEIGHT, UP TO TWENTY-FIVE (25) FEET, EXCEPT THAT THE MINIMUM SIDE YARD SHALL BE THIRTY-FIVE (35) FEET WHEN THE SIDE PROPERTY LINE ABUTS A RESIDENTIAL ZONE.
- MINIMUM REAR YARDS: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-M ZONE: EACH STRUCTURE SHALL BE SET BACK ONE (1) FOOT FROM THE REAR PROPERTY LINE FOR EACH ONE (1) FOOT OF BUILDING HEIGHT, UP TO TWENTY-FIVE (25) FEET, EXCEPT THAT THE MINIMUM REAR YARD SHALL BE THIRTY-FIVE (35) FEET WHEN THE REAR PROPERTY LINE ABUTS A RESIDENTIAL ZONE.
- MINIMUM FRONT YARD: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-M ZONE: EACH STRUCTURE SHALL BE SET BACK ONE (1) FOOT FROM THE FRONT PROPERTY LINE FOR EACH ONE (1) FOOT OF BUILDING HEIGHT.
- MINIMUM STREET FRONTAGE: SIXTY (60) FEET.
- H. PAVEMENT SETBACK FROM LOT BOUNDARIES: TEN (10) FEET.

- 1. CORRECTIONAL PRERELEASE FACILITIES: TEN THOUSAND (10,000) SQUARE FEET
- 2. OTHER USES NONE.
- B. MAXIMUM IMPERVIOUS SURFACE RATIO: I-H ZONE: EIGHTY-FIVE (85) PERCENT.
- . MAXIMUM BUILDING HEIGHT: SEVENTY-FIVE (75) FEET.
- MINIMUM SIDE YARDS: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-H ZONE:
- MINIMUM REAR YARDS: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-H ZONE: THIRTY-FIVE (35) FEET.
- MINIMUM FRONT YARD: PRINCIPAL AND ACCESSORY STRUCTURES IN THE I-H ZONE:
- MINIMUM STREET FRONTAGE: SIXTY (60) FEET.
- H. PAVEMENT SETBACK FROM LOT BOUNDARIES: TEN (10) FEET.

ZONE RPZ DIMENSIONAL REQUIREMENTS

NO BUILDING OR STRUCTURE SHALL BE ERECTED, ALTERED, ENLARGED, REBUILT, OR USED IN R-P RESOURCE PROTECTION ZONE WHICH DOES NOT COMPLY WITH THE FOLLOWING REQUIREMENTS:

- A. MINIMUM REAR YARDS: PRINCIPAL BUILDING OR STRUCTURE, OTHER THAN A BOATHOUSE OR STOREHOUSE FOR FISHERMAN'S GEAR: SEVENTY-FIVE (75) FEET.
- B. MINIMUM SIDE YARDS:
- 1. PRINCIPAL BUILDING OR STRUCTURE: FIFTEEN (15) FEET.
- 2. ACCESSORY BUILDING OR STRUCTURE: FIVE (5) FEET.
- C. MINIMUM SIDE YARD ON SIDE STREETS.
- 1. PRINCIPAL BUILDING OR STRUCTURE: TWENTY (20) FEET.
- 1. PRINCIPAL BUILDING OR STRUCTURE: TWENTY-FIVE (25) FEET.
- 2. ACCESSORY BUILDING OR STRUCTURE: TWENTY-FIVE 25) FEET.
- 1. PRINCIPAL BUILDING OR STRUCTURE: TWO (2) STORIES OR TWENTY-FIVE (25)
- 2. ACCESSORY BUILDING OR STRUCTURE: ONE (1) STORY OR FIFTEEN (15) FEET.
- MAXIMUM BUILDING AREA: PRINCIPAL BUILDING OR GROUP OF BUILDINGS: TEN (10) PERCENT OF LOT AREA.
- G. MINIMUM LOT AREA: TWENTY THOUSAND (20,000) SQUARE FEET.
- H. MINIMUM WIDTH OF LOT: ONE HUNDRED (100) FEET.
- MINIMUM LOT FRONTAGE ON STREET OR SHORELINE: ONE HUNDRED (100) FEET.
- MINIMUM SHORELINE SETBACK: ALL PRINCIPAL STRUCTURES OTHER THAN PERMITTED PIERS, DOCKS, WHARVES, BREAKWATERS, CAUSEWAYS, BRIDGES, BOATHOUSES AND STOREHOUSES FOR FISHERMAN'S GEAR: SEVENTY-FIVE (75)

CONFORMANCE OF LOTS:

UPON APPROVAL OF THE PROPOSED SUBDIVISION, THE FOLLOWING SITE MODIFICATIONS SHALL BE PERFORMED TO BRING THE PROPOSED SUBDIVISION LOTS INTO CONFORMANCE WITH ZONING REGULATIONS. ITEMS OF WORK SHALL BE PERFORMED AS SOON AS POSSIBLE, BUT NO LATER THAN JUNE 2011. ALL PAVEMENT WITHIN 10 FEET OF THE LOT BOUNDARIES WILL BE REMOVED.

ALL BUILDING OR STORAGE STRUCTURES WITHIN THE SETBACKS WILL BE REMOVED. REMOVAL OF IMPERVIOUS SURFACES AS NECESSARY TO MEET THE MAXIMUM

LANDSCAPING SHALL BE CONSERVED OR PLANTED TO ADDRESS SEC. 14-267(a) "REQUIRED LANDSCAPING FOR PARKING AREAS" FOR DEVELOPED LOTS.

1. A MINIMUM OF TWO TREES PER LOT SHALL BE CONSERVED OR PLANTED MEETING THE CITY OF PORTLAND LANDSCAPING AND LANDSCAPE PRESERVATION STANDARDS OF THE CITY OF PORTLAND TECHNICAL MANUAL.

SHEET #

 $\overline{\Omega}$

 \bar{S}

JAND, MAINE DEPARTMENT SECTION SS STREET AINE 04101

RECORD

OF

0

PLAN NUMBER