

DOOR SCHEDULE

TYPICAL EXTERIOR NOTE:
EXTERIOR DOORS TO HAVE MIN U-VALUE .30

MARK	LOCATION	SIZE	THICKNESS	MATERIAL	MFR	FRAME	TRIM	HARDWARE	FINISH	MFR	MODEL NO.	NOTES
A	ENTRY	3'-0" x 6'-6"	1 3/4"	FIBERGLASS	JELO-TURN SMOOTH-FRAME	ALUMINUM	INTERIOR SPRINKLER	LOCKSET 15 RR 15-1/15 HINGES	552AD	SCHLAGE STANLEY	D-SERIES RHODES 420 FIN	DOOR SWEEP AND WEATHERSTRIP, PAINT DOOR, TOP FINISH ALUM. THRESHOLD W/ BR COVER PLATE, INS. DOOR STOP FIN 2 1/2" x 2 1/2" FIN
B	ENTRY	2'-6" x 6'-6"	1 3/4"	FIBERGLASS	JELO-TURN SMOOTH-FRAME	ALUMINUM	INTERIOR SPRINKLER	LOCKSET 15 RR 15-1/15 HINGES	552AD	SCHLAGE STANLEY	D-SERIES RHODES 420 FIN	DOOR SWEEP AND WEATHERSTRIP, PAINT DOOR, TOP FINISH ALUM. THRESHOLD W/ BR COVER PLATE, INS. DOOR STOP FIN 2 1/2" x 2 1/2" FIN
C	INTERIOR	3'-0" x 6'-6"	1 3/4"	HOLLOW CORE FOAM CORE	JELO-TURN SMOOTH-FRAME	WOOD	WOOD	PRIVACY AT BATH 15 RR 15-1/15 HINGES	552AD	SCHLAGE STANLEY	D-SERIES RHODES 420 FIN	DOOR SWEEP AND WEATHERSTRIP, PAINT DOOR, TOP FINISH ALUM. THRESHOLD W/ BR COVER PLATE, INS. DOOR STOP FIN 2 1/2" x 2 1/2" FIN

Code	Unit Description	Qty	Unit Size			Rough Opening		
			Width	Height	Location	Width	Height	Location
0001	TW3042-2, AA-AA	1	6' 3 3/8"	4' 4 7/8"	LIVING ROOM	6' 3 7/8"	4' 4 7/8"	4' 4 7/8"
0002	TW2842, AA	1	2' 9 5/8"	4' 4 7/8"	DINING AREA	2' 10 1/8"	4' 4 7/8"	4' 4 7/8"
0003	TW3032, AA	1	3' 1 5/8"	3' 4 7/8"	KITCHEN	3' 2 1/8"	3' 4 7/8"	3' 4 7/8"
0004	TW2032, AA	1	2' 1 5/8"	3' 4 7/8"	UTILITY RM	2' 2 1/8"	3' 4 7/8"	3' 4 7/8"
0005	TW3046-2, AA-AA	2	6' 3 3/8"	4' 8 7/8"	BR 1, 2 EGRESS	6' 3 7/8"	4' 8 7/8"	4' 8 7/8"

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0004	TW2032	AA				3' 4 7/8"
0005	TW3046-2	AA-AA				4' 8 7/8"

Dimensions:
Unit: 2' 1 5/8"
Rough Opening: 2' 2 1/8"
Max. Cir. Open: 1' 9 7/8"
Subfloor to Sill Stop: 3' 8 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 4.21 SQ FEET
Vent Area: 2.68 SQ FEET
Max. Cir. Open: 2.47 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0002	TW2842	AA				4' 4 7/8"
0003	TW3032	AA				3' 4 7/8"

Dimensions:
Unit: 2' 9 5/8"
Rough Opening: 2' 10 1/8"
Max. Cir. Open: 2' 5 7/8"
Subfloor to Sill Stop: 2' 8 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 8.23 SQ FEET
Vent Area: 4.64 SQ FEET
Max. Cir. Open: 4.62 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0001	TW3042-2	AA-AA				4' 4 7/8"

Dimensions:
Unit: 6' 3 3/8"
Rough Opening: 6' 3 7/8"
Max. Cir. Open: 2' 9 7/8"
Subfloor to Sill Stop: 2' 8 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 18.90 SQ FEET
Vent Area: 10.52 SQ FEET
Max. Cir. Open: 5.23 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0005	TW3046-2	AA-AA				4' 8 7/8"

Dimensions:
Unit: 6' 3 3/8"
Rough Opening: 6' 3 7/8"
Max. Cir. Open: 2' 9 7/8"
Subfloor to Sill Stop: 2' 4 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 20.62 SQ FEET
Vent Area: 11.46 SQ FEET
Max. Cir. Open: 5.71 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0003	TW3032	AA				3' 4 7/8"

Dimensions:
Unit: 3' 1 5/8"
Rough Opening: 3' 2 1/8"
Max. Cir. Open: 2' 9 7/8"
Subfloor to Sill Stop: 3' 8 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 6.87 SQ FEET
Vent Area: 3.85 SQ FEET
Max. Cir. Open: 3.82 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes

Item	Unit Size	Unit Operation	Location	Arm:	N/A	Height
0001	TW3042-2	AA-AA				4' 4 7/8"

Dimensions:
Unit: 6' 3 3/8"
Rough Opening: 6' 3 7/8"
Max. Cir. Open: 2' 9 7/8"
Subfloor to Sill Stop: 2' 8 1/2"
Projection: n/a

Operating Specifications:
Glass Area: 18.90 SQ FEET
Vent Area: 10.52 SQ FEET
Max. Cir. Open: 5.23 SQ FEET

Extension Jamb: None

Zone: Northern
U-Factor: 0.30, SHGC: 0.31, ENERGY STAR® Qualified: Yes