1901 Forest Ave	Owner: Tosy DiPietro	Phone:	7978666	Permit No 9 9 0 28 3
Owner Address: 20 Continental Dr Ptld, NE 04003	Lessee/Buyer's Name: Bud Hallis Auto Repair	Phone: Busines	sName:	PERMITISSUED
Contractor Name: Gane Grancoeur, Inc.	Address: 90 E. Bridge St Westbroom	Phone:		
Past Use:	Proposed Use:	COST OF WORK: \$ 10,000.00	PERMIT FEE: \$ 70.00	APR (1999
Auto Shop	Same	FIRE DEPT. Approved Denied	INSPECTION: Use Group: 5 / Type: 3 / S	CITY OF PORTLAND Zone; CBL:
		Signature: UMm 7	Mo CA 9 Suffy	1 327A-A-003
Proposed Project Description:		PEDESTRIAN ACTIVITIE	ES DISTRICT//P.A.D.)	Zoning Approval:
Repairs to interior 5/8 FS Sheets	ock & complete painting	Action: Approved Approved Denied	with Conditions:	Special Zone or Reviews: ☐ Shoreland ☐ Wetland ☐ Flood Zone
		Signature:	Date:	☐ Subdivision
Permit Taken By:	Date Applied For:	Karch 1999		□ Site Plan maj □minor □mm
 Building permits do not include plumbing, se Building permits are void if work is not started tion may invalidate a building permit and sto 	d within six (6) months of the date of issua	ance. False informa-		☐ Conditional Use ☐ Interpretation ☐ Approved ☐ Denied
				□ Denied
		PERI WITH D	MIT ISSUED	Historic Preservation ☐ Not in District or Landmark ☐ Does Not Require Review
		PERI WITH RI	MIT ISSUED EQUIREMENTS	่ มีNot in District or Landmark
		PERI WITH RI	MIT ISSUED EQUIREMENTS	☐Not in District or Landmark ☐Does Not Require Review
	CERTIFICATION	PERI WITH RI	MIT ISSUED EQUIREMENTS	☑Not in District or Landmark ☐Does Not Require Review ☐Requires Review
I hereby certify that I am the owner of record of the authorized by the owner to make this application a if a permit for work described in the application is	e named property, or that the proposed wor as his authorized agent and I agree to conf	rk is authorized by the owner of form to all applicable laws of th	record and that I have been is jurisdiction. In addition,	□ Not in District or Landmark □ Does Not Require Review □ Requires Review Action: □ Approved □ Approved with Conditions □ Denied
authorized by the owner to make this application a	e named property, or that the proposed wor as his authorized agent and I agree to conf sissued, I certify that the code official's au	rk is authorized by the owner of form to all applicable laws of th athorized representative shall ha	record and that I have been is jurisdiction. In addition,	□ Not in District or Landmark □ Does Not Require Review □ Requires Review Action: □ Approved □ Approved with Conditions
authorized by the owner to make this application a if a permit for work described in the application is	e named property, or that the proposed wor as his authorized agent and I agree to cont sissued, I certify that the code official's au our to enforce the provisions of the code(s	rk is authorized by the owner of form to all applicable laws of th athorized representative shall ha s) applicable to such permit	record and that I have been is jurisdiction. In addition,	□ Not in District or Landmark □ Does Not Require Review □ Requires Review Action: □ Approved □ Approved with Conditions □ Denied
authorized by the owner to make this application a if a permit for work described in the application is	e named property, or that the proposed wor as his authorized agent and I agree to cont sissued, I certify that the code official's au our to enforce the provisions of the code(s	rk is authorized by the owner of form to all applicable laws of th athorized representative shall ha	record and that I have been is jurisdiction. In addition,	□ Not in District or Landmark □ Does Not Require Review □ Requires Review Action: □ Approved □ Approved with Conditions □ Denied
authorized by the owner to make this application a if a permit for work described in the application is areas covered by such permit at any reasonable ho	e named property, or that the proposed wor as his authorized agent and I agree to cont sissued, I certify that the code official's au our to enforce the provisions of the code(s	rk is authorized by the owner of form to all applicable laws of th athorized representative shall ha s) applicable to such permit	record and that I have been is jurisdiction. In addition, ve the authority to enter all	□ Not in District or Landmark □ Does Not Require Review □ Requires Review Action: □ Approved □ Approved with Conditions □ Denied

	COMMENTS	
z/14/00 All repairs ok 83		
· ·		

Foundation:	Туре	Inspection Record Date
Framing:		
Plumbing:		
Final:		
Other:		

BUILDING PERMIT REPORT DATE: 4/1/99 ADDRESS: 1901 ForeST AVE. CBL: 327B-B-963 REASON FOR PERMIT: Repair after fire. BUILDING OWNER: Draccur Trc. USE GROUP S- BOCA 1996 CONSTRUCTION TYPE 3-8 CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: X X23 X27 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sleve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not light than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	
REASON FOR PERMIT: Repair after fire. BUILDING OWNER: Tony D. Pietro PERMIT APPLICANT: Geno francoeur, Tac. USE GROUP S- BOCA 1996 CONSTRUCTION TYPE 3-B CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: X X23 ×27 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	BUILDING PERMIT REPORT
BUILDING OWNER: Do Do Pietro	DATE: 4/1/99 ADDRESS: 1901 Forest Ave. CBL: 327A-A-903
USE GROUP S- BOCA 1996 CONSTRUCTION TYPE 3-B CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: * *23 *2* 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	REASON FOR PERMIT: Repair after Fine.
USE GROUP S— BOCA 1996 CONSTRUCTION TYPE 3—B CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: X X23	BUILDING OWNER: Tony D. Pietro
USE GROUP S— BOCA 1996 CONSTRUCTION TYPE 3—B CONDITION(S) OF APPROVAL This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: X X23	PERMIT APPLICANT: Gene Francoeur Inc.
This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: ** **2 3 ** 2 7 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	and the second control of the contro
This permit is being issued with the understanding that the following conditions are met: Approved with the following conditions: X X23 X27 1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	
1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws. 2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	
2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	
footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor	2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the
placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2	footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
 4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' o.c. between bolts. (Section 2305.17) 5. Waterproofing and damp proofing shall be done in accordance with Section 1813.0 of the building code. 	a maximum 6' o.c. between bolts. (Section 2305.17)

7. Precaution must be taken to protect concrete from freezing. Section 1908.0

It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify

that the proper setbacks are maintained.

9.

Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1996)

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National

Mechanical Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 3e4" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".) Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ¼" and not greater than 2". (Sections 1021 & 1022.0) - Handrails shall be on both sides of stairway. (Section 1014.7)

12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)

13. Stair construction in <u>Use Group R-3 & R-4is a minimum of 10" tread and 7 3/4" maximum rise</u>. All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)

14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4

Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft. (Section 1018.6)

16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)

17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)

- 18. The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of 19. the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements

In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920.3.2.

- A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved 20. type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall maintained to NFPA #13 Standard.
- -23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1996)
 - Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open 24. any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification 25. from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
 - Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
 - All requirements must be met before a final Certificate of Occupancy is issued. 28.
 - 29. All building elements shall meet the fastening schedule as per Table 2305,2 of the City's Building Code (the BOCA National Building Code/1996).
 - Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical 30: Code/1993). (Chapter M-16)
 - 31. Please read and implement the attached Land Use Zoning report requirements.
 - Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code. 32.
 - Glass and glazing shall meet the requirements of Chapter 24 of the building code.
- Fire becreers shill continue through all concented spaces including interstition spaces. 34.


35.

36.

toffses, Building Inspector Lt McDougall, PFD

Marge Schmuckal, Zoning Administrator

^{**}On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.



THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application

Attached Single Family Dwellings/Two-Family Dwelling

Multi-Family or Commercial Structures and Additions Thereto

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on ANY PROPERTY within the City, payment arrangements must be made before permits of any kind are accepted.

ion/Addressof Construction (include Portion of Building): Square Footage of Proposed Structure 1900 square Seessor's Chart, Block & Lot Number	1901 Forest ave. Square Footage of Lot	
13274 Block# A Lot# 003	Owner: Tony Dilietro	Telephone#:
BO Continental On.	essee/Buyer's Name (If Applicable) Bud Wall's Cento Repai	Cost Of Work: Fee \$ 10,000 \$ 30.000
ad Project Description:(Please be as specific as possible)		- /Q
Repairs to interior 3/27	ES SheetRock & complete	t painting
Or's Name Address a Trans		
or's Name, Address & Telephone	0 90 0 0	
Jse: aulo Shop	coeur Inc. 90 C. Bur	GOST. The Oyog2 Rec'd By of
Iso: auto Shop	Coem Inc. 90 C. Bur West bur Proposed Use: 5 ams	7
Jse: Club Shop Separate permits are required for Internation must be conducted in	eternal & External Plumbing, HVAC and Electrical ins	tallation.

2) A Copy of your Construction Contract, if available

Minor or Major site plan review will be required for the above proposed projects. The attached checklist outlines the minimum standards for a site plan.

Unless exempted by State Law, construction documents must be designed by a registered design professional. A complete set of construction drawings showing all of the following elements of construction:

- Cross Sections w/Framing details (including porches, decks w/ railings, and accessory structures) Floor Plans & Elevations

 - Window and door schedules
- Foundation plans with required drainage and dampproofing
- Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to

are codes applicable to this permit.	enter all addition, if a permit for work dear it
gnature of applicant:	enter all areas covered by this permit at any reasonable hour to
Ho G	that any reasonable hour to
Building Permit Face 225 Co-eur	Date: 3/30/99
Building Permit Fee: \$25.00 for the 1st \$1000.cost plus \$5.00 per \$1, Additional Site review and related fees are attached on a	3/30/99
Additional Size 1st \$1000.cost plus \$5.00 per \$1	000.00
Additional Site review and related fees are attached on a	000.00 construction cost thereafter
- 1000 are anached on a	a separate addendum
	- additioning

CITY OF PORTLAND, MAINE

FIRE DEPARTMENT

32 PA . 003

Mr. Anthony	DiPietro	•					
Continental	Drive			egilas de legación frence •	ikana i 16 kiga makila a ir	, Aggles to the Control to	eralingera and enden
Portland, Ma	ine 0410	14			enegalitetikistoiselinetiil		Septembrio se se se si se
•		RE:_	Fire at	1901 F	orest Av	renue :	
Mr. Anthony	DiPietro			· • • •	•	•	
the building the owner(X)	listed a	3/24/99 bove, o	of which	you	a fire are rep	occurre ported t	ed in to be
building, you Inspection D	u must ob	tain a	repair permit Hall be	from	the But	ildina a	and
			•				
		*. *	•		-		
		· • •		very	truly	yours,	
•				Joseph	E. Thoma	as, Jr.	•

Chief

Portland Fire Department

cc: Building and Inspection Division City Assessor's Office