Code Review				Mar 9, 2018
Definitive Stre	eet Brev	ving		
	IBC 2009		NFPA 101	2009
1 floors above grade	502.1			
Sprinklers		None		None
Fire Alarm		Required		Required
Smoke and CO Detectors		Required		Required
Occupant Load	T 1004.1.1		7.3.1.2	
•		Assembly (tables and chairs) 738 sf / 15 = 44 occ.		Assembly (tables and chairs) 738 sf / 15 = 44 occ.
		Assembly (bar seats) 9 = 9 occ.		Assembly (bar seats) 9 = 9 occ.
		Brewery Area 4119 sf / 100 sf = 42 occ.		Brewery Area 4119 sf / 100 sf = 42 occ.
		Business first floor 2563 sf / 100 = 26 occ,		Business first floor 2563 sf / 100 = 26 occ,
		Total IBC Calculated interior Occupant load = 121 occ.		Total interior Occupant load = 121 occ.
		North Outdoor seating = 24 occ.		North Outdoor seating = 24 occ.
		South Outdoor seating and Cornhole = 38 occ.		South Outdoor seating and Cornhole = 38 occ.
		Public Occupant Load Max = 120		Public Occupant Load Max = 120
	200.1	Factor (Industrial Low Harard (F. 2) (brower)	6.1.10	Concret Industrial Occurrency
Use Group(s)	309.1 3031	Factory Industrial Low-Hazard (F-2) (brewery) (A-2) Assembly	6.1.10 12.1	General Industrial Occupancy Assembly (<300)
	5051	Business	12.1	Business
	T 500			
Construction Type	T 503	3B - mixed combustible unprotected		III (200) combustible unprotected
Building Height and Area	T503	A2 = 2 stories and 9,500 sf footprint		
		F2 = 3 story and 18,000 sf footprint		
Building Height		55'		
Building Elements	T 601	0 hr Structural Frame	12.1.6	Assembly allowed on first floor only 1 if under 1000 oc
	T 602	2 hr Bearing Walls Exterior		In type III (000) building

	T 601	0 hr Bearing Walls Interior			
	T 601	0 hr Non-Bearing Walls Interior			
	T 602	0 hr Non-Bearing Walls Exterior (sep. dist >= 30')			
	T 602	1 hr Non-Bearing Walls Exterior (sep. dist <30')			
	705.5	Exterior Wall with >10' sep. needs rating only from inside			
	T 601	0 hr Floor Construction			
	T 601	0 hr Roof Construction			
Separations	508.3	Non Separated Occupancies		6.1.14.3	Mixed Occupancies
	508.2.5	Boiler room 1hr			
	708	1 hr Mechanical Shaft < 4 stories			
	1022.1	1 hr Stair Shaft < 4 stories			
	1018.1	1/2 hr Corridor	:	30.3.6.1.2	1/2 hr corridor
	508.2.5	1 hr Boiler Room		30.3.2.1.1	1 hr Boiler Room
	508.2.5	1 hr Trash Room	1	30.3.2.1.1	1 hr Trash Room
	508.2.5	1 hr Storage Room		30.3.2.1.1	1 hr Storage Room
Distances and Exits	1021.1	2 Exits required		7.4.1.1	2 Means of Egress required
	1016.1	200' Travel Distance to exits no sprinklers		12.2.6.2	200' Maximum Travel distance
		1/2 diagonal distance exit separation without sprinkler			
	1014.3	75' Common Path of Travel		12.2.5.1.2	20' Common Path of Travel for more than 50 occ.
	1018.4	20' Dead End		12.2.5.6.2	20' Dead End
Unprotected Openings	T 705.8	15% when exterior wall sep. dist. is 3'>5'			
	T 705.8	45% when exterior wall sep. dist. is 10'>15'			
	T 705.8	75% when exterior wall sep. dist. is 15'>20'			
	T 705.8	Unlimited when exterior wall sep. dist. is 25'>30'			
	T 705.8	Unlimited when exterior wall sep. dist. is >30'			
Egress Stairs	1009.1	Occ. Load >50 = 44" min width		24.2.5.4	36" min. stair width
	1009.1	Occ. Load <=50 = 36" min width		7.2.2.2.1.2(B)	44" min. over 50 occ.
	1003.3	Handrails can protrude into stair 4.5" max		7.2.2.2.1.2	Handrails can protrude into stair 4.5" max
	1005.2	Door Swings may not reduce egress width by > 1/2			
	1009.2	80" min headroom		7.2.2.2.1.1(a)	6'-8" min. headroom
	1009.3	7" max. riser		7.2.2.2.1.1(a)	7" max. riser

	1009.3	11" min Tread depth	7.2.2.2.1.1(a)	11" min. tread
	1009.6	12' max. total rise between floors or landings	7.2.2.2.1.1(a)	12' max. height between landings
Ramps	1010.2	1:12 (8%) Max slope	7.2.5.2(a)	1:12 max. slope
	1010.6	60" long landings at top and bottom		
	1010.6	2% max slope of landings	7.2.5.2(a)	1:48 max. cross slope
	1010.8	>6" rise must have handrails on both sides of ramp		
Egress Corridors	1018.2	44" min. when Occ. > 50		
	1018.2	36" min. when Occ. <= 50		
	1018.2	24" min. at service corridors to mechanical equipment		
Accessibility		200 deep not apply as State of ME did not adapt it as part of MUREC		
Accessibility	Ch 11 of IBC 2009 does not apply as State of ME did not adopt it as part of MUBEC Must meet ADA 2010			
	Must meet AD			
Plumbing				
	Assembly	69 occupants		
		35 Males		
		1 male toilet, 1 male urinal, 1 lavatory		
		35 Females		
		2 female toilets, 1 lavatory		
	Brewery	10 occupants		
		5 Males		
		1 male toilet, 1 lavatory		
		5 Females		
		1 female toilet, 1 lavatory		