© 2007 - 2017 by ATC IP

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 11/27/17

Analysis Parameters

(1.2 + 0.2Sds) * DL + E 120 deg	Seismic 120 deg
(1.2 + 0.2Sds) * DL + E 180 deg	Seismic 180 deg
(1.2 + 0.2Sds) * DL + E 210 deg	Seismic 210 deg
(1.2 + 0.2Sds) * DL + E 240 deg	Seismic 240 deg
(1.2 + 0.2Sds) * DL + E 300 deg	Seismic 300 deg
(1.2 + 0.2Sds) * DL + E 330 deg	Seismic 330 deg
(0.9 - 0.2Sds) * DL + E Normal	Seismic (Reduced DL) Normal
(0.9 - 0.2Sds) * DL + E 60 deg	Seismic (Reduced DL) 60 deg
(0.9 - 0.2Sds) * DL + E 90 deg	Seismic (Reduced DL) 90 deg
(0.9 - 0.2Sds) * DL + E 120 deg	Seismic (Reduced DL) 120 deg
(0.9 - 0.2Sds) * DL + E 180 deg	Seismic (Reduced DL) 180 deg
(0.9 - 0.2Sds) * DL + E 210 deg	Seismic (Reduced DL) 210 deg
(0.9 - 0.2Sds) * DL + E 240 deg	Seismic (Reduced DL) 240 deg
(0.9 - 0.2Sds) * DL + E 300 deg	Seismic (Reduced DL) 300 deg
(0.9 - 0.2Sds) * DL + E 330 deg	Seismic (Reduced DL) 330 deg
1.0D + 1.0W Service Normal	Serviceability - 60 mph Wind Normal
1.0D + 1.0W Service 60 deg	Serviceability - 60 mph Wind 60 deg
1.0D + 1.0W Service 90 deg	Serviceability - 60 mph Wind 90 deg
1.0D + 1.0W Service 120 deg	Serviceability - 60 mph Wind 120 deg
1.0D + 1.0W Service 180 deg	Serviceability - 60 mph Wind 180 deg
1.0D + 1.0W Service 210 deg	Serviceability - 60 mph Wind 210 deg
1.0D + 1.0W Service 240 deg	Serviceability - 60 mph Wind 240 deg
1.0D + 1.0W Service 300 deg	Serviceability - 60 mph Wind 300 deg
1.0D + 1.0W Service 330 deg	Serviceability - 60 mph Wind 330 deg