

GENERAL FOUNDATION AND CONSTRUCTION NOTES

- CONCRETE TO HAVE A MINIMUM COMPRESSIVE STRENGTH OF 4500 PSI AT 28 DAYS.
- MAXIMUM ALLOWED WATER/CEMENT RATIO = 0.45
- REINFORCED CONCRETE CONSTRUCTION AND MATERIALS SHALL BE IN ACCORDANCE WITH ACI STANDARDS 318.
- MINIMUM CONCRETE COVER OVER REBAR IS 3". OR AS NOTED.
- BACKFILL SHALL BE SELECTED MATERIAL, WELL COMPACTED IN LAYERS NOT EXCEEDING 12".
- BACKFILL SHALL BE PLACED SO AS TO PREVENT ACCUMULATION OF WATER AROUND THE FOUNDATION.
- REINFORCING MATERIAL SHALL BE IN ACCORDANCE WITH ASTM SPECIFICATION A615.
- ALL REBAR TO BE GRADE 60 (UNLESS NOTED OTHERWISE).
- ALL REBAR (HORIZONTAL & VERTICAL) SHALL BE SECURELY WIRE TIED TO PREVENT DISPLACEMENT DURING POURING OF CONCRETE.
- GROUT ALL REBAR DOWELS INTO EXISTING FOUNDATION WITH HILTI HIT-RE 500 V3 EPOXY.
- EMBEDDED STRUCTURAL ANCHOR STEEL SUPPLIED BY AMERICAN TOWER.
- COLD CONSTRUCTION JOINTS TO BE THOROUGHLY CLEANED AND WETTED PRIOR TO SECOND POUR.

FOUNDATION AND ANCHOR TOLERANCES

ALL TOWERS

- CONCRETE DIMENSIONS: PLUS OR MINUS 1"
- DEPTH OF FOUNDATION: PLUS 3" OR MINUS 0"
- DRILLED FOUNDATIONS OUT OF PLUMB: 1.0 DEGREE
- REINFORCING STEEL PLACEMENT: PLUS OR MINUS 1/2" INCLUDING CONCRETE COVER
- PROJECTIONS OF EMBEDMENTS: PLUS OR MINUS 1/4"
- VERTICAL EMBEDMENTS OUT OF PLUMB: 1.0 DEGREE
- SEE CHART BELOW FOR THE MINIMUM OVERLAP LENGTHS OF REBARS IF REQUIRED.

SELF SUPPORT TOWERS

- FACE SPREAD DIMENSION CENTER TO CENTER OF ANCHOR BOLT CIRCLES: PLUS OR MINUS 1/8" PER 5'-0" OF FACE SPREAD
- MAXIMUM DISTANCE FROM CENTERLINE OF ANCHOR BOLT TO CENTERLINE OF FOUNDATION: 1/24TH OF PIER DIAMETER UP TO A MAXIMUM OF 2"
- MAXIMUM DIFFERENCE BETWEEN ANY TWO FOUNDATION ELEVATIONS: 2"
- ANCHOR BOLT SPACING: PLUS OR MINUS 1/8"
- ANCHOR BOLT CIRCLE ORIENTATION : PLUS OR MINUS 0.5 DEGREES
- ANCHOR BOLT CIRCLE DIAMETER: PLUS OR MINUS 1/8"

GUYED TOWERS

- GUY RADIUS: PLUS OR MINUS 3% OF TOWER HEIGHT
- ANCHOR ELEVATION: 3% OF TOWER HEIGHT ABOVE OR BELOW TOWER BASE. IF ELEVATIONS OF ANCHORS VARY BY MORE THAN 3%, ANCHOR RADIUS IS TO BE CHANGED TO KEEP THE ANCHOR LOCATED ON THE GUY FORCE RESULTANT. CALL AMERICAN TOWER FOR ASSISTANCE IF REQUIRED.
- ANCHOR ALIGNMENT: (PERPENDICULAR TO GUY RADIUS); PLUS OR MINUS 1 DEGREE.
- ANCHOR ROD SLOPE: PLUS OR MINUS 1 DEGREE
- ANCHOR ROD ALIGNMENT: TOWARDS TOWER CENTER POINT, PLUS OR MINUS 0.25 DEGREE
- GUY ANCHOR HEAD SIDES VERTICAL: PLUS OR MINUS 1 DEGREE.

STANDARD REBAR CHART					
BAR SIZE	BAR DIAMETER (in.)	WEIGHT (lb/ft)	INSIDE BEND RADIUS	MINIMUM OVERLAP LENGTHS	DRILLED HOLE DIA.
3	0.375	0.376	1 1/8"	1'-0"	--
4	0.500	0.668	1 1/2"	1'-6"	5/8"
5	0.625	1.043	1 7/8"	2'-0"	3/4"
6	0.750	1.502	2 1/4"	2'-0"	7/8"
7	0.875	2.044	2 5/8"	2'-4"	1 1/8"
8	1.000	2.670	3"	2'-8"	1 1/4"
9	1.128	3.400	4 1/2"	3'-0"	1 3/8"
10	1.270	4.303	5"	3'-6"	1 1/2"
11	1.410	5.313	5 1/2"	4'-0"	1 5/8"

QTY REQ'D	REBAR SIZE	LENGTH	TOTAL WEIGHT (LBS)	TYPE	BENDING DIAGRAM					
					A	B				
				ROUND TIE						
				SQUARE OR RECTANGULAR TIE	A	B				
				VERTICAL 90° BEND	A	B	C	D	INSIDE RADIUS	
22	#8	3' - 3 1/2"	193	L-SHAPE 90° BEND	2' - 9"	0' - 9"	0' - 5"	2' - 5"	3"	
				U-SHAPE 90° BEND	A	B	C	D	INSIDE RADIUS	
				U-SHAPE 60° BEND	A	B	C	D	INSIDE RADIUS	
				STRAIGHT	A					
					6	#8	10' - 0"	160		
TOTAL WEIGHT:				354						



THESE DRAWINGS AND/OR THE ACCOMPANYING SPECIFICATION AS INSTRUMENTS OF SERVICE ARE THE EXCLUSIVE PROPERTY OF AMERICAN TOWER. THEIR USE AND PUBLICATION SHALL BE RESTRICTED TO THE ORIGINAL SITE FOR WHICH THEY ARE PREPARED. ANY USE OR DISCLOSURE OTHER THAN THAT WHICH RELATES TO AMERICAN TOWER OR THE SPECIFIED CARRIER IS STRICTLY PROHIBITED. TITLE TO THESE DOCUMENTS SHALL REMAIN THE PROPERTY OF AMERICAN TOWER WHETHER OR NOT THE PROJECT IS EXECUTED. NEITHER THE ARCHITECT NOR THE ENGINEER WILL BE PROVIDING ON-SITE CONSTRUCTION REVIEW OF THIS PROJECT. CONTRACTORS MUST VERIFY ALL DIMENSIONS AND ADVISE AMERICAN TOWER OF ANY DISCREPANCIES. ANY PRIOR ISSUANCE OF THIS DRAWING IS SUPERSEDED BY THE LATEST VERSION ON FILE WITH AMERICAN TOWER.


REV.	DESCRIPTION	BY	DATE
△	FIRST ISSUE	BJK	09/06/17
△			
△			
△			

ATC SITE NUMBER:
10047

ATC SITE NAME:
PORTLAND ME

MAINE

SITE ADDRESS:
225 RIVERSIDE INDUSTRIAL PARKWAY
PORTLAND, ME 04103



Sep 11 2017 4:20 PM

DRAWN BY:	BJK
APPROVED BY:	BMS/AT
DATE DRAWN:	09/06/17
ATC JOB NO.:	OAA706994_C6_03

REBAR LIST

SHEET NUMBER:	REVISION:
A-RL	0