



1 SECOND FLOOR REFLECTED CEILING/SWITCHING PLAN
1/8" = 1'-0"

CEILING TYPES:

- C2 2x4x8 SUSPENDED ACoustICAL TILE
- C3 5/8" x 5/8" x 5/8" GYPSUM BOARD
- C4 METAL SOFFIT EXPOSED TO STRUCTURE ABOVE

CEILING NOTES:

1. SEE DETAILS FOR TYPICAL CEILING
2. ALL SINGLE USER TOILET ROOMS TO BE TYPE C1 @ 8'-0" AFF
3. COORDINATE MECH. RETURNS AND DESIGN/CONTRACTOR
4. COORDINATE ELEC. LAYOUT WITH ELECTRICAL DESIGN/CONTRACTOR
5. TO BE CONCEALED RECESSED HEADS, COLOR MATCHED TO FIELD.

RCP ROOM TAG

ROOM NAME: KITCHEN
ROOM NUMBER: A302 | Cl | 9'-6"
CEILING HEIGHT: 9'-6"

LIGHT FIXTURE SCHEDULE (FIXTURES BY LIGHT FIXTURE, UNLESS NOTED OTHERWISE)

Symbol	Fixture Description	Notes
L1	INCANDESCENT DOWNLIGHT	REFLECTOR: 2013CDMM FRAME: 2003FF LAMPING: PACK NO. 50M
L2	WALL WASHER	CATALOG NO.: 8242EMHCY2 VISOR: 8243VSM LAMPING: 10M CMH
L3	LOW VOLTAGE TRACK LIGHTING	TRACK: 6008RA END FEED: 6048BK TRANSFORMER: 8610EBK LITELACK: 8655BK LAMPING: MR16 BIF-8 50M
L4	2x2 CEILING FLOURESCENT	CATALOG NO.: DP524QL526UN/HH LAMPING: 2 6U T8
L4EM	2x2 CEILING FLOURESCENT/EMERGENCY	CATALOG NO.: DP524QL526UN/HHM LAMPING: 2 6U T8 FACTORY-INSTALLED EMERGENCY POWER BATTERY PACK W/ CHARGER AND INVERTER, BICO OR EQUAL.
L5	1x4 CEILING FLOURESCENT	CATALOG NO.: J54A232 LAMPING: 2 - T8
L6EM	1x4 WALL MOUNT FLOURESCENT	CATALOG NO.: LMB1232UN/HHM LAMPING: 2 - T8 FACTORY-INSTALLED EMERGENCY POWER BATTERY PACK W/ CHARGER AND INVERTER, BICO OR EQUAL.
L7	2x4 CEILING FLOURESCENT	CATALOG NO.: F1M4E4EB1 JACK CHAIN: 52 CHAIN LAMPING: 4 - 54W T5 HIGH OUTPUT
L7EM	2x4 CEILING FLOURESCENT/EMERGENCY	CATALOG NO.: F1M4E4EB1 JACK CHAIN: 52 CHAIN LAMPING: 4 - 54W T5 HIGH OUTPUT FACTORY-INSTALLED EMERGENCY POWER BATTERY PACK W/ CHARGER AND INVERTER, BICO OR EQUAL.
L8	HALO T5 SERIES DOWNLIGHTS	CATALOG NO.: T80-120/27V-T5M-W57 LAMPING: 1 T5 120V/27V/15W FACTORY-INSTALLED EMERGENCY POWER BATTERY PACK W/ CHARGER AND INVERTER, BICO OR EQUAL.
L4	EXTERIOR WALL PACKS	CATALOG NO.: 6XW175VALBK-L LAMPING: 175W - METAL HALIDE (CWA)
L10	PENDANT FLOURESCENT LIGHTING	CATALOG NO.: L5C2132SPAL POWER FEED/CABLE: L5C2C60AL LAMPING: 6 - T5
L11	EXIT SIGNAGE	CATALOG NO.: L11URM
L12	EMERGENCY LIGHTING UNIT	CATALOG NO.: E11212M LAMPING: 2 - 12W SEALED LEAD CALCIUM BATTERY

GRAPHIC LEGEND:

Symbol	Description
⬇	EMERGENCY EXIT SIGNAL
⬆	AUDIO/VISUAL FIRE ALARM (80° A.F.F.)
⬆	VISUAL STROBE FIRE ALARM (80° A.F.F.)
⬆	EMERGENCY PACK
⬆	24x24 FLOURESCENT
⬆	24x48 FLOURESCENT
⬆	12x46 FLOURESCENT
⬆	RECESSED CAN
⬆	METAL HALIDE DOWNLIGHT
⬆	WALL WASHER
⬆	TRACK LIGHTING
⬆	EXTERIOR WALL PACK
⬆	MECHANICAL SUPPLY/RETURN
⬆	ACCESS PANEL
⬆	OVERHEAD DOOR OPERATOR (INVERTER CONTROL - 4 PINS DOWN)
⬆	SINGLE POLE SWITCH
⬆	3-WAY SWITCH
⬆	DIMMER SWITCH
⬆	DUPLEX OUTLET
⬆	6FI OUTLET (Ground Fault)
⬆	220 OUTLET
⬆	CATV (Cable TV)
⬆	TELEPHONE/DATA
⬆	SPECIAL CONNECTION
⬆	SWITCH/OUTLET
⬆	FLOOR OUTLET
⬆	FULL-DOWN DUPLEX OUTLET

NOTE:
SOME OUTLETS MAY BE INDICATED ON LIGHTING PLANS IN CASES WHERE OUTLETS SHARE THE SAME FUNCTION. THESE OUTLETS ARE INDICATED ON THE POWER PLANS.

SECURITY NOTES:
PROVIDE THREE-ZONE CARD-KEY SECURITY SYSTEM AS DIRECTED BY OWNER PER MANUFACTURER'S SPECIFICATIONS.
ZONES: RESERVATE SECURITY CODE FOR EACH ZONE; OFFICE AREA (ENTRY DOORS ONLY); MANHOUSE AREA (PASSAGE DOORS ONLY); YARD AREA (PERIMETER FENCE (TWO POINTS OF ACCESS) SEE SITE PLAN);
ZONES: RESERVATE SECURITY CODE FOR EACH ZONE; OFFICE AREA (ENTRY DOORS ONLY); MANHOUSE AREA (PASSAGE DOORS ONLY); YARD AREA (PERIMETER FENCE (TWO POINTS OF ACCESS) SEE SITE PLAN).

SECURITY NOTES:
PROVIDE THREE-ZONE CARD-KEY SECURITY SYSTEM AS DIRECTED BY OWNER PER MANUFACTURER'S SPECIFICATIONS.
ZONES: RESERVATE SECURITY CODE FOR EACH ZONE; OFFICE AREA (ENTRY DOORS ONLY); MANHOUSE AREA (PASSAGE DOORS ONLY); YARD AREA (PERIMETER FENCE (TWO POINTS OF ACCESS) SEE SITE PLAN).

