City of Portland, Maine - Building	Building or Use Permit Application	389 Congress St	389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8	4-8703, FAX: 874-8716
	Owner. Samaki Watt		Frome: 727-8554	Permit No: 7 L L C
43		Phone:	BusinessName:	PERMIT ISSUED
Richardson	Address: 14 Sherman St.	Phone:		Permit Issued:
0	Proposed Use:	COST OF WORK:	PERMIT FEE:	1661 <b>2 2</b> 130
	same a/ pepairs	FIRE DEPT.   Approved		CITY OF PORTLAND
		Sionature:	Constitue:	Zone: CBL: 335-C-015
		PEDESTRIAN ACT	TIES DISTRICT (P.A.D.)	Zoning Approval:
Sepairs for fire damage.		Action: Approv Approv Denied	Approved Approved with Conditions:	Special Zone or Reviews:  ☐ Shoreland ☐ Wetland
		Signature:	Date:	☐ Flood Zone ☐ Subdivision
	Date Applied For: Actaber	1601	,	□ Site Plan maj □minor □mm □
This permit application does not preclude the Applicant(s Building permits do not include plumbing, septic or elec Building permits are void if work is not started within six tion may invalidate a building permit and stop all work.	This permit application does not preclude the Applicant(s) from meeting applicable State and Federal rules.  Building permits do not include plumbing, septic or electrical work.  Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work	and Federal rules.	5AVOY 773-1573	Zoning Appeal  Variance  Miscellaneous  Conditional Use  Interpretation  Approved
10 15049 344735	3304 to 25049 address=2 954529 St.	8	FRIMIT ISSIIT	Historic Preservation  Onto in District or Landmark  Obes Not Require Review  Requires Review
			CONFINED TO	Action:
ner of record of the rethis application as 1 the application is is any reasonable hou	I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application is issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit	is authorized by the ow m to all applicable lav prized representative s applicable to such perr	ner of record and that I have been so of this jurisdiction. In addition, hall have the authority to enter all nit	☐ Appoved ☐ Approved with Conditions ☐ Denied ☐ Date:
Sammeri Watt	ADDRESS:	DATE:	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE	, TITLE		PHONE:	CEO DISTRICT
White-Permit Desk	mit Desk Green-Assessor's Canary-D.P.W.	D.P.W. Pink-Public File	File Ivory Card-Inspector	M. Carroll

## COMMENTS

		- Orep Wm Calling - Oleo Son

## BUILDING PERMIT REPORT

DATE: 23 OCT. 97 ADDRESS: 2 D	edham ST
REASON FOR PERMIT: Repair after Fire	of Contober ,
BUILDING OWNER: Sanaki Wall	
CONTRACTOR: Kathy Bichardson	ng nakatawa maka maka panganan na kata da panganan To kabat ng milingga panganan na kata da panganan
PERMIT APPLICANT: Samaki Wall APPROVAL: */	X26 Maria Service de Maria de Demos
USE GROUP BOCA 1996 CONS	STRUCTION TYPE 5B

## CONDITION(S) OF APPROVAL

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

 Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)

Precaution must be taken to protect concrete from freezing.

It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is
done to verify that the proper setbacks are maintained.

Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4 Section 407.0 of the BOCA/1996)

All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA

National Mechanical Code/1993).

- Sound transmission control in residential building shall be done in accordance with Chapter 12 section 1214.0 of the city's building code.
- 8. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of clevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38".)
- 9. Headroom in habitable space is a minimum of 7'6".
- 10. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use group minimum 11" tread. 7" maximum rise.
- 11. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6' 8")
- 12. Every sleeping room below the fourth story in buildings of use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of
- special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. ft.
- 13. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
- 14. All vertical openings shall be enclosed with construction having a fire rating of at lest one (1)hour, including fire doors with self closer's.
- 15. The boiler shall be protected by enclosing with (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
- All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 19, 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
  - In the immediate vicinity of bedrooms
  - In all bedrooms

In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and 1-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an 17. approved type. The Fire Alarm System shall be maintained to NFPA #72 Standard. 18. The Sprinkler System shall maintained to NFPA #13 Standard. 19. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 20. 1023. & 1024. Of the City's building code. (The BOCA National Building Code/1996) No construction or demolition work shall begin until you have obtained permits for dumpsters or containers. A work 21. Stop Order shall be issued if this requirement is not met. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to 22. excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a 23. certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's office. 24. Ventilation shall meet the requirements of Chapter 12 Sections 1210, of the City's Building Code. 25. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. 26. All requirements must be met before a final Certificate of Occupancy is issued, 27. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code. (The BOCA 28. National Building Code/1996). Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National 29. Mechanical Code/1993). 30. 31. 32. 33. 34. Samuel Hollises, Code Enforcement cc: Lt. McDougall, PFD Marge Schmuckal

nwo Cobo code # -ESTIMATE NO.\_ GENERAL ESTIMATE BUILDING Temple ESTIMATOR Kathy Richardson LOCATION Z Dedham St. CONTACT P-8108 Pirun or Julie Kenneth TOTAL ESTIMATED QUANTITY TOTAL ESTIMATED DIMENSIONS EXTENSIONS EXTENSIONS DESCRIPTION OF WORK NO. 25000 15 8500 2-8×6-8 - Replace ext. door w/ frame 10000 5 5500 28 x 3 - 6 - Replace window 4500 2500 5 Repair Main Roof 15000 15 15000 2x10 treads Repair exist porch 2X8 FISET 25000 15 30000 2 X 6 P.T Build New roof 1/2" bly P.T over porch 6 asp shingles 15000 15 20000 17" shingles up/13 exposure Install New siding A=16'X8' to gable end 4000 15 450C Replace insulation A= 28 X8 7500 15 2500C A = 28 x 8' - Replace sheetrock and mud/tape 9000 15 30000 Int A = 1100 St = paint int/Ext 4000 15 15000 Ext A = 16' x 8' 5000 15 1 5000 A= 1100 5+2 clean interior 15000 30 3000 Electrical work 15 2000 materials Demolition work 2230 137000