

## shown COMBINATION LIMIT & RELAY CONTROL TEMP. PRESSURE GAUGE COMBINATION LIMIT & RELAY CONTROL ASME RELIEF VALVE 1-1/2" SUPPLY 7" FLUE VENT DIAMETER BURNER 21-1/2 CIRCULATOR 15-1/2" 12-1/4" A 1-1/2" RETURN RIGHT SIDE VIEW FRONT VIEW

## Freeport CT

## Chimney-vented residential model of the high efficiency three-pass Scotch Marine design

- · Beckett or Riello oil burners
- Most models are Energy Star qualified (up to 87.6% A.F.U.E.)
- Full lifetime warranty on cast iron heat exchanger
- Swing-open burner door with safety switch
- Eight sizes: 92,000 to 286,000 outputs





Model Number	Burner Capacity GPH	IBR Net Rating Water (BTU/HR)	A (in.)	B* (in.)	Flue Collar Dia. (in.)	Annual Efficiency AFUE% w/Burner	
						Beckett	Riello
CT-3	.75	80.000	19-1/4	34	7	86.1*	87.6*
CT-35	1.00	104.000	19-1/4	34	7	84.7	84.7
CT-4	1.00	105,000	24-1/4	39	7	86.1*	86.1*
CT-45	1.35	139.000	24-1/4	39	7	84.0	84.0
CT-5	1.35	141,000	29-1/4	44	7	86.1*	86.1*
CT-6	1.65	176,000	34-1/4	49	7	86.1*	86.1*
CT-7	2.00	211,000	39-1/4	54	7	86.1*	
CT-8	2.50	249,000	44-1/4	59	7	▲85.3	-

CT-35 and CT-45 are up-fired versions of CT-3 and CT-4

▲ IBR Combustion Efficiency

★ Dimension B is approximate due to varying burner lengths