

FASTENING SCHEDULE (SEE TABLE 2304.9.1 ME.S. RESIDENTIAL CONSTRUCTION CODE FASTNERS SPACED 4 INCHES OC AT EDGES, 8 INCHES AT INTERMEDIATE
WALL SHEATHING AND 3 INCHES OC AT EDGES, 6 INCHES AT INTERMEDIATE SUPPORTS FOR ROOF SHEATHING.
FASTNERS SPACED 4 INCHES OC AT EDGES, 8 INCHES AT INTERMEDIATE SUPPORTS FOR SUBFLOOR AND
FOR ROOF SHEATHING APPLICATIONS, FASTNERS SPACED 4 INCHES ON CENTER AT EDGES, 8 INCHES AT INTERMEDIATE SUPPORTS.
STAPLES SHALL HAVE A MINIMUM CROWN WIDTH OF 7/16 INCH
FOR ROOF SHEATHING APPLICATIONS, 8d NAILS ARE MINIMUM REQUIRED FOR WOOD STRUCTURAL PANELS
POLEL SUPPORTS AT 24 INCHES. CASING OR FINISH NAILS SPACED 6 INCHES ON PANEL EDGES, 12 INCHES AT INTERMEDIATE SUPPORTS.
CASING OR FINISH NAILS SPACED 6 INCHES ON PANEL EDGES, 12 INCHES AT INTERMIDIATE SUPPORTS. SEE NOTE: P
SEE NOTE: D, 6d, SEE NOTE: C
SEE NOTE: 0
SEE NOTE: N SEE NOTE: C SEE NOHE: C SEE NOTE: F SEE NOTE: F NOTES 16" OC 24" OC 16 INCHES (20 INCHES IF STRENGTH AXIS IN THE LONG DIRECTION OF THE PANEL, UNLESS OTHERWISE MARKED).
1/2 INCH SHEATHING AND 1-1/2 INCH LENGTH FOR 25/32 INCH SHEATHING. PANEL SUPPORTS AT
CORROSION-RESISTANT STAPLES WITH NOMINAL 7/16 INCH CROWN AND 1-1/8 INCH LENGTH FOR STAGGERED ON OPPOSITE SIDES 3"
FACE NAIL AT TOP & BOTTOM AT EACH SPLICE FACE NAIL AT ENDS FACE NAIL BCE NOIL 18NAIL ACE NAIL TOENAIL FACE NAIL BCE NOIL FACE NOIL 16" OC 24" OC OE NAIL 4 - 3" 14 GAGE STAPLE 4 - 3"x0.131" NAIL 3 - 10d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 2 - 20d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 3 - 8d COMMON 3" 14 GAGE STAPLE 3"x0.131" NAIL 16d COMMON 2 - 3" 14 GAGE STAPLE 2 - 3"x0.131" NAIL 2 - 8d COMMON 14 GAGE STAPLE @ 24" OC 3"x0.131" NAIL @ 24" OC 20d COMMON 32" OC 4 - 3" 14 GAGE STAPLE 4 - 3"x0.131" NAIL 3 - 10d COMMON 3-3"14 GAGE STAPLE 3-3"x0.131" NAIL 2-16d COMMON 3-3"14 GAGE STAPLE 3-3"x0.131" NAIL 2-10d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 2 - 16d COMMON 5 - 3" 14 GAGE STAPLE 5 - 3"x0.131" NAIL 3 - 16d COMMON - 3" 14 GAGE STAPLE 4 - 3"x0.131" NAIL 3 - 16d COMMON 2" 16 GAGE 2-3/8"x0.113" NAIL 8d OR 6d 1-3/4" 16 GAGE 2-3/8"x0.113" NAIL m b9 86 SEE SECT. 2308.10.1, TABLE 2308.10.1) RAFTER TO PLATE SUBFLOOR-UNDERLAYMENT SINGLE FLOOR (COMBINATION 3/4" OR LESS & PARTICLE BOARD WOOD STRUCTURAL PANELS 19/32" - 3/4" WOOD STRUCTURAL PANELS
1/2' OR LESS PANEL SIDING (TO FRAMING) PANEL SIDING (TO FRAMING)
1/2" OR LESS **BUILT-UP GIRDER & BEAMS** BUILT-UP GIRDER & BEAMS BUILT-UP OOGNER STUDS EACH STUD & PLATE 1" DIAGONAL BRACE TO OOL**5** MIE TO RAFTER JACK RAFTERS TO HIP DCK &AFTEAS TO HIP JOIST TO BAND JOIST & PARTICLE BOARD 2-BY RIDGE BEAM ROOF RAFTER TO 2-BY RIDGE BEAM ROOF RAFTER TO LEAGE STRIP TO FRAMING) NOTE: LET, LR. -xr≥z 0 T COMMON NAIL - REF TO TOSLE \$ 08.10.4. NA L COMMON OR DEFORMED SHANK
WALLS, REFER TO SECTION 2305. NAILS FOR WALL SHEATHING ARE PERMITTED TO BE COMMON, BOX OR CASING
SPANS ARE 48 INCHES OR MORE. FOR NAILING OF WOOD STRUCTURAL PANEL AND PARTICLEBOARD DIAGRAMS AND SHEAR
NAILS SPACED AT 6 INCHES ON CENTRAL BOX NAILS ARE PERMITTED TO SECREPT AT SUPPORTS WHERE «EΩ TO TO≱LΩ ≥ 08.10.4.1 FOR 1/2 INCH SHEATHING & 1-3/4 INCH LENGTH FOR 25/32 INCH SHEATHING CORROSION-RESISTANT ROOFING NAILS w/ 7/16 INCH DIA. HEAD & 1-1/2 INCH LENGTH FASTNERS SPACED 3 INCHES OC AT EXTERIOR EDGES AND 6 INCHES OC AT INTERMEDIATE SUPPORTS CORROSION-RESISTANT SIDING OR CASING NAIL DEFORMED SHANK COMMON BRACED WALL PANEL 16" OC ALONG EDGE TOENAIL EACH END TYPICAL FACE NAIL TYPICAL FACE NAIL COMMON BOX NAILS ARE PERMITTED TO BE USED EXCEPT WHERE OTHERWISE INDICATED LAP S>LICE FAOE NE FACE NAIL END NAIL END NAIL T4 NAIL BCE Ne TOENAIL TOE NAIL ACE NAIL TOE NAIL TOE NAIL OENAIL 12 - 3" 14 GAGE STAPLE TYP. FACE NAIL 12 - 3"x0.131" NAIL 8 - 16d COMMON 3 - 3" 14 GAGE STAPLE
3 - 3"X0.131" NAIL
2 - 16d COMMON
3 - 3" 14 GAGE STAPLE
4 - 3"X0.131" NAIL
4 - 8d COMMON
3 - "14 GAGE STAPLE
3 - "X0.131" NAIL
2 - 16d COMMON
3" 14 GAUGE STAPLE @ 12" OC
16d @ 16" OC
16d @ 16" OC
3" 14 GAUGE STAPLE @ 12" OC
3"X0.131" NAIL @ 8" OC
16d @ 16" OC
16d @ 16" OC
3" 14 GAUGE STAPLE @ 12" OC
3"X0.131" NAIL @ 8" OC
16d @ 16" OC
3" 14 GAUGE STAPLE @ 12" OC
3" 14 GAUGE STAPLE @ 12" OC
3" 15 GAUGE STAPLE @ 12" OC 3" 14 GAGE STAPLE @ 12" OC 3"x0.131" NAIL @ 12" OC 16d @ 16" OC 3" 14 GAGE STAPLE @ 8" OC 3"x0.131" NAIL @ 8" OC 16d @ 24" OC 16d COMMON
3 - 3" 14 GAGE STAPLE
3 - 3"x0.131" NAIL
2 - 16d COMMON
3" 14 GAGE STAPLE @ 6" OC
3"x0.131" NAIL @ 6" OC
8d @ 6" OC 4 - 3" 14 GAGE STAPLE 4 - 3"x0.131" NAIL 3 - 16d COMMON MINIMUM 4 - 3" 14 GAGE STAPLE 4 - 3"x0.131" NAIL 3 - 8d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 3 - 8d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 3 - 8d COMMON 5 - 3" 14 GAGE STAPLE 5 - 3"x0.131" NAIL 3 - 8d COMMON 3 - 3" 14 GAGE STAPLE 3 - 3"x0.131" NAIL 3 - 16d COMMON 4 - 8d COMMON N N FOR COMPLETE SEE SECT. 2308.10.4.1, TABLE 2308.10.4.1) CEILING JOISTS TO PARALLEL RAFTERS SEE SECT. 2308.10.4.1, TABLE 2308.10.4.1)
CEILING JOISTS, LAPS OVER PARTITIONS AT BRACED WALL PANEL SOLE PLATE TO JOIST OR BLOCKING CONTINUOUS HEADER HO STUD OR RAFTERS TO TOP PLATE BLOCKING BETWEEN JOISTS CONTINUOUS HEADE, 2 PCS JOIST TO SILL OR GIRDER CEILING JOISTS TO PLATE RIM JOIST TO TOP PLATE OR BLOCKING SOLE PLATE TO JOIST STUD TO SOLE PLATE DOUBLE TOP PLATES AND INTERSECTIONS TOP PLATES, LAPS DOUBLE TOP PLATES **BRIDGING TO JOIST** TOPPLATE TO ST DOUBLE STUDS CONNECTION NOTE: LETTER € DETAILS) œ опшо т



