City of Portland, Maine - Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 124 Saugus Street	Owner: Frank Neuts		Phone: 878-58	359	Permit No:		
Owner Address: SAA	Lessee/Buyer's Name:	Phone:	Business	usinessName: 000 44			
Contractor Name: *** Joseph Kinney	Address: *** 75 Arcadia Street 04	Phone 776	: 5-2782		Permit Issued:		
Past Use:	Proposed Use:	COST OF WORK \$8,000		PERMIT FEE: \$ 72.00	M 2 1 12		
single family	Same	FIRE DEPT. Signature:	Denied	INSPECTION: Use Group: R. 3 Type: 5 B BOC A '97 Signature: A Bowke 8-21.	Zone: 7 CBL:		
Proposed Project Description:		PEDESTRIAN A	CTIVITIES	S DISTRICT (P.A.D.)	Zoning Approval:		
8x10 Addition from drive	<i>n</i> ay	1	Approved Approved wi Denied	ith Conditions:	Special Zone or Reviews: ☐ Shoreland ☐ Wetland ☐ Flood Zone		
		Signature:		Date:	□ Subdivision ✓ ✓ ✓		
Permit Taken By: K	Date Applied For: Aug	23 2000 K			☐ Site Plan maj ☐ mnor ☐ mm ☐ 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2		
2. Building permits do not include plumbin	tarted within six (6) months of the date of is			MIT ISSUED EQUIREMENTS	□ Variance □ Miscellaneous □ Conditional Use □ Interpretation □ Approved □ Denied Historic Preservation □ Not in District or Landmark □ Does Not Require Review □ Requires Review Action:		
I hereby certify that I am the owner of record authorized by the owner to make this application if a permit for work described in the application areas covered by such permit at any reasonal SIGNATURE OF APPLICANT	tion as his authorized agent and I agree to on is issued, I certify that the code official?	conform to all applicable s authorized representation	e laws of this ve shall have permit	s jurisdiction. In addition,	☐ Appoved ☐ Approved with Conditions ☐ Denied		
					76 F/C		
RESPONSIBLE PERSON IN CHARGE OF V	VORK, TITLE]	PHONE:	CEO DISTRICT		
Whit	e-Permit Desk Green-Assessor's Ca	nary_D PW Pink_Pu	hlic File Iv	ory Card-Inspector			

COMMENTS

01 291	Markey of I Alace to the way of and and and and
1-21,	roseasures fee vaca la rear grop, ceme (a 26+ 0,1%, cartragon to
	Your, Fondation Walls, OK's Poloroide to Very draw gealer
	Measured felback to rear grop, line @ 26+ O.K. Contractor to Pow, Fondstron Walls, OK'D Poloroide to Verify drain ; pealer Prior to back full. JKW
	THE CONTRACTOR OF THE CONTRACT
10-12	- Cosmed grang & found to be exceptable. Heps Not Done
	- Chacked fraing & found to be exceptable. Heps Not Done yet. SRW.
	Jan 1
	Inspection Record
	Type Date
	Foundation:
	Framing:
	Plumbing:
	Final:
	LIHE

BUILDING PERMIT REPORT

DULDING LEAVIT REPORT
DATE: 8-24-00 ADDRESS: 124 Saugus St. CBL: 336-L-024
REASON FOR PERMIT: 8×10' Addition
BUILDING OWNER: Frank Neuts
PERMIT APPLICANT: Joseph J. Kinney ICONTRACTOR JOSEPH J. KINNEY
USE GROUP: R-3 CONSTRUCTION TYPE: 5B CONSTRUCTION COST: 8,000 PERMIT FEES: 72.00
The City's Adopted Building Code (The BOCA National Building code/1999 with City Amendments) The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)
CONDITION(S) OF APPROVAL
0.4

This p	ermit is being issued with the understanding that the following conditions Shall be met: $\frac{4}{32}$	41	₩ 2,	# 4	*11
13,	x 27, x 29, x 32				

This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

42. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."

- 3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2
- 44. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17
- 5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.
- 6. Precaution must be taken to protect concrete from freezing. Section 1908.0
- 7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)
- 9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211
- 10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.
- Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", In occupancies in Use Group A,B.H-4, I-1, I-2, M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. (Handrails shall be a minimum of 34" but not more than 38". Use Group R-3 shall not be less than 30", but not more than 38"). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 1/4" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7)
 - 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
- † 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise.</u> All other Use Group minimum 11" tread, 7" maximum rise. (Section 1014.0)
- 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
- 15. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
- 16. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
- 17. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closer's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
- 18. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

- 19. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 - In the immediate vicinity of bedrooms
 - In all bedrooms
 - In each story within a dwelling unit, including basements
- 20. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0)
- 21. The Fire Alarm System shall maintained to NFPA #72 Standard.
- 22. The Sprinkler System shall installed and maintained to NFPA #13 Standard.
- 23. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999)
- 24. Section 25 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
- 25. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services.
- 26. Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
- 27. All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done.
 - 28. All requirements must be met before a final Certificate of Occupancy is issued.
- 29. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1999).
 - Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)
 - 31. Please read and implement the attached Land Use Zoning report requirements.
- \$32. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code.
 - 33. Bridging shall comply with Section 2305.16.
 - 34. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2405.0)
 35. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).
 - 35. All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999).
 - P. Samuel Hoffses, Building Inspector

Cc: Lt. McDougall, PFD

Marge Schmuckal, Zoning Administrator

PSH 11/25/99

**This Permit is herewith issued,on the basis of plans submitted and conditions placed the plans, any deviations shall require a separate approval.

***THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD.

**** Certificate of Occupancy Fees: \$50.00 each

***** All PLANS THAT REQUIRE A PROFESSIONAL DESIGN'S SEAL,(AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000 OR REQUIVALENT.

bult 1989

FIRER GLASS BATTS W/K.B. * GuSSET -2x6 PT ANCORE PLATE 2x 6 stubs 16" 0.0 5×10 16" 0.8 DEC PLATE 三百日子 4) 4 frost wall ASPINALT - ADITION-P.T. 2x4 HANDS. ZX8 PT ____ Kristink

THIS IS NOT A PERMIT/CONSTRUCTION CANNOT COMMENCE UNTIL THE PERMIT IS ISSUED

Building or Use Permit Pre-Application Additions/Alterations/Accessory Structures To Detached Single Family Dwelling

In the interest of processing your application in the quickest possible manner, please complete the Information below for a Building or Use Permit.

NOTE**If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

5+.

Saugus

Telephone#: 878-5859 Cost Of Work: Fee \$ 8000 - \$70-6
-71
2000
Drive way
Recd By: 04103 () Me. 776-2782
Code as amended by Section 6-Art II. Iaine Plumbing Code. as amended by Section 6-Art III. In the 1993 BOCA Mechanical Code. Agreement vailable
naluda.
nclude: ucture and the distance from the actual s and roof overhangs, as well as, sheds, DEPT. OF BUILDING ME CITY OF PORTLAND, ME
AUG 2 3 2000
nts of construction: ory structures)

equipment, HVAC equipment (air handling) or other types of work that may require special review must be included.

Foundation plans with required drainage and dampproofing

I hereby certify that I am the Owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his/her authorized agent. I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in this application is issued, I certify that the Code Official's authorized representative shall have the authority to enter all areas covered by this permit at any reasonable hour to enforce the provisions of the codes applicable to this permit.

Electrical and plumbing layout. Mechanical drawings for any specialized equipment such as furnaces, chimneys, gas

Signature of applicant: Joseph & hom	Date: 8/23/00

Location/Address of Construction:



