City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

				<u></u>
Location of Construction:	Owner: Edward T Ger:	achty	Phone:	Permit No: 96039
Owner Address: 54 Ninth St- Ptld ME 04103	Leasee/Buyer's Name:	Phone:	BusinessName:	PERMIT ISSUED
Contractor Name: Reith Geary Past Use:	Address: 53 Ninth St- Ptld ME Proposed Use:	COST OF WORK	255-6455 K: PERMIT FEE:	Permit Issued: MAY 7 1996
1-fam dwlg	l-fam w steps & deck		Denied Use Group: Type:	CITY OF PORTLAND
Proposed Project Description:		Signature: PEDESTRIAN A	Signature: CTIVITIES DISTRICT (P.U.D.)	Zoning Approval:
construct steps & non-att	Special Zone or Reviews: Shoreland Wetland Flood Zone Subdivision			
Permit Taken By: L Chase	Date Applied For: 5/	/14/96		Site Plan maj minor mm m
 This permit application doesn't preclude the A Building permits do not include plumbing, sep Building permits are void if work is not started tion may invalidate a building permit and stop 	 Variance Miscellaneous Conditional Use Interpretation Approved Denied Historic Preservation Not in District or Landmark			
		CARGE LESS LED	CARENER STS	 Does Not Require Review Requires Review Action:
	CERTIFICATION	Nr.		Appoved
I hereby certify that I am the owner of record of the authorized by the owner to make this application as if a permit for work described in the application is areas covered by such permit at any reasonable how	Denied			
huif A for		5 14 56		D. C.M.
SIGNATURE OF APPLICANT	ADDRESS:	DATE:	PHONE:	
RESPONSIBLE PERSON IN CHARGE OF WORK	, TITLE		PHONE:	
White-Per	rmit Desk Green–Assessor's Car	hary-D.P.W. Pink-Put	blic File Ivory Card-Inspector	D. Jadar

.

Type Foundation: Framing: Plumbing: Final: Other:	Inspection Record		3/4/48 orc drui an	523-96-26" & Sono tubes under 484 Plater pourel / no rettration Set backs will be Ott 7-16-96-Guard rail rant in progress / not per order 155 than 30" alone grade
Date				

BUILDING PERMIT REPORT				
DATE: $\frac{16}{MA} \frac{196}{26}$ ADDRESS: $\frac{5}{2}$	4 NINTH SY			
DATE: 16/MB-196 ADDRESS: 5 REASON FOR FERMIT: To Construct to	4'X16 deck with STAIRS			
BUILDING OWNER: <u>Genaghty</u>				
CONTRACTOR: Neith Geary	APPROVED: */ *//×/3*/6			
PERMIT APPLICANT:	DENSED:			

CONDITION OF APPROVAL OR DENIAL

- A1. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A 24 hour notice is required prior to inspection)
 - 2. Precaution must be taken to protect concrete from freezing.
 - 3. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
 - 4. All vertical openings shall be enclosed with construction having a fire rating of at least one(1) hour, including fire doors with selfclosers.
 - Each apartment shall have access to two(2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 - 6. The boiler shall be protected by enclosing with one(1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment. Sprinkler piping serving not more than six sprinklers may be connected to a domestic water supply having a capacity sufficient to provide 0.15 gallons per minute, per square foot of floor throughout the entire area. An INDICATING shut-off valve shall be installed in an accessible location between the sprinkler and, the connection to the domestic water supply. Minimum pipe size shall . be 3/4 inch copper or 1 inch steel. Maximum coverage area of a residential sprinkler is 144 sq. feet per sprinkler.
 - 7. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as <u>means of ecress or rescue</u>, they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508 mm), and a minimum net clear opening of 5.7 sq. feet.
 - 8. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
 - 9. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, section 19, 919.3.2(BOCA National Brilding Code/1993), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):

- 1. In the immediate vicinity of bedrooms
- 2. In all bedrooms

3. In each story within a dwelling unit, including basements In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted.

- 10. Private garages located <u>beneath habitable rooms</u> in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1993)
- (-11. Guardrail & Bandrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A, B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
 - All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10, section & subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1993)
 - 13. Stair construction in Use Group R-3 & R-4 is a minimum of 9" tread and "-----8-1/4" maximum rise. All other Use Group-minimum 11" tread, -7"-maximum -rise.
 - 14. Beadroom in habitable space is a minimum of 7'6".
 - 15. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 16. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
 - 17. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 - 18. The builder of a facility to which Section 4594-C of the Maine State Buman Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
 - 19. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's Office.

Samel Horses, Chief of Inspection Services

/el 3/16/95

5-14-96 FROM: KEITH A. GEARY RE CONSTRUCTION OF DECK-53 Ninth ST. AND ADDITION OF PLATFIEM AND PORTLAND ME. 04103 STAIRS to EXISTING DECK AT (207) 878-3347 54 NINTH ST. FOR EDWARD GERAGHTY. PLATFORM & STAIRS/HANDRAKS D BUILD AND ATTACH 4 FL. X 4 FL PLATFORM TO EXISTING DECK. USING 2X8 P.T. FRAMINS MATERIAL 3 LANDING TO BE SUPPORTED BY 4"X4" PT. POSTS - 4FE IN GROUND w/ 6" SONA TUBES 3 ATTACH STAIRS CONSISTING OF B STRINGERS USING 2X12 FT. LUMBER - Add STAIR TREADS USING SXID P.T. LUMBER 4) Instruct Decking USING 5/4 P.T. Lumber 5) Install HANDRAIL USING 54 A. LUMBER AND 2×4 At. LUMBER W/ 6" SPACED BALLISTERS TO MATCH EXISTING DECK AND HANDRALL 14X16 FREEFLOATING DECK TLEVEL ARER & Construct 14'X16' FREE Flowming PLATFORM USING 2X8 P.T. FRAMING MATERIAL 3) INSTALL 4"X4" AT POSTS EVERY 6' AT PERMITER OF DECK SUPPORTED ON 4"X 12" CEMENT BLOCKS 4) JASTAL S/4 P.T. DECKING AND RAKING to OWNED SPECS. DECK WILL NOT BE ATTACHET TO HOUSE (WORK TO BE DONE FOR THE SUM OF \$ 800.00 LABOR EMATERIAL

