17.	All vertical openings shart be enclosed with construction having a fire rating of at least one (1) nour, including fire doors with self
	closer's. (Over 3 stories in height requirements for fire rating is two (2) hours.) (Section 710.0)
18.	The boiler shall be protected by enclosing with (1)hour fire rated construction including fire doors and ceiling, or by providing automatic
	extinguishment. (Table 302,1.1)
19.	All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of
	the City's Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 &19. (Smoke
	detectors shall be installed and maintained at the following locations):
	In the immediate vicinity of bedrooms
	In all bedrooms
	In each story within a dwelling unit, including basements
	In each story within a dweiling unit, including basements
	In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall
(22)	receive power from a battery when the AC primary power source is interrupted. (Interconnection is required) Section 920,3.2.
(20.)	A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved
	type. (Section 921.0)
21.	The Fire Alarm System shall maintained to NFPA #72 Standard.
22.	The Sprinkler System shall maintained to NFPA #13 Standard.
23.	All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0
	of the City's Building Code. (The BOCA National Building Code/1996)
24.	Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open
	any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
25:	The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification
20.	from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of
	Inspection Services.
26	
26.	Ventilation shall meet the requirements of Chapter 12 Sections 1210.0 of the City's Building Code. (Crawl spaces & attics).
/2 7.	All electrical, plumbing and HVAC permits must be obtained by a Master Licensed holders of their trade. No closing in of walls until
	all electrical (min.72 hours notice) and plumbing inspections have been done.
28.	All requirements must be met before a final Certificate of Occupancy is issued,
/ 2 9.	All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (the BOCA National Building
. 1	Code/1996).
30.	Ventilation of spaces within a building shall be done in accordance with the City's Mechanical Code (The BOCA National Mechanical
	Code/1993). (Chapter M-16)
31.	Please read and implement the attached Land Use Zoning report requirements.
∠X, 32.	Boring, cutting and notching shall be done in accordance with Sections 2305.4.4, 2305.5.1 and 2305.5.3 of the City's Building Code.
₹ 33	Glass and glazing shall meet the requirements of Chapter 24 of the building code.
₹ 33. 34.	All signage, shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code
34.	
25	1996).
35.	
0.5	
36.	
37.	
38.	
[]-]	and the state of t
E Salla	el Holfses, Dividing Inspector
	I + Mationacal Deriv
cc:	Lt. McDougall, PFD
	Marge Schmuckal, Zoning Administrator
PSIf 7/24/99	Asin f
	• • • • • • • • • • • • • • • • • • •
4.4.0	

**On the basis of plans submitted and conditions placed on these plans any deviations shall require a separate approval.

COMMENTS

		9/19/98/recomplexion Doll hack 5 good 11/12/99 Site evaluation
Foundation: Type Foundation: Framing: Plumbing: Final: Other:		slab soty the will bound travely 14' Reac 14' Side from mon uneut holding Mis up 38
Inspection Record Date		ment ph