Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 04/26/18

SILENT KNIGHT
by Honeywell

SK-R

Intelligent Relay Module

The SK-Relay Module is intended for use in intelligent, two-wire systems where the individual address of each module is selected using the built in rotary switches.

For more information about the IntelliKnight system, or to locate you nearest source, please call 800-328-0103.

Description

The SK-Relay is an addressable relay module for use with Silent Knight IntelliKnight series fire alarm control panels (FACPs).

The SK-Relay allows a Silent Knight FACP to switch discrete contacts by code command. The relay contains two isolated sets of Form C contacts, which operate as a DPDT switch. No supervision is provided for the notification appliance circuit.

The SK-Relay contacts can be used for virtually any normally open or normally closed application. Each SK-Relay is programmed with a unique signaling line circuit (SLC) loop address. When an event occurs that controls the SK-Relay, the relay is triggered by the FACP.

Features

- Two sets of Form C contacts
- Rotary address switches for fast installation
- Contacts are rated for a variety of amps (see Specifications)
- Panel controlled status LED that flashes green in normal state and is solid red in alarm
- Relay programming is completely flexible–can be mapped to zone conditions
- Polling LED visible through the cover plate
- Attractive ivory cover plate
- SEMS screws for easy wiring
- UL Listed

SK-Relay

Installation

The SK-Relay mounts directly into a 4” square electrical box. The box must have a minimum depth of 2-1/8”. A surface mount electrical box (System Sensor® PN SMB500) is available from Silent Knight

Compatibility

The SK-Relay is compatible with the following IntelliKnight FACP’s:

5820XL
5820XL-EVS
5808
5700
5600 (Rev 2.0 or higher)

P/N 350127 Rev F
© 2016 Honeywell International Inc.

Reviewed for Code Compliance
Inspections Division
Approved with Conditions
Date: 04/26/18

Model SK-Relay
Intelligent Relay Module

Wiring the SK-Relay Module

Specifications

Physical
4.675" H x 4.275" W x 1.4" D

Shipping Weight: 6.3 oz (196 g)

Environmental
Operating Temperature: 32ºF – 120ºF (0ºC – 49ºC)

Humidity: 10% – 93% non-condensing

Electrical
Operating Voltage: 15 – 32 VDC

End-of-Line Resistance: Not used

SLC Standby & Alarm Current: .255mA max @ 24 VDC (one communication every 5 sec with LED enabled)

Ordering Information

SK-Relay	Relay Module

Accessories

SMB500	4” Square Surface Mount Electrical Box
CB500	Module Barrier

Relay Contact Ratings
3.0A @ 30 VDC resistive

0.9A @ 110 VDC resistive

0.9A @ 125 VAC resistive

0.5A @ 125 VAC inductive (PF = .35)

0.7A @ 75 VAC inductive (PF = .35)

SILENT KNIGHT
by Honeywell

This document is not intended to be used for installation purposes. We try to keep our product information up-to-date and accurate. We cannot cover all specific applications or anticipate all requirements. All specifications are subject to change without notice. For more information, contact Silent Knight 12 Clintonville Road, Northford, CT 06472-1610 Phone: (800) 328-0103, Fax: (203) 484-7118. For Technical Support, Please Call 800-446-6444. **www.silentknight.com**