RESURGAM, MAINE
CITY OF PORTLAND

Reviewed for Code Compliance
Inspections Division
Approved with Conditions

Date: 05/27/16

DOOR SCHEDULE

		SIZE	THK.	F.R.	HDWE SET	REMARKS
		3'-0" x 6'-8"	1 3/4"	–	PRIVACY, DEADBOLT	
		3'-0" x 6'-8"	1 3/4"		PRIVACY, DEADBOLT	
		9'-0" x 7'-0"	2"	–	MFGR HDWRE	
		9'-0" x 7'-0"	2"	–	MFGR HDWRE	
		8'-0" x 7'-0"	2"	–	MFGR HDWRE	
		3'-0" x 6'-8"		–	PRIVACY, DEADBOLT	
		2'-8" x 6'-8"		20-MIN	PRIVACY, EXTERIOR KEYLOCK	MINIMUM 1 3/8" THICK SOLID WOOD OR 1 3/8" HONEYCOMB CORE STEEL DOOR OR 20 MINUTE FIRE RATED DOOR. SEE NOTE 14/DWG A0
07A	EXTERIOR INSULATED GARAGE	2'-8" x 6'-8"	1 3/4"	–	PRIVACY, EXTERIOR KEYLOCK	BASEMENT EXTERIOR EGRESS DOOR
08	EXTERIOR GLASS SLIDERS	8'-0" x 6'-8"		–	PASSAGE, THUMB LOCK	ANDERSEN FRENCHWOOD 400 SERIES; FIBERGLASS EXTERIOR, PRE PRIMED WOOD INTERIOR
09	GARAGE INSULATED ENTRY	3'-0" x 6'-8"	1 3/4"	20 MIN	PRIVACY, EXTERIOR KEYLOCK	MINIMUM 1 3/8" THICK SOLID WOOD OR 1 3/8" HONEYCOMB CORE STEEL DOOR OR 20 MINUTE FIRE RATED DOOR. SEE NOTE 14/DWG A0
10	INTERIOR SC WOOD PANEL	2'-0" x 6'-8"		–	PASSAGE	
11	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
12	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
13	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
14	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
15	INTERIOR BI FOLD	6'-0" x 6'-8"		–	MFGR HDWRE	
16	INTERIOR SC WOOD PANEL	1'-6" x 6'-8"		–	PASSAGE	
17	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
18	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PASSAGE	
19	INTERIOR SC WOOD PANEL	2'-8" x 6'-8"		–	PRIVACY	
20	INTERIOR SC WOOD PANEL	2'-8" x 6'-8"		–	PRIVACY	
21	INTERIOR SC WOOD PANEL	2'-6" x 6'-8"		–	PRIVACY	
22	INTERIOR SC WOOD PANEL	2'-4" x 6'-8"		–	PASSAGE	
23	INTERIOR SC WOOD PANEL	2'-8" x 6'-8"		–	PRIVACY	
24	INTERIOR SC WOOD PANEL	2'-4" x 6'-8"		–	PASSAGE	
25	INTERIOR SC WOOD GLIDING	3'-0" x 6'-8"		–	MFGR HDWRE	
26	INTERIOR SC WOOD GLIDING	2'-6" x 6'-8"		–	PRIVACY	
SECOND FLOOR						
30	INTERIOR WOOD INSUL PANEL	3'-0" x 6'-8"	1 3/4"	–	PRIVACY, KEY LOCK	SELF CLOSING DOOR WITH LATCH
31	INTERIOR SC WOOD PANEL	3'-0" x 6'-8"	1 3/4"	–	PRIVACY, KEY LOCK	

NOTES

1. SPECIFIC SELECTION OF DOOR TYPES, MATERIAL, THICKNESS, VENEER, GLAZING, HINGES, LEVER HANDLES/KNOBS, TRIM AND OTHER RELATED DOOR HARDWARE SELECTED BY OWNER/GC.

2. ZONE 6 OPAQUE DOOR U-FACTOR MUST BE 0.37 OR LESS.

WINDOW SCHEDULE

MARK	TYPE	MODEL NO.	EGRESS	UNIT DIMENSIONS W X H	ROUGH OPENING (MIN)	REMARKS
A	MULLED PAIR DOUBLE HUNG	TW 30410-2	NO	6'-5 1/4" X 5'-0 7/8"	6'-6 1/4" X 5'-0 7/8"	CONFIRM ROUGH OPENING DIMENSION WIDTH FOR MULLED PAIR WITH WINDOW MFGR
B	DOUBLE HUNG	TW 3446	YES	3'-5 5/8" X 4'-8 7/8"	3'-6 1/8" X 4'-8 7/8"	
C	MULLED TRIPLE DOUBLE HUNG	TW 34410-3	NO	10'-8 7/8" X 5'-0 7/8"	10'-10 3/8" X 5'-0 7/8"	CONFIRM ROUGH OPENING DIMENSION WIDTH FOR MULLED TRIPLE WITH WINDOW MFGR
D	DOUBLE HUNG	TW 34410	YES	3'-5 5/8" X 5'-0 7/8"	3'-2 1/8" X 5'-0 7/8"	
E	DOUBLE HUNG	TW 30410	YES	3'-1 5/8" X 5'-0 7/8"	3'-2 1/8" X 5'-0 7/8"	
F	DOUBLE HUNG	TW 2032	NO	2'-1 5/8" X 3'-4 7/8"	2'-2 1/8" X 3'-4 7/8"	
G	GLIDING MULLED UNIT	G53 W/ FIXED CENTER PANE	NO	5'-0" X 3'-0" (SEE REMARKS)	MFGR PROVIDE	PROVIDE GLIDING END UNITS WITH CENTER FIXED PANE-EQUAL PANES. ROUGH OPENING DIMENSIONS PROVIDED BY WINDOW MFGR
H	DOUBLE HUNG	TW 20210	NO	2'-1 5/8" X 3'-0 7/8"	2'-2 1/8" X 3'-0 7/8"	
J	DOUBLE HUNG	TW 2436	NO	2'-5 5/8" X 3'-8 7/8"	2'-6 1/8" X 3'-8 7/8"	
K	MULLED DOUBLE DOUBLE HUNG	TW 34410-2	YES	7'-1 1/4" X 5'-0 7/8"	7'-2 1/4" X 5'-0 7/8"	CONFIRM ROUGH OPENING DIMENSION WIDTH FOR MULLED DOUBLE WITH WINDOW MFGR
L	DOUBLE HUNG	TW 24410	NO	2'-5 5/8" X 5'-0 7/8"	2'-6 1/8" X 5'-0 7/8"	

NOTES

1. WINDOW SCHEDULE BASED ON ANDERSEN 400 SERIES TILT-WASH DOUBLE HUNG AND 400 SERIES GLIDING WINDOWS. WOOD INTERIOR AND VINYL EXTERIOR. OWNER SELECT EXTERIOR COLOR AND INTERIOR PRE-PRIMED FINISH.

2. SPECIFIC SELECTION OF WINDOW TYPES, MATERIAL, THICKNESS, VENEER, GLAZING, HARDWARE, TRIM AND OTHER RELATED ITEMS SELECTED BY OWNER/GC.

3. ALL WINDOWS SHALL BE SILL PAN FLASHED, TYPICAL. CONSULT WINDOW MFGR FOR RECOMMENDED MATERIALS AND TECHNIQUES.

4. MINIMUM ROUGH OPENING DIMENSIONS MAY NEED TO BE INCREASED TO ALLOW FOR USE OF BUILDING WRAPS, SILL PANNING, BRACKETS, FASTENERS OR OTHER ITEMS. (CONSULT MFGR, TYP.)

5. EGRESS WINDOWS SHALL MEET OR EXCEED CLEAR OPENING AREA OF 5.7 SQUARE FEET CLEAR OPENING WIDTH OF 20" MIN. AND CLEAR OPENING HEIGHT OF 24" MIN.

6. ZONE 6 FENESTRATION U-FACTOR FOR WINDOWS MUST BE 0.35 OR LESS.

REGISTERED ARCHITECT
JOHN H. LEASURE
No. 310
STATE OF MAINE

REV.	DATE	STATUS
0	3-28-16	PERMIT SUBMISSION
1	4-15-16	REV 1
2	5-5-16	REV 2

JOHN H. LEASURE ARCHITECT, INC.
6 Q STREET
SOUTH PORTLAND, MAINE 04106

MICHAEL & MARY ANN JIMINO RESIDENCE
1651 WASHINGTON AVENUE
PORTLAND, MAINE

DOOR AND WINDOW SCHEDULES

A11