City of Portland, Maine 389 Congress Street, 0410				CBL: 375 C001001		
Location of Construction:	Owner Name:		Owner Address:	3/3 C001001 Phone:		
91 Auburn St	Shaw's Realty		Po Box 600	1 1		
Business Name:	Contractor Name		Po Box 600 508-378-7211 Contractor Address F PORTLAND Phone			
n/a	Commenwealt		265 Willard St. Quincey 6177700050			
Lessee/Buyer's Name	Phone:		Permit Type:	7.one: 7		
n/a	n/a		Alterations - Commercial	B-2		
Past Use: Proposed Use:			Permit Fee: Cost of Work:	CEO District:		
Commercial / Retail		Retail; interior finish	\$924.00 \$150,000			
alterations			FIRE DEPT: Approved Use Group: Type: 2			
Proposed Project Description:			. (XXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXXX		
Interior Alterations		⊢	Signature: UMM Y	James / Fix		
		Į.	PEDESTRIAN ACTIVITIES DISTÌ			
				oved w/Conditions		
D		T	Signature:	Date:		
Permit Taken By:	Date Applied For: 09/11/2001		Zoning Approval			
gg 1. This permit application of		Special Zone or Review	zs Zoning Appeal	Listoric Preservation		
1. This permit application does not preclude the Applicant(s) from meeting applicable State and Federal Rules.		Shoreland Variance		Not in District or Landmar		
2. Building permits do not include plumbing, septic or electrical work.		☐ Wetland ☐ Miscellaneous		Does Not Require Review		
3. Building permits are void if work is not started within six (6) months of the date of issuance.		☐ Flood Zone ☐ Conditional Use		Requires Review		
False information may in permit and stop all work.		Subdivision Interpretation		Approved		
		Site Plan	Approved	Approved w/Conditions		
		Maj Minor MM	Denied	Domied		
		Date:	Date:	Date		
		9/19/01				
		·/(*t* (PERMIT ISSUED WITH REQUIREMENTS		
jurisdiction. In addition, if a p	owner to make this appli permit for work described	cation as his authorized a	N proposed work is authorized bagent and I agree to conform to ued, I certify that the code official ble hour to enforce the provision.	all applicable laws of this		
SIGNATURE OF APPLICANT		ADDRESS	DATE			

DATE

PHONE

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE

All Purpose Building Permit Application

If you or the property owner owes real estate or personal property taxes or user charges on any property within the City, payment arrangements must be made before permits of any kind are accepted.

Tatal Causes Footogo of Dropped Structu			2A , PORTLAND , ME
Total Square Footage of Proposed Structu	re 3386 S	quare Footage of Lot	N.A.
Tax Assessor's Chart, Block & Lot Chart# 375 Block# C Lot#	Owner:	REALTY COMPANY	Telephone: 508 378 7211
Lessee/Buyer's Name (If Applicable) OLYMPIA SPORTS YRRMOUTH, MAINE 846.3766	Applicant natelephone:	me, address &	Cost Of Work: \$ 150,000
Approximately how long has it been vaccon Proposed use: RETAIL Project description:	_		
Interior Finish Alteration	45 (No CH	ange to Egress	s of structure)
Contractor's name, address & telephone: Who should we contact when the permit Mailing address:	Common w 265 WIU	PEALTH BUILDERG LARO ST, QUINCY	4x Calp

This is not a permit, you may not commence ANY work until the permit is issued

The City's Adopted Building Code (The BOCA National Building Code/1999 with City Amendments)
The City's Adopted Mechanical Code (The BOCA National Mechanical Code/1993)

CONDITION(S) OF APPROVAL

This permit is being issued with the understanding that the following conditions shall be met: \(\frac{\pi}{2}\) \(\frac

1. This permit does not excuse the applicant from meeting applicable State and Federal rules and laws.

2. Before concrete for foundation is placed, approvals from the Development Review Coordinator and Inspection Services must be obtained. (A

24 hour notice is required prior to inspection) "ALL LOT LINES SHALL BE CLEARLY MARKED BEFORE CALLING."
3. Foundation drain shall be placed around the perimeter of a foundation that consists of gravel or crushed stone containing not more than 10 percent material that passes through a No. 4 sieve. The drain shall extend a minimum of 12 inches beyond the outside edge of the footing. The thickness shall be such that the bottom of the drain is not higher than the bottom of the base under the floor, and that the top of the drain is not less than 6 inches above the top of the footing. The top of the drain shall be covered with an approved filter membrane material. Where a drain tile or perforated pipe is used, the invert of the pipe or tile shall not be higher than the floor elevation. The top of joints or top of perforations shall be protected with an approved filter membrane material. The pipe or tile shall be placed on not less than 2" of gravel or crushed stone, and shall be covered with not less than 6" of the same material. Section 1813.5.2

4. Foundations anchors shall be a minimum of ½" in diameter, 7" into the foundation wall, minimum of 12" from corners of foundation and a maximum 6' O.C. between bolts. Section 2305.17

5. Waterproofing and dampproofing shall be done in accordance with Section 1813.0 of the building code.

6. Precaution must be taken to protect concrete and masonry. Concrete Sections 1908.9-19.8.10/ Masonry Sections 2111.3-2111.4.

7. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.

8. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the artic area by means of ½ inch gypsum board or the equivalent applied to the garage side. (Chapter 4, Section 407.0 of the BOCA/1999)

9. All chimneys and vents shall be installed and maintained as per Chapter 12 of the City's Mechanical Code. (The BOCA National Mechanical Code/1993). Chapter 12 & NFPA 211

10. Sound transmission control in residential building shall be done in accordance with Chapter 12, Section 1214.0 of the City's Building Code.

- 11. Guardrails & Handrails: A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42". In occupancies in Use Group A, B.H-4, I-1, I-2, M, R, public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect. Handrails shall be a minimum of 34" but not more than 38". Exception: Handrails that form part of a guard shall have a height not less than 36 inches (914 mm) and not more than 42 inches (1067 mm). Handrail grip size shall have a circular cross section with an outside diameter of at least 1 ½" and not greater than 2". (Sections 1021 & 1022.0). Handrails shall be on both sides of stairway. (Section 1014.7) R-3 (ONE & TWO FAMILY DWELLINGS) GUARD HEIGHT IS 36" MINIMUM.
 - 12. Headroom in habitable space is a minimum of 7'6". (Section 1204.0)
 - 13. Stair construction in <u>Use Group R-3 & R-4 is a minimum of 10" tread and 7 %" maximum rise.</u> All other Use Group minimum 11" tread. T' maximum rise. (Section 1014.0)
 - 14. The minimum headroom in all parts of a stairway shall not be less than 80 inches. (6'8") 1014.4
 - 15. The Minimum required width of a corridor shall be determined by the most restrictive of the criteria criter section 1011.3 but not less then 36°.
 - 16. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches (610mm). The minimum net clear opening width dimension shall be 20 inches (508)mm, and a minimum net clear opening of 5.7 sq. ft. (Section 1010.4)
 - 17. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units. (Section 1010.1)
 - 18. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with self closure's. (Over 3 stories in height requirements for fire rating is two (2) hours. (Section 710.0)
 - 19. The boiler shall be protected by enclosing with (1) hour fire rated construction including fire doors and ceiling, or by providing automatic extinguishment. (Table 302.1.1)

9/1

20. All single and multiple station smoke detectors shall be of an approved type and snatt be installed in accordance with me pro-Building Code Chapter 9, Section 920.3.2 (BOCA National Building Code/1999), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations): In the immediate vicinity of bedrooms In all bedrooms In each story within a dwelling unit, including basements 21. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type. (Section 921.0) 22. The Fire Alarm System shall be installed and maintained to NFPA #72 Standard. 23. The Sprinkler System shall be installed and maintained to NFPA #13 Standard. 24. All exit signs, lights and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023.0 & 1024.0 of the City's Building Code. (The BOCA National Building Code/1999) 25. Section 25 - 135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year". 26. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act Title 5 MRSA refers, shall obtain a certification from a design professional that the plans commencing construction of the facility, the builder shall submit the certification the Division of Inspection Services. 27. Ventilation and access shall meet the requirements of Chapter 12 Sections 1210.0 and 1211.0 of the City's Building Code. (Crawl spaces & attics). 28. All electrical, plumbing and HVAC permits must be obtained by Master Licensed holders of their trade. No closing in of walls until all electrical (min. 72 hours notice) and plumbing inspections have been done. 29. All requirements must be met before a final Certificate of Occupancy is issued. 30. All building elements shall meet the fastening schedule as per Table 2305.2 of the City's Building Code (The BOCA National Building Code/1996). 31. Ventilation of spaces within a building shall be done in accordance with the City's Mechanical code (The BOCA National Mechanical Code/1993). (Chapter M-16)

32. Please read and implement the attached Land Use Zoning report requirements.

33. Boring, cutting and notching shall be done in accordance with Sections 2305.3, 2305.3.1, 2305.4.4 and 2305.5.1 of the City's Building Code. 34. Bridging shall comply with Section 2305.16. 35. Glass and glazing shall meet the requirements of Chapter 24 of the building code. (Safety Glazing Section 2406.0) 36. All flashing shall comply with Section 1406.3.10. 37. All signage shall be done in accordance with Section 3102.0 signs of the City's Building Code, (The BOCA National Building Code/1999). Building Inspector E. MoDougall, PFD Marge Schmuckal, Zoning Administrator Michael Nugent, Inspection Service Manager **This permit is herewith issued, on the basis of plans submitted and conditions placed on these plans, any deviations shall require a separate approval.

...THIS PERMIT HAS BEEN ISSUED WITH THE UNDERSTANDING THAT ALL THE CONDITIONS OF THE APPROVAL SHALL BE COMPLETED. THEREFORE, BEFORE THE WORK IS COMPLETED A REVISED PLAN OR STATEMENT FROM THE PERMIT HOLDER SHALL BE SUBMITTED TO THIS OFFICE SHOWING OR EXPLAINING THAT THE CONDITIONS HAVE BEEN MET. IF THIS REQUIREMENT IS NOT RECEIVED YOUR CERTIFICATE OF OCCUPANCY SHALL BE WITHHELD. (You Shall Call for Inspections)

****ALL PLANS THAT REQUIRE A PROFESSIONAL DESIGNER'S SEAL, (AS PER SECTION 114.0 OF THE BUILDING CODE) SHALL ALSO BE PRESENTED TO THIS DIVISION ON AUTO CAD LT. 2000, DXF FORMAT OR EQUIVALENT.


*****CERTIFICATE OF OCCUPANCY FEE \$50.00


DUPLICATE

CITY OF PORTLAND, MAINE

DEPAF	DEPARTMENT DATE					
San Diction Oliver						
RECEIVED FROM						
ADDRESS AND CLICK TEST						
	At Culture Street					
-						
TINU	ITEM	REVENUE CODE	DOLL AMOL	AR INT		
	Building Dr	*XX		! !		
			934,	00		
				1		
(last 1/96	a				
			1			
	B (375 C	00				
			1			
				——		
□ CASH □ CHECK □ OTHER TOTAL						
RECEIVED DV						
GBF INFORMATION SYSTEMS Box 878, Portland, ME 04 104 (207) 774-1482 Commercial Printing • Business Forms • Advertising Specialties • Labels 200747-BP						
Sommercial Frinting ● Business Forms ● Advertising Specialties ● Labels						







SECTION 01000 - GENERAL CONDITIONS

- A. CODES, PERMITS AND APPROVALS

- RECORD OF INSPECTIONS SHALL BE MAINTAINED ON THE JOB SITE, IN ACCORDANCE WITH CITY REQUIREMENTS AND FORMAT.

- ENTIRE SCOPE OF WORK TO BE COMPLETED IN TIMELY MANNER WITHIN PREASONABLE LIMITS, AS SET FORTH BY THE LANDLORD AND THE TENANT.
- DATES CAN ONLY BE CHANGED BY WRITTEN LETTER FROM MR. ROBERT BOLAND, OPERATIONS MANAGER FOR OLYMPIA SPORTS.
- TENANT'S CONTRACTOR IS REQUIRED TO KEEP A DAILY JOURNAL DURING CONSTRUCTION, TO BE TURNED OVER TO OLYMPIA SPORTS AT THE END OF CONSTRUCTION.

CHANGE ORDERS

- GENERAL CONTRACTOR MUST NOTIFY OLYMPIA SPORTS IMMEDIATELY OF ANY FIELD CONDITIONS RESULTING IN INCREASED COST.

- SUBSTANTIAL COMPLETION SHALL BE DEFINED AS ALL WORK COMPLETED AS REQUIRED TO OBTAIN ALL DOCUPANCY PERMITS AND TO A POINT AS TO ACCOMMODATE ALL FIXTURING, MERCHANDISE, AND OPERATING PUNCTIONS OF THE TENANT.
- CONTRACTOR SHALL BE RESPONSIBLE FOR INSTALLATION AND SHAFTLY OF ALL UTILITY SERVICES TO THE SPACE. ALL UTILITY SERVICES TO THE SPACE. ALL UTILITY OF ALL UTILITY SERVICES TO THE SPACE. ALL UTILITY SERVICE WITH SERVICES WIT

GENERAL CONSTRUCTION NOTES

- WOOD DOORS SHALL MEET ALL APPLICABLE REQUIREMENTS OF THE AMERICAN WOODWORK INSTITUTE "DUALITY STANDARDS" AND "NATIONAL" WOODWORK MANUFACTURERS ASSOCIATION SPECIFICATIONS" UNLESS OTHERWISE NOTED.
- 10. SET BENCHMARK AT 42° ABOVE HIGH POINT OF FLOOR. SET STANDARD HEIGHT AND ALL VERTICAL DIMENSIONS FROM THIS RENCHMARK TO ENSURE THEY ARE LEVEL

- SLAIWALL: QUANTITY AND SIZES OF SLAIWALL PANELS TO BE SUPPLIED TO OWNER BY TENANTS CENERAL CONTRACTOR. ALL SLATWALL SCREWS TO BE CONTRESUM AND SCREWED DIRECTLY INTO MILE WALL FRAMMS, ESE DETAILS ON SIEET AS. INSTALL IN STRICT CONFORMANCE WITH MANUFACTURERS PRINTED SPECIFICATIONS. INSTALL ALL LEFTOVER SLATWALL ON OFEN WALLS IN STOCKHOOM. AS DIRECTED BY OWNER.
- MIRRORS: ALL MIRRORS IN STORE ARE TO BE SUPPLIED AND INSTALLED BY GENERAL CONTRACTOR UNLESS OTHERWISE NOTED. ALL MOULDINGS SHALL BE MITERED AT ALL CONTRACTOR.
- GYPSUM DRYWALL: USE ONLY 5'8' TYPÉ "X" GYPSUM DRYWALL WITH TAPERED EDGES. INSTALL AND FRIEND STRICT CONFORMANCE WITH MIGHTS SPECIFICATION. PROVIDE "LEVEL 4" RINISH THROUGHOUT.

- PAINTING: ALL PAINTING SHALL BE DONE IN STRICT CONFORMANCE WITH IMFGRS IMPRINTED SPECIFICATIONS. APPLY ONE PRIME COAT AND TWO PRIME FOATS MINIMAIN ALL WALLS TOO PERPAYABLE SHEQUIED PRIOR TO PAINT APPLACATION. LISC ONLY ALL WALLS TOO PERPAYABLE SHEQUIED PRIOR TO PAINT APPLACATION. LISC ONLY PAINTING CONTRACTOR TO LEAVE ADEQUATE (I QUART MINIMAIN) PAINT OF EACH COLUMN AND HERS ON SITE FOR TOUGH-FOR YOUR
- PROTECTION: THE TENANT'S GENERAL CONTRACTOR IS RESPONSIBLE FOR PROTECTING INSTALLED FINISHES FROM DAMAGE FROM LATER WORK.

DURING TURINOVER OF CERTAIN AREAS, THE GENERAL CONTRACTOR SHOULD CONTRACT WITH A "PROFESSIONAL CLEANING SERVICE" TO PROVIDE CLEANING AS FOLLOWS:

- CLEAN ALL LAMINATE, COUNTERS, SHELVES AND MIRRORS WITH APPROPRIATE CLEANSING AGENTS.
- CLEAN ALL WINDOWS WITH APPROPRIATE CLEANSERS.
 DAMP WIPE ALL TRACK LIGHTS AND REMOVE ALL LABELS AND RESIDUE.

- 2. CLEAN ALL TOILET ROOM FIXTURES WITH ENVIRONMENTAL CLEANSERS.
- 4. ALL SUFFACES AND FINSHES TO BE FREE OF ALL MARKS, STAINS OR BLEMISHES. DUST, DRIT, PAINT SPECKS, AND THE LIKE.
- 6. CLEAN ENTIRE AREA AND READY FOR OCCUPANCY BY OLYMPIA SPORTS.

NOTES TO GENERAL CONTRACTORS

MATERIAL SHIPPING

- BY GENERAL CONTRACTOR. FURNISH AND INSTALL ALL MERCHANDISE FIXTURING

- INSTALLATION BY GENERAL CONTRACTOR
- FURNISH SIGNAGE FOR INSTALLATION BY SIGN SUBCONTRACTOR GENERAL CONTRACTOR TO COORDINATE

FIRE RATINGS

LIST OF ABBREV.

- ELECTRIC ELEVATION EQUAL EQUIPMENT EACH WAY EXTERIOR FLOOR DRAIN
 FIRE EXTINGUISHER
 FINISH FLOOR
 FACE OF MASONRY
 FACE OF GRUD
 FIRE RETARDANT TO
 FLOOR SHIK
 FOOTING
- GALVANIZED

 GENERAL DONTRACTUM
 GALLONS PER MINUTE
 GROUND
 GYPBUM WALL BOARD
 GYPBUM
- LAMMATE LAVATORY LOCATE

- T&G TYP. TONGUE AND GROOVE TYPICAL UNLESS OTHERWISE NOTED URINAL

LOCATION MAPS

- CARPET (CLASS II) BASED ON ASTM - 648 - 86 NFPA 253 SMOKE DENSITY - 321 BASED ON ASTM - 646 - 86 PADIANT TEST - 22 WATTS.CM2
- BASED ON ASTM E 84 MED. DENSITY FIBERBOARD MED. DENSITY FIBERBOARD CORENIGH PRESSURE LAMINATE FINISH THICKNESS 3/4* FLAME SPREAD 160 - 185 FUJEL CONTRIBUTED 105 - 115 SMOKE DEVELOPED 335 - 420
- HIGH PRESSURE LAMINATE (CLASS III)
- CEILING SYSTEM (CLASS) CLASS "A" PLAME SPREAD: 0 - 25

FLOORING:

AUDIO/VIDEO:

TENANT'S VENDOR CONTACTS

JERRY ANDERSON 506-393-2591

RUSTY BREWER 207-797-7534 OFFICE 207-797-0973 FAX

CUNNINGHAM SECURITY 313 READ ST. PORTLAND, MAINE 04103

PAUL CUNNINGHAM 207-878-5858 OFFICE

M.R. BREWER WOODWORKING 91 BELL STREET. PORTLAND, MAINE 04103

STORE DATA

GROSS LEASED AREA 3386 SF 100% 2684 SF 80% SALES AREA

STOCKROOMOFFICE/ 702 SF 20% TOILETS

DRAWING INDEX

NEOKRAFT SIGN 686 MAIN STREET LEWISTON, ME 04240

CAPITOL LIGHT 270 LOCUST STREET HARTFORD, CT 06141-0179

DAVID MULLANE 860-549-1230 860-560-8315 FAX

800-241-6678

PHELPS LOCK

JAMIE UNDERWOOD 508-869-6393

TIMOTHY WINKLER 810-679-4400 810-679-4510

LOSS PREVENTION:

CURIC FEET SHELVING 12" WIDE 18" WIDE 24" WIDE	2328 CF 0 CF 192 CF
TOTAL CUBIC FEET	2520 CF

FLOOR PLAN

DETAILS

REFLECTED CEILING PLAN

PROJECT TEAM

TENANT:
OLYMPIA SPORTS CENTER
468 U.S. ROUTE 1
YARMOUTH, ME 04066
ATTH: PAUL PRIZPATRICK, OPERATIONS MANAGER
(207) 846-9756 OFFICE
(207) 846-1048 FAX

GENERAL CONTRACTOR: COMMONWEALTH DUILDERG, INC. 253 WILLARD ST. CUINCY, MA 02109 ATTN: PATHICK DUFFIN. PROJECT MGR. (617) 770-0000 OFFICE (617) 847-1527 FAX

OLYMPIA Sports

₩ WB PLASTIC LAMINATE: BLACK MATTE, BLACK FORMICA #509-58

™

PAINT: WHITE B.M. #855 ACOUSTICAL TILE: ARMSTRONG "SECOND LOOK" (c) NO CEILING

MATERIALS KEY

CARPET: PROVIDED BY TENAN INSTALLED BY G.C.

V.C.T. 12" X 12" ARMSTRONG
IMPERIAL VCT PLOOR TILE.
PROVIDED BY TENANT.
INSTALLED BY G.C.

CARPET TILE:
PROVIDED BY TENANT.
INSTALLED BY G.C.

PHOVIDED BY TENANT. PROVIDED BY TENANT.

CONCRETE SEALER:
KURE-N-SEAL
SC-236 WATER BASE
PROVIDED AND INSTALL

FA RUBBER TRANSITION STRIP:
MERCER 8146, 1 5/8" WIDE
BLACK PROVIDED BY TENAN
INSTALLED BY G.C.

F9 RUBBER TRANSITION STRIP: MERCER #153, 1 "WIDE BLACK. PROVIDED BY TENANT. INSTALLED BY G.C.

GYPSUM WALLBOARD: 58' TYPE 'X', PAINTED

GYPSUM WALLBOARD: 5/8" TYPE "X", UNPAINTED

PLASTIC LAMINATE:
WHITE MATTE, WHITE
FORMICA 1949-58

PAINT: WHITE, B.M. #869, EGGSHELL FINISH PAINT: BLACK, B.M. #80 EGGSHELL FINISH

PAINT: RED. B.M. "CARNIVAL RED".

PAINT: BLACK B.M. 480 SEMI-GLOSS FINISH



15 Franklin Street Art Portland, Maine 04101 phone 207 772 4656 fax 207 828 4656

FOR CONSTRUCTION

OLYMPIA SPORTS NORTHGATE PLAZA PORTLAND, ME

COVER SHEET

PROJECT NO. 01111.08 2001 O BOOTT SIMONS ARCHITECTS

A-0

