



# Quadruple 1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP Floor Beam\FB02

Dry | 1 span | No cantilevers | 0/12 slope


February 19, 2017 16:54:08

BC CALC® Design Report



Build 5684  
Job Name: 127 BRAMBLEWOOD  
Address:  
City, State, Zip: ,  
Customer: ROB TWOMBLY  
Code reports: ESR-1040

File Name: BC CALC Project  
Description: KITCHEN CEIL BM  
Specifier:  
Designer:  
Company:  
Misc:



## Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind	Roof Live
B0, 3-1/2"	3,360 / 0	1,556 / 0			
B1, 3-1/2"	3,360 / 0	1,556 / 0			

## Load Summary

Tag	Description	Load Type	Ref.	Start	End	100%	90%	115%	160%	125%	Trib.
1	BEDROOM FLOOR	Unf. Area (lb/ft <sup>2</sup> )	L	00-00-00	12-00-00	40	10				14-00-00
2	INT WALLS	Unf. Lin. (lb/ft)	L	00-00-00	12-00-00	0	100				n/a

## Controls Summary

	Value	% Allowable	Duration	Case	Location
Pos. Moment	13,642 ft-lbs	48.9%	100%	1	06-00-00
End Shear	4,028 lbs	31.9%	100%	1	01-01-00
Total Load Defl.	L/424 (0.327")	56.7%	n/a	1	06-00-00
Live Load Defl.	L/620 (0.224")	58.1%	n/a	2	06-00-00
Max Defl.	0.327"	32.7%	n/a	1	06-00-00
Span / Depth	14.6	n/a	n/a	0	00-00-00

## Bearing Supports

	Dim. (L x W)	Value	% Allow Support	% Allow Member	Material
B0 Post	3-1/2" x 3-1/2"	4,916 lbs	n/a	53.5%	Unspecified
B1 Post	3-1/2" x 3-1/2"	4,916 lbs	n/a	53.5%	Unspecified

## Cautions

Member is not fully supported at post B0. A connector is required at this bearing.  
Member is not fully supported at post B1. A connector is required at this bearing.

## Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

BC CALC® Design Report



Build 5684

Job Name: 127 BRAMBLEWOOD

Address:

City, State, Zip: ,

Customer: ROB TWOMBLY

Code reports: ESR-1040

File Name: BC CALC Project


Description: KITCHEN CEIL BM

Specifier:

Designer:

Company:

Misc:

**Connection Diagram**

a minimum = 2" c = 5-1/2"

b minimum = 2-1/2" d = 24"

Beams 7 inches wide will be assumed to be either top-loaded only, or equally loaded from each side.

Bolts are assumed to be Grade A307 or Grade 2 or higher.

Member has no side loads.

Connectors are: 1/2 in. Staggered Through Bolt

**Disclosure**

Completeness and accuracy of input must be verified by anyone who would rely on output as evidence of suitability for particular application. Output here based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCi®, BOISE GLULAM™, SIMPLE FRAMING SYSTEM®, VERSA-LAM®, VERSA-RIM PLUS®, VERSA-RIM®, VERSA-STRAND®, VERSA-STUD® are trademarks of Boise Cascade Wood Products L.L.C.