



Triple 1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP

Floor Beam\FB03

Dry | 1 span | No cantilevers | 0/12 slope


February 19, 2017 16:54:27

BC CALC® Design Report



Build 5684
 Job Name: 127 BRAMBLEWOOD
 Address:
 City, State, Zip: ,
 Customer: ROB TWOMBLY
 Code reports: ESR-1040

File Name: BC CALC Project
 Description: LIV / DIN CEIL BM
 Specifier:
 Designer:
 Company:
 Misc:



Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind	Roof Live
B0, 3-1/2"	1,920 / 0	1,167 / 0			
B1, 3-1/2"	1,920 / 0	1,167 / 0			

Load Summary

Tag	Description	Load Type	Ref.	Start	End	100%	90%	115%	160%	125%	Trib.
1	BEDROOM	Unf. Area (lb/ft^2)	L	00-00-00	12-00-00	40	10				08-00-00
2	INT WALLS	Unf. Lin. (lb/ft)	L	00-00-00	12-00-00	0	100				n/a

Controls Summary

	Value	% Allowable	Duration	Case	Location
Pos. Moment	8,566 ft-lbs	40.9%	100%	1	06-00-00
End Shear	2,529 lbs	26.7%	100%	1	01-01-00
Total Load Defl.	L/506 (0.274")	47.4%	n/a	1	06-00-00
Live Load Defl.	L/813 (0.17")	44.3%	n/a	2	06-00-00
Max Defl.	0.274"	27.4%	n/a	1	06-00-00
Span / Depth	14.6	n/a	n/a	0	00-00-00

Bearing Supports

	Dim. (L x W)	Value	% Allow Support	% Allow Member	Material
B0 Post	3-1/2" x 3-1/2"	3,087 lbs	n/a	33.6%	Unspecified
B1 Post	3-1/2" x 3-1/2"	3,087 lbs	n/a	33.6%	Unspecified

Cautions

Member is not fully supported at post B0. A connector is required at this bearing.
 Member is not fully supported at post B1. A connector is required at this bearing.

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

BC CALC® Design Report



Build 5684

Job Name: 127 BRAMBLEWOOD

Address:

City, State, Zip: ,

Customer: ROB TWOMBLY

Code reports: ESR-1040

File Name: BC CALC Project

Description: LIV / DIN CEIL BM


Specifier:

Designer:

Company:

Misc:

Connection Diagram



a minimum = 2" c = 5-1/2"

b minimum = 2-1/2" d = 24"

Bolts are assumed to be Grade A307 or Grade 2 or higher.

Member has no side loads.

Connectors are: 1/2 in. Staggered Through Bolt

Disclosure

Completeness and accuracy of input must be verified by anyone who would rely on output as evidence of suitability for particular application. Output here based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCi®, BOISE GLULAM™, SIMPLE FRAMING SYSTEM®, VERSA-LAM®, VERSA-RIM PLUS®, VERSA-RIM®, VERSA-STRAND®, VERSA-STUD® are trademarks of Boise Cascade Wood Products L.L.C.