

City of Portland, Maine – Building or Use Permit Application 389 Congress Street, 04101, Tel: (207) 874-8703, FAX: 874-8716

Location of Construction: 66 Bramblewood Dr		Owner: Kavilonias, John & /Diane		Phone:		Permit No: 60854	
Owner Address:		Leasee/Buyer's Name:		Phone:		Business Name:	
Contractor Name: Kierstead Co.		Address: 39 Baltimore Ave So. Fld, ME 04106		Phone: 799-6801		<div style="border: 2px solid black; padding: 5px; text-align: center;"> PERMIT ISSUED AUG 28 1996 CITY OF PORTLAND </div>	
Past Use: 1-fam		Proposed Use: Same		COST OF WORK: \$ 500.00		PERMIT FEE: \$ 35.00	
Proposed Project Description: Const Additional Deck (12 x 22)		FIRE DEPT. <input type="checkbox"/> Approved <input type="checkbox"/> Denied		INSPECTION: Use Group <i>13</i> Type <i>5B</i> <i>BOC093</i>		Zone: CBL: 377-F-011	
		Signature:		Signature:		Zoning Approval: <i>OK - 8/27/96</i>	
PEDESTRIAN ACTIVITIES DISTRICT (P.U.D.) Action: <input type="checkbox"/> Approved <input type="checkbox"/> Approved with Conditions <input type="checkbox"/> Denied		Signature:		Date:		Special Zone or Reviews: <input type="checkbox"/> Shoreland <input type="checkbox"/> Wetland <input type="checkbox"/> Flood Zone <input type="checkbox"/> Subdivision <input type="checkbox"/> Site Plan maj <input type="checkbox"/> minor <input type="checkbox"/> mm <input type="checkbox"/>	
Permit Taken By: <i>Mary Gresik</i>		Date Applied For: <i>26 August 1996</i>					

1. This permit application doesn't preclude the Applicant(s) from meeting applicable State and Federal rules.
2. Building permits do not include plumbing, septic or electrical work.
3. Building permits are void if work is not started within six (6) months of the date of issuance. False information may invalidate a building permit and stop all work..

PERMIT ISSUED WITH REQUIREMENTS

CERTIFICATION

I hereby certify that I am the owner of record of the named property, or that the proposed work is authorized by the owner of record and that I have been authorized by the owner to make this application as his authorized agent and I agree to conform to all applicable laws of this jurisdiction. In addition, if a permit for work described in the application issued, I certify that the code official's authorized representative shall have the authority to enter all areas covered by such permit at any reasonable hour to enforce the provisions of the code(s) applicable to such permit

Robert Kierstead
 SIGNATURE OF APPLICANT **ROBERT KIERSTEAD** ADDRESS: *39 Baltimore Ave S.R.* DATE: *26 August 1996* PHONE:

RESPONSIBLE PERSON IN CHARGE OF WORK, TITLE PHONE:

Zoning Appeal

Variance
 Miscellaneous
 Conditional Use
 Interpretation
 Approved
 Denied

Historic Preservation

Not in District or Landmark
 Does Not Require Review
 Requires Review

Action:

Approved
 Approved with Conditions
 Denied

Date: _____

CEO DISTRICT 7

BUILDING PERMIT REPORT

DATE: 28 - Aug - 96 ADDRESS: 66 Bramblewood Dr.
REASON FOR PERMIT: to Construct deck (12'x22')
BUILDING OWNER: Kazilonius
CONTRACTOR: owner
PERMIT APPLICANT: " " ~~DELETED:~~ *1, *5, *7

CONDITION OF APPROVAL OR PERMIT

- * 1. Before concrete for foundation is placed, approvals from the ~~Development Review coordinator~~ and Inspection Services must be obtained. (A24 hour notice is required prior to inspection)
- 2. Precaution must be taken to protect concrete from freezing.
- 3. It is strongly recommended that a registered land surveyor check all foundation forms before concrete is placed. This is done to verify that the proper setbacks are maintained.
- 4. Private garages located beneath habitable rooms in occupancies in Use Group R-1, R-2, R-3 or I-1 shall be separated from adjacent interior spaces by fire partitions and floor/ceiling assembly which are constructed with not less than 1-hour fire resisting rating. Private garages attached side-by-side to rooms in the above occupancies shall be completely separated from the interior spaces and the attic area by means of 1/2 inch gypsum board or the equivalent applied to the garage means of 1/2 inch gypsum board or the equivalent applied to the garage side. (Chapter 4 section 407.0 of the BOCA/1996)
- * 5. Guardrail & Handrails-A guardrail system is a system of building components located near the open sides of elevated walking surfaces for the purpose of minimizing the possibility of an accidental fall from the walking surface to the lower level. Minimum height all Use Groups 42", except Use Group R which is 36". In occupancies in Use Group A,B, H-4, I-1, I-2 M and R and public garages and open parking structures, open guards shall have balusters or be of solid material such that a sphere with a diameter of 4" cannot pass through any opening. Guards shall not have an ornamental pattern that would provide a ladder effect.
- 6. Headroom in habitable space is a minimum of 7'6".
- * 7. Stair construction in Use Group R-3 & R-4 is a minimum of 10" tread and 7 3/4" maximum rise. All other Use Group minimum 11" tread, 7" maximum rise.
- 8. The minimum headroom in all parts of a stairway shall not be less than 80 inches.
- 9. Every sleeping room below the fourth story in buildings of Use Groups R and I-1 shall have at least one operable window or exterior door approved for emergency egress or rescue. The units must be operable from the inside without the use of special knowledge or separate tools. Where windows are provided as means of egress or rescue, they shall have a sill height not more than 44 inches (1118mm) above the floor. All egress or rescue

windows from sleeping rooms shall have a minimum net clear opening height dimension of 24 inches(610mm). The minimum net clear opening width dimension shall be 20 inches (508mm), and a minimum net clear opening of 5.7 sq. feet.

10. Each apartment shall have access to two (2) separate, remote and approved means of egress. A single exit is acceptable when it exits directly from the apartment to the building exterior with no communications to other apartment units.
 11. All vertical openings shall be enclosed with construction having a fire rating of at least one (1) hour, including fire doors with selfclosers.
 12. The boiler shall be protected by enclosing with on (1) hour fire-rated construction including fire doors and ceiling, or by providing automatic extinguishment.
 13. All single and multiple station smoke detectors shall be of an approved type and shall be installed in accordance with the provisions of the City's building code Chapter 9, Section 19, 919.3.2 (BOCA National Building Code/1996), and NFPA 101 Chapter 18 & 19. (Smoke detectors shall be installed and maintained at the following locations):
 1. In the immediate vicinity of bedrooms
 2. In all bedrooms
 3. In each story within a swelling unit, including basements
- In addition to the required AC primary power source, required smoke detectors in occupancies in Use Groups R-2, R-3 and I-1 shall receive power from a battery when the AC primary power source is interrupted. (Interconnection is required)
14. A portable fire extinguisher shall be located as per NFPA #10. They shall bear the label of an approved agency and be of an approved type.
 15. The Fire Alarm System shall be maintained to NFPA #72 Standard.
 16. The Sprinkler System shall maintained to NFPA #13 Standard.
 17. All exit signs, lights, and means of egress lighting shall be done in accordance with Chapter 10 Section & Subsections 1023. & 1024. of the City's building code. (The BOCA National Building Code/1996)
 18. All construction and demolition debris must be disposed at the City's authorized reclamation site. The fee rate is attached. Proof of such disposal must be furnished to the office of Inspection Services before final Certificate of Occupancy is issued or demolition permit is granted.
 19. Section 25-135 of the Municipal Code for the City of Portland states, "No person or utility shall be granted a permit to excavate or open any street or sidewalk from the time of November 15 of each year to April 15 of the following year".
 20. The builder of a facility to which Section 4594-C of the Maine State Human Rights Act, Title 5 MRSA refers, shall obtain a certification from a design professional that the plans of the facility meet the standards of construction required by this section. Prior to commencing construction of the facility, the builder shall submit the certification to the Division of Inspection Services.
 21. This permit does not excuse the applicant from obtaining any license which may be needed from the City Clerk's Office.

Applicant: Robert Kierstead

Date: 8/27/96

Address: 66 Bramblewood Dr

C-B-L: 377-F-011

CHECK-LIST AGAINST ZONING ORDINANCE

Date - Existing

Zone Location - R-2

Interior or corner lot - New deck 12' x 22'

Proposed Use/Work - 

Sewage Disposal -

Lot Street Frontage -

Front Yard - N/A

Rear Yard - 25' req - 80' shown

Side Yard - 12' req - 48' & 68' shown

Projections -

Width of Lot -

Height -

Lot Area - 14,496 sq ft per assessors

2899.2 sq ft
~~3489.2 sq ft~~

Lot Coverage/ Impervious Surface - 20% max

Area per Family -

Off-street Parking -

Loading Bays -

Site Plan -

Shoreland Zoning/ Stream Protection -


Flood Plains -


	12x18 =	216
	22x24	528
new	12x22	264
deck	9x12	108
	24x20	672

1788 sq ft



John Diane
KAZI JONES





Log Bolts
at ea. post

2x8 Frame
2x10 Girder
8" Sona Tubes

please check off the appropriate description

FOUNDATION

_____ Frost Wall, min 4' below grade.
8" thick

_____ Sono Tube, 4' below grade.
6" min. on footing, hard pan or
bedrock.

_____ Other

SILL

_____ Size

SPAN OF SILL

_____ Distance between foundation supports

JOISTS SPAN

16' o.c.

JOISTS SIZE

_____ 2 x 6 _____ 2 x 8 _____ 2 x 10

DISTANCE BETWEEN JOISTS

_____ 16" o.c. _____ 24" o.c. _____ other

DECKING

_____ 5/4 _____ other explain

GUARD HEIGHT

_____ 36" _____ 42"

DISTANCE BETWEEN BALUSTER

_____ 4" spacing between

STAIR CONSTRUCTION

minimum 9" tread

maximum 8 1/4" rise

please use space below for drawing of deck with measurements.

Estimated Cost of Deck \$2500.00