

REScheck Software Version 5.5.0

Inspection Checklist

Energy Code: 2009 IECC

Requirements: 100.0% were addressed directly in the REScheck software

Text in the "Comments/Assumptions" column is provided by the user in the REScheck Requirements screen. For each requirement, the user certifies that a code requirement will be met and how that is documented, or that an exception is being claimed. Where compliance is itemized in a separate table, a reference to that table is provided.

Section # & Req.ID	Pre-Inspection/Plan Review	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
103.2 [PR1] ¹	Construction drawings and documentation demonstrate energy code compliance for the building envelope.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
103.2, 403.7 [PR3] ¹	Construction drawings and documentation demonstrate energy code compliance for lighting and mechanical systems. Systems serving multiple dwelling units must demonstrate compliance with the commercial code.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.6 [PR2] ²	Heating and cooling equipment is sized per ACCA Manual S based on loads per ACCA Manual J or other approved methods.	Heating: Btu/hr Cooling: Btu/hr	Heating: Btu/hr Cooling: Btu/hr	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

Additional Comments/Assumptions:

1	High Impact (Tier 1)	2	Medium Impact (Ti	er 2)	3	Low Impact (Tier 3)
L				<u> </u>	<u> </u>	zen mipace (ner 5)

Project Title: 6 Lambert Street Copy 2 Copy 2 Copy 2 Copy 2 Data filename:

Report date: 07/11/16

Page 2 of 6

Section # & Req.ID	Foundation Inspection	Complies?	Comments/Assumptions
3	A protective covering is installed to protect exposed exterior insulation	□Complies □Does Not	Requirement will be met.
9)	and extends a minimum of 6 in. below grade.	□Not Observable □Not Applicable	
403,8 [FO12] ²	Snow- and ice-melting system controls installed.	□Complies □Does Not	Requirement will be met,
(4)		□Not Observable □Not Applicable	

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)

Section # & Req.ID	Framing / Rough-In Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
402.4.4 [FR20] ¹	Fenestration that is not site built is listed and labeled as meeting AAMA/WDMA/CSA 101/I.S.2/A440 or has infiltration rates per NFRC 400 that do not exceed code limits.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
402.4.5 [FR16] ²	IC-rated recessed lighting fixtures sealed at housing/interior finish and labeled to indicate ≤2.0 cfm leakage at 75 Pa.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
405.2 [FR25] ¹	All ducts in unconditioned spaces or outside the building envelope are insulated to ≥R-6.	R	R	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.2,2 [FR13] ¹	All joints and seams of air ducts, air handlers, filter boxes, and building cavities used as return ducts are sealed.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403,2,3 [FR15] ³	Building cavities are not used for supply ducts.			☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
403.3 [FR17] ²	HVAC piping conveying fluids above 105 °F or chilled fluids below 55 °F are insulated to ≥R-3.	R	R	☐Complies ☐Does Not ☐Not Observable ☐Not Applicable	Requirement will be met.
403.4 [FR18] ²	Circulating service hot water pipes are insulated to R-2.	R	R	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.5 [FR19] ²	Automatic or gravity dampers are installed on all outdoor air intakes and exhausts.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1 High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)
				4

Section # & Req.ID	Insulation Inspection	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
303.1 [IN13] ²	All installed insulation is labeled or the installed R-values provided.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
402.1.1, 402.2.5, 402.2.6 [IN1] ¹	Floor insulation R-value.	R Wood Steel	R Wood Steel	□Complies □Does Not □Not Observable □Not Applicable	See the Envelope Assemblies table for values.
303.2, 402.2.6 [IN2] ¹	Floor insulation installed per manufacturer's instructions, and in substantial contact with the underside of the subfloor.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
402.1.1, 402.2.4, 402.2.5 [IN3] ¹	Wall insulation R-value. If this is a mass wall with at least ½ of the wall insulation on the wall exterior, the exterior insulation requirement applies.	R Wood Mass Steel	R Wood Mass Steel	□Complies □Does Not □Not Observable □Not Applicable	See the Envelope Assemblies table for values.
303.2 [IN4] ¹	Wall insulation is installed per manufacturer's instructions.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

1	High Impact (Tier 1)	2	Medium Impact (Tier 2)	3	Low Impact (Tier 3)
				·	

Section # & Req.ID	Final Inspection Provisions	Plans Verified Value	Field Verified Value	Complies?	Comments/Assumptions
402.1.1, 402.2.1, 402.2.2 [FI1] ¹	Ceiling insulation R-value. Where > R-30 is required, R-30 can be used if insulation is not compressed at eaves. R-30 may be used for 500 ft² or 20% (whichever is less) where sufficient space is not available.	R- ☐ Wood ☐ Steel	R Wood Steel	□Complies □Does Not □Not Observable □Not Applicable	See the Envelope Assemblies table for values.
303.1.1.1, 303.2 [FI2] ¹	Ceiling insulation installed per manufacturer's instructions. Blown insulation marked every 300 ft ² .			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
402.4.2, 402.4.2.1 [Fi17] ¹	Building envelope tightness verified by blower door test result of <7 ACH at 50 Pa. This requirement may instead be met via visual inspection, in which case verification may need to occur during insulation inspection.	ACH 50 =	ACH 50 =	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.2.2 [FI4]¹ ₩	Post construction duct tightness test result of ≤8 cfm to outdoors, or ≤12 cfm across systems. Or, rough-in test result of ≤6 cfm across systems or ≤4 cfm without air handler. Rough-in test verification may need to occur during Framing Inspection.	cfm	cfm	□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403,6 [FI5] ¹	Heating and cooling equipment type and capacity as per plans.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.1.1 [FI9] ²	Programmable thermostats installed on forced air furnaces.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.1.2 [FI10] ²	Heat pump thermostat installed on heat pumps.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
403.4 [FI11] ²	Circulating service hot water systems have automatic or accessible manual controls.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
401.3 [Fi7] ²	Compliance certificate posted.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.
303.3 [Fi18] ³	Manufacturer manuals for mechanical and water heating equipment have been provided.			□Complies □Does Not □Not Observable □Not Applicable	Requirement will be met.

F					
1 1	High Impact (Tier 1)	1 .	Marallerina January and Atlanta 21	1 ~	(T) 3)
1 1	High Impact (Tier 1)	1 Z	Medium Impact (Tier 2)	€ - ≾	I ow Impact (Tier 3)
	J	1			Lan unback (tich a)



Insulation Rating	R-Value	
Above-Grade Wall	21.00	
Below-Grade Wall	0.00	
Floor	30.00	
Ceiling / Roof	60.00	
Ductwork (unconditioned spaces):	-	
Glass & Door Rating	U-Factor	SHGC
Window		
Door		
Heating & Cooling Equipment	Efficiency	
Heating System:	9 11 150	
Cooling System:		
Water Heater:	_	
Name:	Date <u>:</u>	

Comments