



NOTES:

- WINDOWS:**
- DOUBLE HUNG WINDOWS ARE PARADIGM VERSATEC II, W/3 1/2" FLAT CASING, SILL NOSE, PREMIUM GLASS/AND SCREENS.
 - CASEMENTS ARE PARADIGM CRAFTEC, 3/4" IG GLASS, LOW E W/3 1/2" FLAT CASING, SILL NOSE, PREMIUM GLASS/AND SCREENS.
 - WINDOWS TO HAVE GRILLES AS SHOWN ON THE ELEVATIONS
- INTERIOR DOORS ARE TWO-PANEL SOLID, MOULDED W/SOLID, DOUBLE-RABBETED JAMBS.
- BATH AND LAUNDRY FANS TO BE EITHER BROAN QTXE SERIES OR PANASONIC FAN OR FAN/LIGHT COMBOS. EXHAUST TO OUTSIDE USING SOLID METAL DUCTWORK AND CONTAINED WITHIN CONDITIONED SPACE.
- DRYER TO BE VENTED TO OUTSIDE USING METAL DUCTWORK, SEALED AT ALL JOINTS WITH AN OUTSIDE CAP.

WINDOW SCHEDULE

MARK	WINDOW*	QTY	DESCRIPTION
A	DH4060	8	EGRESS
B	DH4066	3	
C	DH3244-2	1	
D	DH2848	2	
E	C2824	7	

*ALL WINDOWS ARE PARADIGM. DOUBLE HUNGS ARE VERSATEC II. CASEMENTS ARE CRAFTEC. WITH 3 1/2" FLAT CASING AND SILL NOSE ATTACHED.

DOOR SCHEDULE

MARK	SIZE	QTY	DESCRIPTION
1	3-0 X 6-8	1	THERMA-TRU SMOOTH STAR S80 DOOR W/14" SIDELIGHT
2	3-0 X 6-8	1	THERMA-TRU SE514 90 MIN FIRE RATED DOOR
3	3-0 X 6-8	1	THERMA-TRU TS206 TRADITIONS STEEL DOOR
4	3-0 X 6-8	2	SOLID CORE MOULDED 4 PANEL DOOR WITH SOLID RABBETED JAMBS.
5	2-8 X 6-8	2	" " " " " " " "
6	3-0 X 6-8	1	POCKET DOOR - SOLID CORE MOULDED 4 PANEL
7	5-0 X 6-8	2	DOUBLE ACTING DOOR - SOLID CORE MOULDED 4 PANEL
8	1-6 X 6-8	1	SOLID CORE MOULDED 4 PANEL DOOR WITH SOLID RABBETED JAMBS.
9	2-0 X 6-8	1	" " " " " " " "
10	4-0 X 6-8	1	DOUBLE ACTING DOOR - SOLID CORE MOULDED 4 PANEL
11	6-0 X 6-8	1	PARADIGM CRAFTEC PATIO DOOR

- NOTES:**
- ALL EXTERIOR DOORS TO HAVE 6 9/16" JAMBS
 - PARADIGM WINDOWS TO HAVE LOW E GLAZING. U=.32
 - THERMATRU SMOOTH STAR EXTERIOR DOOR: U= .24



Owner/Builder:
HIGGINS BUILDERS
PORTLAND, MAINE

Engineer:
Stephen W. Tibbetts, P.E.
Professional Civil Engineer
15 Oak Ridge Road Brunswick, Maine 04011
(207) 725-2667

Project:
NEW RESIDENCE
696 AUBURN ST
PORTLAND, MAINE

Date: JULY 23, 2015
Scale: 1/4" = 1'
Revisions:

FLOOR PLAN

A1